



CoogeeChemicals

Manufacturers & Importers of Mining, Industrial and Agricultural
Chemicals and Tank Terminal Operator
- Privately owned and proudly Western Australian -

Specifications Sulphuric Acid 98%

Chemical Formula	H ₂ SO ₄																		
Chemical Name	Sulphuric Acid																		
Synonyms	Brimstone Acid; Dipping Acid; Acid Mist; Hydrogen Sulphate; Sulphuric Acid																		
Description	Sulphuric acid is a clear water white solution, with a strong odour. The viscous liquid must avoid most inorganic materials, alkalis and water as it reacts violently.																		
Usage	<ul style="list-style-type: none">• Fertiliser production of Superphosphate• Mining for heap leaching• Chemical manufacturing of numerous compounds• Batteries																		
Typical Analysis	<table><tr><th>Sulphuric Acid</th><th>Min. 98% w/w</th><th>Impurities (mg/kg)</th></tr><tr><td>Iron (Fe)</td><td></td><td>< 50</td></tr><tr><td>Arsenic (As)</td><td></td><td>< 5</td></tr><tr><td>Copper (Cu)</td><td></td><td>< 5</td></tr><tr><td>Lead (Pb)</td><td></td><td>< 5</td></tr><tr><td>Mercury (Hg)</td><td></td><td>< 2</td></tr></table>	Sulphuric Acid	Min. 98% w/w	Impurities (mg/kg)	Iron (Fe)		< 50	Arsenic (As)		< 5	Copper (Cu)		< 5	Lead (Pb)		< 5	Mercury (Hg)		< 2
Sulphuric Acid	Min. 98% w/w	Impurities (mg/kg)																	
Iron (Fe)		< 50																	
Arsenic (As)		< 5																	
Copper (Cu)		< 5																	
Lead (Pb)		< 5																	
Mercury (Hg)		< 2																	
Typical Properties	<table><tr><td>Specific Gravity (20%)</td><td>1.84</td></tr><tr><td>Boiling Point</td><td>335°C @ 101.3 kPa</td></tr><tr><td>Solubility</td><td>Miscible in water</td></tr><tr><td>Chemical Stability</td><td>Stable in ambient conditions</td></tr></table>	Specific Gravity (20%)	1.84	Boiling Point	335°C @ 101.3 kPa	Solubility	Miscible in water	Chemical Stability	Stable in ambient conditions										
Specific Gravity (20%)	1.84																		
Boiling Point	335°C @ 101.3 kPa																		
Solubility	Miscible in water																		
Chemical Stability	Stable in ambient conditions																		
Delivery Details	Road Tanker <ul style="list-style-type: none">• Large = 25 to 55 tonnes• Small = 5000 to 10,000 litres Discharge Details <ul style="list-style-type: none">• Pump mounted on tanker. All leads have Clipsal 56 series, 4 pin, 10 amp, 440 volt, 3 phase plugs and are 10m long.• Discharge hose length is 6.5 metres fitted with 50mm or 80mm male NATO camlock fitting.• Can be delivered in single semi or road train.																		
Safety Information	Please refer to our current MSDS (www.coogee.com.au)																		

Postal Address
P.O. Box 5051
Rockingham Beach
Western Australia 6969

Administration:
Telephone: (08) 9439 8200
Facsimile: (08) 9439 8300
Email: ccadmin@coogee.com.au

Business Relations:
Telephone: (08) 9439 8200
Facsimile: (08) 9439 8300
Email: businessrelations@coogee.com.au

