



The LINE OPAL RECESSED is suitable across both residential and commercial projects. If the four different lengths are not enough, you can connect them together and create your own.

FEATURES

- + Recessed design providing simplicity and functionality
- + Quick and easy connection system
- + Easy installation into ceiling with spring clips attached to fitting
- + 1-10V dimming & non-dimming versions available upon request (*minimum order quantity applies*)
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



GENERAL SPECIFICATIONS

LED	15W 30W 45W 60W
Lumens	1200 lm 2300 lm 3900 lm 4600 lm (3000K) 1230 lm 2424 lm 3955 lm 4850 lm (4000K)
Efficacy	80 lm/w 76 lm/w 86 lm/w 76 lm/w (3000K) 82 lm/w 81 lm/w 88 lm/w 81 lm/w (3000K)
Colour Temperature	3000K, Warm White 4000K, Cool White
Material	Powder Coated Aluminium
Finish	White Black
Beam	90°
CRI	90+
IP	40
Colour Deviation	SDCM ≤3
UGR	<21
Lifetime	>60,000hrs L80 B10
Warranty	5 Years

ACCESSORY CODES

Recessed Connection Kit	7-LR56CONNECT
--------------------------------	---------------


PROJECT DETAILS

PROJECT:

TYPE:

NOTES:

DIMENSIONS (mm)



⌀ 613mm | 1213mm | 1813mm | 2413mm



⌀ (Including Mounting Clips) 65mm

⌀ 56mm (Without Mounting Clips) 45mm

DRIVER SPECIFICATIONS

L 105 x W 43 x H 24 mm

240V Remote Flicker Free Driver

15W 300mA | **30W** 600mA

45W 900mA | **60W** 1200mA

Dimming Phase Cut Dimming

Power Factor >0.90

PRODUCT CODES

613mm, 15W, White, 3000K	7-LR560615W903
613mm, 15W, White, 4000K	7-LR560615W904
613mm, 15W, Black, 3000K	7-LR560615B903
613mm, 15W, Black, 4000K	7-LR560615B904
1213mm, 30W, White, 3000K	7-LR561230W903
1213mm, 30W, White, 4000K	7-LR561230W904
1213mm, 30W, Black, 3000K	7-LR561230B903
1213mm, 30W, Black, 4000K	7-LR561230B904
1813mm, 45W, White, 3000K	7-LR561845W903
1813mm, 45W, White, 4000K	7-LR561845W904
1813mm, 45W, Black, 3000K	7-LR561845B903
1813mm, 45W, Black, 4000K	7-LR561845B904
2413mm, 60W, White, 3000K	7-LR562460W903
2413mm, 60W, White, 4000K	7-LR562460W904
2413mm, 60W, Black, 3000K	7-LR562460B903
2413mm, 60W, Black, 4000K	7-LR562460B904