

## LITE 108

The high-performance LITE 108 combines high lumen per watt efficacy and dynamic illumination. It also features a uniquely designed heat sink, for maximum heat dissipation in projects with minimum ceiling space.


- Precision reflector with clear lens – For better light distribution.
- Specially designed heat sink – For class leading heat dissipation.
- IP44 Rated – Suitable for wet areas.
- IC-4 Rated.
- > 55,000hrs L90B10 Lifetime.

### PROJECT DETAILS

#### PROJECT

#### TYPE

#### NOTES



#### DIMENSIONS

W Ø108 mm H 56 mm

#### CUT-OUT

Ø92mm

#### LUMINAIRE OPTIONS

##### LED & LUMENS OPTIONS (3000K | 4000K)

12W  
1060lm | 1130lm      10W  
860lm | 880lm

##### BEAM OPTIONS

60° STANDARD 36°

##### FINISHES

WHITE  BLACK

#### GENERAL SPECIFICATIONS

EFFICACY Up to 94 Lm/W

COLOUR 3000K, Warm White  
4000K, Cool White

MATERIAL Powder Coated Material

CRI 92+

IP 44

COLOUR DEVIATION SDCM ≤2

UGR <23

LIFETIME > 55,000hrs L90B10

WARRANTY 5 Years

#### DRIVER SPECIFICATIONS

DIMENSIONS L 104 x W 43 x H 24mm

POWER 300mA | 250mA 240V  
Remote Dimmable Driver

DIMMING Phase Cut Dimming

POWER FACTOR > 0.90

#### PRODUCT CODES

White, 3000K 118-LI2L12W603

White, 4000K 118-LI2L12W604

Black, 3000K 118-LI2L12B603

Black, 4000K 118-LI2L12B604

#### ACCESSORIES

36° Reflector 118-RFLL36

#### DRIVER CODES

12W 118-300MA

10W 118-250MA

