

LITE 108 IP 65

The high-performance LITE 108 combines high lumen per watt efficacy and dynamic illumination. It also features a uniquely designed heat sink, for maximum heat dissipation in projects with minimum ceiling space.


- Precision reflector with clear lens – For better light distribution.
- Specially designed heat sink – For class leading heat dissipation.
- IP65 Rated – Suitable for very wet areas.
- IC-4 Rated.
- > 55,000hrs L90B10 Lifetime.

PROJECT DETAILS

PROJECT

TYPE

NOTES



DIMENSIONS

W Ø108 mm H 56 mm

CUT-OUT

Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

12W
1060lm | 1130lm

10W
860lm | 880lm

BEAM OPTIONS

60° STANDARD 36°

FINISHES

WHITE BLACK

GENERAL SPECIFICATIONS

EFFICACY Up to 94 Lm/W

COLOUR 3000K, Warm White
4000K, Cool White

MATERIAL Powder Coated Material

CRI 92+

IP 65

COLOUR DEVIATION SDCM ≤2

UGR <23

LIFETIME > 55,000hrs L90B10

WARRANTY 5 Years

DRIVER SPECIFICATIONS

DIMENSIONS L 104 x W 43 x H 24mm

POWER 300mA | 250mA 240V
Remote Dimmable Driver

DIMMING Phase Cut Dimming

POWER FACTOR > 0.90

PRODUCT CODES

White, 3000K, IP 65 118-LI2L12W603IP

White, 4000K, IP 65 118-LI2L12W604IP

Black, 3000K, IP 65 118-LI2L12B603IP

Black, 4000K, IP 65 118-LI2L12B604IP

ACCESSORIES

36° Reflector 118-RFLL36

DRIVER CODES

12W 118-300MA

10W 118-250MA

