


PRO ADJUSTABLE

The Pro Adjustable downlight has been designed for versatility. With a tilting ability of up to 40° and a rotation of up to 350°, the Pro Adjustable allows complete control of the light direction. Ensuring that you always have the maximum light distribution from the LED.

- Precision reflector options – for better light distribution.
- Specially designed heatsink – for class leading heat dissipation.
- Adjustable up to 40° and rotatable up to 350°.
- IC-4 Rated
- Black baffle design for eliminating glare.



DIMENSIONS W1 Ø70 mm W2 Ø106 mm H 65mm
CUT-OUT Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

10W 965lm | 1015lm
8W 835lm | 880lm

BEAM OPTIONS

60° **STANDARD** 36° 24°

FINISHES

☐ WHITE ☒ BLACK

GENERAL SPECIFICATIONS

EFFICACY Up to 110 Lm/W
COLOUR 3000K, Warm White
4000K, Cool White
MATERIAL Powder Coated Material
FINISH White | Black
CRI 97+
IP 20
COLOUR DEVIATION SDCM ≤2
UGR <19
LIFETIME > 55,000hrs L90B10
WARRANTY 7 Years

DRIVER SPECIFICATIONS

DIMENSIONS L 98 x W 38 x H 24 mm
POWER 300mA | 250mA 240V
Remote Flicker Free
Dimmable Driver
DIMMING Phase Cut Dimming
POWER FACTOR > 0.90

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60° **118-PR7AR11W603**
White, 4000K, 60° **118-PR7AR11W604**
Black, 3000K, 60° **118-PR7AR11B603**
Black, 4000K, 60° **118-PR7AR11B604**

ACCESSORIES

36° Reflector **118-RFLA36**
24° Reflector **118-RFLA24**

DRIVER CODES

10W **118-300MA**
8W **118-250MA**

DALI DIMMING AVAILABLE UPON REQUEST

