

EDGE 100 G3

Incorporating a minimal trim design, with advanced LED engines to achieve intense illumination with a high lumen per watt efficacy. Our Generation 3 Series of downlights are unmatched, featuring higher quality lighting, more effective heat dissipation, and stronger LEDs.

- Adjustable head up to 25°.
- Precision reflector with clear lens – for better light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and glare reduction.
- Generation 3 LED technology – up to 15% more lumens.
- Suitable for concrete installation – concrete canister sold separately.



DIMENSIONS W Ø100 mm H 105 mm
CUT-OUT Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

13W 1400lm | 1500lm **10W** 1170lm | 1270lm **8W** 1025lm | 1125lm

BEAM OPTIONS (REFLECTOR / LENS)

60° REFLECTOR **STANDARD** 60° 36° 24° 15°

FINISHES

☐ WHITE ☒ BLACK

GENERAL SPECIFICATIONS

EFFICACY Up to 140 Lm/W
COLOUR 2700K, Warm White
4000K, Cool White
MATERIAL Powder Coated Material
CRI 92+
IP 44
COLOUR DEVIATION SDCM ≤2
UGR <15
LIFETIME > 55,000hrs L90B10
WARRANTY 7 Years

DRIVER SPECIFICATIONS

DIMENSIONS L 104 x W 43 x H 24mm
POWER 350mA | 300mA | 250mA
240V Remote Flicker Free
Dimmable Driver
DIMMING Phase Cut Dimming
POWER FACTOR > 0.90

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60° **118-ED3L13W603**
White, 4000K, 60° **118-ED3L13W604**
Black, 3000K, 60° **118-ED3L13B603**
Black, 4000K, 60° **118-ED3L13B604**

ACCESSORIES

36° Reflector **118-RFLP36**
24° Reflector **118-RFLP24**
15° Reflector **118-RFLP15**
60° Lens **118-LSE360**
36° Lens **118-LSE336**
24° Lens **118-LSE324**
15° Lens **118-LSE315**
Honeycomb **118-EDGE3HC**

DRIVER CODES

DRIVER SOLD SEPERATELY

13W **118-350MA**
10W **118-300MA**
8W **118-250MA**

DALI DIMMING AVAILABLE UPON REQUEST

