

EDGE XS

The EDGE XS packs a powerful punch! Providing intense illumination with very little energy. Featuring a low-height heatsink.

- Precision reflector with clear lens – For better light distribution.
- Specially designed low-height heat sink – For cramped ceiling spaces.
- Deep set lamp position – For visual comfort and glare reduction.
- Side facing cable output – For spaces that require a tighter fit.



DIMENSIONS W1 Ø103 mm W2 Ø62 mm H 83 mm
CUT-OUT Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

11W STANDARD
1065lm | 1070lm

8W
920lm | 920lm

6W
740lm | 745lm

BEAM OPTIONS

60° STANDARD **36°** **24°** **15°**

FINISHES

☐ WHITE ☒ BLACK

GENERAL SPECIFICATIONS

EFFICACY	Up to 124 Lm/W
COLOUR	3000K, Warm White 4000K, Cool White
MATERIAL	Powder Coated Material
CRI	92+
IP	44
COLOUR DEVIATION	SDCM ≤2
UGR	<13
LIFETIME	> 55,000hrs L90B10
WARRANTY	5 Years

DRIVER SPECIFICATIONS

DIMENSIONS	L 98 x W 40 x H 22 mm
POWER	300mA 240mA 180mA 240V Remote Flicker Free Dimmable Driver
DIMMING	Phase Cut Dimming
POWER FACTOR	> 0.90

DALI DIMMING AVAILABLE UPON REQUEST

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60°	118-ED3X13W603
White, 4000K, 60°	118-ED3X13W604
Black, 3000K, 60°	118-ED3X13B603
Black, 4000K, 60°	118-ED3X13B604

ACCESSORIES

36° Reflector	118-RFLX36
24° Reflector	118-RFLX24
15° Reflector	118-RFLX15

