

PRO ROUND G3

The Generation 3 FAZE PRO is a specifically designed to enhance. Utilising superior LED technology, combined with a high CRI, and a re-engineered heatsink; this series of downlights are guaranteed to bring your spaces to life, in an efficient manner.

- Precision reflector or lens options – for enhanced light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and low glare.
- Generation 3 LED technology.
- Suitable for concrete installation – concrete cannister not included.



DIMENSIONS W Ø106mm H 95mm

CUT-OUT Ø92mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

13W 1400lm | 1500lm **10W** 1170lm | 1270lm **8W** 1025lm | 1125lm

BEAM OPTIONS (REFLECTOR / LENS)

60° REFLECTOR **STANDARD** **60°** **36°** **24°** **15°**

FINISHES

☐ WHITE ☒ BLACK

GENERAL SPECIFICATIONS

| | |
|-------------------------|--|
| EFFICACY | Up to 140 Lm/W |
| COLOUR | 3000K, Warm White 4000K, Cool White |
| MATERIAL | Powder Coated Material |
| CRI | 92+ |
| IP | 44 |
| COLOUR DEVIATION | SDCM ≤2 |
| UGR | <15 |
| LIFETIME | > 55,000hrs L90B10 |
| WARRANTY | 7 Years |

DRIVER SPECIFICATIONS

| | |
|---------------------|--|
| DIMENSIONS | L 107 x W 43 x H 25 |
| POWER | 350mA 300mA 250mA 240V Remote Flicker Free Dimmable Driver |
| DIMMING | Phase Cut Dimming |
| POWER FACTOR | > 0.90 |

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

| | |
|-------------------|------------------------|
| White, 3000K, 60° | 118-PR3LR13W603 |
| White, 4000K, 60° | 118-PR3LR13W604 |
| Black, 3000K, 60° | 118-PR3LR13B603 |
| Black, 4000K, 60° | 118-PR3LR13B604 |

ACCESSORIES

| | |
|---------------|-------------------|
| 36° Reflector | 118-RFLP36 |
| 24° Reflector | 118-RFLP24 |
| 15° Reflector | 118-RFLP15 |
| 60° Lens | 118-LSE360 |
| 36° Lens | 118-LSE336 |
| 24° Lens | 118-LSE324 |
| 15° Lens | 118-LSE315 |

DRIVER CODES

DRIVER SOLD SEPERATELY

| | |
|-----|------------------|
| 13W | 118-350MA |
| 10W | 118-300MA |
| 8W | 118-250MA |

DALI DIMMING AVAILABLE UPON REQUEST

