PRO MINI ROUND G3

The Generation 3 FAZE PRO is specifically designed to enhance. Utilising superior LED technology, combined with a high CRI, and a re-engineered heatsink; this series of downlights are guaranteed to bring your spaces to life, in an efficient manner.

- Precision reflector or lens options – for enhanced light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and low glare.
- Generation 3 LED technology.

PROJECT DETAILS

PROJECT

TYPE

NOTES

DIMENSIONS	W Ø84mm H 98mm
CUT-OUT	I Ø76mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

10W	**8W**
1170lm | 1270lm	1025lm | 1125lm

BEAM OPTIONS (REFLECTOR / LENS)

60° REFLECTOR STANDARD | **60°** | **36°** | **24°** | **15°**

FINISHES

WHITE | **BLACK**

GENERAL SPECIFICATIONS

EFFICACY	Up to 140 Lm/W
COLOUR	3000K, Warm White 4000K, Cool White
MATERIAL	Powder Coated Material
CRI	92+
IP	44
COLOUR DEVIATION	SDCM ≤2
UGR	<15
LIFETIME	> 55,000hrs L90B10
WARRANTY	7 Years

DRIVER SPECIFICATIONS

DIMENSIONS	L 98 x W 38 x H 24
POWER	300mA | 250mA 240V Remote Flicker Free Dimmable Driver
DIMMING	Phase Cut Dimming
POWER FACTOR	> 0.90

PRODUCT CODES

White, 3000K, 60°	**118-PR3MR11W603**
White, 4000K, 60°	**118-PR3MR11W604**
Black, 3000K, 60°	**118-PR3MR11B603**
Black, 4000K, 60°	**118-PR3MR11B604**

ACCESSORIES

36° Reflector	**118-RFLP36**
24° Reflector	**118-RFLP24**
15° Reflector	**118-RFLP15**
60° Lens	**118-LSE360**
36° Lens	**118-LSE336**
24° Lens	**118-LSE324**
15° Lens	**118-LSE315**

DRIVER CODES

DRIVER SOLD SEPERATELY

10W	**118-300MA**
8W	**118-250MA**

DALI DIMMING AVAILABLE UPON REQUEST

1300 438 609
fazelight.com