


CORE XS SUSPENSION

The CORE XS simultaneously creates a stylish feature whilst also providing sufficient task lighting.

- High CRI – Defining architectural details and finishes.
- Quick connection system – For durability and easy installation.
- Flicker free driver – To prevent eye strain.
- Available in 3 beam angles – For the perfect light application.
- High quality lenses – For superior light emissions.



DIMENSIONS **W** Ø95mm **H** 105mm
CANOPY DIMENSIONS **H3** 30mm **W1** Ø60mm
CABLE LENGTH **H2** 2m

LUMINAIRE OPTIONS
BEAM OPTIONS
60° STANDARD 40° 20°
FINISHES
 WHITE **BLACK**
BAFFLE FINISHES
 BLACK STANDARD **WHITE** GOLD

GENERAL SPECIFICATIONS
LED LUMENS (3000K | 4000K)
11W 1200 lm | 1300 lm
EFFICACY Up to 118 Lm/W
COLOUR 3000K, Warm White
4000K, Cool White
MATERIAL Powder Coated Aluminium
CRI 92+
IP 20
COLOUR DEVIATION SDCM ≤2
UGR <18
LIFETIME > 55,000hrs L80B10
WARRANTY 5 Years

DRIVER SPECIFICATIONS
POWER 300mA 240V
Built-In Driver
DIMMING Phase-Cut
POWER FACTOR > 0.95
DALI DIMMING AVAILABLE UPON REQUEST

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES
White, 3000K, 60° **118-COSXS11W603**
White, 4000K, 60° **118-COSXS11W604**
Black, 3000K, 60° **118-COSXS11B603**
Black, 4000K, 60° **118-COSXS11B604**

ACCESSORIES
40° Lens **118-LSCX40**
20° Lens **118-LSCX20**
White Baffle **118-CORXS BW**
Gold Baffle **118-CORXS BG**

