

# Materials Handling





## Stackable Stillage

- Galvanised for use inside and outdoors.
- Designed to store long awkward objects for easy transport.
- Stackable to make use of the vertical space.
- Engineering certified to design requirements of AS4991-2004 Lifting Devices and AS4100-2020 Steel Structures.
- Maximum total load placed inside the stillage = 1000kgs.
- Maximum stacking height when fully loaded = 4 stillages high.
- Posts are removable for easy transport and storage when not in use.

Item Code	Load Capacity	External Dimension (mm)	Internal Dimension (mm)	Unit Weight	Safe Stacking Height
MH0100	1000kgs	1430W X 1060D x 1200H	1320W x 950D x 1010H	42kgs	4



## Collapsible Stillage Mesh Cage

- Can be stored in 840/838mmD racking.
- Maximum total load placed inside the cage = 1000kgs.
- Maximum stacking height when fully loaded = 4 cages high.
- Engineering certified to design requirements of AS4991-2004 Lifting Devices and AS4100-2020 Steel Structures.
- Solid base to prevent small items falling through.
- Fold down gates on 2 sides.
- 4-way fork entry.
- Constructed with heavy duty base with SHS frame and 50x50x3.5mm mesh walls.

Item Code	Load Capacity	Dimension (mm)	Collapsed Height	Unit Weight	Safe Stacking Height
MH0125	1000kgs	1150W x 1150D x 1120H	355mm	80kgs	4



## Wire Cages for Pallets

- Designed to fit over a standard Australian pallet 1165x1165mm.
- 100x50x6mm mesh construction.
- Turn your pallets into cages, full height and half height available.
- Pallet not included.

Item Code	Dimension (mm)	Unit Weight	Gate Style	Pallet Attachment
MH0115	1170W x 1170D x 800H	45kgs	Double drop down gate	4 lugs
MH0116	1170W x 1170D x 400H	28kgs	1 drop down gate	4 lugs



MH0115



MH0016

## Galvanised Mesh Cage

- 100x50x6mm mesh construction.
- Single cages sitting on the ground or on pallet racking beam have a maximum allowable load of 1,000kgs.
- If cages are stacked (up to a maximum of 3 high), the maximum load in any of the stacked cages must not exceed 500kgs.
- Can be folded down for easy transport or storage when not in use.

Item Code	Load Capacity	Stack Capacity	Dimension (mm)	Collapsed Height	Unit Weight	Safe Stacking Height
MH0121	1000kgs	500kgs	1156W x 1156D x 894H	333mm	65kgs	3



## Castor Wheels

Item Code	Load Capacity	Mounting type	Swivel or Fixed	Brake/Lock	Diameter	Width of Wheel
MH0050	100kgs	M12 Single thread bolt	Swivel	Yes	100mm	30mm
MH0051	100kgs	M8 4-bolt	Swivel	Yes	100mm	30mm
MH0052	100kgs	M8 4-bolt	Fixed	No	100mm	30mm
MH0054	300kgs	M10 4-bolt	Swivel	Yes	125mm	50mm
MH0056	300kgs	M10 4-bolt	Fixed	No	125mm	50mm



MH0050



MH0051



MH0052



MH0054



MH0056





Scan to contact us

**Perth**

26 Sangiorgio Court,  
Osborne Park WA 6017  
T (08) 9258 7166  
[perth@globalind.com.au](mailto:perth@globalind.com.au)

**Melbourne**

122 Radnor Drive,  
Deer Park VIC 3023  
T (03) 9338 8000  
[melbourne@globalind.com.au](mailto:melbourne@globalind.com.au)

**Brisbane**

Unit 3, 43 Rudd Street  
Oxley QLD 4075  
T (07) 3272 1225  
[brisbane@globalind.com.au](mailto:brisbane@globalind.com.au)

**Sydney**

40 Lyn Parade,  
Prestons NSW 2170  
T (02) 8103 5095  
[sydney@globalind.com.au](mailto:sydney@globalind.com.au)