

Industrial Shelving

2025

1300 76 26 86 GLOBALIND.COM.AU

Longspan Shelving



2025 INDUSTRIAL SHELVING CATALOGUE

Longspan Shelving

APEX Longspan Shelving can be easily configured to suit your requirements, with a wide range of standard heights, depths, and lengths available. This flexibility makes it an inexpensive mid-range storage solution, ideal for a variety of applications, products, and industries.

With its streamlined design, longspan suits a range of commercial, industrial and residential spaces from workshops to storerooms, home garages to shipping containers, and manufacturing facilities and much more.

By investing in the right shelving, you can significantly enhance storage capacity and streamline operations at your warehouse or free up space in your home. With its superior ability to utilise vertical space, customised design options, organisational capabilities, and robust strength, longspan shelving is a practical and cost-effective choice.

It is recommended that all longspan shelving of heights greater than 3000mm must anchored to the ground with appropriate anchors for stability and anything shorter is recommended to be anchored but is not a requirement.





Beam Length	Overall First Bay Length	Overall Add-on Bay Length	Max Capacity per Beam Pair	Frame Height	Frame Depth
900mm	1020mm	960mm	890kgs	900mm / 1000mm / 2000mm / 2400mm / 3000mm / 4000mm	460mm / 600mm / 900mm / 1200mm
1200mm	1320mm	1260mm	660kgs		
1500mm	1620mm	1560mm	530kgs		
1800mm	1920mm	1860mm	450kgs		
2100mm	2220mm	2160mm	385kgs		
2400mm	2520mm	2460mm	300kgs		












Features and benefits of Longspan Shelving

- · Quick and easy assembly.
- · Lightweight yet durable.
- Easily adjust levels every 50mm increment or add-on to existing longspan.
- Upright frames are bolted together rather than welded. This ensures greater structural flexibility and strength over a longer period of time and prolonged use.
- Shelves are retained within the beam step, creating a flush and neat level.
- Compatible with a range of accessories, such as drawers, tubs and cable rack.

GLOBALIND.COM.AU 3

Longspan Accessories








Longspan Modular Workbench Accessories

Customise and enhance your Longspan shelving or workbench with our versatile range of modular accessories.

Best suited for 900mm and 1800mm long beams with 600mm deep frames,

this range includes drawer units, overhead cabinets and stainless steel benchtops, perfect for creating a clean and organised setup.

ltem	Туре	Size
SLH400	Overhead cabinet	893mmL x 250mmD x 445mmH
SLH405	2 drawer unit	893mmL x 558mmD x 375mmH
SLH410	1 drawer unit	893mmL x 558mmD x 375mmH
SLH440	250mmH divider to suit SLH410	250mmH
SLH445	110mmH divider to suit SLH405	110mmH
SLH455	Stainless Steel Bench Top	890mmL x 675mmD x 25mmH
SLH460	Stainless Steel Bench Top	1786mmL x 675mmD x 25mmH
SLH520	Stainless steel volcano punch panel	933mmL x 610mmH









2025 INDUSTRIAL SHELVING CATALOGUE

APEX Pallet Racking Workbenches

Pallet Racking Workbenches are heavy duty and high quality, great for any warehouse, workshop, or garage. As standard, they come complete with 18mm particle, post caps and board supports.

It is recommended to fit 300kg castor wheels to the 2-tier rack workbenches to make them mobile.



2-tier Rack Workbench

Beam Length	Overall External Length	Recommended Board Supports	Depth	Height
1372mm	1552mm	2 per shelf		914mm
2591mm	2770mm	3 per shelf	609mm / 838mm / 1219mm	
2743mm	2920mm	3 per shelf		



4-tier Rack Workbench

Beam Length	Overall External Length	Recommended board supports for 838mm levels	Recommended z-clips for upper shelf	Depth	Height	Top Shelf Capacity
1372mm	1552mm	2 per shelf	4 per shelf	838mm	914mm high	Maximum
2591mm	2770mm	3 per shelf	6 per shelf	with 415mm top	to benchtop and 1829mm	100kgs (2 × 50kgs
2743mm	2920mm	3 per shelf	8 per shelf	shelves	high overall	shelves)

Longspan Workbenches

Longspan workbenches are lightweight, yet durable making them easy to assemble and install. Suits a variety of uses an storage items. Add-on to longspan shelving to create your own custom setup.

All workbenches come complete with post caps and are compatible with 100kgs castor wheels.



2-tier Rack Workbench

Beam Length	Overall External Length	Frame Depth	Frame Height	
900mm	1020mm			
1200mm	1320mm			
1500mm	1620mm	460mm / 600mm / 900mm / 1200mm	Overall 900mm	
1800mm	1920mm			
2100mm	2220mm			
2400mm	2520mm			



4-tier Rack Workbench

Beam Length	Overall External Length	Frame Depth	Frame Height	Top Shelf Capacity
900mm	1020mm			
1200mm	1320mm			Maximum 100kgs (2 × 50kgs shelves)
1500mm	1620mm	900mm with 460mm top shelf	900mm high to benchtop and 2000mm high overall	
1800mm	1920mm			
2100mm	2220mm			
2400mm	2520mm			

GLOBALIND.COM.AU

Gondola Shelving

Gondola Shelving is available as single-sided or double-sided configurations and widely used in retail settings such as grocery stores, supermarkets, chemists, hardware stores and variety stores. When buying and loading gondola shelving, it's important to keep weight limits in mind. Each bay can hold up to 240kg UDL per side (with a maximum height of 2100mm). Individual shelves and wire baskets can support up to 80kg UDL each. The shelves are made from 0.8mm steel, while the backing panels are made from 1.0mm steel for added strength.








A wide range of accessories that will perfectly compliment your gondola shelving setup:

- Increased storage capacity compared to traditional industrial 900Lx400Dx250H wire shelf baskets & matching dividers.
- · Wire front fences & shelf dividers.
- Chrome single prong hooks ranging between 100-300mm in length.
- Chrome hooks with ticket holder between 150-345mm long.
- 900L drawers on wheels.
- Magazine holders.
- 790mm internal corner bays. Available in single or double-sided configurations.

Height:	Width:	Raised Shelf Depths:	Base Shelf Depth:	Maximum Bay Load:	Maximum Shelf Capacity:
1500mm / 1800mm (1500+300mm extension) / 2100mm	900mm	350mm / 400mm / 450mm	450mm	240kgs UDL per side	80kgs UDL












2025 INDUSTRIAL SHELVING CATALOGUE

Galvanised Rivet Shelving

Galvanised rivet shelving is used for a variety of applications including box or archive storage, storerooms, parts storage, workshops and even cool room shelving.

Its electro galvanised surface treatment and the ability to remove the shelves and clean them means it can be used as cool room shelving. Being electro galvanized (otherwise known as zinc plated) the surface is metallic and caution should be used when choosing a cleaning product.









Beam Length	Beam ties	Max Capacity	Post Height	Bay Depth	Maximum Bay Capacity
910mm	N/A	250kgs	1829mm / 2134mm / 2438mm	430mm / 570mm	750kgs UDL
1210mm	1	250kgs			
1510mm	1	220kgs			
1810mm	2	200kgs			
2110mm	3	170kgs			
2410mm	3	150kgs			

Particle board is commonly used for general purpose applications and the steel galvanised panels are generally used for grocery applications and the mesh deck for cool rooms. Beam ties are used to hold together the front and back z-beams, which also strengthens the shelving unit.

Rolled Upright Type (RUT) Shelving

Rolled Upright Type (RUT) Shelving is a quality steel modular shelving systems suitable for many applications.

Each bay consists of a shell with adjustable shelves. The shelves will hold 90kg evenly distributed and you may have as many or as few adjustable shelves as you require. Each bay will hold a maximum of 800kg.

Depths	Shelf Size	Shelf Capacity	Maximum Bay Capacity	Bay Height	Bay Length
320mm	895×295mm	90kgs	800kgs	2175mm	900mm
420mm	895×295mm				
620mm	895×295mm				







GLOBALIND.COM.AU 7



Scan to contact us



f Global Industrial

Perth

26 Sangiorgio Court, Osborne Park WA 6017 T (08) 9258 7166 perth@globalind.com.au

Brisbane

Unit 3, 43 Rudd Street Oxley QLD 4075 T (07) 3272 1225 brisbane@globalind.com.au

Melbourne

122 Radnor Drive, Deer Park VIC 3023 T (03) 9338 8000 melbourne@globalind.com.au

Sydney

40 Lyn Parade, Prestons NSW 2170 T (02) 8103 5095 sydney@globalind.com.au