

Draft Preliminary Land Capability, Salinity and Contamination Assessment -Ingleside Release Area, Ingleside NSW

For: NSW Department of Planning & Environment

OCTOBER, 2015

Project Name:	Preliminary Land Capability, Salinity and Contamination Assessment - Ingleside Release Area, Ingleside NSW
Project Number:	30011289
Report for: NSW Department of Planning & Environment	

PREPARATION, REVIEW AND AUTHORISATION

Revision #	Date	Prepared by	Reviewed by	Approved for Issue by
DRAFT	21/10/2014	Steven Shaw, Daniel Saunders and Ben Morris	Chris Masters	Daniel Saunders
DRAFT	19/06/2015	Lachlan Edwards	Daniel Saunders	Daniel Saunders
DRAFT	01/09/2015	Lachlan Edwards	Daniel Saunders	Daniel Saunders
DRAFT	01/10/2015	Lachlan Edwards	Daniel Saunders	Daniel Saunders

ISSUE REGISTER

Distribution List	Date Issued	Number of Copies
NSW Department of Planning & Infrastructure:	01/10/2015	1
SMEC staff:		
Associates:		
SMEC Project File:	01/10/2015	1

SMEC COMPANY DETAILS

SMEC Australia Pty Ltd

PO BOX 1052, North Sydney, NSW 2059

Tel: (02) 9925 5555

Fax: (02) 9925 5566

Email: Daniel. Saunders@Smec.com

www.smec.com

The information within this document is and shall remain the property of SMEC Australia Pty Ltd



EXECUTIVE SUMMARY

SMEC Australia Pty Ltd was engaged by NSW Department of Planning & Environment (DP&E) to prepare a Preliminary Land Capability, Salinity and Contamination Assessment for the Ingleside Release Area, Ingleside NSW.

The purpose of undertaking a Preliminary Land Capability, Salinity and Contamination Investigation is to determine any land constraints and the soil and groundwater characteristics of the site for the purposes of supporting significant urban development.

Based on the original scope of works it was planned to undertake intrusive ground investigations across the area to determine the ground conditions and allow detailed slope stability and contamination assessments to be undertaken. Subsequent constraints around site access meant that an intrusive ground investigation was not possible, therefore, SMEC has undertaken a visual Land Capability slope risk analysis of 10 previously delineated set zones within the Ingleside precinct that contain slopes that may potentially pose a risk to property.

Specifically, the Land Capability Assessment included a site inspection to identify slope characteristics, identify current and potential slope failure mechanisms to inform a slope risk assessment and categorise slope mechanisms in accordance with the Landslide Risk Management guidelines by Australian Geomechanics Society (AGS, 2007).

Based on the findings of the risk analysis in the Land Capability Assessment it has been established that the tolerable risk to future development for the identified slope failure mechanisms has not been met, as the risk for the ten sites inspected within the precinct (refer to Appendix F) is classed as moderate. Recommendations to reduce the risk to tolerable levels may include scaling the slope, installation of rock bolts and consideration of development location. These risk analyses were based on high level observations. The analysis is conservative because comprehensive and detailed geological mapping of the site was not possible. The location and proximity of any future development to an identified slope failure mechanism will potentially alter the calculated risk level. As such it should be noted that there may be other active or potential slope mechanisms that were not identified. On this basis it is recommended that for any site development, a specific slope stability assessment should be undertaken to assess the slope risk based on a detailed site inspection or investigation.

An assessment of the soil landscapes within the subject area identified that the Hawkesbury, Lambert and Oxford Falls soil landscape groups are recognised as having a higher susceptibility to erosion. The subject area is considered to present as a high erosion hazard due to the characteristics of a colluvial and erosional soil landscapes combined with high rainfall intensity which can result in high soil loss conditions. This high erosion hazard implies that significant erosion will occur during development and after land use is established, even with intensive soil conservation measures. Such erosion hazards infer that planning will need to carefully consider the balance between the probability of long term erosion damage and maintenance or repair needed to ensure the viability of the land use. Where practicable, construction programing should aim to minimise the potential for soil loss by condensing the time from the beginning of land disturbance activities to rehabilitation.

In order to determine the potential for land contamination, salinity and other environmental constraints within the subject area, a Preliminary Environmental Site Assessment with limited surface soil sampling was conducted and supported by documentation relating to the subject area to identify potential sources of contamination associated with current and historical land use.



The subject area is entirely underlain by the Hawkesbury Sandstone formation of the Wianamatta Group (*Sydney 1:100 000 Series Geological Sheet*) and comprises a variety of soil landscapes recognised under the *Soil Landscapes of the Sydney 1:100 000 Sheet*. Soil landscapes mapped within the subject area include Gymea, Oxford Falls, Hawkesbury, Somersby and Lambert.

This study indicates that the regional groundwater flow direction is expected to generally flow to the north-east in accordance with the general site topography, with localised variations in areas located nearer to water bodies and creek lines. Local groundwater can occur at depths ranging from 10-20 metres below ground level (mbgl) and regional groundwater are likely to be deeper at 100-200 mbgl. Water quality information contained within the bore logs is limited; however, information that is provided identifies salinity characteristics as good, which indicates reasonable water quality and non-saline groundwater conditions are likely. The limited soil samples collected and analysed for salinity also indicate a 'Non-saline' classification for soils.

Acid sulfate soils are not considered to present a risk within the subject area, given the mapped soils units and elevation of the subject area (ie generally >100m above sea level).

As the future land use is likely to consist of various types of residential use within some commercial/industrial use, this study has adopted the residential criteria for Health Investigation Levels (HILs). Due to site access constraints within the subject area, limited surface soil sampling was conducted at assessable locations within the subject area only. All samples were analysed for a broad suite of analytes including, Metals (8), BTEX, TPH, OCC and OPP Pesticides, PCBs and PAHs. No soil sample obtained from within the subject area exceeded the adopted site assessment criteria for contaminated land.

While no soil sample exceeded the adopted site assessment criteria, due to the limited nature of the investigation the potential remains for contamination to be present within the subject area. The sources of contamination are likely to be related to the following identified activities or Areas of Environmental Concern (AECs) within the subject area:

- The use of uncontrolled fill material and guarry activities.
- Commercial and industrial facilities.
- Small farm holdings, market gardens and nurseries.
- Hazardous materials within existing buildings and site structures.
- Septic effluent systems.
- Potential fly tipping of waste in unoccupied lands.

On-Site Effluent Assessment

SMEC undertook an On-Site Effluent Assessment for the Ingleside Release Area (2015). The assessment found that the soil landscapes within the Wirreanda Valley and Bayview Heights areas present a number of soil related environmental constraints for on-site effluent systems. Soil depths of less than 0.6 metres to bedrock may not have enough capacity to filter nutrients and pathogens. Shallow soils often have a highly variable depth, and incur a risk of effluent resurfacing near the land application area. Any decisions about the on-site management of sewage should consider these impacts. It is recommended that individual lots may be required to undertake a specific site evaluation at the development application stage which may eliminate areas not suitable for on-site sewage management.

Further investigations will be required as part of future development applications together with additional work during the construction phase. Specific investigations would include but not necessarily be limited to:



- Detailed environmental investigation (comprising subsurface sampling and laboratory testing) in the nominated AECs, primarily in those areas which lie within the proposed "development footprint". The purpose of this work would be to quantify the level of contamination (if any) and delineate contaminated areas in order to facilitate the preparation of remediation action plans (RAP).
- Additional hazardous building material assessments should be undertaken of all buildings in the subject area that are to be demolished/renovated.
- Additional investigation should be undertaken in development areas which are to be excavated deeper than three metres or into rock at shallower depth, where direct sampling and testing of salinity has not been carried out.
- Installation of groundwater bores well in advance of construction and monitoring/sampling/analysis before, during and after construction, to monitor and assess changes in groundwater quality, electrical conductivity and level as a result of the development. The bores would be strategically located on a catchment basis near creek lines.
- Detailed geotechnical investigations on a stage-by-stage basis for determination of pavement thickness designs and lot classifications.

Overall SMEC sees no substantive reason with respect to Land Capability, Salinity and Contamination, why the subject area could not be developed from an urban development perspective subject to recommendations associated with additional investigations and implementation of appropriate mitigation measures.



TABLE OF CONTENTS

1	INTR	ODUCTION	1
	1.1	Objectives	1
	1.2	Scope of works	1
	1.2.1	Land Capability	1
	1.2.2	Soil Salinity Assessment	2
	1.2.3	Site Contamination Assessment	2
	1.3	Limitations	2
2	LANI	D CAPABILITY ASSESSMENT	4
	2.1	Site Location and Description	4
	2.2	Land Use	4
	2.3	Topography and Hydrology	6
	2.4	Soils	6
	2.5	Geology	8
	2.6	Hydrogeology	8
	2.7	Slope Risk and Stability	8
	2.8	Erosional and Sedimentation Characteristics	. 11
	2.9	On-site Sewage Management	.12
	2.10	Salinity	.13
	2.11	Acid Sulfate Soil Risk	.13
3	SALI	NITY ASSESSMENT	14
	3.1	Assessment Criteria	.14
	3.2	Subject area Investigation and Methodology	.14
	3.3	Site Assessment	.14
	3.4	Quality Control and Quality Assurance (QAQC)	.15
	3.5	Salinity Analytical Results	.15
	3.6	Discussion Of Results	.16
4	CON	TAMINATION ASSESSMENT	17
	4.1	Site History Review	. 17
	4.2	Site Inspection	.20
	4.3	Risk Assessment of AECs	.20
	4.4	Potential AEC Within Subject area	.21
	4.5	Potential Receptors of Concern and Pathways	.23
	4.6	Persistence in the Environment	.23
	4.7	Assessment Criteria	.24



	4.8	Subject Area Investigation and Methodology	. 25
	4.9	Quality Control and Quality Assurance (QAQC)	.25
	4.10	Contamination Analytical Results	.26
	4.11	Summary of Contaminated Lands	.26
5	CON	CLUSIONS AND RECOMMENDATIONS	28
	5.1	Land Capability Assessment	.28
	5.2	On-Site Sewage Assessment	.28
	5.3	Salinity Assessment	.29
	5.4	Contamination Assessment	.29
6	REF	ERENCES	31

LIST OF APPENDICES

APPENDIX A - FIGURES

APPENDIX B - GROUNDWATER DATABASE SEARCH

APPENDIX C - HISTORICAL AERIAL PHOTOGRAPHS

APPENDIX D - LABORATORY SUMMARY TABLES

APPENDIX E - LABORATORY REORTS

APPENDIX F - GEOTECHNICAL REPORT

1 INTRODUCTION

SMEC Australia Pty Ltd (SMEC) was engaged by NSW Department of Planning & Environment (DP&E) to prepare a Land Capability, Salinity and Contamination Assessment for the Ingleside Release Area, Ingleside NSW. This report is a technical paper developed to inform the precinct planning process for Ingleside. The precinct planning is being developed as a partnership between the Department of Planning and Environment, Pittwater Council and Urban Growth NSW.

The Ingleside precinct occupies approximately 700 hectares within Pittwater Council Local Government Area (LGA) and is located approximately 20 km north-east of the Sydney CBD.

The location of the Ingleside precinct (subject area) is presented in Figure 1.

It is understood that the subject area will accommodate a mixture of land uses including environmental living, low and medium density dwellings (and a range of other land uses) in the future, in order to meet the strategic planning requirements of the NSW State Government.

1.1 Objectives

The key objectives of the Land Capability, Salinity and Contamination Assessment for the subject area were to:

- Identify and map soil landscapes within the subject area and the limitations of the land.
- Undertake limited salinity and contamination soil sampling and analysis.
- Assess and provide recommendations for slope stability across the precinct.
- Identify any potential areas of concern from a contamination perspective.
- Map the suitability of land for urban development.
- Provide recommendations for any additional investigations to be undertaken prior to commencing urban development in the precinct.

1.2 Scope of works

The scope of works undertaken for the Land Capability, Salinity and Contamination assessments is provided in the following sections:

1.2.1 Land Capability

Based on the original scope of works it was planned to undertake intrusive ground investigations across the area to determine the ground conditions and allow detailed slope stability assessments to be undertaken. Subsequent constraints around site access meant that an intrusive ground investigation was not possible, therefore, SMEC has undertaken a visual slope risk analysis of 10 previously delineated set zones within the Ingleside Precinct and supported by the slope risk assessment technical paper (Ingleside Precincts Slope Risk Assessment Report, SMEC 2014) located in Appendix F.

Specifically, the revised scope of works for the Land Capability assessment comprised:

• Site inspection of the ten sites to identify slope characteristics as visible from the road side or clearly identifiable public land.



- Identify current and potential slope failure mechanisms to inform a slope risk assessment.
- Categorise slope mechanisms in accordance with the Landslide Risk Management guidelines dated March 2007 by Australian Geomechanics Society (AGS, 2007).
- Conduct a risk estimation of identified slope mechanisms (i.e. comparative analysis of likelihood of a slope failure versus consequence of the failure).
- Evaluation of the estimated (assessed) risk by comparing against acceptance criteria.

1.2.2 Soil Salinity Assessment

The scope of works for the salinity assessment comprised the following:

- A review of available preliminary soil information to determine soil conditions and salinity potential within the subject area.
- Collection and laboratory analysis surface soil samples (including QAQC) from accessible locations within the subject area.
- Laboratory analysis of soil samples for Electrical Conductivity (EC), pH, sulfate and chloride.

1.2.3 Site Contamination Assessment

In order to determine the potential for land contamination and particular environmental constraints in the subject area, a Phase 1 Preliminary Environmental Site Assessment (PESA) with limited surface soil sampling was conducted.

The scope of works for the ESA comprised the following:

- Review of available documentation relating to the subject area to identify potential sources of contamination associated with current and historical land use; including:
 - Current and historical aerial photographs.
 - Soil, acid sulfate soils, geological and hydrogeological maps and information.
 - Groundwater borehole database search.
 - Environment Protection Authority (EPA) regulatory database searches.
- A detailed desktop assessment of the subject area to evaluate the risks of contamination within the subject area and identify locations where contamination may pose a potential risk to human health or the environment.
- A general site inspection of the subject area.
- Limited surface soil sampling at accessible locations within the subject area.
- Identify areas where further investigation may be required to characterise the nature and extent of any potential contamination.
- Preparation of a Draft Land Capability, Salinity and Contamination Assessment report presenting information gained during the above tasks.
- Preparation of Final Land Capability, Salinity and Contamination Assessment report including consideration of comments from relevant stakeholders.

1.3 Limitations

This report has been prepared for NSW Department of Planning and Environment. The findings of this report are based on the scope of works defined in **Section 1.2**. SMEC



performed the works in a manner consistent with the normal level of care and expertise exercised by members of the environmental assessment profession.

The purpose of this report is to provide a preliminary assessment of Land Capability, Salinity and Contamination characteristics of the Ingleside release area. This report does not provide a complete assessment of the defined subject area or the surrounding area.

The absence of any identified hazardous materials within the subject area should not be interpreted as a guarantee that such materials do not exist. As this is a preliminary, broad scale Land Capability assessment, it is not intended to be comprehensive.

The findings of the report are based on a review of desktop information, limited soil sampling and visual observations only and are therefore merely indicative of the environmental condition.

No warranty, expressed or implied, is made as to the information and professional advice included in this report. This document has been prepared in good faith and no responsibility can be accepted for inaccuracies contained in any information provided third parties.

The report shall only be used for the purposes stated in the signed contract and shall not be relied upon by any party other than the NSW Department of Planning and Environment for the Ingleside Release Area project.



2 LAND CAPABILITY ASSESSMENT

2.1 Site Location and Description

For the purposes of assessment and reporting, the subject area comprises the following subprecincts:

- Wirreanda Valley
- North Ingleside
- Bayview Heights
- South Ingleside.

Collectively, the sub-precincts are generally bordered by the following:

- West Wirrianda Creek and the Ku-ring-gai Chase National Park.
- North Ku-ring-gai Chase National Park and the suburb of Church Point.
- East Warriewood Escarpment, Katandra Bushland Sanctuary and the suburb of Mona Vale.
- South Garrigal National Park and the suburb of Elanora Heights.

It is understood that the subject area adopted by DP&E for the Ingleside precinct will accommodate a mixture of land uses including environmental living, low and medium density dwellings (and a range of other land uses) in the future, in order to meet the strategic planning requirements of the NSW State Government.

2.2 Land Use


The subject area contains a number of existing land uses including recreational, private residential, commercial/industrial, schools, hobby farms and nursery related uses.

Private use of the land includes large residential blocks, commercial/industrial activities (including nursery and various commercial uses), schools, recreational camps and various other uses.

Approximately one third of the subject area is owned by the NSW State Government agencies. Key public landowners within the subject area are listed below:

- Department of Education and Communities.
- Department of Planning and Environment.
- Department of Primary Industries Lands.
- Roads and Maritime Services.
- Sydney Water.
- Pittwater Council.





2.3 Topography and Hydrology

The landscape of the subject area generally consists of relatively steep areas close to the Warriewood/Ingleside Escarpment, through to lower lying areas around the centre of the precinct (Powder Works Road, McLean Street etc.). Mona Vale Road dissects the subject area and generally follows the ridge line through the subject area. Elevations throughout the subject area generally range from a high of 200 m above sea level near the Baha'i Temple to low of 80 m above sea level in the area around Emmaus Road. In general, the subject area north of Mona Vale Road falls towards the north and north-east while the subject area south of Mona Vale Road falls towards the south-east.

Further discussion on the topography within the subject area is provided in the geotechnical / slope risk assessment report (Appendix F).

There are two creek lines located within the subject area north of Mona Vale Road. Wirreanda Creek follows the western edge of the subject area and flows to the north before discharging into McCarrs Creek, while Cicada Glen Creek flows to the north from Chiltern Road before also discharging into McCarrs Creek.

There are three creek lines located within the subject area south of Mona Vale Road. Mullet Creek (and its tributaries) flow to the south-east from King Road and Hyman Eizenberg Drive. Fern Creek and Narrabeen Creek begin at the Warriewood Escarpment and flow towards the south-east. All creek lines to the south of Mona Vale Road discharge into Narrabeen Lakes.

Figure 2, Appendix A identifies the creek lines and topography in relation to the subject area.

2.4 Soils

The subject area comprises a variety of soil landscapes recognised under the *Soil Landscapes of the Sydney 1:100 000 Sheet*. Soil landscapes mapped within the subject area include Gymea, Oxford Falls, Hawkesbury, Somersby and Lambert.

Descriptions and characteristics of the various soil landscapes identified within the subject area are provided in Table 1 below. Figure 3, Appendix A identifies the locations of the various soil landscape groups mapped throughout the subject area.



Table 1 Soils descriptions under the Soil Landscapes of the Sydney 1:100 000 Sheet

Soil Type	Landscape	Soils
Somersby	Gently undulating to rolling rises on deeply weathered Hawkesbury Sandstone plateau. Local relief to 40 m, slopes <15%. Rock outcrop is absent. Crests are broad and convex, valleys are narrow and concave. Extensively cleared, low eucalypt open-woodland and scrubland.	Moderately deep to deep (100-300 cm) Red Earths (Gn2.14) and Yellow Earths (Gn 2.24, Gn2.21) overlying laterite gravels and clays on crests and upper slopes; Yellow Earths (Gn2.21, Gn2.24) and Earthy Sands (Uc5.11, Uc5.22) on mid slopes; Grey Earths (Gn2.81), Leached Sands (Uc2.23) and Siliceous Sands (Uc1.22) on lower slopes and drainage lines; Gleyed Podzolic Soils (Dg3.82, Dg4.51) in low lying poorly drained areas.
Oxford Falls	Hanging valleys on Hawkesbury Sandstone. Local relief <80 m, slopes <15%. Occasional broad benches and broken scarps. Valley floors are relatively wide, gently inclined and often poorly drained. Low eucalypt woodland, scrub heathland and sedgeland.	Moderately deep to deep (50 >150 cm) Earthy Sands (Ue5.23), Yellow Earths (Gn2.84, Gn2.94), Siliceous Sands (Ue 1.21) on slopes; deep (>200 cm) Leached Sands (Uc 2.12), Podzols (Uc2.32, Uc2.36) and Grey Earths (Gn2.81) on valley floors.
Hawkesbury	Lugged, rolling to very steep hills on Hawkesbury Sandstone. Local relief 40-200m, slopes >25% Rock outcrop >50%. Narrow crests and ridges, narrow incised valleys, steep sideslopes with rocky benches, broken scarps and boulders. Mostly uncleared eucalypt open-woodland (dry sclerophyll forest) and tall open-forest (wet sclerophyll forest).	Shallow (>50 cm), discontinuous Lithosols, Siliceous Sands (Ucl.21) associated with rock outcrop; Earthy Sands (Uc5.11, Uc5.23), Yellow Earths (Gn2.24) and some Yellow Podzolic Soils (Dy4.11) on inside of benches and along joints and fractures; localised Yellow and Red Podzolic Soils (Dy4.11, Dy5.21, Dr5.11, Dr5.21) associated with shale lenses; Siliceous Sands (Uc1.2) and secondary Yellow Earths (Gn2.41) along drainage lines.
Gymea	Undulating to rolling rises and low hills on Hawkesbury Sandstone. Local relief 20-80m, slopes 10-25%. Rock outcrop <25%. Broad convex crests, moderately inclined side slopes with wide benches, localised rock outcrop on low broken scarps. Extensively cleared open-forest (dry sclerophyll forest) and eucalypt woodland.	Shallow to moderately deep (30-100 cm) Yellow Earths (Gn2.24) and Earthy Sands (Uc5.11, Uc5.23) on crests and inside of benches; shallow (<20 cm) Siliceous Sands (Ucl.21) on leading edges of benches; localized Gleyed Podzolic Soils (Dg4.21) and Yellow Podzolic Soils (Dy4.11, Dy5.11, Dy5.4V on shale lenses; shallow to moderately deep (<100 cm) Silkeous Sands (Ucl.1.2) and Leached Sands (Uc2.21) along drainage lines.
Lambert	Undulating to rolling low hills on Hawkesbury Sandstone. Local relief 20- 120m, slopes <20%. Rock outcrop >50%. Broad ridges, gently to moderately inclined	Shallow(<50 cm), discontinuous Earthy Sands (Uc5.11, Uc5.22) and Yellow Earths (Gn2.2) on crests and inside of benches; shallow (<20 cm) Siliceous Sands/Lithosols (Uc1,2) on

Soil Type	Landscape	Soils
	slopes, wide rock benches with low broken scarps, small hanging valleys and areas of poor drainage. Open and closedheathland, scrub and occasional low eucalypt open woodland.	leading edges; shallow to moderately deep (<150 cm) Leached Sands (Uc2.21), Grey Earths (Gn2.81) and Gleyed Podzolic Soils (Dg4.21) in poorly drained areas; localised Yellow Podzolic Soils (Dy4.1, Dy5.2) associated with shale lenses.

2.5 Geology

The Sydney 1:100 000 Series Geological Sheet indicates that the subject area is entirely underlain by the Hawkesbury Sandstone formation (mapping unit Rh) of the Wianamatta Group from the Triassic Period.

The Hawkesbury Sandstone formation typically comprises medium to coarse-grained quartz sandstone with very minor shale and laminate lenses. Figure 4, Appendix A identifies the mapped geology throughout the subject area.

2.6 Hydrogeology

SMEC completed a search of the Department of Water and Energy Online Database to identify groundwater bores within the subject area. The search indicated that there are 50 registered boreholes in the subject area.

Regional groundwater is expected to generally flow to the north-east in accordance with the general site topography with localised variations in areas located nearer to water bodies and creek lines.

Water quality information contained within the bore logs is limited; however, the information that is available identifies salinity characteristics as good to fresh which indicates reasonable water quality and non-saline groundwater conditions. This is anticipated given the geology of the subject area.

The recorded bore depths range from 5.3 mbgl in GW014179 to 210 mbgl in GW104265. Recorded historical standing water levels within the bores range from 14 mbgl in GW101503 to 105 mbgl in GW105671. The recorded bore depths and water levels indicate that there is likely more than one aguifer within the subject area.

The locations of existing groundwater boreholes within the subject area can be seen in Figure 5, Appendix A. Appendix B presents the works summary records from the groundwater database search for each groundwater bores identified within the subject area.

2.7 Slope Risk and Stability

The Land Capability assessment included a site inspection of the 10 previously delineated set zones within the Ingleside precinct (see Figure 2), that contain slopes that may potentially pose a risk to property, to identify slope characteristics, and identify current and potential slope failure mechanisms to inform a slope risk assessment and categorise slope mechanisms in accordance with the Landslide Risk Management guidelines dated March 2007 by Australian Geomechanics Society (AGS, 2007).






Figure 2. Site map for risk locations assessed

The methodology of assessing the risks at the site comprised the following steps:

- Site inspection involving a geological and geomorphologic appraisal
- Hazard identification
- Risk estimation.

The site inspections comprised site observations and recording of surface features including geomorphological characteristics, evident failure mechanisms, erosion and indications of slope instability.

Slope characterisation was undertaken for each precipice in order to:

- Identify whether the slope has current or potential slope instability issues
- Classify the types of slope instability, if relevant
- Assess the physical extent of the areas affected by instability being considered, including the location, areal extent and volume involved
- Assess the likely initiating event(s), the physical characteristics of the materials involved, and the failure mechanics
- Estimate the resulting anticipated travel distance and velocity of movement
- Identify if risks from a possible slope hazards to existing or future property are acceptable.

As access to private properties was not possible, SMEC has undertaken a visual slope risk analysis in line with AGS (2007) guidelines, which are included in Appendix F. These slope risk analyses involved the inspection of the slope characteristics at 10 sites (Figure 1, Appendix F). Inspections were undertaken from accessible areas, generally either from the roadside or clearly identifiable public land.

The data collected during the site visit by a senior geotechnical engineer has enabled the definition and characterisation of slope instability mechanisms at the 10 sites. Three main mechanisms were identified. These are listed below:

- Mechanism 1: Block falls up to 1 m from precipices up to 2 m in height
- Mechanism 2: Block falls up to 1 m from precipices up to 5 m in height
- Mechanism 3: Block falls up to 2 m from overhangs

SMEC considered three future uses for any land development and made assumptions with regards to the temporal probability for these uses (detailed in Appendix F Section 4.3.4). The three land uses considered are:

- Residential areas
- Roads
- Recreational areas

A risk assessment was undertaken for each of the slope instability mechanisms. For risk to property, the assessment was primarily based on a qualitative approach involving the estimation of the likelihood of a slope failure versus the consequence of the failure.

The findings of the slope risk analysis identified the risk level as 'moderate'. On this basis, the tolerable risk to property for the identified failure mechanisms has not been met. Recommendations to reduce risk to acceptable levels may include scaling the slope, installation of rock bolts and due consideration of the developments location.



Risk analyses were based on high level observations. The analyses are conservative because comprehensive and detailed geological mapping of the site was not possible. Accordingly there may be other active or potential slope mechanisms that were not identified. On this basis it is recommended that for any site development, a location-specific slope stability assessment should be undertaken to assess the slope risk based on a detailed site inspection or investigation.

2.8 Erosional and Sedimentation Characteristics

The erosion hazard is dependent on a combination of climate, landform, soil, land use and land management factors. The qualitative categories are of erosion hazard are 'low', 'moderate', 'high', 'very high' and 'extreme'.

The subject area has typical geomorphic characteristics of a colluvial (loose, unconsolidated sediments) and erosional (wearing away) soil landscapes. Generally, erosional landscapes are the source of soil materials deposited in a receiving colluvial landscape. Colluvium generally accumulates as gently sloping aprons or fans, either at the base of or within gullies and hollows on hill slopes down gradient.

Soil erosion hazards refer to the susceptibility of a parcel of land to the prevailing components of erosion. The 'Soil Loss Class' is a measure of erosional hazard that underpins the erosional control aspects of the *Managing Urban Stormwater: Soils and Construction* document (Landcom, 2004) listed for each soil landscape in Table 2.

Following assignment of a soil loss class, soil erodibility is assessed. Soil erodibility is a measure of the susceptibility of individual soil particle to detach and transport by rainfall and runoff. The K-factor range for soil landscapes within the subject area is 0.025 to 0.046. In general, the Hawkesbury, Lambert and Oxford Falls soil landscape groups are recognised as having a higher susceptibility to erosion than the other soil landscapes groups within the subject area.

Rainfall erosivity is another factor determining the soil loss class. Rainfall erosivity is a measure of the ability of rainfall to cause erosion. It is the product of two components: total energy and 30 minute intensity for each storm. In NSW it varies from 750 in western parts of the state to over 10,000 in on part of the north coast. The R-factor for Ingleside is 4000. Slopes exceeding 7% are considered high erosional risk in accordance with *Managing Urban Stormwater: Soils and Construction* (Landcom, 2004).

The annual rainfall distribution for Sydney area is seasonably variable. Given categorisation of the subject area as a high erosion risk, scheduling of construction activities during February and March (up to six months of the year in areas with higher soil loss classes) would require special measures in addition to best management practise is applied all year round.

High erosion hazard implies that significant erosion could occur during development of the particular land use and that appropriate erosion control measures would be needed to minimise long-term erosion risk. Control of short term erosion could be provided by simple soil conservation measures but long-term erosion control would involve intensive measures.

Very high erosion hazard implies that significant erosion could occur during development and after land use is established, even with intensive soil conservation measures. This category of erosion hazard infers that planning will need to carefully consider the balance between the probability of long term erosion damage and maintenance or repair needed to ensure the ongoing viability of the land use.



Where practicable, construction programing should aim to minimise the potential for soil loss by condensing the time from the beginning of land disturbance activities to rehabilitation to less than six months, subject to a detailed risk assessment. Further, on lands with a very high erosion hazard:

- (i) Attempt to confine specific land disturbance to those times of the year when the rainfall erosivity is low; or
- (ii) Show specific measures within Site Environmental Management Plans to address the high erosion hazard.

Erosion mitigation aims to reduce the severity of erosion should it occur. Erosion mitigation is a general term used to embrace all those activities, aimed at the control of soil erosion and the reduction of its impact on all forms of land use.

Table 2: Urban development limitations.

Soil Type	Limitations
Somersby	Localised permanently high water tables, areas of laterite and stony soil, very low soil fertility, highly permeable soil and slightly reactive Soil Loss 58 t/ha for topsoil and 162 t/ha for subsoil
Oxford Falls	Very high soil erosion hazard, perched water tables and swamps, highly permeable soil, very low to low soil fertility, localised rock outcrop. Moderately reactive Soil Loss 91 t/ha for topsoil and 131 t/ha for subsoil
Hawkesbury	Extreme soil erosion hazard, mass movement (rock fall) hazard, steep slopes, rock outcrop, shallow, stony, highly permeable soil, low soil fertility. Slightly reactive Soil Loss 109 t/ha for topsoil and 394 t/ha for subsoil
Gymea	Localised steep slopes, high soil erosion hazard, rock outcrop, shallow highly permeable soil, very low soil fertility. Slightly reactive <u>Soil Loss</u> - 19 t/ha for topsoil and 464 t/ha for subsoil
Lambert	Very high soil erosion hazard, rock outcrop, seasonally perched water tables, shallow, highly permeable soil, very low soil fertility. Slightly reactive Soil Loss 17 t/ha for topsoil and 197 t/ha for subsoil

2.9 On-site Sewage Management

SMEC undertook an On-Site Effluent Assessment for the Ingleside Release Area (2015). The assessment found that the soil landscapes within the Wirreanda Valley and Bayview Heights areas present a number of soil-related environmental constraints. Soil depths of less than 0.6 metres to bedrock may not have enough capacity to filter nutrients and pathogens. Shallow soil often has a highly variable depth, and incurs a risk of effluent surfacing near the

land application area. Any decisions about the on-site management of sewage should consider these issues.

Soil landscapes in the broader subject area can be typically <0.5 metres in the Hawkesbury, Gymea and Lambert soil profile and can present wide sandstone benches on side slopes and with associated rock outcrops. These soil landscapes are characterised by low water holding capacity, low to very low cation exchange capacity (CEC), and low nutrient status. They can be seasonally waterlogged with connected seepage areas and may also seasonally feed into hillside wetlands. Soil depths to bedrock can marginally increase in the Somersby and Oxford Falls soil landscapes with ranges of 0.5–1.0 m.

It is important that on-site sewage management issues are addressed as early as possible in the planning and development process as existing and proposed on-site sewage management within the subject area has potential to impact on the natural and managed parts of the water cycle through pollution of ground and surface waters with pathogens and nutrients. Moderate soil limitations can sometimes be overcome by appropriate selection, design, and sizing of on-site systems, or by modifying the site.

Ideally, the assessment proceeds from a broad evaluation and desktop analysis to more detailed subdivision survey work. It is recommended that individual lots may be required to undertake a specific site evaluation at the development application stage which may eliminate areas not suitable for on-site sewage management.

2.10 Salinity

The Soil Landscapes of the Sydney 1:100 000 Sheet, (Table 4.3 Soil Limitations for Each Soil Material) identifies that there is no known occurrence of salinity within any of the soil units (Somersby, Oxford Falls, Hawkesbury, Gymea and Lambert) mapped within the subject area.

Further discussion on the salinity characteristics of the subject area is provided in Section 3 of this report.

2.11 Acid Sulfate Soil Risk

Acid sulfate soils (ASS) are acidic soil horizons (layers) resulting from the aeration of soil materials rich in iron sulfides. ASS generally occur within the following environments:

- Marine or estuarine sediments deposited during the Holocene period.
- Soils environments <5 metres above sea level.
- Marine or estuarine settings/environments.

The Soil Landscapes of the Sydney 1:100 000 Sheet, (Table 4.3 Soil Limitations for Each Soil Material) identifies that there is <u>no known occurrence</u> of ASS within any of the soil units (Somersby, Oxford Falls, Hawkesbury, Gymea and Lambert) mapped within the subject area.

Given the mapped soils units and elevation of the subject area (generally >100 m above sea level) ASS are not considered to present a risk within the subject area.

Figure 3, Appendix A identifies the areas within the vicinity of the subject area where ASS are known to occur.



3 SALINITY ASSESSMENT

In order to determine the potential for salinity within the subject area, surface soils were collected and analysed during the site inspection within the subject area. Sampling locations were identified on a subjective basis. It is noted that sampling activities were conducted prior to the revision of the subject area. As such only samples obtained from within the revised subject area are discussed in the following sections.

3.1 Assessment Criteria

Soil salinity is commonly assessed with respect to EC of a 1:5 soil:water extract (EC 1:5). This value can be converted to ECe (electrical conductivity of a saturated extract) by multiplication by a factor dependent on soil texture ranging from 6 for shale to 17 for sand.

Hazelton and Murphy (2007) classify soil salinity on the basis of ECe and describe the following salinity classes for assessing soil salinity:

'Non saline': <2 mS/cm

'Slightly saline': 2-4 mS/cm

'Moderately saline': 4-8 mS/cm

'Very saline': 8-16 mS/cm

'Highly saline': >16 mS/cm

The adopted soil salinity assessment criteria are presented in Table D3, Appendix D.

3.2 Subject area Investigation and Methodology

The principal question of the investigation is to assess the potential risks posed by soil salinity with the subject area. All sampling design plans and fieldwork were undertaken by suitably qualified, trained and experienced personnel in general accordance with the Department of Land and Water Conservation, *Site Investigations for Urban Salinity*, Sydney, 2002.

Due to constraints around site access within the subject area, limited surface soil sampling was conducted at assessable public locations within the subject area only. Samples obtained were analysed for EC, pH, sulfate and chloride.

All surface soil samples were collected using a stainless steel trowel. The sample was then transferred directly from the trowel in to laboratory supplied sample jars. New disposable nitrile gloves were worn for the collection of each sample and the trowel was decontaminated with a phosphate free detergent (Decon 90) between each sample location.

3.3 Site Assessment

Visual evidence of soil salinity was not observed throughout the subject area during the limited field investigations.

All soil samples collected and analysed were surface or near-surface soil samples obtained from approximately 0.0-0.2m.

The field texture of the soil samples collected ranged from orange brown clayey sands to dark grey silty clays.



The locations of the salinity soil samples collected within the subject area are presented in Figure 8, Appendix A.

3.4 Quality Control and Quality Assurance (QAQC)

All fieldwork was performed by suitably qualified subcontractors in accordance with SMEC's standard operating procedures.

All samples were collected directly into laboratory supplied sample jars. To avoid potential cross-contamination a clean pair of nitrile gloves was worn prior to the collection of each sample. All equipment that came into contact with multiple sample locations was decontaminated with Decon 90 and rinsed prior to use at each location.

All sample jars were filled with sample directly from a stainless steel trowel and immediately placed in an ice-filled esky to keep the samples below a temperature of approximately 4°C.

A chain of custody form was completed with the sample names, sampling date and required analyses. The Chain of Custody (COC) form and the samples were then sent in a sealed esky to the NATA accredited laboratory ALS for analysis within the prescribed analyte holding times.

Analytical methods complied with NEPM and NSW EPA requirements.

The laboratory reports and certificates and COC information are provided in Appendix E.

A total of 72 soil samples were collected from within the subject area and analysed for salinity by the primary laboratory. Two intra–laboratory blind duplicate soil samples S15/2 (S15/1) and S283 (S283/2) was also analysed ALS.

In general all Relative Percent Differences (RPD's) for replicate samples S283/2 and S15/1 were within the recognised quality control interval of ±50%. Some exceptions were noted (moisture, sulfate, chloride), however, it is considered that the exceptions are reflective of the heterogeneous nature of the surface material sampled.

It is therefore considered that the field duplicate/laboratory QA/QC is adequate for the purposes of this investigation.

RPD results for salinity analysis are presented in Table D4, Appendix D.

3.5 Salinity Analytical Results

Laboratory EC results were converted to ECe values using a soil class factor of 8.6 (based on the average soil type encountered).

The reported EC results range from 6 μ S/cm (0.006 mS/cm) to 214 μ S/cm (0.214 mS/cm). The converted ECe results ranged from 0.1 mS/cm to 1.8 mS/cm.

Based on the assessment criteria detailed in section 5.1, the results indicate that all soil samples analysed were <2 mS/cm and therefore can be classified as being Non-saline.

Table D3, Appendix D presents soil analytical results for salinity analysis with comparison to the adopted salinity classes presented in Section 5.1.



3.6 Discussion Of Results

Analytical results for soil samples collected and analysed for salinity from within the subject area indicate that all soil samples can be classified as being Non-saline.

The reported analytical results confirm desktop information which identified that there is no known occurrence of salinity within any of the soil units (Somersby, Oxford Falls, Hawkesbury, Gymea and Lambert) mapped within the subject area (*Soil Landscapes of the Sydney 1:100 000 Sheet*, Table 4.3 Soil Limitations for Each Soil Material).

Based on the information presented above, a salinity management plan is not considered necessary and no further assessment of soil salinity within the subject area is required.



4 CONTAMINATION ASSESSMENT

4.1 Site History Review

In order to determine the potential for land contamination and particular environmental constraints in the subject area, a Stage 1 Preliminary Environmental Site Assessment (PESA) was conducted for the subject area. This included an appraisal of the potential for site contamination that may have resulted from past and present land uses to determine Areas of Environmental Concern (AEC).

In addition to the PESA a limited surface soil sampling program was also conducted at immediately assessable locations within the subject area. It is noted that sampling activates were conducted prior to the revision of the subject area. As such only samples obtained from within the revised subject area are discussed in the following sections.

The methodology for the site history assessment of the subject area consisted of the following:

- Review of past and present aerial photographs obtained from the NSW Department of Lands. Aerial Photographs from 1930, 1947, 1965, 1978, 1991, and 2014 were reviewed to determine potential past/present contaminating activities.
- Database search of registered groundwater bores within the subject area via the NSW Natural Resource Atlas online resource.
- Identification of the subject area, including location of surrounding infrastructure, area, boundaries, and a review of the physical site setting including regional and local geology, hydrology and hydrogeology.
- Database search of EPA contaminated land record and public record for licences, applications and notices.
- Database search of EPA environment protection licences, applications, notices, audit or pollution studies and reduction programs.
- A desktop review of information relevant to the history of sites within the subject area to determine past and present land uses.
- A site inspection on 16 July 2014 by a SMEC environmental scientist to visually assess present and past potentially contaminating activities, current landforms and site condition.

Aerial imagery dated between 1930 and 2012 was reviewed to assess major changes to land use within the subject area.

Table 3 lists the historical aerial photographs that were obtained and the review observations.

Appendix C presents the aerial images summarised within Table 3.



Table 3 Summary of Historical Aerial Photograph Information

Year	Site Description and Surrounding Area	Potential (AEC)
6 March1930 Sydney Survey Run 1 - 12 B/W Scale 1:22,000	Minimal development appears to have occurred within the release area prior to the 1930s. The main exceptions occur within the south and south-east of the subject area where a number of roads and small farm/agricultural developments are visible. A parcel of cleared land (square in appearance) is visible within the north-eastern portion of the subject area. The cleared area appears to be in the general vicinity of the present day location of Bayview Heights Estate.	Areas developed as small farm/agricultural holdings within the South and South-eastern portion of the subject area. Cleared area towards north-eastern tip of the subject area.
Jan 1947 Broken Bay, Runs 39 and 40 B/W Scale 1:12,000	Other than the development of additional farm/agricultural type developments within the south and south- west of the subject area; there is little change in comparison to the 1930 image. The cleared area towards north-eastern tip (visible in the 1930 image) is no longer visible in the 1947 image.	Areas developed as small farm holdings / market gardens / nurseries within the South and Southeastern portion of the subject area.
23 September 1965 Cumberland Run 12E and 13E B/W Scale 1:2,200	The southern portion of the release area has been further developed. More lots appear to have been developed for agricultural type activities. Many of the plots (particularly within the center and south-eastern sections of the subject area) contain long rectangular greenhouse/shed type structures assumed to be related to farming or nursery operations. The golf course (Monash Country Club) has also been developed within the southern section of the release area.	Areas developed as small farm holdings / market gardens / nurseries within the North, Central, South and South-eastern portions of the subject area.
	There are a few additional developed lots within the northern and central portions of the release area, that from appearance are assumed to be small farm/agricultural developments and a large area of scaring/cleared land is visible within the northern tip which is presumed to be the development of the Bayview Heights Estate.	
	Some development has occurred within the north- western section of the subject area. Several roads have been developed since 1947 and there is evidence of land clearance activities, however the nature of the land use is difficult to determine.	
	Construction of the Baha'i Temple is visible within the image.	



Year 29 March 1978 Cumberland Run 7 and 8 B/W Scale 1:16,000	Site Description and Surrounding Area	Potential (AEC)
	Other than the development of some additional farming/agricultural plots and rural properties throughout the subject area; there appears to be little obvious change in comparison to the 1965 image.	Areas developed as small farm holdings / market gardens / nurseries, Septic effluent systems on rural properties throughout the subject area.
14 August 1991 Sydney Run 5 Colour Scale 1:25,000	 Obvious changes from the 1978 image include: Development of light industrial activities (Sophie Ave, etc.). Scarring/land clearance evident (potential quarry locations) east and west of Wirreanda Rd North, Bungendore St, Addison Rd, on the northern side of Powder Works Rd near Wilson Ave (present day Council works depot) and on the northern side of Lane Cove Rd at the intersection with View Rd Construction of water tower on Wattle Rd. 	Areas developed as small farm holdings / market gardens / nurseries, Septic effluent systems on rural properties throughout the subject area. Lots developed for light industrial activates throughout the subject area (Sophie Ave, etc.). Potential quarry locations and fill materials.
2012 Bing Maps Colour Scale Unknown	Other than the development of some additional rural properties throughout the release area; there appears to be little obvious major change in comparison to the 1991 image.	Areas developed as small farm holdings / market gardens / nurseries, Septic effluent systems on rural properties throughout the subject area. Lots developed for light industrial activates throughout the subject area (Sophie Ave, etc.) Potential quarry or former quarry locations.



An online search of the EPA Contaminated Land Records Database (http://www.epa.nsw.gov.au/prclmapp/searchregister.aspx) was conducted on 24 June 2014. No notice records or management notices were identified for any site within the subject area. In addition, no records were held in relation to the land within a one kilometre radius of the subject area as at the search date.

An online search of the EPA Protection of the Environment Operations Act public register (http://www.epa.nsw.gov.au/prpoeoapp) was conducted on 24 June 2014. No environment protection licences, applications, notices, audits or pollution studies and reduction programs were identified for any site within the subject area. In addition, no environment protection licences, applications, notices, audits or pollution studies and reduction programs were identified for any site within a one kilometre radius of the subject area as at the search date.

No historical environmental reports were reviewed by SMEC in relation to the subject area for this report.

4.2 Site Inspection

A SMEC environmental scientist conducted a visual site inspection on 16 July 2014. Due to site access limitations, the site inspection consisted of observations from public roads and visual inspection to determine potential AEC and to field check desktop information.

The purpose of the visual site inspection was to gather non-invasive data to support the conceptual understanding of the spatial extent of historic and contemporary activities within the subject area.

The site inspection was undertaken to try to identify, locate and map the following surface features where they existed within the subject area:

- Disturbed ground possibly in the form of trenches or mounds.
- Illegal waste disposal, including domestic rubbish and building rubble (including asbestos fragments and sheets).
- Unnatural changes in vegetation (including evidence of cleared ground or vegetation potentially impacted by contamination).
- Potential environmental receivers.

4.3 Risk Assessment of AECs

A level of low, medium or high risk from a contamination perspective has been assigned based on qualitative judgment from observations made during the site inspection, information obtained during the desk top review and the extent of the proposed works for the proposed rezoning. Table 4 summarises the risk criteria developed to assess the AECs.



Table 4: Summary of Risk Criteria for AECs

Risk	AEC Risk Assessment Criteria
Low	Low potential of residual soil and/or groundwater contamination to exist within the extent concept proposal footprint. Low probability of engaging any potential contaminated land associated with identified AEC due to extent of proposed works.
Medium	Medium potential of residual soil and/or groundwater contamination to exist within the extent concept proposal footprint. Contaminated soil and / or groundwater associated with identified AEC may be engaged due to the extent of the proposed works.
High	High potential of some level of residual soil and/or groundwater contamination to exist within the extent concept proposal footprint. Contaminated soil and / or groundwater associated with identified AEC are likely to be engaged due to the extent of the proposed works. Further investigations recommended.

It should be noted that while the risk ranking system categorises the various AECs as 'high' to 'low' risk, this does not indicate that contamination has or has not occurred. Rather, it highlights the need that further assessment may be required. Further data would give greater confidence on these risk levels.

4.4 Potential AEC Within Subject area

Given the general history of land use within the subject area it is expected that any identified contamination would likely to be limited to relatively localised areas.

Table 5 presents the general high level AEC, potential impacts, risk rating and contaminants of concern within the subject area from a contamination perspective.

Figure 7, Appendix A identifies the AEC within the subject area from a contamination perspective.



Table 5 Potential AEC within Subject area

Table 6 Toterma	Table 5 Potential AEC Within Subject area					
AEC	Potential High Level Impacts	Risk	Potential Contaminants of Concern			
Uncontrolled Fill Material	Potential impacts to soil (and groundwater). The potential exists that contaminated heterogeneous fill material may have been used either within subsurface strata (i.e. used as backfill for lots to level sites) or stockpiled on lots within the subject area.	Medium	Metals (8) arsenic (As), cadmium (Cd), chromium (Cr), copper (Cu), mercury (Hg), nickel (Ni), lead (Pb) and zinc (Zn), PAHs, Total Petroleum Hydrocarbons (TPH), Benzene, toluene, ethylbenzene and xylene (BTEX), Polycyclic Aromatic Hydrocarbons (PAHs) Polychlorinated biphenyls (PCB), Organochlorine and Organophosphorous Pesticides (OCP& OPP), and asbestos			
Industrial facilities and Vehicle/Equip ment Maintenance	Potential impacts to soil (and groundwater). The potential for petroleum hydrocarbon impacts exists as a result of vehicle / equipment maintenance activities being conducted within the subject area particularly on commercial / industrial lots within the subject area.	Medium	Metals – lead (Pb), solvents, Volatile Organic Hydrocarbons (VOC), PAHs, TPH, BTEX			
Small farm holdings / market gardens and nurseries	Potential soil (and groundwater) impacts - The potential exists that OCC and OPP pesticides and herbicides may have been used particularly on small farm holdings / market garden and nursery lots within the subject area.	High	OCP & OPP Pesticides			
Existing Buildings and Site Structures	Potential soil impacts - The potential exists that older site structures throughout the subject area may contain a variety of contaminated materials including PCBs within electrical fittings, lead based paints, Synthetic Mineral Fibers (SMF) and Asbestos based products.	High (for structures built prior to 1986)	PCBs, Lead (paint), Synthetic Mineral Fibers (SMF) and Asbestos			
Septic effluent	Potential soil (and groundwater) impacts –	Medium	Fecal coliforms, Various			



AEC	Potential High Level Impacts	Risk	Potential Contaminants of Concern
systems	The potential exists that Septic effluent systems will be located throughout the subject area. Potential impacts relate to fecal coliforms and the use of domestic cleaning products.		metals
Fly Tipping	Potential soil impacts - The potential exists for illegal dumping on road verges and lots throughout the subject area.	Low	Metals, PAHs, TPH, BTEX, PCB, OCP, OPP and asbestos

4.5 Potential Receptors of Concern and Pathways

Based on the information available, the potential receptors include:

- Residents (existing and future), workers and general public with the subject area.
- Transient users of areas around the subject area.
- Construction workers involved in potential redevelopment of the subject area.
- Flora and fauna in areas within and around the subject area.
- Aquatic ecosystems of Wirreanda, Cicada Glen and McCarrs Creek(s) to the north and Mullet (and its tributaries), Fern, Narrabeen Creek(s) and Narrabeen Lakes to the south-east.

Based on the information available, the potential pathways include:

- Direct contact with contaminated soil and potentially groundwater.
- Ingestion or inhalation of soils and dust.
- Inhalation of vapours from soils and potentially groundwater.

4.6 Persistence in the Environment

The potential contaminants of concern identified which have a relatively high degree of persistence in the environment are:

- Asbestos.
- Lead.
- Agricultural pesticides
- VOCs
- Some PAHs.
- Longer chain hydrocarbons (ie >C29).



4.7 Assessment Criteria

Assessment criteria for the soil analytical results are discussed below. Evaluation against assessment criteria is used to identify levels of contamination that may pose ecological or health risks to existing and future users of the site.

It is noted that a new, amended National Environment Protection (Assessment of Site Contamination) Measure (NEPM) has been approved by all Australian States and Territories. The NEPM was first published in 1999 and updated in 2013 by the National Environment Protection Council (NEPC), and provides national standards for a variety of environmental issues, including the assessment of site contamination in Schedule B(1) Guideline on Investigation Levels for Soil and Groundwater.

NEPM (2013) has undertaken the development of health-based screening levels (HSLs) for petroleum hydrocarbons to address consistent human health risk in Australian conditions. The HSLs were derived through the consideration of health effects only, with particular emphasis on the vapour exposure pathway. HSLs have been derived for petroleum hydrocarbons for different land uses, media, soil types and depths to contamination.

The management limits (MLs) for TPH fractions in soil (NEPM 2013), are more conservative than the HSLs and therefore SMEC has adopted these as screening levels for TPH fractions for this investigation.

Analytical results are also compared with the NEPM (2013) provisional phytotoxicity-based ecological investigation levels (EILs) to determine potential risks to current and future ecological receptors at the site for select analytes (As, DDT, Pb, naphthalene, Cr, Cu, Ni, Zn).

The NEPM (2013) EIL values rely on site-specific inputs and calculations, and were derived specifically for sandy loam soils or soils of a closely similar texture with a pH in the range of 6 to 8. They are intended for assessment screening purpose only.

Ecological screening levels (ESLs) are relevant in terms of petroleum impacted soils where ecological receptors are present. The ESLs presented in Table 1B(6) of the NEPM (2013) are compared against various land uses for fine or coarse soil textures.

For the purpose of this investigation TPH fractions will be compared to fine soil texture for Urban Residential/Public Open Space and Commercial/Industrial land use.

As the future land-use is likely to be predominantly various residential within some commercial/industrial, the adopted assessment criteria for assessing the soil contaminants have been sourced from:

- NEPM (2013) HILs for Residential (A, B, C) and Commercial/Industrial (HIL D) for organic and inorganic chemicals.
- NEPM (2013) ESLs and MLs for TPH.
- NEPM (2013) EILs.
- For analytes in which there are no listed criteria, the laboratory Limits of Reporting (LOR) will be taken as screening level for this investigation.
- Where more than one value is listed for any particular analyte the most conservative value has been used as a screening level.

The adopted soil assessment criteria for the site are summarised in Table D1, Appendix D.



4.8 Subject Area Investigation and Methodology

The principal question of the investigation is to assess the risks posed by potential contamination for the proposed land use of the subject area for urban development.

SMEC undertook the works in accordance with a site specific Job Safety and Environmental Analysis (JSEA) Plan. The aim of the plan was to manage the potential risks to human health and safety associated with fieldwork activities.

All fieldwork was undertaken by suitably qualified, trained and experienced personnel.

Due to limitations around site access within the subject area limited surface soil sampling was conducted at assessable locations within the subject area only. All samples obtained were analysed for a broad suit of analytes including, metals (8), BTEX, TPH, OCC and OPP pesticides, PCBs and PAHs.

The locations of the contamination soil samples collected within the subject area are presented in Figure 8, Appendix A.

All surface soil samples were collected using a stainless steel trowel. The sample was then transferred directly from the trowel in to laboratory supplied sample jars. New disposable nitrile gloves were worn for the collection of each sample and the trowel was decontaminated with Decon 90 between each sample location.

4.9 Quality Control and Quality Assurance (QAQC)

All fieldwork was performed by suitably qualified subcontractors in accordance with SMEC's standard operating procedures.

All samples were collected directly into laboratory supplied sample jars. To avoid potential cross-contamination a clean pair of nitrile gloves was worn prior to the collection of each sample. All equipment that came into contact with multiple sample locations was decontaminated with Decon 90 and rinsed prior to use at each location.

All sample jars were filled with sample directly from a stainless steel trowel and immediately placed in an ice-filled esky to keep the samples below a temperature of approximately 4°C.

A chain of custody form was completed with the sample names, sampling date and required analyses. The Chain of Custody (COC) form and the samples were then sent in a sealed esky to the NATA accredited laboratory ALS for analysis within the prescribed analyte holding times.

Analytical methods complied with NEPM and NSW EPA requirements.

The laboratory reports and certificates and Chain of Custody (COC) information are provided in Appendix E.

A total of 12 soil samples were collected from within the subject area and analysed for contaminants of concern by the primary laboratory. Two intra–laboratory blind duplicate soil samples S15/2 (S15/1) and S283 (S283/2) was also analysed ALS.

In general all Relative Percent Differences (RPD's) for replicate samples S283/2 and S15/1 were within the recognised quality control interval of ±50%. Some exceptions were noted for some metals analytes and TPH fractions, however, it is considered that the exceptions are reflective of the heterogeneous nature of the surface material sampled.



It is therefore considered that the field duplicate/laboratory QA/QC is adequate for the purposes of this investigation.

RDP results for contamination analysis are presented in Table D2, Appendix D.

4.10 Contamination Analytical Results

All soil samples were surface soil samples obtained from approximately 0.0 -0.2m. The soil samples ranged from orange brown clayey sand to dark grey clayey silty sand. Soil analytical results obtained from the subject area were compared to the adopted site criteria.

Results indicate the following for soils respective to the criteria:

 No soil sample obtained from within the subject area exceeded the adopted site assessment criteria.

Other soil analytical results indicated that:

- Metals (8) concentrations were below the site assessment criteria for all samples analysed.
- Concentrations of PAH analytes, TPH and BTEX were generally either below their LOR or below the adopted site criteria in all samples analysed. The only exceptions were:
 - PAHs (sum of total 1.3 mg/kg), TRH C₁₀-C₄₀ (210 mg/kg) and TPH C₂₉-C₃₆ (100 mg/kg) were detected at levels either equal to or marginally above the LOR (but below site assessment criteria in sample S164. The sample was obtained from an undeveloped bush lot. The minor levels of PAH and hydrocarbons detected are probably reflective of residual oils from eucalyptus vegetation and combusted organics associated with bush fire ash likely to be in the area; and
 - OC Pesticides (DDE 0.13 mg/kg) were detected at levels marginally above the LOR (but below site assessment criteria in sample S38. It is noted sample S38 was obtained from within the vicinity of Powder Works Nursery located on Wilson Avenue.
- Remaining, OCP, OPP, PCB and phenol concentrations were below their LOR or below the adopted site criteria in all samples analysed.

Table D1, Appendix D presents soil analytical results for contamination analysis with comparison to the adopted site assessment criteria.

4.11 Summary of Contaminated Lands

Land contamination is most often the result of past land uses. It can arise from activities that took place on or adjacent to a site and be the result of improper chemical handling or disposal practices, or accidental spillages or leakages of chemicals during transport or storage. Activities not directly related to a site may also cause contamination; for example, from diffuse sources such as polluted groundwater migrating under a site or dust settling out from industrial emissions. All construction activities prior to 1986 have the potential for asbestos-containing materials (ACM) to be present.

Due to the high level nature of this investigation it is recommended that the contamination status of individual sites should be assessed at as part of any future development application (DA) process. This may require further assessment of soil and groundwater conditions.



The findings of the preliminary soil contamination survey indicate soil qualities within the survey area are low risk for contamination. Localised contamination issues are likely to be associated with landfilling associated with cut and fill building pads, quarrying activities, construction equipment handling yards, and agricultural activities like nursery and market gardens where buildings are likely to contain asbestos sheeting in their construction. It is likely that underground utilities contain asbestos materials within service conduits and communications pits.

There is the potential for contaminated land to be disturbed by construction activities associated with ground engaging activities required for the proposed development of the subject area.

Potential environmental impacts associated with the proposal in relation to contaminated land management include:

- Increasing waste amounts from improper practices such as poor fill management.
- Contaminated or hazardous waste not being correctly disposed of.
- Adverse effects on human health (construction personnel, travelling public or nearby communities).
- Release of contaminants to underlying soils.
- Release of contaminants to groundwater.
- Movement of contaminated sediments into waterways.
- Adverse effects on flora and fauna.

Given the expected depth of groundwater in the vicinity of the subject area, it is considered unlikely that groundwater would be directly intercepted. During development, groundwater quality may be affected if recharge water caries pollutants generated from the proposal construction work. Sources of potential pollution could include nutrient rich water generated from nurseries, on-site sewage management systems, drainage from contaminated soil stockpiles or from spills of fuels, oil or other chemicals used in historical land uses.



5 CONCLUSIONS AND RECOMMENDATIONS

The following sections summarise the conclusions of the land capability, salinity and contamination assessment and the recommendations arising from the investigation.

5.1 Land Capability Assessment

The Land Capability Assessment included a site inspection at slope risk analysis of 10 previously delineated set zones within the Ingleside precinct to identify slope characteristics, identify current and potential slope failure mechanisms to inform a slope risk assessment and categorise slope mechanisms in accordance with the Landslide Risk Management guidelines by Australian Geomechanics Society (AGS, 2007). Appendix F outlines the risk analysis framework.

Based on the findings of the risk analysis it has been established that the tolerable risk to future development for the identified slope failure mechanisms has not been met, as the risk for the ten sites inspected within the precinct is classed as moderate. The report presenting the slope risk analysis undertaken within the precinct is contained in Appendix F. Recommendations to reduce the risk to tolerable levels may include; scaling the slope, installation of rock bolts and consideration of development location. These risk analyses were based on high level observations. The analysis is conservative because comprehensive and detailed geological mapping of the site was not possible. As such it should be noted that there may be other active or potential slope mechanisms that were not identified. The location and proximity of any future development to an identified slope failure mechanism will potentially alter the calculated risk level.

On this basis it is recommended that for any site development a specific slope stability assessment should be undertaken to assess the slope risk based on a detailed site inspection or investigation.

The subject area is considered to present as a high erosion hazard due to the typical characteristics of a colluvial and erosional soil landscapes combined with high rainfall intensity which can generate high soil loss. This high erosional hazard implies that significant erosion will occur during development and after land use is established, even with intensive soil conservation measures. Erosion hazards will need to be considered at the development application stage. Where practicable, construction programing should aim to minimise the potential for soil loss by condensing the time from the beginning of land disturbance activities to rehabilitation. This study indicates that the regional groundwater flow direction is expected to generally flow to the north-east in accordance with the general site topography with localised variations in areas located nearer to water bodies and creek lines. Local groundwater can occur at depths ranging from 10-20 mgbl and regional groundwater are likely to be deeper at 100-200 mbgl. Water quality information contained within the bore logs is limited; however, information that is provided identifies salinity characteristics as good, which indicates reasonable water quality and non-saline groundwater conditions are likely. The limited soil samples collected and analysed for salinity also indicate a 'Non-saline' classification for soils.

5.2 On-Site Sewage Assessment

SMEC undertook an On-Site Effluent Assessment for the Ingleside Release Area (2015). The assessment found that the soil landscapes within the Wirreanda Valley and Bayview Heights areas present a number of soil related environmental constraints for on-site effluent systems. Soil depths of less than 0.6 metres to bedrock may not have enough capacity to filter nutrients and pathogens. Shallow soils often have a highly variable depth, and incur a



risk of effluent resurfacing near the land application area. Any decisions about the on-site management of sewage should consider these impacts. It is recommended that individual lots may be required to undertake a specific site evaluation at the development application stage which may eliminate areas not suitable for on-site sewage management.

5.3 Salinity Assessment

With regard to the salinity investigation, the following is concluded:

- There is no known occurrence of salinity within any of the soil units (Somersby, Oxford Falls, Hawkesbury, Gymea and Lambert) mapped within the subject area.
- All soil samples obtained and analysed from the subject area were <2 mS/cm and therefore classified as being non-saline.

Based on the information presented above, a salinity management plan is not considered necessary and no further assessment of soil salinity within the subject area is required.

5.4 Contamination Assessment

With regard to the contamination investigation, the following is concluded:

- The subject area contains a number of existing land uses including recreational, private residential, commercial/industrial, schools, hobby farms and nursery related uses.
- The subject area comprises 5 soil landscapes: Gymea, Oxford Falls, Hawkesbury, Somersby, Lambert.
- There is no known occurrence of acid sulfate soils within any of the soil units (Somersby, Oxford Falls, Hawkesbury, Gymea and Lambert) mapped within the subject area. Given the mapped soils units and elevation of the subject area (generally >100m above sea level) ASS are not considered to present a risk within the subject area.
- No soil sample obtained from within the subject area exceeded the adopted site assessment criteria.
- OC pesticides (DDE 0.13 mg/kg) were detected at levels marginally above the LOR (but below site assessment criteria) in sample S38. The sample was obtained from within the vicinity of Powder Works Nursery located on Wilson Avenue.
- PAHs (sum of total 1.3 mg/kg), TRH C10-C40 (210 mg/kg) and TPH C29-C36 (100 mg/kg) were detected at levels either equal to or marginally above the LOR (but below site assessment criteria) in sample S164. The sample was obtained from an undeveloped bush lot. It is assumed that the minor levels PAH and hydrocarbons detected are probably reflective of vehicle emissions within the area.
- Potential high level AEC, from a contamination perspective, that could exist throughout the subject area include:
 - The use of uncontrolled fill material.
 - Industrial facilities and vehicle / equipment maintenance.
 - Small farm holdings / market gardens and nurseries.
 - Existing buildings and site structures.
 - Septic effluent systems.
 - Fly tipping.



Given the general history of land use within the subject area it is expected that any identified contamination would likely to be limited to relatively localised areas.

With regard to the contamination investigation, the following is recommended:

- The contamination status of each site should be further assessed as part of any future DA process. This may require further assessment of soil and groundwater conditions.
- A Remediation Action Plan should be developed to manage potential sources of contamination should they be identified during additional investigation stages.

Page | 30

6 REFERENCES

Australian Soil Resource Information System (http://www.asris.csiro.au/index_ie.html), viewed 25 June 2014.

Chapman, G.A. and Murphy, C.L. (1989), *Soil Landscapes of the Sydney 1:100,000 sheet*. Soil Conservation Service of N.S.W, Sydney.

Chapman, G.A. and Murphy, C.L., Tille, P.J., Atkinson, G. and Morse, R.J. (1989), *Soil Landscapes of the Sydney 1:100,000 sheet*. Soil Conservation Service of N.S.W, Sydney.

Department of Land and Water Conservation, *Site Investigations for Urban Salinity*, Sydney, 2002.

DNR Groundwater Database (www.nratlas.nsw.gov.au), viewed 25 June 2014

Geological Survey of New South Wales, Department of Mineral Resource, *Sydney Geology Map, 1:100,000 Geological Series Sheet 9130* (Edition 1), 1983.

Hazelton, P. A. and Murphy, B. W, 2007, *Interpreting Soil Test results: What do all the numbers mean?*, NSW Department of Natural Resources.

NSW EPA - Search for Environment Protection licences, applications, notices, audits or pollution studies and reduction programs – (http://www.epa.nsw.gov.au/prpoeoapp/default.aspx?range=Licence&searchrange=general, viewed 24 June 2014.

NSW EPA - Search the contaminated land record -http://www.epa.nsw.gov.au/prcImapp/searchregister.aspx, viewed 24 June 2014.

NEPC (1999) National Environmental Protection (Assessment of Site Contamination) Measure (NEPM).

NSW DECC (2006) Guidelines for the NSW Site Auditor Scheme (2nd Edition).


NSW EPA, Contaminated Sites – Guidelines for Consultants Reporting on Contaminated Sites, 1997.


NSW EPA (1997) Guidelines for Consultants reporting on Contaminated Sites.


SMEC Australia (2015) On Site Effluent Subdivision Assessment for development of the Ingleside Release Area, Ingleside, NSW.




APPENDIX A - FIGURES




















APPENDIX B - GROUNDWATER DATABASE SEARCH

FARMING

Converted From HYDSYS GW014179

Licence:10BL007801 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC GENERAL USE Work Type: Well

Work Status : Supply Obtained Construct. Method: (Unknown)

Completion Date: 01-Jan-1959

Owner Type :Private **Commenced Date:**

Final Depth: 5.30 m **Drilled Depth:** 5.30 m

Contractor Name: Driller: Assistant Driller's Name :

> Property: - N/A **Standing Water Level:**

GWMA:603 - SYDNEY BASIN (Unknown) Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 202 Licensed: CUMBERLAND NARRABEEN 202

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin :212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing: 6272942 Latitude (S) :33° 40' 17" Elevation Source :(Unknown) **Easting :**339549 **Longitude** (**E**) :151° 16' 9"

GS Map :0055B3 MGA Zone:56 Coordinate Source : GD., PR. MAP

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$;A-Aperture;GS-Grain كايد, بر-بريسية; ID (mm) Interval Details (Unknown)

To (m) OD (mm) 0.20 1346 H P Component Type
1 1 Casing Brick From (m) 0.00

Water Bearing Zones

To (m) Thickness (m) WBZ Type D.D.L. (m) Yield (L/s) S.W.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

(No Water Bearing Zone Details Found)

Drillers Log

From (m) 0.00 To (m) Thickness(m Drillers Description 0.22 0.22 Loam Sandy Geological Material Comments Loam Sandstone 5.33 0.22 5.11 Sandstone

Remarks

*** End of GW014179 ***

GW014464 Converted From HYDSYS

Licence :10BL009510 Licence Status Cancelled

Authorised Purpose(s) Intended Purpose(s)
DOMESTIC IRRIGATION

Work Type :Bore open thru rock DOMESTIC
Work Status :(Unknown) ORCHARDS (GROUNDWATER)

Construct. Method :Cable Tool
Owner Type :Private

Commenced Date : Final Depth : 33.50 m **Completion Date :**01-Aug-1960 Drilled Depth : 33.50 m

Contractor Name : Driller : Assistant Driller's Name :

Property: - N/A Standing Water Level:

GWMA:603 - SYDNEY BASIN Salinity: (Unknown)

GW Zone: - Yield:

Site Details

Site Chosen By County Parish Portion/Lot DP

Form A :CUMBERLAND NARRABEEN 69
Licensed :CUMBERLAND NARRABEEN 7 25951

Region: 10 -SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 212 -HAWKESBURY RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District :

 Elevation :
 Northing :6271365
 Latitude (S) :33° 41' 7"

 Elevation Source :(Unknown)
 Easting :338534
 Longitude (E) :151° 15' 29"

GS Map :0055B3 MGA Zone :56 Coordinate Source :GD.,PR. MAP

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;S-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

H P Component Type From (m) To (m) OD (mm) ID (mm) Interval Details
1 1 Casing Threaded Steel -0.10 12.00 152 ID (mm) Interval Details (Unknown)

1 1 Opening Perforations 0.00 152 1 Mechanically Slotted; SL: Omm; A: Omm

Water Bearing Zones

 From (m)
 To (m) Thickness (m) WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 6.00
 6.00
 0.00 Unconsolidated
 3.00
 0.03
 (Unknown)

 30.40
 30.40
 0.00 Consolidated
 3.00
 0.10
 (Unknown)

Drillers Log

From (m)To (m)Thickness(m)Drillers DescriptionGeological MaterialComments0.0012.1912.19Soil Clay Water SupplySoil12.1933.5221.33Sandstone Water SupplySandstone

Remarks

MONA VALE RD INGLESIDE

*** End of GW014464 ***

FARMING

Converted From HYDSYS GW014465

Licence: 10BL011016 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC GENERAL USE Work Type :Bore open thru rock

Work Status :(Unknown) Construct. Method :Cable Tool Owner Type :Private

Commenced Date: Final Depth: 39.00 m Completion Date: 01-Nov-1960 **Drilled Depth:** 39.00 m

Contractor Name: Driller: Assistant Driller's Name :

> Property: - N/A **Standing Water Level:**

GWMA:603 - SYDNEY BASIN (Unknown) Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County 69

Form A: CUMBERLAND NARRABEEN Licensed: CUMBERLAND NARRABEEN C 25951

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing:6271412 Latitude (S) :33° 41' 6" Elevation Source :(Unknown) **Easting :**338454 **Longitude** (E) :151° 15′ 26″

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD..PR. MAP

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

To (m) OD (mm) 0.90 152 ID (mm) Interval Details
Cemented H P Component Type
1 1 Casing Asbestos Cement From (m) 0.00

Water Bearing Zones

To (m) Thickness (m) WBZ Type D.D.L. (m) Yield (L/s) S.W.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

(No Water Bearing Zone Details Found)

Drillers Log

From (m) 0.00 To (m) Thickness(m Drillers Description 30.48 30.48 Sandstone Geological Material Comments

30.48 Sandstone 8.53 Mudstone Sandstone Mudstone 30.48 39.01

Remarks

LOT 7 MONA VALE RD INGLESIDE

*** End of GW014465 ***

DOMESTIC

Converted From HYDSYS GW014466

Licence: 10BL010502 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)

DOMESTIC

Work Type :Bore open thru rock Work Status :(Unknown)

Construct. Method :Cable Tool Owner Type :Private

Commenced Date: Final Depth: 35.30 m 35.40 m Completion Date: 01-May-1960 **Drilled Depth:**

Contractor Name: Driller:

Assistant Driller's Name :

Property: - GREEN ACRES

GWMA:603 - SYDNEY BASIN (Unknown) Salinity: Yield:

GW Zone: -

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 63 Licensed: CUMBERLAND NARRABEEN PT 63

Standing Water Level:

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 213 - SYDNEY COAST - GEORGES RIVER Scale:1:25,000 Grid Zone:56/1

Area / District:

Elevation: Northing:6270818 Latitude (S) :33° 41' 26" Elevation Source :(Unknown) **Easting:** 340259 **Longitude** (E) :151° 16' 36"

GS Map :0055B3 MGA Zone:56 Coordinate Source : GD., PR. MAP

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

From (m) 0.00 To (m) OD (mm) 1.50 152 ID (mm) Interval Details
Cemented H P Component Type
1 1 Casing Asbestos Cement

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

0.00 Consolidated 16.40 (Unknown)

Drillers Log

To (m) Thickness(m Drillers Description
1.21 1.21 Soil
35.35 34.14 Sandstone W.: -Geological Material From (m) Comments 1.2 Soil
34.14 Sandstone Water Supply Soil Sandstone 1.21

Remarks

INGLESIDE RD NTH NARRABEEN

*** End of GW014466 ***

INDUSTRIAL

Converted From HYDSYS GW047779

Licence: 10BL110873 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC Work Type :Bore open thru rock IRRIGATION

Work Status :(Unknown) Construct. Method: Rotary Air Owner Type :Private

Commenced Date: Final Depth: 67.00 m Completion Date: 01-Oct-1979 **Drilled Depth:** 67.00 m

Contractor Name: Driller: Assistant Driller's Name :

> Property: - N/A **Standing Water Level:**

0-500 ppm GWMA: -Salinity:

GW Zone: Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 169 Licensed: CUMBERLAND NARRABEEN 169 752046

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin :212 - HAWKESBURY RIVER Grid Zone: Scale:

Area / District:

Elevation: Northing: 6271958 **Latitude (S) :**33° 40′ 48″

Elevation Source :(Unknown) **Easting :**337854 **Longitude** (E) :151° 15' 3"

GS Map :0055B3 MGA Zone:56 **Coordinate Source:**

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

From (m) To (m) OD (mm)
0.00 18.00 150 ID (mm) Interval Details

Driven into Hole H P Component Type
1 1 Casing P.V.C.

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m) 0-500 ppm 33.60 1.40 Consolidated 16.50

Drillers Log

To (m) Thickness(m Drillers Description
1.00 1.00 Soil
9.00 8.00 Clay Soft Shale From (m) Geological Material Comments 1.00 Soil
8.00 Clay Soft Shale
8.00 Sandstone
24.60 Sandstone
1.40 Water Supply 0.00 Soil Clay 1.00 9.00 Sandstone 9.00 33.60 33.60 35.00 Sandstone (Unknown) 32.00 Sandston 35.00 67.00 Sandstone

Remarks

*** End of GW047779 ***

Converted From HYDSYS GW050971

Licence:10BL109711 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s) **DOMESTIC** DOMESTIC

Work Type :Bore open thru rock Work Status: Supply Obtained Construct. Method :Cable Tool

Owner Type :Private

Commenced Date: Final Depth: 17.00 m Completion Date: 01-Apr-1979 **Drilled Depth:** 17.00 m

Contractor Name:

Driller:1435 ISELT, John Hans

Assistant Driller's Name :

Property: - N/A **Standing Water Level:**

GWMA: -Salinity: (Unknown)

GW Zone: Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County Form A: CUMBERLAND NARRABEEN L8 DP30325 (87)

Licensed: CUMBERLAND NARRABEEN 8 30325

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: **Northing:**6272670 Latitude (S) :33° 40' 25" Elevation Source :(Unknown) **Easting :**339162 **Longitude** (E) :151° 15′ 54″

GS Map :0055B3 MGA Zone:56 **Coordinate Source:**

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

H P Component Type
1 1 Casing Welded Steel From (m) -0.20

To (m) OD (mm) 1.40 165 ID (mm) Interval Details

Driven into Hole

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m) 10.90 0.10 Consolidated 5.80 (Unknown)

Drillers Log

To (m) Thickness(m Drillers Description Geological Material From (m) Comments 0.00 0.40 0.40 0.80 0.40 Topsoil Sandy 0.40 Clay Shale 10.10 Sandstone Yellow Topsoil Clay Sandstone 0.80 10.90 10.10 Tonostone Bands 0.10 Sandstone Yellow Open Water Supply 2.60 Sandstone Yellow 0.80 10.90 10.90 11.00 Ironstone Sandstone 11.00 13.60 Sandstone 13 60 3.40 Sandstone Grey Sandstone

Remarks

*** End of GW050971 ***

Converted From HYDSYS GW051799

Licence:10BL113896 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) **DOMESTIC** NOT KNOWN

Work Status: Supply Obtained Construct. Method :Cable Tool

Work Type :Bore

Owner Type :Private

Commenced Date: Final Depth: 27.50 m Completion Date :01-Jan-1981 **Drilled Depth:** 27.50 m

Contractor Name: Driller: Assistant Driller's Name :

Property: - N/A

Standing Water Level:

0-500 ppm GWMA: -Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 179 Licensed: CUMBERLAND NARRABEEN 179

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin :212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing: 6271820 Latitude (S) :33° 40' 52" Elevation Source :(Unknown) **Easting :**338166 **Longitude** (E) :151° 15′ 15″

GS Map :0055B3 MGA Zone:56 **Coordinate Source:**

Construction Negative depths indicate Above Ground Level;

H-Hole; P-Pipe; OD-Outside Diameter; ID-Inside Diameter; C-Cemented; SL-Slot Length; A-Aperture; GS-Grain Size; Q-Quantity; PL-Placement of Gravel Pack; PC-Pressure Cemented; S-Sump; CE-Centralisers

H P Component Type From (m) To (m) OD (mm) ID (mm) Interval

Casing Welded Steel 0.30 3.00 162 Suspended in Clamps

Water Bearing Zones

To (m) Thickness (m) WBZ Type
9.50 0.50 Consolidated
11.50 0.50 Unconsolidated Yield (L/s) S.W.L. (m) D.D.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m) (Unknown) (Unknown)

9.00

Drillers Log

From (m) Geological Material Comments Sandstone

 To (m)
 Thickness(m)
 Drillers Description

 9.00
 9.00
 Sandstone Multicoloured

 11.00
 2.00
 Sandstone Water Bearing

 27.50
 16.50
 Sand Silty Water Bearing
 9.00 11.00 Sand

Remarks

*** End of GW051799 ***

Converted From HYDSYS GW051861

Licence:10BL113891 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) **DOMESTIC** DOMESTIC

Work Status: Supply Obtained Construct. Method :Cable Tool

Owner Type :Private

Work Type :Bore

Commenced Date: Final Depth: 42.00 m Completion Date :01-Jan-1981 **Drilled Depth:** 42.00 m

Contractor Name:

Driller:

GWMA: -

GW Zone: -

Assistant Driller's Name :

Property: - N/A

Standing Water Level:

Salinity: (Unknown)

Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN L52 (179) Licensed: CUMBERLAND NARRABEEN L52 (179)

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Northing:6271745 Latitude (S) :33° 40' 55" **Elevation:**

Elevation Source :(Unknown) **Easting :**338199 **Longitude** (E) :151° 15′ 16″

GS Map :0055B3 MGA Zone:56 **Coordinate Source:**

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

H P Component Type
1 1 Casing Threaded Steel

From (m) To (m) OD (mm) ID (mm) Interval Details
0.30 1.00 152 Suspended in Clamps

Water Bearing Zones

To (m) Thickness (m) WBZ Type
19.00 1.00 Unconsolidated
39.00 1.00 Unconsolidated Yield (L/s) S.W.L. (m) D.D.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m) 18.00 38.00 9.40 27.50 (Unknown) (Unknown)

Drillers Log

 LOG

 To (m)
 Thickness(m)
 Drillers
 Description

 18.00
 18.00
 Sandstone Coloured

 38.00
 20.00
 Sand Silty Water Bearing

 40.00
 2.00
 Sand Water Bearing

 42.00
 2.00
 Sand Silty
 From (m) Geological Material Comments 0.00 Sandstone 18.00 38.00 Sand Sand 40.00

Remarks

*** End of GW051861 ***

DOMESTIC

Converted From HYDSYS GW055934

Licence :10BL121705 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s)

DOMESTIC

Work Type :Bore open thru rock Work Status: (Unknown)

Construct. Method :Cable Tool Owner Type :Private

Commenced Date: Final Depth: 60.00 m Completion Date: 01-Dec-1981 **Drilled Depth:** 60.00 m

Contractor Name:

Driller:1441 BARRETT, Roy Max

Assistant Driller's Name :

Property: - N/A **Standing Water Level:**

GWMA: -Salinity: Good

GW Zone: Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN L16 (87) Licensed: CUMBERLAND NARRABEEN L16 (P+ Port 87)

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 213 - SYDNEY COAST - GEORGES RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing: 6272692 Latitude (S) :33° 40' 25"

Elevation Source :(Unknown) **Easting :**340320 **Longitude** (E) :151° 16' 39"

GS Map :0055B3 MGA Zone:56 **Coordinate Source:**

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

From (m) 0.00 To (m) OD (mm) 3.00 200 ID (mm) Interval Details
Suspended in Clamps H P Component Type
1 1 Casing Threaded Steel

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) From (m) Salinity (mg/L) 15.00 6.00

45.00 Consolidated

Drillers Log

To (m) Thickness(m Drillers Description 34.00 34.00 Sandstone Water Sup 34.00 Clay Seams Water S From (m) Geological Material Comments 34.00 Sandstone Water Supply 34.00 Clay Seams Water Supply 26.00 Sandstone White Water Supply 0.00 Sandstone Clay Sandstone 34.00

Remarks

*** End of GW055934 ***

Converted From HYDSYS GW055984

Licence:10BL121849 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s) DOMESTIC

STOCK

DOMESTIC Work Type :Bore Work Status :(Unknown) STOCK

Construct. Method :Cable Tool Owner Type :Private

Commenced Date: Final Depth: 53.00 m Completion Date: 01-Dec-1981 **Drilled Depth:** 53.00 m

Contractor Name: Driller: Assistant Driller's Name :

Property: - N/A

Standing Water Level:

GWMA: -Salinity: (Unknown)

GW Zone: Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 203 Licensed: CUMBERLAND NARRABEEN 203

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin :212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing:6272867 Latitude (S) :33° 40' 19" Elevation Source :(Unknown) **Easting :**339776 **Longitude** (E) :151° 16′ 18″

GS Map :0055B3 MGA Zone:56 **Coordinate Source:**

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

From (m) -0.30 To (m) OD (mm) 1.70 152 H P Component Type
1 1 Casing (Unknown)

ID (mm) Interval Details
Suspended in Clamps

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) Yield (L/s) D.D.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m) 19.00 27.00 1.00 (Unknown) 1.00 (Unknown) (Unknown) (Unknown) 18.00 26.00 48.00 49.00 1.00 (Unknown) (Unknown)

Drillers Log

From (m) 0.00 To (m) 16.00 Thickness(m Drillers Description Geological Material Comments 16.00 Sandstone Sandstone 16.00 18.00 2.00 Ironstone Ironstone 28.00 30.00 44.00 45.00 18 00 10.00 Sandstone Shaley Water Bearing Sandstone 28.00 30.00 2.00 Ironstone 14.00 Sand Silty 1.00 Ironstone Ironstone Sand 44.00 Ironstone 45.00 53.00 8.00 Sand Silty Water Bearing Sand

Remarks

*** End of GW055984 ***

STOCK

GW057745 Converted From HYDSYS

Licence :10BL123454 Licence Status Lapsed

 Work Type :Bore open thru rock
 Authorised Purpose(s)
 Intended Purpose(s)

 Work Status :(Unknown)
 DOMESTIC
 IRRIGATION

Construct. Method :Cable Tool

Owner Type :Private

Commenced Date: Final Depth: 150.00 m Completion Date: 01-Sep-1982 Drilled Depth: 150.00 m

Contractor Name:

Driller :1435 ISELT, John Hans

Assistant Driller's Name :

Property: - N/A

GWMA: - Salinity: 0-500 ppm

GW Zone: - Yield:

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

Form A :CUMBERLANDNARRABEENL10 DP25951 (69)Licensed :CUMBERLANDNARRABEEN10 25951

Standing Water Level:

Region: 10 - SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 212 - HAWKESBURY RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District:

 Elevation :
 Northing :6271306
 Latitude (S) :33° 41' 9"

 Elevation Source :(Unknown)
 Easting :338540
 Longitude (E) :151° 15' 29"

GS Map :0055B3 MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

Water Bearing Zones

 From (m)
 To (m) Thickness (m) WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 24.80
 25.00
 0.20 Consolidated
 25.00
 0.03
 Fresh

 145.10
 146.00
 0.90 Consolidated
 32.00
 0.27
 Fresh

Drillers Log

From (m)	To (m)	Thickness(m Drillers Description	Geological Material Comments
0.00	0.60	0.60 Topsoil	Topsoil
0.60	0.90	0.30 Gravel Sandy	Gravel
0.90	12.10	11.20 Sandstone Yellow Silty	Sandstone
12.10	13.90	1.80 Sandstone Silty	Sandstone
13.90	24.80	10.90 Sandstone Yellow Silty	Sandstone
24.80	25.00	0.20 Sandstone Yellow Silty Open	Sandstone
25.00	37.10	12.10 Sandstone Red Silty	Sandstone
37.10	49.00	11.90 Sandstone Yellow Silty	Sandstone
49.00	52.20	3.20 Sandstone Grey	Sandstone
52.20	135.30	83.10 Sandstone Yellow	Sandstone
135.30	138.50	3.20 Clay Sandy	Clay
138.50	145.10	6.60 Sandstone Yellow	Sandstone
145.10	146.00	0.90 Sandstone Yellow Open Water Supply	Sandstone
146.00	150.00	4.00 Sandstone	Sandstone

Remarks

*** End of GW057745 ***

Converted From HYDSYS GW059821

Licence: 10BL151475 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) Work Type :Bore open thru rock **DOMESTIC** DOMESTIC STOCK Work Status: (Unknown) STOCK

Construct. Method: Rotary Owner Type :Private

Commenced Date: 01-Feb-1993 Final Depth: 116.00 m Completion Date: 03-Feb-1993 **Drilled Depth:** 116.00 m

Contractor Name :INTERTECH DRILLING

Driller:1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Property: - SMITH **Standing Water Level:** 14.50 m

140.00 mg/L Fresh GWMA: -Salinity: GW Zone: Yield: 1.30 L/s

Site Details

Site Chosen By Parish County Portion/Lot DP

Form A: CUMBERLAND NARRABEEN 169 Licensed: CUMBERLAND NARRABEEN 169 752046

Region: 10 - SYDNEY SOUTH COAST HORNSBY CMA Map:9130-4S River Basin: 212 - HAWKESBURY RIVER Scale:1:25,000 Grid Zone:56/1

Area / District:

Northing:6272001 Latitude (S) :33° 40' 46" **Elevation:**

Elevation Source :(Unknown) **Easting :**337729 Longitude (E) :151° 14' 58"

GS Map :0055A3 MGA Zone:56 Coordinate Source :GD..ACC.MAP

Negative depths indicate Above Ground Level; Construction

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

From (m) To (m) OD (mm)
42.00 116.00 152 ID (mm) Interval Details

Down Hole Hammer Component Type Hole Hole 1 Casing 1 Casing PVC Class 9 -0.50 4.70 (Unknown) 4.70 Pressure Cemented 0.00

Water Bearing Zones

Casing

To (m) Thickness (m) WBZ Type S.W.L. (m) Yield (L/s) Hole Depth (m) From (m) 83.00 D.D.L. (m) Duration (hr) Salinity (mg/L) 107.50 14.50 116.00

Drillers Log

From (m) 42.00 Geological Material Comments 60.00

To (m) Thickness(m Drillers Description
60.00 18.00 SANDSTONE/GREY F.G.
61.00 1.00 SANDSTONE/BED SHALE
61.20 0.20 FRACTURED
68.00 6.80 SANDSTONE GREY F.G.
83.00 15.00 SANDSTONE GREY SMALL FRACT/BED SHALES
107.00 24.00 SANDSTONE GREY SMALL FRACT/BED SHALES
107.50 0.50 FRACTURED W.D.
116.00 8.50 SANDSTONE COURSE OPEN GRAIN W.B. 61.00 61.20 68.00 83.00 107.00

Remarks

Previous Lic No: 10BL131472 due to alteration work.

*** End of GW059821 ***

Converted From HYDSYS GW060293

Licence :10BL127611 Licence Status Cancelled

> Authorised Purpose(s) Intended Purpose(s) IRRIGATION IRRIGATION

> > Scale:1:25,000

Work Type :Bore open thru rock Work Status :(Unknown)

Construct. Method :Cable Tool Owner Type :Private

Commenced Date: Final Depth: 34.00 m Completion Date: 01-Sep-1986 **Drilled Depth:** 34.00 m

Contractor Name:

Driller:1435 ISELT, John Hans

Assistant Driller's Name :

Property: - N/A **Standing Water Level:**

GWMA: -Salinity: Fresh

GW Zone: Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County Form A: CUMBERLAND NARRABEEN L2 DP52208 (139)

Licensed: CUMBERLAND NARRABEEN LT11 DP52208 PT139 Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-4S HORNSBY

Grid Zone:56/1

River Basin: 212 - HAWKESBURY RIVER Area / District:

Elevation: Northing: 6271542 Latitude (S) :33° 41' 1" Elevation Source :(Unknown) **Easting :**337892 **Longitude** (**E**) :151° 15' 4"

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD..ACC.MAP

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

H P Component Type
1 1 Casing Welded Steel

From (m) -0.20 To (m) OD (mm) 4.40 168 ID (mm) Interval Details

Driven into Hole

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) From (m) Salinity (mg/L) 29.20 1.10 Consolidated 18.00

Drillers Log

To (m) Thickness(m Drillers Description
1.40 1.40 Soil Sandy
3.60 2.20 Sandstone Yellow
3.60 2.20 Clav Laver From (m) Geological Material Comments ness(m Drillers Description
1.40 Soil Sandy
2.20 Sandstone Yellow
2.20 Clay Layer
2.60 Sandstone Grey
1.10 Sandstone Grey Coarse Water Supply Soil Sandstone 1.40 1.40 Clay Sandstone Sandstone 3.60 29.20 29.20 30.30 30.30 34.00 3.70 Sandstone Grey Sandstone

Remarks

*** End of GW060293 ***

STOCK

Converted From HYDSYS GW060467

Licence :10BL122807 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC Work Type :Bore open thru rock IRRIGATION Work Status: (Unknown) IRRIGATION

Construct. Method: (Unknown) Owner Type :Private

Commenced Date: Final Depth: 130.10 m Completion Date: 01-Jan-1982 **Drilled Depth:** 0.00

Contractor Name: Driller: Assistant Driller's Name :

Property: - N/A

Standing Water Level: GWMA: -(Unknown) Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County Form A: CUMBERLAND NARRABEEN L14 DP12115 (81)

Licensed: CUMBERLAND NARRABEEN 15 12115

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 213 - SYDNEY COAST - GEORGES RIVER Scale :1:25,000 Grid Zone:56/1

Area / District:

Northing:6271903 **Elevation:** Latitude (S) :33° 40' 50" Elevation Source :(Unknown) **Easting :**339251 **Longitude** (E) :151° 15' 57"

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD.,ACC.MAP

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

H P Component Type
1 1 Casing Asbestos Cement From (m) 0.00

To (m) OD (mm) ID (mm) Interval Details
9.10 152 Driven into Hole

Water Bearing Zones

To (m) Thickness (m) WBZ Type D.D.L. (m) Yield (L/s) S.W.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

(No Water Bearing Zone Details Found)

Drillers Log

To (m) Thickness(m Drillers Description Geological Material Comments

Remarks

*** End of GW060467 ***

Converted From HYDSYS GW061466

Licence:10BL133892 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC

Work Type :Bore Work Status: (Unknown) Construct. Method: (Unknown)

Owner Type :Private

Commenced Date: Final Depth: 76.20 m 0.00 Completion Date: 01-Jan-1983 **Drilled Depth:**

Contractor Name: Driller: Assistant Driller's Name :

Property: - N/A

Standing Water Level:

GWMA: -(Unknown) Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 61 Licensed: CUMBERLAND NARRABEEN

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin :212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing:6272709 Latitude (S) :33° 40' 24" Elevation Source :(Unknown) **Easting :**339495 **Longitude** (E) :151° 16' 7"

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD.,ACC.MAP

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers
H P Component Type From (m) To (m) OD (mm) ID (mm) Interval Details
1 0 Casing P.V.C. 0.00 0.00 152 (Unknown)

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

(No Water Bearing Zone Details Found)

Drillers Log

To (m) Thickness(m Drillers Description From (m) Geological Material Comments

Remarks

*** End of GW061466 ***

Converted From HYDSYS GW062272

Licence: 10BL143759 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s) DOMESTIC IRRIGATION

Work Type :Bore open thru rock

Work Status :(Unknown)

STOCK

Construct. Method: (Unknown) Owner Type :Private

Commenced Date: Final Depth: 114.00 m **Completion Date: Drilled Depth:** 0.00

Contractor Name:

Driller:

Assistant Driller's Name : Property: - N/A

Standing Water Level:

GWMA: -(Unknown) Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 81 Licensed: CUMBERLAND NARRABEEN PT81

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 213 - SYDNEY COAST - GEORGES RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing: 6271592 Latitude (S) :33° 41' 0" Elevation Source :(Unknown) **Easting :**339076 **Longitude** (E) :151° 15′ 50″

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD.,ACC.MAP

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers
H P Component Type From (m) To (m) OD (mm) ID (mm) Interval Details
1 0 Casing (Unknown) 0.00 0.00 150 (Unknown)

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

(No Water Bearing Zone Details Found)

Drillers Log

To (m) Thickness(m Drillers Description From (m) Geological Material Comments

Remarks

*** End of GW062272 ***

GW063622 Converted From HYDSYS

Licence :10BL135164 Licence Status Active

 Authorised Purpose(s)
 Intended Purpose(s)

 DOMESTIC
 DOMESTIC

Work Type :Bore Work Status :(Unknown) Construct. Method :Cable Tool

Owner Type :Private

Commenced Date: Final Depth: 46.00 m Completion Date: 01-Sep-1986 Drilled Depth: 46.00 m

Contractor Name:

Driller :1435 ISELT, John Hans

Assistant Driller's Name :

Property: - N/A Standing Water Level:

GWMA: - Salinity: Fresh

GW Zone: - Yield:

Site Details

Site Chosen By County Parish Portion/Lot DP
Form A :CUMBERLAND NARRABEEN L2 DP30325 (87)

Licensed :CUMBERLAND NARRABEEN 2 30325

Region: 10-SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 212-HAWKESBURY RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District:

 Elevation :
 Northing :6273154
 Latitude (S) :33° 40' 10"

 Elevation Source :(Unknown)
 Easting :340363
 Longitude (E) :151° 16' 41"

GS Map :0055B3 MGA Zone :56 Coordinate Source :GD.,ACC.MAP

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

 H
 P
 Component Type
 From (m)
 To (m)
 OD (mm)
 ID (mm)
 Interval
 Details

 1
 1
 Casing
 Steel
 -0.30
 6.20
 168
 Cemented

 1
 1
 Casing
 Pressure Cemented
 0.00
 6.20
 168
 (Unknown)

Water Bearing Zones

 From (m)
 To (m) Thickness (m) WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 22.30
 22.50
 0.30 Consolidated
 20.00
 0.10
 Fresh

 37.20
 37.80
 0.60 Consolidated
 9.00
 0.30
 Fresh

Drillers Log

Remarks

*** End of GW063622 ***

STOCK

STOCK

Converted From HYDSYS GW064440

Licence:10BL138571 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC Work Type :Bore

Work Status :(Unknown) Construct. Method :Rotary Air Owner Type :Private

Commenced Date: Final Depth: 150.00 m Completion Date: 01-Nov-1988 **Drilled Depth:** 0.00

Contractor Name: Driller: Assistant Driller's Name :

Property: - N/A

Standing Water Level:

GWMA: -(Unknown) Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County Form A: CUMBERLAND NARRABEEN L1 DP213794 (83)

Licensed: CUMBERLAND NARRABEEN LT1 DP213794 Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE

River Basin :212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing: 6271952 Latitude (S) :33° 40' 48" Elevation Source :(Unknown) **Easting :**338477 **Longitude** (E) :151° 15' 27"

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD.,ACC.MAP

Construction Negative depths indicate Above Ground Level;

H-Hole; P-Pipe; OD-Outside Diameter; ID-Inside Diameter; C-Cemented; SL-Slot Length; A-Aperture; GS-Grain Size; Q-Quantity; PL-Placement of Gravel Pack; PC-Pressure Cemented; S-Sump; CE-Centralisers

H P Component Type From (m) To (m) OD (mm) ID (mm) Interval

Casing Steel 0.00 33.00 168 Driven into Hole

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

6.00 Consolidated (Unknown)

Drillers Log

To (m) Thickness(m Drillers Description Geological Material From (m) Comments

Remarks

PUMP TEST DATA SUSPECT

*** End of GW064440 ***

GW064441

Licence :10BL160105 Licence Status Active

Drilled Depth:

 $\label{eq:Authorised Purpose} \textbf{Authorised Purpose}(s) \qquad \qquad \textbf{Intended Purpose}(s)$

 Work Type :Bore
 INDUSTRIAL
 INDUSTRIAL

 Work Status :Supply Obtained
 RECREATION (GROUNDWATER)
 RECREATION (GROUNDWATER)

150.00 m

Work Status :Supply Obtained Construct. Method :Down Hole Hammer

Owner Type :Private

Commenced Date: 23-Aug-1990

Completion Date: 18-Sep-1990

Final Depth: 150.00 m

Contractor Name :INTERTECH DRILLING

Driller :1466 FERGUSON, Gary

Assistant Driller's Name :

Property: - HAMAZKAINE Standing Water Level: 31.90 m

GWMA: - Salinity: Good
GW Zone: - Yield: 1.25 L/s Cumulative

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

Form A :CUMBERLAND NARRABEEN 1//808703 Licensed :CUMBERLAND NARRABEEN 1 808703

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin : Grid Zone : Scale :

Area / District :

Elevation Source: Easting: 338950 Longitude (E):151° 15' 46"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

 H
 P
 Component Type
 From (m)
 To (m)
 OD (mm)
 ID (mm)
 Interval
 Details

 1
 Hole
 Hole
 0.00
 150.00
 152
 Down Hole
 Hammer

1 1 Casing Steel -0.50 6.50 168.3 158.7 C: .5-6.5m; Seated on Bottom

Water Bearing Zones

 From (m)
 To (m)
 Thickness (m)
 WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 84.00
 86.00
 2.00
 0.02
 86.00
 86.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00
 150.00

Drillers Log

To (m) Thickness(m Drillers Description
6.00 6.00 SANDSTONE
9.00 3.00 SANDSTONE /FINE CLAY
21.00 12.00 BROWN SANDSTONE,SILT AND CLAY
24.00 3.00 BLACK SANDSTONE,SILT AND CLAY
48.00 24.00 RED SANDSTONE,IRON AND CLAY
87.00 39.00 PINK SANDSTONE, SILT AND CLAY
96.00 9.00 RED SANDSTONE,IRON AND CLAY
99.00 3.00 DARK GREY SHALE AND CLAY
99.00 3.00 DARK GREY SHALE AND CLAY
117.00 18.00 PALE PINK SANDSTONE AND CLAY
117.00 18.00 PALE PINK SANDSTONE AND CLAY Geological Material Sandstone Sandstone From (m) 0.00 Comments 6.00 9.00 Sandstone 21.00 24.00 Sandstone Sandstone 48.00 Sandstone Sandstone Shale Sandstone 87.00 96.00 99.00 117.00 150.00 33.00 WHITE SANDSTONE AND CLAY Sandstone

Remarks

PREVIOUS LIC NO: 10BL141627

*** End of GW064441 ***

Converted From HYDSYS GW064442

Licence:10BL160104 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)

45.00 m

Work Type :Bore **INDUSTRIAL** INDUSTRIAL RECREATION (GROUNDWATER) Work Status: Supply Obtained RECREATION (GROUNDWATER)

Construct. Method :Rotary Air Owner Type :Private

Commenced Date: Final Depth: 115.00 m Completion Date: 01-Nov-1988 **Drilled Depth:** 115.00 m

Contractor Name:

Driller: Assistant Driller's Name :

> Property: - HAMAZKAINE **Standing Water Level:**

GWMA: -Salinity: Good

GW Zone: Yield: 0.30 L/s

Site Details

Site Chosen By Parish Portion/Lot DP County Form A: CUMBERLAND NARRABEEN LT 1 DP 808703

Licensed: CUMBERLAND NARRABEEN 1 808703

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 212 - HAWKESBURY RIVER Scale :1:25,000 Grid Zone:56/1

Area / District:

Elevation: Northing:6272107 Latitude (S) :33° 40' 43" Elevation Source :(Unknown) **Easting :**338526 Longitude (E) :151° 15' 29"

GS Map :0055B3 MGA Zone:56 Coordinate Source :GD..ACC.MAP

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

H P Component Type
1 1 Casing P.V.C.

From (m) To (m) OD (mm)
0.00 13.00 168 ID (mm) Interval Details

Driven into Hole

Water Bearing Zones

To (m) Thickness (m) WBZ Type 115.00 25.00 (Update) S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) From (m) Salinity (mg/L) 90.00 45.00

25.00 (Unknown)

Drillers Log

To (m) Thickness(m Drillers Description 3.00 3.00 Gravel 100.00 97.00 Sandstone Water Co-Geological Material From (m) Comments 3.00 Gravel 97.00 Sandstone Water Supply 15.00 Shale Water Supply Gravel Sandstone 3.00 100.00 Shale

Remarks

PREVIOUS LIC NO: 10BL138709

*** End of GW064442 ***

DOMESTIC

GW068615

Licence :10BL141903 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)

Work Type :Bore Work Status :(Unknown) Construct. Method :Rotary

Owner Type:

Commenced Date :10-Feb-1981 Final Depth : 125.00 m Completion Date :17-Feb-1981 Drilled Depth : 125.00 m

Contractor Name: SLADE DRILLING

Driller: SLADE, W.E.

Assistant Driller's Name :

Property: - WILLCOCKS Standing Water Level: 15.50 m

GWMA: - Salinity:

GW Zone: - **Yield**: 0.45 L/s

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

Form A :CUMBERLAND NARRABEEN 174//752046 Licensed :CUMBERLAND NARRABEEN 174 752046

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

 Elevation :
 Northing :6272464
 Latitude (S) :33° 40' 32"

 Elevation Source :
 Easting :338486
 Longitude (E) :151° 15' 28"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

 H
 P
 Component Type
 From (m)
 To (m)
 OD (mm)
 ID (mm)
 Interval
 Details

 1
 Hole
 Hole
 0.00
 125.00
 155
 Rotary

 1
 1
 Casing
 P.V.C.
 0.00
 12.00
 155
 Driven into Hole

Water Bearing Zones

From (m)	To (m) Thi	ickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
5.00	6.00	1.00			0.06	9.00		
91.00	93.00	2.00			0.16	94.00		
99.00	100.00	1.00	0.00		0.08	101.00		
114 00	116 00	2 00	15 50		0.15	125 00		

Drillers Log

	G				
From (m)	To (m)	Thickness(m]	Drillers Description	Geological Material	Comments
0.00	2.00	2.00 5			
2.00	27.00	25.00 \$	SOFT MUDSTONE AND SHALE		
27.00	107.00	80.00 1	HARD SANDSTONE		
107.00	109.00	2.00 5	SHALE		
109.00	125.00	16.00 \$	SANDSTONE		

Remarks

*** End of GW068615 ***

GW100017

Licence :10BL153221 Licence Status Active

 Work Type :Bore
 DOMESTIC
 DOMESTIC

 Work Status :(Unknown)
 IRRIGATION
 IRRIGATION

 Construct. Method :Other
 STOCK
 STOCK

Owner Type:

Commenced Date : Final Depth : 151.00 m **Completion Date :**23-Oct-1993 **Drilled Depth :** 151.00 m

Contractor Name :INTERTECH DRILLING

Driller :1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Property: - SANTA MULE Standing Water Level:

GWMA: - Salinity: 200.00 mg/L

GW Zone: - Yield:

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

Form A :CUMBERLAND NARELLAN 38 12115 Licensed :CUMBERLAND NARRABEEN 38 12115

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation : Northing :6271502 Latitude (S) :33 $^{\circ}$ 41 $^{\circ}$ 3" Elevation Source : Easting :339206 Longitude (E) :151 $^{\circ}$ 15 $^{\circ}$ 55"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

 H
 P
 Component Type
 From (m)
 To (m)
 OD (mm)
 ID (mm)
 Interval Details

 1
 Hole
 Hole
 6.00
 203
 Rotary Air

 1
 Hole
 Hole
 151.00
 156
 Rotary Air

 1
 1 Casing
 Steel
 -0.50
 6.50
 C: 0-6m; Seated on Bottom

Water Bearing Zones

From (m)	To (m) Th	ickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
12.50	13.00	0.50				6.00		150.00
60.00	80.00	20.00			0.25	6.00		200.00
99.00	104.00	5.00			0.05	6.00		200.00
139.00	150.00	11.00	62.00		0.10	6.00		

Drillers Log

Dimers	LUg			
From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	2.00	2.00 OVERBURDEN & FILLING		
2.00	3.50	1.50 ORANGE MED. GRAIN S.S.		
3.50	3.80	0.30 WHITE CLAY BAND		
3.80	5.00	1.20 ORANGE & WHITE MED. GRAIN S.S.		
5.00	41.00	36.00 WHITE S.S. & BED CLAY		
41.00	41.20	0.20 SMALL CAVITY		
41.20	50.00	8.80 WHITE S.S. & BED SHALE		
50.00	51.00	1.00 WHITE S.S. & BED SHALE		
51.00	51.50	0.50 SHALE BANDS		
51.50	60.00	8.50 WHITE S.S. & BED SHALE		
60.00	80.00	20.00 WHITE OPEN S.S. & WATER BEARING		
80.00	99.00	19.00 WHITE/ORANGE S.S. CLAY IN MATRIX		
99.00	99.20	0.20 SMALL CAVITY		
99.20	104.00	4.80 WHITE S.S. & BED SHALE		
104.00	112.00	8.00 WHITE GREY S.S. MED. GRAIN		
112.00	115.00	3.00 WHITE S.S. & BED SHALE		
115.00	132.00	17.00 WHITE L.G.S.S. WITH SMALL FRACTURED		
132.00	137.00	5.00 WHITE S.S. OPEN WATER BEARING		
137.00	139.00	2.00 WHITE S.S. & BED SHALE		
139.00	151.00	12.00 WHITE S.S. MED. GRAIN		
151.00	151.00	0.00 E.O.H.		

Remarks

*** End of GW100017 ***

GW100648

Licence :10BL157628 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)

Work Type :Bore DOMESTIC DOMESTIC
Work Status :(Unknown) STOCK

Construct. Method: Rot. Rev. Circ. Air

Owner Type:

Commenced Date : Final Depth : 120.00 m **Completion Date :**13-May-1996 **Drilled Depth :** 120.00 m

Contractor Name :J.H. ISELT

Property: - N/A

Driller :1435 ISELT, John Hans

Assistant Driller's Name :

ner's Name:

GWMA: - Salinity: Fresh

Standing Water Level:

GW Zone: - Yield:

Site Details

Site Chosen ByCountyParishPortion/Lot DPDrillerForm A :CUMBERLANDNARRABEEN2//595804Licensed :CUMBERLANDNARRABEEN2 595804

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

 Elevation :
 Northing :6273489
 Latitude (S) :33° 39' 59"

 Elevation Source :
 Easting :339622
 Longitude (E) :151° 16' 13"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;S-Sump;CE-Centralisers

 H
 P
 Component Type
 From (m)
 To (m)
 OD (mm)
 ID (mm)
 Interval
 Details

 1
 Hole
 Hole
 0.00
 120.00
 150
 Rotary

1 1 Casing P.V.C. -0.30 3.00 160 C: 0-3m; Driven into Hole

Water Bearing Zones

 From (m)
 To (m) Thickness (m) WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 59.50
 59.70
 0.20
 30.00
 120.00
 0.12
 120.00
 1.00
 Fresh

Drillers Log

 From (m)
 To (m)
 Thickness(m)
 Drillers Description
 Geological Material
 Comments

 0.00
 0.30
 0.30 Topsoil
 <td

Remarks

*** End of GW100648 ***

GW100838

Licence:10BL157556 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC

STOCK

Work Type :Bore Work Status: (Unknown) Construct. Method: Rotary

Owner Type:

Commenced Date: Final Depth: 90.50 m Completion Date :27-Mar-1996 **Drilled Depth:** 90.50 m

Contractor Name :INTERTECH DRILLING

Driller:1648 AULD, Richard

Assistant Driller's Name :

Property: - N/A **Standing Water Level:**

GWMA: -100.00 mg/L Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County Client Driller Form A: CUMBERLAND NARRABEEN 13//803203 Licensed: CUMBERLAND NARRABEEN 13 803203

Region: 10 - SYDNEY SOUTH COAST CMA Map:

Grid Zone: River Basin: Scale:

Area / District:

Elevation: Northing: 6272390 Latitude (S) :33° 40' 35" **Elevation Source: Easting :**339276 **Longitude** (E) :151° 15′ 58″

GS Map: **Coordinate Source:** MGA Zone:56

Negative depths indicate Above Ground Level; Construction

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

To (m) OD (mm) 1.30 210 ID (mm) Interval Details
Rotary Component Type From (m) 0.00 Hole Hole 210 158 Hole Hole 1.30 10.80 Rotary 10.80 90.50 Hole Hole Rotary

1 Casing Steel -1.00 11.00 168.3 158.7 C: -.1-10.8m; Welded; Driven into Hole

Water Bearing Zones

From (m)	To (m) Th	ickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
35.50	40.50	5.00			0.10	42.50	0.25	80.00
60.30	65.80	5.50			0.40	66.50	0.25	80.00
78.00	78.70	0.70			0.20	78.50	0.25	100.00

Drillers Log

Dillicis	LUS			
From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	0.80	0.80 SANDY LOAM		
0.80	1.30	0.50 GREY CLAY		
1.30	26.50	25.20 SANDSTONE BROWN/GREY BANDS CLAY MATRIX		
26.50	27.40	0.90 GREY CLAY		
27.40	28.50	1.10 IRON STONE		
28.50	29.50	1.00 SANDSTONE, GREY, QUARTZ MATRIX		
29.50	30.00	0.50 IRONSTONE		
30.00	30.60	0.60 GREY MUDSTONE		
30.60	35.50	4.90 SANDSTONE; LT GREY, CLAY MATRIX		
35.50	40.50	5.00 SANDSTONE, BWN, QUARTZ MAT		
40.50	49.70	9.20 SANDSTONE; LT GREY, CLAY MATRIX		
49.70	51.10	1.40 IRONSTONE		
51.10	59.20	8.10 SANDSTONE; LT. GREY, COARSE GRAIN		
59.20	60.30	1.10 IRONSTONE		
60.30	65.80	5.50 SANDSTONE LT.GREY, PEBBLY QUARTZ MATRIX		
65.80	71.50	5.70 SANDSTONE LT. GREY C.G.		
71.50	71.90	0.40 GREY MUDSTONE		
71.90	78.70	6.80 SANDSTONE, LT. BWN, NARROW QUARTZ BANDS		
78.70	80.90	2.20 IRONSTONE		
80.90	82.30	1.40 SANDSTONE LT GREY, QUARTZ MATRIX		
82.30	86.40	4.10 SANDSTONE; LT GREY C.G.		
86.40	90.50	4.10 BANDED SANDSTONE - IRONSTONE, SOFT & FRACTURED		

Remarks

*** End of GW100838 ***

GW101494

Licence :10BL158124 Licence Status Cancelled

Authorised Purpose(s)
RECREATION (GROUNDWATER)
Intended Purpose(s)
IRRIGATION

Work Type :Bore Work Status :(Unknown) Construct. Method :Rotary

Owner Type:

Commenced Date : Final Depth : 140.00 m **Completion Date :**29-Aug-1997 **Drilled Depth :** 140.00 m

Contractor Name: B.B. DRILLING

Driller :1649 BARRETT, Michael Gerard

Assistant Driller's Name :

Property: - N/A Standing Water Level:

GWMA: - Salinity:

GW Zone: - Yield:

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

Form A :CUMBERLAND NARRABEEN 2//525908 Licensed :CUMBERLAND NARRABEEN 2 525908

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

 Elevation :
 Northing :6270626
 Latitude (S) :33° 41' 32"

 Elevation Source :
 Easting :340256
 Longitude (E) :151° 16' 35"

2. Sugardo (2)

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

H P Component Type From (m) To (m) OD (mm) ID (mm) Interval Details
1 Hole Hole 0.00 140.00 150 Percussion

1 1 Casing Steel 0.00 3.00 150 Suspended in Clamps

Water Bearing Zones

 From (m)
 To (m) Thickness (m) WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 14.90
 120.00
 105.10
 14.90
 110.00
 0.20
 140.00
 8.00
 Good

Drillers Log

From (m) To (m) Thickness(m Drillers Description Geological Material Comments

 rom (m)
 To (m)
 Thickness(m
 Drillers Description

 0.00
 60.00
 60.00
 SANDSTONE, DARK GREY

 60.00
 120.00
 60.00
 SANDSTONE, WHITE

 120.00
 140.00
 20.00
 SHALE, DARK GREY

Remarks

Form A Remarks:

COMMENT IN COMPLETION DETAILS. "OPEN HOLE"

*** End of GW101494 ***

GW101503

Licence :10BL158708 Licence Status Active

Authorised Purpose(s)Intended Purpose(s)INDUSTRIALINDUSTRIAL

Work Type :Bore

Work Status :Supply Obtained Construct. Method :Cable Tool Owner Type :Private

Commenced Date: Final Depth: 46.00 m Completion Date: 08-Feb-1984 Drilled Depth: 46.00 m

Contractor Name :J.H. ISELT

Driller :986 ISELT, John Hans

Assistant Driller's Name :

Property: - SMITH Standing Water Level: 14.00 m

GWMA: - Salinity: Fresh

GW Zone : - Yield : 1.25 L/s

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

From A CHIMPERIAND
NARRABEEN
160 752046

Form A :CUMBERLAND NARRABEEN 169 752046
Licensed :CUMBERLAND NARRABEEN 169 752046

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin : Grid Zone : Scale :

Area / District :

 Elevation :
 Northing :6272001
 Latitude (S) :33° 40' 46"

 Elevation Source :
 Easting :337755
 Longitude (E) :151° 14' 59"

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

 H
 P
 Component Type
 From (m)
 To (m)
 OD (mm)
 ID (mm)
 Interval
 Details

 1
 Hole
 Hole
 0.00
 46.00
 152
 Percussion

1 1 Casing P.V.C. -0.50 4.70 C: 0-4.7m; Driven into Hole

Water Bearing Zones

From (m)	To (m) Thickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
12.10	12.40 0.30	8.00	16.00	0.19	16.00		Fresh
30 80	31 30 0 50	14 00	17 00	1 25	46 00		Fresh

Drillers Log

	U			
From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	2.10	2.10 SANDY GRAVEL	Gravel	
2.10	8.50	6.40 YELLOW SANDSTONE	Sandstone	
8.50	9.30	0.80 GREY SANDSTONE	Sandstone	
9.30	12.10	2.80 YELLOW SANDSTONE	Sandstone	
12.10	12.40	0.30 GREY SANDSTONE(OPEN AND W.B.)	Sandstone	
12.40	30.30	17.90 GREY SANDSTONE	Sandstone	
30.30	30.80	0.50 SHALE	Shale	
30.80	31.30	0.50 GREY SANDSTONE(COARSE OPEN & W.B.	Sandstone	
31.30	36.40	5.10 GREY SANDSTONE	Sandstone	
36.40	36.70	0.30 SHALE	Shale	
36.70	46.00	9.30 GREY SANDSTONE	Sandstone	

Remarks

Form A Remarks:

13 STAGE GRUNDFOR SUBMERSIBLE 415 VOLT 3 PHASE 1 1/2 INCH DIAMETER DELIVERY PUMP

*** End of GW101503 ***

GW101504

Licence :10BL158707 Licence Status Active

Work Type :Bore Authorised Purpose(s)
INDUSTRIAL

Work Status :Supply Obtained

Construct. Method :Rotary
Owner Type :Private

Commenced Date: Final Depth: 48.00 m Completion Date: 09-Feb-1993 Drilled Depth: 48.00 m

Contractor Name :INTERTECH DRILLING

Driller :1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Property: - SMITH

GWMA: - **Salinity**: 180.00 mg/L **GW Zone**: - **Yield**: 1.60 L/s

Site Details

Site Chosen By

County

Parish

Portion/Lot DP

Form A :CUMBERLAND NARRABEEN LT 169 DP 752046 Licensed :CUMBERLAND NARRABEEN 169 752046

Standing Water Level:

Intended Purpose(s)

INDUSTRIAL

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation : Northing :6271942 Latitude (S) :33 $^{\circ}$ 40 $^{\circ}$ 48 $^{\circ}$ Elevation Source : Easting :337859 Longitude (E) :151 $^{\circ}$ 15 $^{\circ}$ 3 $^{\circ}$

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

H P Component Type From (m) To (m) OD (mm) ID (mm) Interval Details

1 Hole Hole 0.00 40.00 152 Down Hole Hammer

1 1 Casing Steel -0.60 9.60 C: 0-9.6m; Seated on Bottom

Water Bearing Zones

 From (m)
 To (m) Thickness (m) WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 35.00
 35.30
 0.30
 24.00
 1.60
 48.00
 180.00

Drillers Log

 From (m)
 To (m)
 Thickness(m)
 Drillers Description
 Geological Material
 Comments

 0.00
 3.00
 3.00
 TOPSOIL AND CLAY
 Topsoil

 3.00
 9.00
 6.00 CLAY AND SANDSTONE
 Clay

 9.00
 24.00
 15.00
 SANDSTONE, F.G.GREY. SMALL AMT CLAY
 Sandstone

 24.00
 36.00
 12.00
 SANDSTONE AND QUARTZ. LOT OF CLAY
 Sandstone

 36.00
 36.30
 0.30
 FRACTURE W.B. W.B. IS. LPS
 Invalid Code

 36.30
 48.00
 11.70
 SANDSTONE AND QURTZ. OPEN GRAIN
 Sandstone

Remarks

*** End of GW101504 ***

GW101751

Licence:10BL158944 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC Work Type :Bore STOCK Work Status :(Unknown) STOCK

Construct. Method :Rotary Air

Owner Type:

Commenced Date: Final Depth: 132.00 m Completion Date: 01-Feb-1999 **Drilled Depth:** 132.00 m

Contractor Name :INTERTECH

MILGATE, Dean John Driller:1736

Assistant Driller's Name :

Property: - N/A **Standing Water Level:** 36.00 m

GWMA: -102.00 mg/L Salinity: GW Zone: -Yield: 1.80 L/s

Site Details

Site Chosen By Parish Portion/Lot DP County Client Driller Form A: CUMBERLAND NARRABEEN 1//596295 Licensed: CUMBERLAND NARRABEEN 1 596295

> Region: 10 - SYDNEY SOUTH COAST CMA Map:

Grid Zone: River Basin: Scale:

Area / District:

Elevation: Northing:6272483 Latitude (S) :33° 40' 32" **Elevation Source: Easting :**339433 **Longitude** (E) :151° 16′ 5″

GS Map: **Coordinate Source:** MGA Zone:56

Negative depths indicate Above Ground Level; Construction

46.00

49.00

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm) 5.60 210 ID (mm) Interval Details
Rotary Air Component Type From (m) 0.00 Hole Hole Rotary Air C: 0-5.6m; Driven into Hole Hole Hole 5.60 132.00 159 168.3 158.7 Casing -0.40 5.60 Steel PVC Class 9 -0.40 140 Screwed and Glued; Suspended in Clamps Casing Opening Slots - Vertical PVC Class 9; Sawn; SL: 100mm; A: 4mm

140

Water Bearing Zones

	0							
From (m)	To (m) Th	nickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
46.00	49.00	3.00			0.10	54.00	0.25	90.00
74.50	75.00	0.50			0.60	78.00	0.25	96.00
112.50	113.00	0.50			0.30	114.00	0.25	109.00
123.00	123.50	0.50			0.80	132.00	0.50	102.00

Comments

Drillers Log

	U			
From (m)	To (m)	Thickness(m	Drillers Description	Geological Material
0.00	2.00	2.00	Fill	Fill
2.00	6.50	4.50	Grey Sandstone M.G.	Sandstone
6.50	7.00	0.50	Grey Clay	Clay
7.00	18.00	11.00	Weathered Sandstone	Sandstone
18.00	24.00	6.00	Sandstone and Quartz	Sandstone
24.00	25.00	1.00	Grey Clay	Clay
25.00	40.00	15.00	Grey Sandstone M.G.	Sandstone
40.00	40.50	0.50	Grey Clay	Clay
40.50	45.00	4.50	Grey Sandstone M.G.	Sandstone
45.00	46.00	1.00	Grey Clay	Clay
46.00	49.00	3.00	Sandstone and Quartz, Fractured	Sandstone
49.00	51.00	2.00	Ironstone	Ironstone
51.00	60.00	9.00	Sandstone and Quartz	Sandstone
60.00	74.50	14.50	Grey Sandstone M.G.	Sandstone
74.50	75.00	0.50	Sandstone and Quartz, Fractured	Sandstone
75.00	90.00	15.00	White Sandstone M.G.	Sandstone
90.00	92.00	2.00	Ironstone	Ironstone
92.00	112.50	20.50	White Sandstone M.G.	Sandstone
112.50	113.00	0.50	Sandstone and Quartz, Fractured	Sandstone
113.00	123.00	10.00	White Sandstone M.G.	Sandstone
123.00	123.50	0.50	Sandstone and Quartz, Fractured	Sandstone
123.50	132.00	8.50	Grey Sandstone M.G.	Sandstone

Remarks

*** End of GW101751 ***

GW103073

Licence:10BL159597 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC STOCK

STOCK

Work Type :Bore Work Status :(Unknown) Construct. Method :Rotary Air

Owner Type:

Commenced Date: Final Depth: 150.00 m Completion Date :29-Mar-2000 **Drilled Depth:** 150.00 m

Contractor Name :INTERTECH

READY, Mark Edward Driller:1737

Assistant Driller's Name :

Property: - N/A **Standing Water Level:**

GWMA: -140.00 mg/L Salinity:

GW Zone: -Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County Client Driller Form A: CUMBERLAND NARRABEEN 255//752046

Licensed: CUMBERLAND NARRABEEN 232

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District:

Elevation: Northing:6272593 Latitude (S) :33° 40' 28" **Elevation Source: Easting :**339163 **Longitude** (E) :151° 15′ 54″

GS Map: **Coordinate Source:** MGA Zone:56

Negative depths indicate Above Ground Level; Construction

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm) 5.60 210 ID (mm) Interval Details

Down Hole Hammer P Component Type From (m) 0.00 Hole Hole 5.60 150.00 Down Hole Hammer

Hole Hole 1 Casing Steel 168.3 158.7 C: -.1-5.6m; Driven into Hole -0.40 5.60

Water Bearing Zones

To (m) Thickness (m) WBZ Type 82.00 1.00 S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Salinity (mg/L) 140.00 From (m) 81.00 Duration (hr) 43.00

Drillers Log

	_			
From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	0.50	0.50 SANDY LOAM	Loam	
0.50	3.50	3.00 YELLOW SANDSTONE M.G.	Sandstone	
3.50	16.00	12.50 WHITE SANDSTONE M.G.	Sandstone	
16.00	16.20	0.20 IRONSTONE	Ironstone	
16.20	24.00	7.80 YELLOW SANDSTONE WITH IRON	Sandstone	
24.00	30.00	6.00 WHITE SANDSTONE M.G	Sandstone	
30.00	46.00	16.00 LT GREY SANDSTONE M.G.	Sandstone	
46.00	46.50	0.50 IRONSTONE	Ironstone	
46.50	59.00	12.50 YELLOW SANDSTONE M.G.	Sandstone	
59.00	62.00	3.00 WHITE SANDSTONE M.G.	Sandstone	
62.00	73.00	11.00 LT GREY SANDSTONE M.G.	Sandstone	
73.00	73.50	0.50 IRONSTONE	Ironstone	
73.50	82.00	8.50 LT GREY SANDSTONE/QUARTZ BANDS	Sandstone	
82.00	82.30	0.30 IRONSTONE	Ironstone	
82.30	85.00	2.70 PINK TO WHITE SANDSTONE M.G.	Sandstone	
85.00	135.00	50.00 LT GREY SANDSTONE M.G.	Sandstone	
135.00	150.00	15.00 LT TO DARK GREY SANDSTONE M.G.	Sandstone	

Remarks

*** End of GW103073 ***

GW103160

Licence :10BL159765 Licence Status Active

Work Type :BoreAuthorised Purpose(s)Intended Purpose(s)Work Status :(Unknown)DOMESTICDOMESTICSTOCKSTOCK

Construct. Method :Rotary Air

Owner Type:

Commenced Date : Final Depth : 120.50 m **Completion Date :**03-Aug-2000 **Drilled Depth :** 120.50 m

Contractor Name :INTERTECH

Driller :1783 CRUMP, William

Assistant Driller's Name :

Property: - N/A Standing Water Level:

GWMA: - Salinity: 145.00 mg/L

GW Zone: - Yield:

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN1831//812302Licensed :CUMBERLANDNARRABEEN1831 812302

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

 Elevation :
 Northing :6271548
 Latitude (S) :33° 41' 1"

 Elevation Source :
 Easting :338282
 Longitude (E) :151° 15' 19"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

To (m) OD (mm) 9.00 205 ID (mm) Interval Details
Rotary Air Component Type From (m) 0.00 Hole Hole Hole Hole 9.00 11.50 210 Down Hole Hammer 120.50 11.50 155 Down Hole Hammer Hole Hole C: -.1-11.6m; Welded; Driven into Hole Suspended in Clamps Casing Steel -0.40 11.60 168.3 158.7 Casing P.V.C. -0.40 17.50 140 1 Opening Slots - Vertical PVC Class 9; Sawn; SL: .1mm; A: 4mm

Water Bearing Zones

From (m) To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L) 15,00 18.00 3.00 0.30 18.00 0.25 153.00 105.00 107.00 2.00 0.05 108.00 0.25 145.00

Drillers Log

Dimers	Lug		
From (m)	To (m)	Thickness(m Drillers Description	Geological Material
0.00	9.00	9.00 FILL	Fill
9.00	14.00	5.00 SANDSTONE GREY	Sandstone
14.00	15.00		Sandstone
15.00	18.00		Sandstone
18.00	20.00		Quartz
20.00	22.00		Sandstone
22.00	32.00		Sandstone
32.00	38.00		Sandstone
38.00	40.00		Sandstone
40.00	41.00		Sandstone
41.00	42.50		Sandstone
42.50	43.00		Quartz
43.00	45.00		Sandstone
45.00	52.00		Sandstone
52.00	54.50		Siltstone
54.50	59.00		Sandstone
59.00	61.00		Sandstone
61.00	66.00		Sandstone
66.00	67.00		Shale
67.00	77.00		Sandstone
77.00	78.00		Sandstone
78.00	93.50		Sandstone
93.50	105.00		Sandstone
105.00	107.00		Sandstone
107.00	112.50		Sandstone
112.50	113.00		Sandstone
113.00	120.50	7.50 SANDSTONE GREY	Sandstone

Comments

Remarks

*** End of GW103160 ***

GW103538

Licence :10BL159951 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
DOMESTIC DOMESTIC

STOCK

Work Type :Bore DOMES
Work Status :(Unknown) STOCK

Construct. Method :Rotary Air

Owner Type:

Commenced Date : Final Depth : 132.00 m **Completion Date :**17-Jan-2001 **Drilled Depth :** 132.00 m

Contractor Name :INTERTECH

Driller :1737 READY, Mark Edward

Assistant Driller's Name :

Property: - N/A Standing Water Level:

GWMA: - **Salinity:** 139.00 mg/L

GW Zone: - Yield:

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientForm A :CUMBERLANDNARRABEEN2//596295Licensed :CUMBERLANDNARRABEEN2 596295

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District:

 Elevation :
 Northing :6272500
 Latitude (S) :33° 40' 31"

 Elevation Source :
 Easting :339309
 Longitude (E) :151° 15' 60"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm) 5.60 210 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole 156.5 Down Hole Hammer C: 3-5.6m; Driven into Hole Hole Hole 5.60 132.00 1 Casing 158.7 5.60 168.3 Steel -0.40

1 1 Casing PVC Class 9 -0.40 47.60 140 Screwed and Glued; Suspended in Clamps

Water Bearing Zones

From (m)	To (m)	Thickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
54.00	55.00	1.00			0.10	60.00	25.00	150.00
88.00	89.00	1.00			0.10	90.00	25.00	150.00
112.00	113.00	1.00			0.40	114.00	25.00	140.00
115.00	117.00	2.00	32.00		0.10	120.00	50.00	139.00

Drillers Log

	U		
From (m)	To (m)	Thickness(m Drillers Description	Geological Material Comments
0.00	0.50	0.50 OVERBURDEN	Overburden
0.50	2.00	1.50 WEATHERED SANDSTONE	Sandstone
2.00	14.00	12.00 WHITE TO PINK SANDSTONE M.G.	Sandstone
14.00	19.00	5.00 YELLOW SANDSTONE M.G.	Sandstone
19.00	19.20	0.20 IRONSTONE	Ironstone
19.20	20.00	0.80 GREY SANDSTONE M.G.	Sandstone
20.00	20.40	0.40 WHITE CLAY	Clay
20.40	21.00	0.60 WHITE SANDSTONE M.G.	Sandstone
21.00	21.50	0.50 WHITE CLAY	Clay
21.50	26.00	4.50 IRONSTONE	Ironstone
26.00	37.00	11.00 WHITE SANDSTONE M.G.	Sandstone
37.00	37.50	0.50 IRONSTONE	Ironstone
37.50	39.00	1.50 GREY CLAYSTONE	Clay
39.00	57.00	18.00 WHITE SANDSTONE M.G.	Sandstone
57.00	78.00	21.00 LT GREY SANDSTONE	Sandstone
78.00	90.00	12.00 WHITE TO RED SANDSTONE M.G.	Sandstone
90.00	99.00	9.00 LT GREY SANDSTONE M.G.	Sandstone
99.00	99.20	0.20 IRONSTONE	Ironstone
99.20	102.00	2.80 WHITE TO GREY SANDSTONE M.G.	Sandstone
102.00	111.00	9.00 LY GREY SANDSTONE M.G.	Sandstone
111.00	113.00	2.00 DK GREY SANDSTONE M.G.	Dacite(Tonalite)
113.00	115.00	2.00 WHITE SANDSTONE QUARTZ	Sandstone
115.00	115.30	0.30 IRONSTONE	Ironstone
115.30	117.00	1.70 LT GREY SANDSTONE + QUARTZ	Sandstone
117.00	125.00	8.00 DK GREY SANDSTONE M.G.	Dacite(Tonalite)
125.00	132.00	7.00 LT GREY SANDSTONE M.G.	Sandstone

Remarks

*** End of GW103538 ***

GW104173

Licence :10BL160499 Licence Status Active

Work Type :BoreAuthorised Purpose(s)Intended Purpose(s)Work Status :DOMESTICDOMESTICSTOCKSTOCK

Construct. Method :Rotary
Owner Type :

Commenced Date : Final Depth : 150.50 m **Completion Date :**01-Mar-2002 **Drilled Depth :** 150.50 m

Contractor Name :INTERTECH DRILLING

Driller :1783 CRUMP, William

Assistant Driller's Name :

Property: - N/A Standing Water Level:

GWMA: - **Salinity:** 134.00 mg/L

GW Zone: - Yield:

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientForm A :CUMBERLANDNARRABEENLT D DP 33150Licensed :CUMBERLANDNARRABEEND 33150

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation : Northing :6272118 Latitude (S) :33° 40' 43"
Elevation Source : Easting :338993 Longitude (E) :151° 15' 47"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm)
5.50 210
150.50 158 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Down Hole Hammer C: -.1-5.5m; Driven into Hole Hole Hole 5.50 150.50 1 Casing 158.7 168.3 -0.50 5.50 Steel

1 1 Casing PVC Class 9 -0.50 89.50 140 130 Screwed and Glued; Suspended in Clamps

Water Bearing Zones

From (m)	To (m)	Thickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
86.30	90.00	3.70			0.30	90.50	0.25	97.00
94.00	100.00	6.00			0.30	102.50	0.25	106.00
142.00	142.50	0.50			0.90	144.50	0.25	120.00
143.50	144.00	0.50	50.00		1.10	150.50	0.25	134.00

Drillers Log

Dittels	LUS		
From (m)	To (m)	Thickness(m Drillers Description	Geological Material Comments
0.00	2.00	2.00 SAND AND ROCKS	Sand
2.00	4.00	2.00 PINK SANDSTONE	Sandstone
4.00	27.00	23.00 SANDSTONE LIGHT BROWN	Sandstone
27.00	28.50	1.50 IRONSTONE AND QUARTZ	Ironstone Gravel
28.50	30.00	1.50 CLAYSTONE DARK GREY	Claystone
30.00	44.00	14.00 SANDSTONE LIGHT GREY	Sandstone
44.00	44.30	0.30 CLAY, CREAM	Clay
44.30	45.50	1.20 IRONSTONE , QUARTZ	Ironstone Gravel
45.50	47.00	1.50 CLAYSTONE DARK GREY	Claystone
47.00	56.50	9.50 SANDSTONE LIGHT GREY	Sandstone
56.50	58.00	1.50 CLAY STIFF, GREY	Clay
58.00	61.00	3.00 IRONSTONE AND QUARTZ	Ironstone Gravel
61.00	62.00	1.00 IRONSTONE, BANDS OF CLAY	Ironstone
62.00	85.00	23.00 SANDSTONE LIGHT GREY	Sandstone
85.00	86.00	1.00 SANDSTONE QUARTZ	Sandstone
86.00	86.30	0.30 IRONSTONE	Ironstone
86.30	90.00	3.70 SANDSTONE, QUARTZ	Sandstone
90.00	94.00	4.00 IRONSTONE, SANDSTONE	Ironstone
94.00	100.00	6.00 SANDSTONE, QUARTZ	Sandstone
100.00	105.50	5.50 SANDSTONE LIGHT GREY	Sandstone
105.50	110.00	4.50 SANDSTONE D/G. FRACT.	Sandstone
110.00	142.00	32.00 SANDSTONE GREY	Sandstone
142.00	142.50	0.50 FINE QUARTZ	Quartz
142.50	143.50	1.00 SANDSTONE GREY	Sandstone
143.50	144.00	0.50 SANDSTONE QUARTZ, FRACT.	Sandstone
144.00	150.50	6.50 SANDSTONE GREY	Sandstone

Remarks

*** End of GW104173 ***

GW104217

Licence :10BL160567 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK STOCK
Construct Method Potery

Construct. Method :Rotary
Owner Type :Private

Commenced Date : Final Depth : 150.00 m **Completion Date :**05-Mar-2002 **Drilled Depth :** 150.00 m

Contractor Name :INTERTECH DRILLING

Driller :1783 CRUMP, William

Assistant Driller's Name :

Property: - SACCO Standing Water Level: 58.00 m

GWMA: - **Salinity**: 134.00 mg/L **GW Zone**: - **Yield**: 0.20 L/s

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEENLT 26 DP 12115Licensed :CUMBERLANDNARRABEEN26 12115

Diemet Combine and American Combine and Co

Region:10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation: Northing:6272141 Latitude (S):33° 40' 43"
Elevation Source: Easting:339505 Longitude (E):151° 16' 7"

GS Map: MGA Zone :56 Coordinate Source :Map Interpretation

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm)
5.50 210
150.00 158 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Down Hole Hammer C: -.1-5.5m; Driven into Hole Hole Hole 5.50 150.00 1 Casing 158.7 168.3 -0.50 5.50 Steel

1 1 Casing PVC Class 9 -0.55 89.50 140 130 Screwed and Glued; Suspended in Clamps

Water Bearing Zones

From (m)	To (m)	Thickness (m)	WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
60.50	61.00	0.50				0.10			120.00
94.00	101.50	7.50				0.30			128.00
116.00	117.00	1.00				0.30			134.00
132.00	133.00	1.00		58.00		0.20			134.00

Drillers Log

Dimers	Lug		
From (m)	To (m)	Thickness(m Drillers Description	Geological Material Comments
0.00	1.50	1.50 SANDS AND LARGE ROCKS	Sandstone
1.50	3.00	1.50 SANDSTONE RED	Sandstone
3.00	21.00	18.00 SANDSTONE LIGHT BROWN	Sandstone
21.00	21.50	0.50 CLAY DARK BROWN	Clay
21.50	29.00	7.50 SANDSTONE LIGHT BROWN	Sandstone
29.00	30.50	1.50 SHALE	Shale
30.50	45.00	14.50 SANDSTONE LIGHT GREY	Sandstone
45.00	45.50	0.50 SHALE	Shale
45.50	50.00	4.50 SANDSTONE GREY	Sandstone
50.00	55.00	5.00 IRONSTONE/QUARTZ	Ironstone
55.00	60.50	5.50 SANDSTONE GREY	Sandstone
60.50	61.00	0.50 QUARTZ	Invalid Code
61.00	75.00	14.00 SANDSTONE L/G	Sandstone
75.00	76.50	1.50 IRONSTONE	Ironstone
76.50	79.00	2.50 SANDSTONE QUARTZ	Sandstone
79.00	79.50	0.50 IRONSTONE FRACTURED	Ironstone Gravel
79.50	89.00	9.50 SANDSTONE QUARTZ	Sandstone
89.00	93.50	4.50 SANDSTONE FRACTURED	Sandstone
93.50	94.00	0.50 CLAY/QUARTZ	Clay
94.00	101.50	7.50 SANDSTONE/QUARTZ	Sandstone
101.50	102.00	0.50 IRONSTONE	Ironstone
102.00	107.00	5.00 SANDSTONE GREY	Sandstone
107.00	107.30	0.30 CLAY	Clay
107.30	116.00	8.70 SANDSTONE GREY	Sandstone
116.00	117.00	1.00 SAND/QUARTZ FINE	Sand
117.00	132.00	15.00 SANDSTONE L/G	Sandstone
132.00	133.00	1.00 SANDSTONE QUARTZ	Sandstone
133.00	150.00	17.00 SANDSTONE GREY	Sandstone

Remarks

GW104265

Licence:10BL160616 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC Work Type :Bore

STOCK Work Status: Supply Obtained STOCK Construct. Method: Rotary

Owner Type :Private **Commenced Date:** Final Depth: 210.00 m Completion Date: 18-Apr-2002 **Drilled Depth:** 210.00 m

Contractor Name :INTERTECH DRILLING

Driller:1783 CRUMP, William

Assistant Driller's Name :

Property: - N/A **Standing Water Level:** 43.00 m

GWMA: -134.00 mg/L Salinity: GW Zone: -Yield: 0.10 L/s

Site Details

Site Chosen By Parish Portion/Lot DP County Client Form A: CUMBERLAND NARRABEEN LT 71 DP 752046 Licensed: CUMBERLAND NARRABEEN 71 752046

Region: 10 - SYDNEY SOUTH COAST CMA Map:

Grid Zone: River Basin: Scale:

Area / District:

Elevation: Northing:6272512 Latitude (S) :33° 40' 31" **Elevation Source: Easting :**339916 **Longitude** (E) :151° 16' 23"

GS Map: MGA Zone:56 Coordinate Source :Map Interpretation

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

 From (m)
 To (m)
 OD (mm)

 0.00
 5.50
 210

 5.50
 210.00
 160
 ID (mm) Interval Details

Down Hole Hammer Component Type Hole Hole Down Hole Hammer C: -.1-5.5m; Driven into Hole Hole Hole 1 Casing 168.3 158.7 -0.50 5.50 Steel -0.50 5.50 -0.50 59.50 1 Casing PVC Class 9 140 130 Screwed and Glued; Suspended in Clamps

Water Bearing Zones

From (m)	To (m) Thi	ckness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
48.00	50.00	2.00			0.10	54.00	0.25	120.00
80.00	84.00	4.00			0.10	84.00	0.25	126.00
101.50	102.00	0.50			0.10	102.00	0.25	132.00
111.00	112.00	1.00			0.10	114.00	0.25	134.00
142 00	146 00	2 00	42.00		0 10	210 00	0.25	124 00

Comments

Drillers Log

Drillers	Log		
From (m)	To (m)	Thickness(m Drillers Description	Geological Material
0.00	1.00	1.00 SAND	Sand
1.00	8.00	7.00 SANDSTONE SOFT	Sandstone
8.00	26.00	18.00 SANDSTONE/IRONSTONE	Sandstone
26.00	28.00	2.00 CLAYSTONE	Claystone
28.00	32.00	4.00 SILTSTONE	Siltstone
32.00	37.00	5.00 SANDSTONE/IRONSTONE	Sandstone
37.00	42.00	5.00 SANDSTONE GREY	Sandstone
42.00	48.00	6.00 SILTSTONE	Siltstone
48.00	50.00	2.00 IRONSTONE AND QUARTZ	Ironstone Gravel
50.00	54.00	4.00 SANSDSTONE GREY	Sand
54.00	58.00		Ironstone Gravel
58.00	65.00		Sandstone
65.00	80.00		Sandstone
80.00	84.00		Sandstone
84.00	101.50		Sandstone
101.50	102.00		Sandstone
102.00	104.00		Sandstone
104.00	111.00		Sandstone
111.00	112.00		Sandstone
112.00	143.00		Sandstone
143.00	146.00		Sandstone
146.00	166.00		Sandstone
166.00	170.00		Sandstone
170.00	198.00		Sandstone
198.00	202.00		Sandstone
202.00	205.00		Sandstone
205.00	210.00	5.00 SANDSTONE DARK GREY	Sandstone

Remarks

STOCK

GW104417

Licence :10BL160790 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK

Construct. Method :Rotary
Owner Type :Private

Commenced Date : Final Depth : 180.00 m **Completion Date :**23-Aug-1982 **Drilled Depth :** 180.00 m

Contractor Name :unknown

Driller :1783 CRUMP, William

Assistant Driller's Name :

Property: - N/A **Standing Water Level:** 33.00 m

GWMA: - **Salinity**: 134.00 mg/L **GW Zone**: - **Yield**: 0.20 L/s

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientForm A :CUMBERLANDNARRABEENLT 8 DP 30325

Licensed :CUMBERLAND NARRABEEN 8 30325

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

 Elevation :
 Northing :6272609
 Latitude (S) :33° 40' 28"

 Elevation Source :
 Easting :340101
 Longitude (E) :151° 16' 31"

GS Map : MGA Zone :56 Coordinate Source :Map Interpretation

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm)
5.50 210
180.00 159 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Down Hole Hammer C: -.1-5.5m; Driven into Hole Hole Hole 5.50 180.00 1 Casing 168.3 158.7 -0.50 5.50 Steel

1 1 Casing PVC Class 9 -0.50 47.50 140 Screwed and Glued; Suspended in Clamps

Water Bearing Zones

From (m)	To (m)	Thickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
45.00	48.00	3.00			0.10	48.00	0.25	134.00
67.00	70.00	3.00			0.20	72.00	0.25	134.00
71.50	72.50	1.00			0.30	78.00	0.25	134.00
133.00	135.00	2.00	33.00		0.20	138.00	0.25	134.00

Drillers Log

From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	1.00	1.00 TOPSOIL	Topsoil	
1.00	10.00	9.00 SANDSTONE LIGHT BROWN	Sandstone	
10.00	14.00	4.00 SHALE	Shale	
14.00	32.00	18.00 SANDSTONE LIGHT BROWN	Sandstone	
32.00	32.50	0.50 CLAY WHITE	Clay	
32.50	35.00	2.50 SANDSTONE WHITE	Sandstone	
35.00	35.50	0.50 CLAY	Sandstone	
35.50	39.00	3.50 SANDSTONE WHITE	Sandstone	
39.00	44.70		Sandstone	
44.70	45.00		Clay	
45.00	48.00		Sandstone	
48.00	67.00		Sandstone	
67.00	70.00		Sandstone	
70.00	71.50		Sandstone	
71.50	72.50		Ironstone Gravel	
72.50	74.00		Sandstone	
74.00	75.50		Sandstone	
75.50	95.00		Sandstone	
95.00	95.30		Clay	
95.30	111.00		Sandstone	
111.00	112.00		Sandstone	
112.00	133.00		Sandstone	
133.00	135.00		Sandstone	
135.00	180.00	45.00 SANDSTONE GREY	Sandstone	

Remarks

*** End of GW104417 ***

STOCK

GW104418

Licence :10BL160792 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK
Construct. Method :Rotary

Owner Type :Private

Commenced Date : Final Depth : 180.00 m **Completion Date :**21-Aug-2002 **Drilled Depth :** 180.00 m

Contractor Name :INTERTECH DRILLING

Driller :1783 CRUMP, William

Assistant Driller's Name :

GWMA: - **Salinity**: 134.00 mg/L **GW Zone**: - **Yield**: 0.30 L/s

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEENLT B DP 403166Licensed :CUMBERLANDNARRABEENB 403166

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation : Northing :6272310 Latitude (S) :33° 40' 37" Elevation Source : Easting :338914 Longitude (E) :151° 15' 44"

GS Map: MGA Zone :56 Coordinate Source :Map Interpretation

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-L-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure$

To (m) OD (mm) 5.50 210 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Down Hole Hammer C: -.1-5.5m; Driven into Hole Hole Hole 5.50 180.00 157 168.3 158.7 Casing -0.50 5.50 Steel

1 1 Casing Steel -0.50 5.50 168.3 158.7 C. -1.1-5.5m, Driven Into Hole
1 1 Casing PVC Class 9 -0.50 71.50 140 Screwed and Glued; Suspended in Clamps

Water Bearing Zones

To (m) Thickness (m) WBZ Type 94.00 7.50 S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Salinity (mg/L) 134.00 From (m) 86.50 0.25 96.00 0.25 114.00 114.50 0.50 71.00 0.05 120.00 0.25 134.00

Drillers Log

From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	0.50	0.50 TOPSOIL	Topsoil	
0.50	17.00	16.50 SANDSTONE LIGHT BROWN	Sandstone	
17.00	22.00	5.00 SANDSTONE GREY	Sandstone	
22.00	23.00	1.00 SHALE	Shale	
23.00	28.00	5.00 SANDSTONE GREY	Sandstone	
28.00	28.30	0.30 CLAY	Clay	
28.30	29.00	0.70 IRONSTONE	Ironstone	
29.00	30.00	1.00 SANDSTONE QUARTZ	Sandstone	
30.00	35.00	5.00 SANDSTONE LIGHT BROWN SOFT	Sandstone	
35.00	43.00	8.00 SANDSTONE WHITE	Sandstone	
43.00	45.00	2.00 IRONSTONE FRACTURED	Ironstone Gravel	
45.00	57.00	12.00 SANDSTONE GREY	Sandstone	
57.00	60.00	3.00 SHALE SOFT	Shale	
60.00	68.00	8.00 SANDSTONE GREY	Sandstone	
68.00	69.00	1.00 IRONSTONE	Ironstone	
69.00	86.50	17.50 SANDSTONE GREY	Sandstone	
86.50	93.00	6.50 SANDSTONE FINE QUARTZ	Sandstone	
93.00	94.00	1.00 FINE QUARTZ SOFT	Invalid Code	
94.00	98.00	4.00 SANDSTONE FINE QUARTZ	Sandstone	
98.00	114.00	16.00 SANDSTONE GREY	Sandstone	
114.00	114.50	0.50 SANDSTONE QUARTZ	Sandstone	
114.50	180.00	65.50 SANDSTONE GREY	Sandstone	

Remarks

*** End of GW104418 ***

DOMESTIC

STOCK

Intended Purpose(s)

DOMESTIC

STOCK

GW105253

Licence:10BL162186

Licence Status Active Authorised Purpose(s)

Work Type :Bore

Work Status: Supply Obtained Construct. Method :Rotary Air

Owner Type:

Commenced Date: Final Depth: 192.50 m Completion Date: 16-Oct-2003 **Drilled Depth:** 192.50 m

Contractor Name :INTERTECH DRILLING

Driller:1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Property: - MARFLEET **Standing Water Level:** 87.00 m

206.00 mg/L GWMA: -Salinity: GW Zone: -Yield: 0.10 L/s

Site Details

Site Chosen By Parish Portion/Lot DP County Client Driller Form A: CUMBERLAND NARRABEEN 9 30325

Licensed: CUMBERLAND NARRABEEN 9 30325

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin :212 - HAWKESBURY RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: 0.00 **Northing:**6273242 Latitude (S) :33° 40' 8" Elevation Source :(Unknown) **Easting :**340553 **Longitude** (E) :151° 16' 49"

GS Map: **Coordinate Source:** MGA Zone:56

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

To (m) OD (mm) 5.60 205 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole 5.60 102.50 102.50 192.50 Hole Hole 159 Down Hole Hammer 154 Down Hole Hammer Hole Hole Steel -0.40 5.60 168.3 158.7 C: 0-5.6m; Driven into Hole Casing

Screwed and Glued; Suspended in Clamps PVC Class 9 24.00 Casing -0.40 140

1 Opening Slots - Diagonal PVC Class 9; SL: .1mm; A: 4mm

Water Bearing Zones

From (m)	0	Thickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
26.50	27.50	1.00			0.20	30.50	0.25	125.00
127.00	128.00	1.00			0.10	132.50	0.25	142.00
151.00	151.30	0.30			0.10	156.50	0.25	220.00
184.50	185.50	1.00	87.00		0.10	186.50	0.50	240.00

Drillers Log

0		
To (m)	Thickness(m Drillers Description	Geological Material Comments
0.20	0.20 TOPSOIL	Topsoil
6.20	6.00 SANDSTONE LT GREY M/G	Sandstone
6.50	0.30 CLAY WHITE	Clay
24.50	18.00 SANDSTONE GREY BROWN/IRONSTONE	Sandstone
42.50	18.00 SANDSTONE F.W.GREY BROWN M/G	Sandstone
56.50	14.00 SANDSTONE BROWN/IRONSTONE	Sandstone
57.50		Invalid Code
		Sandstone
		Invalid Code
		Sandstone
		Sandstone
		Sandstone
		Invalid Code
		Sandstone
190.50		Invalid Code
192.50	2.00 SANDSTONE GREY	Sandstone
	To (m) 0.20 6.20 6.50 24.50 42.50 57.50 127.70 128.00 137.00 147.50 175.00 186.50 188.00	To (m) Thickness(m Drillers Description 0.20 0.20 TOPSOIL C.20 0.20 TOPSOIL C.20 0.20 TOPSOIL C.20 0.30 CLAY WHITE C.24.50 0.30 CLAY WHITE C.24.50 18.00 SANDSTONE GREY BROWN/IRONSTONE 42.50 18.00 SANDSTONE F.W.GREY BROWN M/G 56.50 14.00 SANDSTONE BROWN/IRONSTONE 57.50 1.00 F. SANDSTONE BROWN/IRONSTONE 127.70 70.20 SANDSTONE GREY/DARK GREY M.G 128.00 0.30 F.W. SANDSTONE GREY/DARK GREY M.G 147.50 10.50 SANDSTONE DARK GREY 175.00 27.50 SANDSTONE GREY/DARK GREY M.G 186.50 11.50 F. SANDSTONE GREY/DARK GREY M.G 188.00 1.50 SANDSTONE GREY W. 188.00 1.50 SANDSTONE GREY/DARK GREY 190.50 2.50 RED SHALE 190.50

Remarks

*** End of GW105253 ***

GW105255

Licence :10BL600322 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK STOCK

Construct. Method :Rotary
Owner Type :

Commenced Date : Final Depth : 114.00 m **Completion Date :**16-Oct-2003 **Drilled Depth :** 114.00 m

Contractor Name: ULTRA DRIILING

Driller :1423 DODD, Alan Marcus

Assistant Driller's Name :

Property: - FARAH Standing Water Level: 44.00 m

GWMA: - **Salinity:** 96.00 mg/L **Yield:** 1.00 L/s

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientForm A :CUMBERLANDNARRABEEN264 752046Licensed :CUMBERLANDNARRABEEN264 752046

Region: 10-SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 213-SYDNEY COAST - GEORGES RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District :

 Elevation :
 0.00
 Northing :6272855
 Latitude (S) :33° 40' 20"

 Elevation Source :(Unknown)
 Easting :339944
 Longitude (E) :151° 16' 25"

GS Map: MGA Zone :56 Coordinate Source :

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-L-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure$

To (m) OD (mm) 36.00 170 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Hole Hole 36.00 114.00 130 Down Hole Hammer 1 Casing Steel 0.30 2.00 160 Driven into Hole 1 Casing PVC Class 9 0.30 36.00 Glued; Driven into Hole

Water Bearing Zones

To (m) Thickness (m) WBZ Type 67.00 1.00 From (m) 66.00 S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Salinity (mg/L) 68.00 0.60 68.00 1.00 100.00 72.00 73.00 1.00 44.00 75.00 1.00 75.00 1.50 96.00

Drillers Log

 From (m)
 To (m)
 Thickness(m)
 Drillers Description
 Geological Material
 Comments

 0.00
 2.00
 2.00 CLAY
 Clay

 2.00
 22.00 BROKEN SANDSTONE
 Invalid Code

 22.00
 30.00 SHALE
 Shale

 30.00
 76.00 WHITE SANDSTONE
 Invalid Code

 76.00
 83.00
 7.00 SANDSTONE/SHALE
 Sandstone

 83.00
 114.00
 31.00 WHITE SANDSTONE
 Invalid Code

Remarks

Previous Lic No:10BL162212

*** End of GW105255 ***

GW105671

Licence :10BL162365 Licence Status Active

Authorised Purpose(s)Intended Purpose(s)DOMESTICDOMESTIC

Work Type :Bore DOME
Work Status :Supply Obtained

Construct. Method :Down Hole Hammer Owner Type :Private

Commenced Date : Final Depth : 180.00 m **Completion Date :**22-Oct-2003 **Drilled Depth :** 180.00 m

Contractor Name: Ultradrilling

Driller :1600 DODD, Bradley Alan

Assistant Driller's Name :

Property: - BIRD Standing Water Level: 105.00 m

GWMA: - **Salinity:** 110.00 mg/L

GW Zone: - Yield: 105.00 L/s cumulative

Site Details

Site Chosen By

County
Parish
Portion/Lot DP

Form A :CUMBERLAND NARRABEEN 2//618622 Licensed :CUMBERLAND NARRABEEN 2 618622

Region: 10 -SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 212 -HAWKESBURY RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District :

 Elevation :
 0.00
 Northing :6274438
 Latitude (S) :33° 39' 29"

 Elevation Source :(Unknown)
 Easting :340693
 Longitude (E) :151° 16' 55"

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-L-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure$

To (m) OD (mm) 72.00 174 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Down Hole Hammer Glued; Driven into Hole Hole Hole 72.00 180.00 140 Casing Steel 0.30 1.00 168

1 Casing PVC Class 9 0.30 72.00 140 Glued; Driven into Hole; Open End

Water Bearing Zones

To (m) Thickness (m) WBZ Type 163.00 1.00 From (m) 162.00 S.W.L. (m) **D.D.L.** (m) Yield (L/s) Salinity (mg/L) 110.00 Hole Depth (m) Duration (hr) 164.00 0.40 1.00 174.00 175.00 1.00 105.00 180.00 0.60 2.00 110.00

Drillers Log

 From (m)
 To (m)
 Thickness(m)
 Drillers Description
 Geological Material
 Comments

 0.00
 1.00
 1.00 soil, dirt
 Soil

 1.00
 3.00
 2.00 clay
 Clay

 3.00
 66.00
 63.00 sandstone, soft yellow
 Sandstone

 66.00
 150.00
 84.00 sandstone, shale
 Sandstone

 150.00
 174.00
 24.00 shale
 Shale

 174.00
 180.00
 6.00 shale, red
 Shale

Remarks

updated from original form ${\tt A}$

*** End of GW105671 ***

GW106327

Licence :10BL163449 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK STOCK
Construct. Method :Down Hole Hammer

Owner Type :Private

Commenced Date: Final Depth: 180.00 m Completion Date: 07-Jul-2004 Drilled Depth: 180.00 m

Contractor Name :INTERTECH

Driller :1783 CRUMP, William

Assistant Driller's Name :

Property: - HAUGH Standing Water Level: 49.50 m

GWMA: - Salinity: 198.00 mg/L

GW Zone: - Yield: 0.40 L/s cumualtive

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN82//875079Licensed :CUMBERLANDNARRABEEN82 875079

Region: 10 - SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 212 - HAWKESBURY RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District :

 Elevation :
 0.00
 Northing :6273453
 Latitude (S) :33° 40' 1"

 Elevation Source :(Unknown)
 Easting :340803
 Longitude (E) :151° 16' 58"

GS Map: MGA Zone: 56 Coordinate Source: GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

To (m) OD (mm) 5.50 206 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole 5.50 72.00 Hole Hole 72.00 159 Down Hole Hammer 180.00 Down Hole Hammer Hole Hole 155 -0.50 5.50 168.3 158.7 Screwed and Glued; Suspended in Clamps Casing PVC Class 9 11.00 Casing -0.50 140 Screwed and Glued; Driven into Hole; Open End 1 Opening Slots - Diagonal PVC Class 9; Sawn; SL: .1mm; A: 3mm; Screwed and Glued

Water Bearing Zones

From (m)	To (m)	Thickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
11.30	11.50	0.20			0.10			149.00
18.30	21.10	2.80			0.10			201.00
52.00	55.00	3.00	49.50		0.01			198.00

Drillers Log

	U				
From (m)	To (m)		Orillers Description	Geological M	Iaterial
0.00	3.00	3.00 sa	and, silty	Sand	
3.00	11.30	8.30 sa	andstone, light grey	Sandstone	
11.30	11.50	0.20 sa	andstone, fractured	Sandstone	
11.50	15.00	3.50 sa	andstone, light brown	Sandstone	
15.00	15.20	0.20 sa	andstone, fractured	Sandstone	
15.20	17.50	2.30 sa	andstone, light brown	Sandstone	
17.50	18.30	0.80 sa	andstone, very soft	Sandstone	
18.30	21.00	2.70 sa	andstone, quartz	Sandstone	
21.00	21.10	0.10 sa	andstone, fracture	Sandstone	
21.10	21.70	0.60 sa	andstone, grey	Sandstone	
21.70	22.20	0.50 cl	lay, white	Clay	
22.20	33.00	10.80 sa	andstone, ironstone bands	Sandstone	
33.00	40.00	7.00 sa	andstone, grey	Sandstone	
40.00	40.20	0.20 cl	lay, white	Clay	
40.20	52.00	11.80 sa	andstone, grey	Sandstone	
52.00	55.00	3.00 sa	andstone, dark grey	Sandstone	
55.00	93.50	38.50 sa	andstone, grey	Sandstone	
93.50	93.70	0.20 sa	andstone, fracture	Sandstone	
93.70	153.50	59.80 sa	andstone, grey	Sandstone	
153.50	159.00	5.50 si	ilt, stone	Silt	
159.00	164.00	5.00 sa	andstone, grey	Sandstone	
164.00	165.50		ilt, stone, grey	Silt	
165.50	178.00	12.50 si	ilt, stone red	Silt	
178.00	180.00	2.00 si	ilt stone, grey	Silt	

Comments

Remarks

updated from original form ${\tt A}$

*** End of GW106327 ***

GW106695

Licence :10BL164232 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC
Work Status :Supply Obtained STOCK STOCK

Work Status :Supply Obtained Construct. Method :Down Hole Hammer

Owner Type :Private

Commenced Date : Final Depth : 120.00 m **Completion Date :**23-Nov-2004 **Drilled Depth :** 120.00 m

Contractor Name :INTERTECH

Driller :1783 CRUMP, William

Assistant Driller's Name :

Property: - DAWE Standing Water Level: 38.00 m

GWMA: - Salinity: 132.00 mg/L

GW Zone: - Yield: 0.90 L/s cumulative

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN6//1044346Licensed :CUMBERLANDNARRABEEN6 1044346

Region: 10-SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 213-SYDNEY COAST - GEORGES RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District :

 Elevation :
 Northing :6272628
 Latitude (S) :33° 40' 27"

 Elevation Source :
 Easting :339830
 Longitude (E) :151° 16' 20"

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure\$

Н	P	Componen	t Type	From (m)	To (m)	OD (mm)	ID (mm) Interva	d Details
1		Hole	Hole	0.00	5.50	208		Down Hole Hammer
1		Hole	Hole	5.50	120.00	156		Down Hole Hammer
1	1	Casing	PVC Class 9	-42.00	53.00			Screwed and Glued
1	1	Casing	Steel	-0.40	5.60	156	146.4	Driven into Hole; Open End
1	1	Casing	PVC Class 9	-0.40	30.00	140		Screwed and Glued; Suspended in Clamps
1	1	Opening	Slots - Diagonal	30.00	42.00	140		PVC Class 9; Sawn; SL: .1mm; A: 3mm; Screwed and Glued
1	1	Opening	Slots - Diagonal	53.00	59.60	140		PVC Class 9; Sawn; SL: .1mm; A: 3mm; Screwed and Glued
1		Annulus	Concrete	-0.10	5.50	208	168	

Water Bearing Zones

Tailer Bearing Bottes								
From (m)	To (m) Thi	ckness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
31.00	35.00	4.00			0.20			145.00
53.00	54.00	1.00			0.20			144.00
67.00	70.00	3.00	38.00		0.20			140.00
72.00	86.00	14.00			0.30			132.00

Comments

Drillers Log

Dimers	Lug		
From (m)	To (m)	Thickness(m Drillers Description	Geological Material
0.00	2.00	2.00 fill, sandstone, rocker clay	Fill
2.00	4.00	2.00 sandstone, very soft	Sandstone
4.00	20.00	16.00 sandstone, light brown	Sandstone
20.00	26.00	6.00 sandstone, quartz bands	Sandstone
26.00	27.00	1.00 clay, soft	Clay
27.00	31.00	4.00 sandstone, light brown	Sandstone
31.00	35.00	4.00 sandstone, quartz soft	Sandstone
35.00	41.00	6.00 ironstone, sandstone,	Ironstone
41.00	41.30	0.30 clay	Clay
41.30	41.60	0.30 quartz, course	Quartz
41.60	44.00	2.40 clay	Clay
44.00	49.00	5.00 siltstone	Siltstone
49.00	53.00	4.00 sandstone, grey	Sandstone
53.00	54.00	1.00 sandstone, fractured	Sandstone
54.00	57.00	3.00 sandstone, quartz	Sandstone
57.00	67.00	10.00 sandstone, grey	Sandstone
67.00	67.50	0.50 quartz, course	Quartz
67.50	70.00	2.50 sandstone, grey	Sandstone
70.00	72.00	2.00 ironstone	Ironstone
72.00	86.00	14.00 sandstone, fractured quartz	Sandstone
86.00	90.00	4.00 sandstone, grey	Sandstone
90.00	94.00	4.00 sandstone, ironstone, fractured quartz	Sandstone
94.00	95.00	1.00 clay, sandstone, soft	Clay
95.00	102.00	7.00 sandstone, quartz bands	Sandstone

Remarks

102.00

updated from original form A

18.00 sandstone, grey

Sandstone

GW107194

Licence:10BL163459 Licence Status Active

Work Type :Bore

Work Status: Supply Obtained

Construct. Method :Rotary - Percussion (Down Hole Hammer)

Owner Type :Private

Commenced Date : Final Depth : 192.00 m **Completion Date :**28-Sep-2004 **Drilled Depth :** 192.00 m

Contractor Name : CENTRAL WEST WATER DRILLING

Driller :1812 REYNOLDS, Christopher Howard R

Assistant Driller's Name :

Property: - SWIFT Standing Water Level: 18.00 m

GWMA: - Salinity:

GW Zone: - Yield: 0.40 L/s cumulative

Site Details

Site Chosen By County Parish Portion/Lot DP

Form A :CUMBERLAND NARRABEEN 137 752046
Licensed :CUMBERLAND NARRABEEN 137 752046

Authorised Purpose(s)

DOMESTIC

STOCK

Intended Purpose(s)

DOMESTIC STOCK

Region :10 - SYDNEY SOUTH COAST CMA Map :

River Basin: Grid Zone: Scale:

Area / District :

 Elevation :
 Northing :6271355
 Latitude (S) :33° 41' 7"

 Elevation Source :
 Easting :337051
 Longitude (E) :151° 14' 31"

GS Map: MGA Zone: 56 Coordinate Source: GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-Loslot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ P-Pipe; OD-Outside\ Diameter; D-Inside\ D-Ins$

H P Component Type From (m) To (m) OD (mm) ID (mm) Interval Details
1 Hole Hole 0.00 192.00 200 Rotary - Percussion (Down Hole Hammer)

1 Hole Hole 0.00 192.00 200 Rotary - Percussion (Down Hole Hammer)
1 1 Casing PVC Class 9 -0.40 192.00 164 163.8 Riveted and Glued; Driven into Hole; Open End; S: 170~192m
1 1 Opening Slots - Vertical 0.00 0.00 164 PVC Class 9; Casing - Hand Sawn Slot; SL: 200mm; A: 2mm; Riveted and Glued

Water Bearing Zones

 From (m)
 To (m)
 Thickness (m)
 WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 74.00
 170.00
 96.00
 18.00
 0.40
 2.00
 2.00

Drillers Log

To (m) Thickness(m Drillers Description
3.00 3.00 tospsoil
4.00 1.00 clay, sandy From (m) 0.00 Geological Material Comments Topsoil Clay Sandstone 1.00 clay, sandy 16.00 sandstone 2.00 shales, grey 30.00 sandstone 3.00 20.00 22.00 52.00 56.00 4 00 20.00 22.00 Shale Sandstone 52.00 4.00 clays 114.00 sandstone Claystone 56.00 170.00 Sandstone 22.00 shales, grey

Remarks

updated from original form A

*** End of GW107194 ***

GW107518

Licence:10BL164091 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC

Work Type :Bore Work Status : Supply Obtained

Construct. Method: (Unknown) Owner Type :Private

Commenced Date: Final Depth: 120.00 m Completion Date: 01-Jul-2005 **Drilled Depth:** 120.00 m

Contractor Name :unknown

Driller:400 UNKNOWN, Unkown

Assistant Driller's Name :

Property: - CHOULARTON **Standing Water Level:** GWMA: -Salinity:

GW Zone: -Yield: 500 L/day

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 208//752046 Licensed: CUMBERLAND NARRABEEN 208 752046

Region: 10 - SYDNEY SOUTH COAST CMA Map:9130-1S MONA VALE River Basin: 213 - SYDNEY COAST - GEORGES RIVER Grid Zone:56/1 Scale:1:25,000

Area / District:

Elevation: Northing:6272572 Latitude (S) :33° 40' 29" **Elevation Source: Easting :**339395 **Longitude** (E) :151° 16' 3"

Coordinate Source :GIS - Geographic Information System GS Map: MGA Zone:56

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers H OP Component Type From (m) To (m) OD (mm) Interval Details

(No Construction Details Found)

Water Bearing Zones

To (m) Thickness (m) WBZ Type S.W.L. (m) D.D.L. (m) Yield (L/s) Hole Depth (m) Duration (hr) Salinity (mg/L)

(No Water Bearing Zone Details Found)

Drillers Log

From (m) To (m) Thickness(m Drillers Description Geological Material

Remarks

Type of casing PVC, diameter of casing 150mm updated from AG form

*** End of GW107518 ***

GW107528

Licence :10BL165517 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC
Work Status :Supply Obtained STOCK STOCK

Work Status :Supply Obtained
Construct. Method :Down Hole Hammer

Owner Type :Private

Commenced Date : Final Depth : 180.30 m **Completion Date :**28-Sep-2005 **Drilled Depth :** 180.30 m

Contractor Name :INTERTECH

Driller :1950 WYATT, Brett Roy

Assistant Driller's Name :

Property: - MORRIS Standing Water Level: 83.60 m

GWMA: - Salinity: 390.00 mg/L

GW Zone: - Yield: 0.60 L/s cumulative

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientForm A :CUMBERLANDNARRABEEN156//752046Licensed :CUMBERLANDNARRABEEN156 752046

Region :10-SYDNEY SOUTH COASTCMA Map :9130-1SMONA VALERiver Basin :213-SYDNEY COAST - GEORGES RIVERGrid Zone :56/1Scale :1:25,000

Area / District :

Elevation: Northing:6273541 Latitude (S):33° 39' 58" Elevation Source: Easting:340683 Longitude (E):151° 16' 54"

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers H P Component Type From (m) To (m) OD (mm) Interval Details

1		Hole	Hole	0.00	5.60	202		Down Hole Hammer
1		Hole	Hole	5.60	102.30	165		Down Hole Hammer
1		Hole	Hole	102.30	180.30	159		Down Hole Hammer
1	1	Casing	Steel	-0.20	5.80	165	155.4	Driven into Hole
1	1	Casing	PVC Class 9	-0.20	59.80	140		Screwed and Glued; Suspended in Clamps
1	1	Opening	Slots - Diagonal	17.80	23.80	140		PVC Class 9; Sawn; SL: 100mm; A: 3mm
1	1	Opening	Slots - Diagonal	29.80	41.80	140		PVC Class 9; Sawn; SL: 100mm; A: 3mm
1	1	Opening	Slots - Diagonal	47.80	53.80	140		PVC Class 9; Sawn; SL: 100mm; A: 3mm
1		Annulus	Concrete	0.00	5.80	165		

Water Bearing Zones

From (m)	To (m) Thi	ckness (m) WBZ Type	S.W.L. (m)	D.D.L. (m) Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
19.80	20.30	0.50		0.08			132.00
35.70	50.90	15.20	17.00	0.13			155.00
130.50	131.20	0.70		0.10			225.00
156.00	166.00	10.00	83.60	0.30			390.00

Drillers Log

	U			
From (m)	To (m)	Thickness(m Drillers Description	Geological Material Comme	nts
0.00	1.00	1.00 clay, light brown	Clay	
1.00	2.00	1.00 sandstone, brown weathered	Sandstone	
2.00	2.80	0.80 sandstone & ironstone, brown, water bearing	Sandstone	
2.80	13.60	10.80 sandstone, brown	Sandstone	
13.60	14.40	0.80 shale, grey	Shale	
14.40	19.80		Sandstone	
19.80	20.30		Sandstone	
20.30	26.50		Sandstone	
26.50	26.90		Clay	
26.90	35.70		Sandstone	
35.70			Quartz	
35.80	37.00		Ironstone	
37.00	37.30		Clay	
37.30	47.70		Sandstone	
47.70	47.90		Shale	
47.90	50.80		Sandstone	
50.80	50.90		Sandstone	
50.90	63.50		Sandstone	
63.50	67.80		Shale	
67.80	71.70		Sandstone	
71.70	78.60		Shale	
78.60	130.50		Sandstone	
130.50	131.20		Sandstone	
131.20	166.00		Sandstone	
166.00	180.30	14.30 shale, grey silty, red silty shale	Shale	

Remarks

Form A Remarks:

GW	71	Λ^{r}	15つ	O
(TV	, ,	v	2	a

130.5 - 131.2 very unstable - aire lifted at 132m 0.5lps updated from original form A

*** End of GW107528 ***

GW108106

Licence :10BL600255 Licence Status Active

Authorised Purpose(s) Intended Purpose(s) DOMESTIC DOMESTIC Work Type :Bore

STOCK Work Status: Supply Obtained STOCK

Construct. Method: Down Hole Hammer Owner Type :Private

Commenced Date: Final Depth: 180.00 m **Drilled Depth:** Completion Date: 15-May-2006 180.00 m

Contractor Name :INTERTECH

Driller:1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Standing Water Level: Property: - MEDWAY 50.00 m

GWMA: -Salinity:

GW Zone: -Yield: 0.70 L/s cumulative

Site Details

Site Chosen By County Parish Portion/Lot DP Client Form A: CUMBERLAND NARRABEEN 8 1044346 Licensed: CUMBERLAND NARRABEEN 8 1044346

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District:

Elevation: Northing: 6272580 Latitude (S) :33° 40' 29" **Elevation Source: Easting :**339684 Longitude (E) :151° 16' 14"

GS Map: MGA Zone:56 Coordinate Source: GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

н	ľ	Componen	t Type	From (m)	10 (m)	OD (mm)	ID (mm) Interval	Details
1		Hole	Hole	0.00	5.50	203		Down Hole Hammer
1		Hole	Hole	5.50	120.00	164		Down Hole Hammer
1		Hole	Hole	120.00	180.00	160		Down Hole Hammer
1	1	Casing	Steel	-0.50	5.50	168	158.4	Driven into Hole; Suspended in Clamps; Open End
1	1	Casing	PVC Class 9	-0.50	71.50	140		Screwed and Glued; Suspended in Clamps; Open End
1		Annulus	Concrete	0.00	5.50	203		

Water Bearing Zones

From (m)	To (m) Thic	ekness (m) WBZ Type	S.W.L. (m)	D.D.L. (m) Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
35.00	42.00	7.00		0.01			156.00
66.00	66.30	0.30		0.49			130.00
90.50	93.00	2.50		0.10			130.00
130.00	131.50	1.50	50.00	0.10			148.00

Drillers Log

From (m)	To (m) T	hickness(m Drillers Description	Geological Material
0.00	1.00	1.00 sand, clay	Sand
1.00	15.00	14.00 sandstone, weathered	Sandstone
15.00	15.20	0.20 clay, grey	Clay
15.20	28.00	12.80 sandstone, weathere d	Sandstone
28.00	30.00	2.00 ironstone	Ironstone
30.00	35.00	5.00 shale	Shale
35.00	42.00	7.00 sandstone, grey quartz	Sandstone
42.00	44.00	2.00 claym grey	Clay
44.00	51.50	7.50 sandstone, grey	Sandstone
51.50	66.00	14.50 sandstone, grey quartz	Sandstone
66.00	66.30	0.30 quartz, fractured	Quartz
66.30	88.00	21.70 sandstone, grey quartz	Sandstone
88.00	88.50	0.50 ironstone	Ironstone
88.50	90.50	2.00 sandstone, grey	Sandstone
90.50	93.00	2.50 quartz	Quartz
93.00	94.50	1.50 sandstone, grey	Sandstone
94.50	95.00	0.50 clay, grey	Clay
95.00	100.00	5.00 sandstone, grey	Sandstone
100.00	103.00	3.00 sandstone, grey clay quartz	Sandstone
103.00	104.00	1.00 sandstone, grey	Sandstone
104.00	107.00	3.00 sandstone, grey clay	Sandstone
107.00	122.00	15.00 sandstone, grey	Sandstone
122.00	130.00	8.00 sandstone, grey siltstone	Sandstone
130.00	131.50	1.50 sandstone, grey quartz	Sandstone
131.50	158.00	26.50 sandstone, grey	Sandstone
158.00	160.00	2.00 siltstone	Siltstone
160.00	170.00	10.00 sandstone, grey siltstone	Sandstone
170.00	180.00	10.00 sandstone, grey	

Remarks

updated from original form A

G_{1}	X71	ΛQ	1	N
	v v	ua		.,.,

*** End of GW108106 ***

GW108450

Licence :10BL601060 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK STOCK

Construct. Method :Down Hole Hammer Owner Type :Private

Commenced Date : Final Depth : 150.00 m **Completion Date :**19-Jan-2007 **Drilled Depth :** 150.00 m

Contractor Name :INTERTECH DRILLING

Driller: 1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Property: - SHIELDS Standing Water Level: 41.30 m

GWMA: - Salinity: 110.00 mg/L

GW Zone: - Yield: 0.55 L/s Cumulative

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN86//12115Licensed :CUMBERLANDNARRABEEN86 12115

Region: 10-SYDNEY SOUTH COASTCMA Map: 9130-1SMONA VALERiver Basin: 213-SYDNEY COAST - GEORGES RIVERGrid Zone: 56/1Scale: 1:25,000

Area / District :

 Elevation :
 Northing :6271876
 Latitude (S) :33° 40' 51"

 Elevation Source :
 Easting :339185
 Longitude (E) :151° 15' 55"

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; S-L-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers\ PC-Pressure$

To (m) OD (mm) 2.70 203 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole 2.70 150.00 -0.30 2.70 Hole Hole 161 Down Hole Hammer Driven into Hole; Suspended in Clamps; Open End 158.4 Casing 168 Steel -0.30 PVC Class 9 -0.30 41.70 Screwed and Glued; Suspended in Clamps Casing Annulus Concrete 2.70 0.00 203

Water Bearing Zones

	0						
From (m)	To (m) Thi	ckness (m) WBZ Type	S.W.L. (m)	D.D.L. (m) Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
35.50	37.00	1.50		0.02			125.00
73.00	75.00	2.00		0.10			98.00
101.00	103.00	2.00		0.23			92.00
133.00	137.00	4.00	41.30	0.20			110.00

Comments

Drillers Log

	J		
From (m)	To (m)		Geological Material
0.00	0.50	0.50 Soil, sandy	Soil
0.50	22.00	21.50 Sandstone, yellow	Sandstone
22.00	25.00	3.00 Ironstone	Ironstone
25.00	35.50	10.50 Sandstone, grey	Sandstone
35.50	37.00	1.50 Sandstone-Quartz, water bearing	Sandstone
37.00	38.00	1.00 Clay band	Clay
38.00	49.00	11.00 Sandstone, grey	Sandstone
49.00	63.00	14.00 Sandstone-Quartz	Sandstone
63.00	73.00	10.00 Sandstone, grey	Sandstone
73.00	75.00	2.00 Sandstone-Quartz, water bearing	Sandstone
75.00	101.00	26.00 Sandstone, grey	Sandstone
101.00	103.00	2.00 Sandstone-Quartz, water bearing	Sandstone
103.00	116.00	13.00 Sandstone, grey	Sandstone
116.00	117.00		Siltstone
117.00	129.00		Sandstone
129.00	129.50		Clay
129.50	133.00		Sandstone
133.00	137.00		Sandstone
137.00	139.00		Sandstone
139.00	148.50		Sandstone
148.50	149.00		Siltstone
149.00	150.00	1.00 Sandstone, grey	Sandstone

Remarks

updated from original form A

*** End of GW108450 ***

GW108510

Licence :10BL600637 Licence Status Active

 Work Type :Bore
 Authorised Purpose(s)
 Intended Purpose(s)

 DOMESTIC
 DOMESTIC

Work Status :Supply Obtained STOCK STOCK

Construct. Method :Down Hole Hammer Owner Type :Private

Commenced Date : Final Depth : 102.00 m **Completion Date :**27-Sep-2006 **Drilled Depth :** 102.00 m

Contractor Name :INTERTECH DRILLING

Driller :1489 BARDEN, Colin Leslie

Assistant Driller's Name :

Property: - CRAIG PERKINS INVESTMENTS Standing Water Level: 32.40 m

GWMA: - **Salinity:** 125.00 mg/L

GW Zone: - Yield: 2.40 L/s Cumulative

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN1//598867Licensed :CUMBERLANDNARRABEEN1 598867

Region :10 -SYDNEY SOUTH COASTCMA Map :9130-1SMONA VALERiver Basin :212 -HAWKESBURY RIVERGrid Zone :56/1Scale :1:25,000

Area / District :

Elevation : Northing :6273441 Latitude (S) :33° 40′ 1″ Elevation Source : Easting :339452 Longitude (E) :151° 16′ 6″

GS Map: MGA Zone: 56 Coordinate Source: GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers$

To (m) OD (mm) 2.60 203 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Hole Hole 2.60 102.00 164 Down Hole Hammer Driven into Hole; Suspended in Clamps; Open End 2.60 168 158.4 Casing Steel -0.40 PVC Class 9 -0.40 17.60 Screwed and Glued; Suspended in Clamps Casing Annulus Concrete 0.00 2.60 203

Water Bearing Zones

 From (m)
 To (m)
 Thickness (m)
 WBZ Type
 S.W.L. (m)
 D.D.L. (m)
 Yield (L/s)
 Hole Depth (m)
 Duration (hr)
 Salinity (mg/L)

 54.00
 58.00
 4.00
 0.20
 115.00

 85.50
 90.00
 4.50
 32.40
 2.20
 52.20

Drillers Log

	0			
From (m)	To (m)	Thickness(m Drillers Description	Geological Material	Comments
0.00	0.60	0.60 Soil, sandy	Soil	
0.60	2.80	2.20 Sandstone, weathered	Sandstone	
2.80	5.40	2.60 Shale	Shale	
5.40	7.00	1.60 Sandstone, weathered	Sandstone	
7.00	8.00	1.00 Shale	Shale	
8.00	15.00	7.00 Sandstone, grey	Sandstone	
15.00	22.00	7.00 Sandstone, yellow	Sandstone	
22.00	43.00	21.00 Sandstone, grey	Sandstone	
43.00	45.00	2.00 Sandstone, grey Quartz	Sandstone	
45.00	47.00	2.00 Sandstone, grey	Sandstone	
47.00	50.00		Sandstone	
50.00	54.00	4.00 Sandstone, grey	Sandstone	
54.00	58.00		Sandstone	
58.00	67.00	9.00 Sandstone, grey	Sandstone	
67.00	73.00	6.00 Sandstone, grey Quartz	Sandstone	
73.00	85.50		Sandstone	
85.50	90.00	4.50 Quartz	Quartz	
90.00	102.00	12.00 Sandstone, grey	Sandstone	

Remarks

updated from original form A

*** End of GW108510 ***

GW108676

Licence:10BL601385 Licence Status Active

> Authorised Purpose(s) Intended Purpose(s) **DOMESTIC** DOMESTIC

Work Status: Abandoned Bore Construct. Method: Down Hole Hammer

Owner Type :Private

Work Type :Spear

Commenced Date: Final Depth: 120.00 m Completion Date: 01-Mar-2007 **Drilled Depth:** 120.00 m

Contractor Name : Highland Drilling

Driller:1771 DELAMONT, Brett

Assistant Driller's Name :

Property: - CONGAGLEN **Standing Water Level:** GWMA: -Salinity: GW Zone: Yield:

Site Details

Site Chosen By Parish Portion/Lot DP County

Form A: CUMBERLAND NARRABEEN 2//579095 Licensed: CUMBERLAND NARRABEEN 2 579095

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District:

Elevation: Northing: 6272803 Latitude (S) :33° 40' 22" **Elevation Source: Easting :**340538 Longitude (E) :151° 16' 48"

Coordinate Source :GIS - Geographic Information System GS Map: MGA Zone:56

Negative depths indicate Above Ground Level; Construction

 $H-Hole; P-Pipe; OD-Outside\ Diameter; ID-Inside\ Diameter; C-Cemented; SL-Slot\ Length; A-Aperture; GS-Grain\ Size; Q-Quantity; PL-Placement\ of\ Gravel\ Pack; PC-Pressure\ Cemented; S-Sump; CE-Centralisers and the properties of the properties$

H P Component Type 1 Hole Hole

From (m) To (m) OD (mm)
0.00 120.00 200 ID (mm) Interval Details

Down Hole Hammer

Water Bearing Zones

To (m) Thickness (m) WBZ Type D.D.L. (m) Yield (L/s) S.W.L. (m) Hole Depth (m) Duration (hr) Salinity (mg/L) From (m)

(No Water Bearing Zone Details Found)

Drillers Log

To (m) 24.00 72.00 84.00 From (m) 0.00 Thickness(m Drillers Description Geological Material Comments 24.00 sandstone, pink orange Sandstone Sandstone 48.00 sandstone, fine grey 24.00 12.00 shale 30.00 sandstone, fine grey 6.00 shale 72.00 Shale 84.00 114.00 114.00 120.00 Sandstone

Remarks

Abandoned bore. updated from original form A

*** End of GW108676 ***

GW108708

Licence :10BL601568 Licence Status Active

 Work Type :Bore
 Authorised Purpose(s)
 Intended Purpose(s)

 DOMESTIC
 DOMESTIC

Work Status :Supply Obtained STOCK STOCK

Construct. Method :Down Hole Hammer Owner Type :Private

Commenced Date : Final Depth : 150.00 m **Completion Date :**19-Apr-2007 **Drilled Depth :** 150.00 m

Contractor Name :INTERTECH DRILLING

Driller:1997 SHEEHY, Paul

Assistant Driller's Name :

Property: - ADDISON Standing Water Level: 38.00 m

GWMA: - Salinity: 270.00 mg/L

GW Zone: - Yield: 0.85 L/s cumulative

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN1//595401Licensed :CUMBERLANDNARRABEEN1 595401

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation : Northing :6272996 Latitude (S) :33 $^{\circ}$ 40 $^{\circ}$ 15 $^{\circ}$ Elevation Source : Easting :339338 Longitude (E) :151 $^{\circ}$ 16 $^{\circ}$ 1 $^{\circ}$

GS Map: MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

To (m) OD (mm) 5.60 203 ID (mm) Interval Details

Down Hole Hammer Component Type From (m) 0.00 Hole Hole Hole Hole 5.60 150.00 158 Down Hole Hammer Casing -0.40 5.60 Driven into Hole; Open End Steel 168 PVC Class 9 -0.40 95.60 Screwed and Glued; Suspended in Clamps; Open End Casing

1 1 Opening Slots - Diagonal 72.00 90.00 140 PVC Class 9; Sawn; SL: 100mm; A: 3mm

Water Bearing Zones

From (m)	To (m) Th	ickness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
37.00	42.00	5.00			0.10			121.00
73.00	76.00	3.00			0.10			150.00
108.50	112.00	3.50			0.65			270.00

Drillers Log

From (m)	To (m)	Thickness(m Drillers Description	Geological Material Comments
0.00	0.20	0.20 topsoil	Topsoil
0.20	21.00	20.80 sandstone, grey	Sandstone
21.00	21.50	0.50 ironstone	Ironstone
21.50	31.50	10.00 sandstone, grey	Sandstone
31.50	34.00	2.50 sandstone, quartz	Sandstone
34.00	37.00	3.00 sandstone, grey	Sandstone
37.00	42.00	5.00 sandstone, quartz	Sandstone
42.00	56.50	14.50 sandstone, grey	Sandstone
56.50	67.00	10.50 sandstone, quartz	Sandstone
67.00	73.00	6.00 sandstone, grey	Sandstone
73.00	76.00	3.00 sandstone, quartz	Sandstone
76.00	77.00	1.00 sandstone, grey	Sandstone
77.00	78.50	1.50 siltstone, clay band	Siltstone
78.50	85.00	6.50 sandstone, grey	Sandstone
85.00	85.50	0.50 siltstone, clay band	Siltstone
85.50	94.00	8.50 sandstone, quartz	Sandstone
94.00	94.50	0.50 clay, quartz band	Clay
94.50	98.00	3.50 sandstone, quartz	Sandstone
98.00	108.50	10.50 sandstone, grey	Sandstone
108.50	112.00	3.50 sandstone, quartz	Sandstone
112.00	128.50	16.50 sandstone, grey	Sandstone
128.50	130.00	1.50 siltstone	Siltstone
130.00	136.00	6.00 sandstone, grey	Sandstone
136.00	140.00	4.00 siltstone	Siltstone
140.00	150.00	10.00 sandstone, grey	Sandstone

Remarks

updated from original form ${\tt A}$

*** End of GW108708 ***

GW108831

Licence :10BL601319 Licence Status Active

Authorised Purpose(s) Intended Purpose(s)
Work Type :Bore DOMESTIC DOMESTIC

Work Status :Supply Obtained STOCK STOCK

Construct. Method :Down Hole Hammer Owner Type :Private

Commenced Date : Final Depth : 180.00 m **Completion Date :**17-Apr-2007 **Drilled Depth :** 180.00 m

Contractor Name :INTERTECH DRILLING

Driller:1997 SHEEHY, Paul

Assistant Driller's Name :

Property: - SCARF Standing Water Level: 21.00 m

GWMA: - Salinity:

GW Zone: - **Yield**: 0.20 L/s cumulative

Site Details

Site Chosen ByCountyParishPortion/Lot DPClientDrillerForm A :CUMBERLANDNARRABEEN2//595401Licensed :CUMBERLANDNARRABEEN2 595401

Region: 10 - SYDNEY SOUTH COAST CMA Map:

River Basin: Grid Zone: Scale:

Area / District :

Elevation: Northing:6272957 Latitude (S):33° 40' 16" Elevation Source: Easting:339422 Longitude (E):151° 16' 4"

GS Map : MGA Zone :56 Coordinate Source :GIS - Geographic Information System

Construction Negative depths indicate Above Ground Level;

H-Hole;P-Pipe;OD-Outside Diameter;ID-Inside Diameter;C-Cemented;SL-Slot Length;A-Aperture;GS-Grain Size;Q-Quantity;PL-Placement of Gravel Pack;PC-Pressure Cemented;S-Sump;CE-Centralisers

H	P	Componen	t Type	From (m)	To (m)	OD (mm)	ID (mm) Interval Details
1		Hole	Hole	0.00	5.60	203	Down Hole Hammer
1		Hole	Hole	5.60	180.00	158	Down Hole Hammer
1	1	Casing	Steel	-0.40	5.60	168	Seated on Bottom; Open End
1	1	Casing	PVC Class 9	-0.40	107.60	140	Screwed and Glued; Suspended in Clamps; Open End
1	1	Opening	Slots - Diagonal	20.00	24.00	140	PVC Class 9; Sawn; SL: 100mm; A: 3mm
1	1	Opening	Slots - Diagonal	57.00	60.00	140	PVC Class 9; Sawn; SL: 100mm; A: 3mm
1	1	Opening	Slots - Diagonal	90.00	102.00	140	PVC Class 9; Sawn; SL: 100mm; A: 3mm
1		Annulus	Concrete	0.00	5.60	203	

Water Bearing Zones

From (m)	To (m) Thic	kness (m) WBZ Type	S.W.L. (m)	D.D.L. (m)	Yield (L/s)	Hole Depth (m)	Duration (hr)	Salinity (mg/L)
22.00	22.50	0.50			0.05			115.00
89.00	91.00	2.00			0.10			140.00
98.00	98.50	0.50			0.05			151.00

Comments

Drillers Log

	0		
From (m)	To (m)		Geological Material
0.00	0.50	0.50 topsoil	Topsoil
0.50	13.00	12.50 sandstone, yellow	Sandstone
13.00	13.50	0.50 clay	Clay
13.50	22.00	8.50 sandstone, yellow	Sandstone
22.00	22.50	0.50 sandstone, quartz	Sandstone
22.50	23.00	0.50 clay	Clay
23.00	43.00	20.00 sandstone, yellow	Sandstone
43.00	52.50	9.50 sandstone, quartz	Sandstone
52.50	55.50	3.00 sandstone, grey	Sandstone
55.50	56.50	1.00 shale, soft	Shale
56.50	58.50		Sandstone
58.50	64.50		Shale
64.50	74.00		Sandstone
74.00	77.00		Shale
77.00	89.00		Sandstone
89.00	91.00		Sandstone
91.00	94.00		Sandstone
94.00	95.00		Sandstone
95.00	98.00		Sandstone
98.00	98.50		Sandstone
98.50	100.50		Sandstone
100.50	102.00		Sandstone
102.00	121.00		Sandstone
121.00	125.00		Shale
125.00	145.00		Sandstone
145.00	146.00		Shale
146.00	180.00	34.00 sandstone, grey	Sandstone


Remarks

updated from original form A

CW1	08831
\ T VV I	UAA.TI

*** End of GW108831 ***






DATE 26/08/2014	0 100 200 400 600 800 1,000 1:25,000 Metres	PAGE SIZE A4	COORDINATE SYSTEM GDA 1994 MGA Zone 56	
APPENDIX C	FIGURE TITLE Aerial - 1930			
PROJECT NO. 3001228	9 PROJECT TITLE Ingleside Precinct			© S
CREATED BY R. Chatfie	eld SOURCES Vector backdrop data © MDS 2	2013		map that omis sole



© SMEC Australia Pty Ltd 2014. All Rights Reserved

formation contained on this map is up to date and accurate, this ap contains data from a number of sources - no warranty is given at the information contained on this map is free from error or mission. Any reliance placed on such information shall be at the let risk of the user. Please verify the accuracy of all information ior to using it. This map is not a design document.




DATE 26/08/2014	0 100 200 400 600 800 1.000 PAGE SIZE A4 COORDINATE SYSTEM GDA 1994 MGA Zone 56	
APPENDIX C	FIGURE TITLE Aerial - 1947	
PROJECT NO. 3001228	9 PROJECT TITLE Ingleside Precinct	© S
CREATED BY R. Chatfie	eld SOURCES Vector backdrop data © MDS 2013	map that i omis sole



© SMEC Australia Pty Ltd 2014. All Rights Reserved

formation contained on this map is up to date and accurate, this ap contains data from a number of sources - no warranty is given at the information contained on this map is free from error or mission. Any reliance placed on such information shall be at the let risk of the user. Please verify the accuracy of all information ior to using it. This map is not a design document.



DATE 28/08/2014

0 100 200 400 600 800 1,000
PAGE SIZE A4

COORDINATE SYSTEM
GDA 1994 MGA Zone 56

APPENDIX C

FIGURE TITLE Aerial - 1965

PROJECT NO. 30012289

PROJECT TITLE Ingleside Precinct


CREATED BY R. Chatfield

SOURCES Vector backdrop data © MDS 2013



© SMEC Australia Pty Ltd 2014. All Rights Reserved

formation contained on this map is up to date and accurate, this ap contains data from a number of sources – no warranty is given at the information contained on this map is free from error or mission. Any reliance placed on such information shall be at the let risk of the user. Please verify the accuracy of all information for to using it. This map is not a design document.



DATE 28/08/2014

Output

Date 28/08/2014

Outp



© SMEC Australia Pty Ltd 2014. All Rights Reserved

Disclaimer: While all reasonable care has been taken to ensure the information contained on this map is up to date and accurate, this map contains data from a number of sources - no warranty is given hat the information contained on this map is free from error or mission. Any reliance placed on such information shall be at the sole risk of the user. Please verify the accuracy of all information nirfor husing it This man is not a design document.



DATE 26/08/2014	0 100 200 400 600 800 1.000 PAGE SIZE A4 COORDINATE SYSTEM GDA 1994 MGA Zone 56	
APPENDIX C	FIGURE TITLE Aerial - 1991	
PROJECT NO. 3001228	9 PROJECT TITLE Ingleside Precinct	© Dir
CREATED BY R. Chatfie	ld SOURCES Vector backdrop data © MDS 2013	tha on so



© SMEC Australia Pty Ltd 2014. All Rights Reserved

formation contained on this map is up to date and accurate, this ap contains data from a number of sources – no warranty is given at the information contained on this map is free from error or mission. Any reliance placed on such information shall be at the let risk of the user. Please verify the accuracy of all information for to using it. This map is not a design document.



APPENDIX C FIGURE TITLE Aerial - 2012

PROJECT NO. 30012289 PROJECT TITLE Ingleside Precinct

CREATED BY R. Chatfield SOURCES Vector backdrop data © MDS 2013



© SMEC Australia Pty Ltd 2014. All Rights Reserved

formation contained on this map is up to date and accurate, this ap contains data from a number of sources - no warranty is given at the information contained on this map is free from error or mission. Any reliance placed on such information shall be at the let risk of the user. Please verify the accuracy of all information ior to using it. This map is not a design document.

APPENDIX D – LABORATORY SUMMARY TABLES



Metals Organochlorine (OC) Pesticides Aldrin + Dielc Total Chlore eta-BHC LOR Health Investigation Levels (NEPM 2013) 100 40 400 NEPM 2013 HIL Residential 500 150 300 90 NEPM 2013 HIL Residential E 1200 30000 120 1200 60000 10 90 600 400 240000 730 6000 400000 45 530 NEPM 2013 HIL Residential D 1500 3000 900 3600 **Ecological Screening Level for TPH** NEPM 2013 ESLs for TPH in urban resider NEPM 2013 ESLs for TPH in commercial/Industrial (fine) 185 135 Management Limits for TPH Fractions in soil (NEPM 2013) Ecological Investigation Levels 21 1121 45 325
 <5</th>
 <1</th>
 15
 26
 <0.1</th>
 12
 70
 <0.05</th>
 ES1405222 0-0.2 0-0.2 <0.2 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <1 | <0.2 S154 ES1405222 <0.2 <0.5 <0.5 <0.5 <0.5 <0.5 <1 <0.2 6 6/03/2014 0-0.2 0-0.2 0-0.2 S444 ES1405222 <0.5 <0.5 <0.5 <0.5 <0.5 <1 <0.2 S212 6/03/2014 ES1405222 ES1405222 6/03/2014 ES1405222 6/03/2014 0-0.2 S140 6/03/2014 ES1405222 0-0.2 0-0.2 0-0.2 0-0.2 S164 6/03/2014 ES1405222 6/03/2014 ES1405222 ES1405222 6/03/2014 S15/2 - Field Duplicate 6/03/2014 ES1405222 0-0.2 ES1405891 0-0.2 14/03/2014 S283/2 - Field Duplicate 14/03/2014 ES1405891 14/03/2014 ES1405891 **Statistical Summary**
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14< 14 12 <5 6 14 14 14 2 0 13 <5 <1 <2 10 ND 4 14 14 1 7 14 11
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14
 14< 14 10 Number of Results Number of Detects

<0.1

 <0.2</th>
 <0.5</th>
 <0.05</th>
 <0.05</th>

 <0.2</th>
 <0.5</th>
 <0.5</th>
 <0.5</th>
 <0.5</th>
 <0.1</th>
 <0.2</th>

 ND
 ND
 ND
 ND
 ND
 ND
 ND
 ND

Number of Guideline Exceedances Number of Guideline Exceedances(Detects Only) NEW NEPM acronyms:

Minimum Concentration

Minimum Detect Maximum Concentration Maximum Detect Average Concentration Median Concentration Standard Deviation

ACLs = Added Contaminant Limits ESLs = Ecological Screening Level HSL = Health Screening Levels EIL = Ecological Investigation Level NL = Not Limiting A&B = Low to high density residential

C = Residential / Open Space D = Commercial / Industrial



Organophosphorous (OP) Pesticides PAH/Pr LOR Health Investigation Levels (NEPM 2013) NEPM 2013 HIL Residential 10 NEPM 2013 HIL Residential E 20 500 100 50 NEPM 2013 HIL Residential D 2500 **Ecological Screening Level for TPH** NEPM 2013 ESLs for TPH in urban resider 1.4 NEPM 2013 ESLs for TPH in commercial/Industrial (fine) Management Limits for TPH Fractions in soil (NEPM 2013) Ecological Investigation Levels ES1405222 0-0.2 0-0.2 <.0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 S154
 1.2
 <0.5</td>
 <0.5</td>

 1.2
 <0.5</td>
 <0.5</td>

 1.2
 <0.5</td>
 <0.5</td>
 ES1405222 6/03/2014 0-0.2 0-0.2 0-0.2 S444 ES1405222 S212 6/03/2014 ES1405222 ES1405222 6/03/2014
 <0.05</th>
 <th 1.2 <0.5 <0.5 ES1405222 6/03/2014 0-0.2 S140 6/03/2014 ES1405222 0-0.2
 <0.05</th>
 <th 1.2 <0.5 <0.5 $\frac{<0.05}{<0.05} < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.05 < 0.0$ 0-0.2 0-0.2 0-0.2 S164 6/03/2014 ES1405222 6/03/2014 ES1405222 0.6 1.2 <0.5 <0.5 1.2 <0.5 <0.5 ES1405222 6/03/2014 \$\cdot \cdot S15/2 - Field Duplicate 6/03/2014 ES1405222 0-0.2 1.2 <0.5 <0.5 1.2 <0.5 <0.5 1.2 <0.5 <0.5 ES1405891 0-0.2 0.6 14/03/2014 S283/2 - Field Duplicate 14/03/2014 ES1405891 14/03/2014 ES1405891 **Statistical Summary** 14 14 0 0 <0.05 <0.05 < ND ND
 14
 14
 14
 14
 14
 14
 14

 0
 0
 0
 0
 0
 0
 0

 <0.05</td>
 <0.05</td>
 <0.1</td>
 <0.5</td>
 <0.5</td>
 <0.5</td>
 <0.5</td>

 ND
 ND
 ND
 ND
 ND
 ND
 ND
 Number of Results 14 14 0 0 14 0 14 0 14 0 14 0 14 0 14 14 14 14 0 1 14 14 0 0 0 Number of Detects
 0
 0
 0
 0
 0

 <0.05</td>
 <0.05</td>
 <0.05</td>
 <0.2</td>

 ND
 ND
 ND
 ND
 ND
 <0.2 <0.05 ND ND <0.05 <0.05 <0.2 ND
 0
 0
 0

 <0.05</td>
 <0.05</td>
 <0.05</td>

 ND
 ND
 ND
 <0.2 ND <0.05 ND <0.05 ND 5 <0.05 ND <0.05 <0.05 0.6 Minimum Concentration < 0.5 Minimum Detect ND ND ND ND Maximum Concentration <0.05 <0.05 <0.05 <0.05 <0.05 <0.05 <0.05 <0.05 <0.2 <0.05 <0.05 <0.05 <0.2 <0.05 <0.05 <0.05 <0.2 <0.05 0.7 0.9 1.2 1.5 <0.5 0.9 Maximum Detect Average Concentration Median Concentration Number of Guideline Exceedances Number of Guideline Exceedances(Detects Only)

NEW NEPM acronyms:

ACLs = Added Contaminant Limits
ESLs = Ecological Screening Level
HSL = Health Screening Levels
EIL = Ecological Investigation Level
NL = Not Limiting
A&B = Low to high density residential
C = Residential / Open Space

D = Commercial / Industrial

2 of 3



mat Gardonno Excoodanoo	enols													TRH						TPH		
	Benzo(g,h,i)perylene	Chrysene	යු Dibenz(a,h)anthracene රි	Mg/kg	Horene mg/kg	Solution (1,2,3-c,d) pyrene	ଞ୍ଚି Naphthalene ସ୍	Sk Phenanthrene	Sum of PAH	mg/kg	S C6-C10 Fraction	ਤੇ ਟਿ6-C10 Fraction minus BTEX (F1) ਨੋ	Sylp>C10-C16 Fraction	වූ >C16-C34 Fraction නි	by>C34-C40 Fraction	යි විට >C10-C40 Fraction (sum) කි	ತ್ತು>C10-C16 Fraction minus Naphthalene (F2) ಹ	62 - 92 kg	mg/kg	C15 - C28	% (C29-C36 kg	මු +C10 - C36 (Sum of total)
LOR	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	10	10	50	100	100	50	50	10	50	100	100	50
Health Investigation Levels (NEPM 2013)																						
NEPM 2013 HIL Residential A																						
NEPM 2013 HIL Residential B																						
NEPM 2013 HIL Residential C																						
NEPM 2013 HIL Residential D																						
Ecological Screening Level for TPH																						
NEPM 2013 ESLs for TPH in urban residential and public open space (fine)											180		120	1300	5600							
NEPM 2013 ESLs for TPH in commercial/Industrial (fine)											215		170	2500	6600							
Management Limits for TPH Fractions in soil (NEPM 2013)																						
Urban residential/public open space (fine)											800		1000	3500	10000							
Commercial/ Industrial (fine)											800		1000	5000	10000							
Ecological Investigation Levels																						
NEPM 1999 EIL																						
NEPM 2013 ACL in public open space							170															
Average concentration																						
NEPM EILs (Calculated Value ACL + Average)																						

Field_ID	Sampled_Date	SDG	Sample_Depth																						
S154	6/3/20114	ES1405222	0-0.2	0.6	0.6	<0.5	1.3	<0.5	<0.5	<0.5	0.8	6.9	1.4	<10	<10	<50	150	130	280	<50	<10	<50	<100	130	130
S469	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S444	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S212	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S38	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S91	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S140	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S164	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	0.7	<0.5	<0.5	<0.5	<0.5	1.3	0.6	<10	<10	<50	100	110	210	<50	<10	<50	<100	100	100
S41	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S15/1	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S15/2 - Field Duplicate	6/03/2014	ES1405222	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	160	100	260	<50	<10	<50	120	110	230
S283	14/03/2014	ES1405891	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S283/2 - Field Duplicate	14/03/2014	ES1405891	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
S130	14/03/2014	ES1405891	0-0.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50

Statistical Summary																						
Number of Results	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14
Number of Detects	1	1	0	2	0	0	0	1	2	2	0	0	0	3	3	3	0	0	0	1	3	3
Minimum Concentration	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<10	<10	<50	<100	<100	<50	<50	<10	<50	<100	<100	<50
Minimum Detect	0.6	0.6	ND	0.7	ND	ND	ND	0.8	1.3	0.6	ND	ND	ND	100	100	210	ND	ND	ND	120	100	100
Maximum Concentration	0.6	0.6	<0.5	1.3	<0.5	<0.5	<0.5	0.8	6.9	1.4	<10	<10	<50	160	130	280	<50	<10	<50	120	130	230
Maximum Detect	0.6	0.6	ND	1.3	ND	ND	ND	0.8	6.9	1.4	ND	ND	ND	160	130	280	ND	ND	ND	120	130	230
Average Concentration	0.28	0.28	0.25	0.36	0.25	0.25	0.25	0.29	0.8	0.36	5	5	25	69	64	73	25	5	25	55	64	53
Median Concentration	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	5	5	25	50	50	25	25	5	25	50	50	25
Standard Deviation	0.094	0.094	0	0.3	0	0	0	0.15	1.8	0.31	0	0	0	39	28	97	0	0	0	19	28	61
Number of Guideline Exceedances	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Number of Guideline Exceedances(Detects Only)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Number of Guideline Exceedances(Dete NEW NEPM acronyms: ACLs = Added Contaminant Limits ESLs = Ecological Screening Level HSL = Health Screening Levels EIL = Ecological Investigation Level NL = Not Limiting A&B = Low to high density residential C = Residential / Open Space D = Commercial / Industrial



SDG	ES1405222	ES1405222	222	ES1405891	ES1405891	222	i
Field ID	S15/1	S15/2	RPD (%)	S283	S283/2	RPD (%)	i
Date	6/03/2014	6/03/2014	(70)	14/03/2014	14/03/2014	(70)	1

	ChemName	Units	LOR					Ī	
	Benzene		0.2	<0.2	<0.2	0	<0.2	<0.2	0
-	Ethylbenzene	mg/kg mg/kg	0.5	<0.2	<0.2	0	<0.2	<0.5	0
-	Toluene			<0.5	<0.5	0	<0.5	<0.5	0
	Xylene (m & p)	mg/kg mg/kg	0.5	<0.5	<0.5	0	<0.5	<0.5	0
втех	Xylene (iii & p) Xylene (o)	mg/kg	0.5	<0.5	<0.5	0	<0.5	<0.5	0
	Xylene (Total)	mg/kg	0.5	<0.5	<0.5	0	<0.5	<0.5	0
-	Napthalene	mg/kg	1	<1	<1	0	<1	<1	0
-	Sum of BTEX	mg/kg	0.2	<0.2	<0.2	0	<0.2	<0.2	0
	Lead	mg/kg	5	15	33	75	8	<5	105
	Arsenic	mg/kg	5	<5	<5	0	<5	<5	0
-	Cadmium	mg/kg	1	<1	<1	0	<1	<1	0
-	Chromium (III+VI)	mg/kg	2	6	9	40	<2	4	120
	Copper	mg/kg	5	14	18	25	<5	<5	0
	Mercury	mg/kg		<0.1	<0.1	0	<0.1	<0.1	0
-	Nickel	mg/kg	2	2	4	67	<2	<2	0
-	Zinc	mg/kg	5	62	68	9	10	<5	120
	4,4-DDE	mg/kg	0.05	< 0.05	<0.05	0	<0.05	<0.05	0
-	alpha-BHC	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
	Aldrin	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
-	Aldrin + Dieldrin	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
-	beta-BHC	mg/kg	0.05	<0.05	< 0.05	0	<0.05	< 0.05	0
H	Total Chlordane (sum)	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
-	Chlordane (trans)	mg/kg	0.05	<0.05	< 0.05	0	<0.05	< 0.05	0
es	d-BHC	mg/kg	0.05	<0.05	< 0.05	0	<0.05	< 0.05	0
ici	4.4 DDD	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
est	4.4 DDT	mg/kg	0.2	<0.2	<0.2	0	<0.2	<0.2	0
٠. ٦	DDT+DDE+DDD	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
0	Dieldrin	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
ē	Hexachlorobenzene (HCB)	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
<u>o</u>	appha-Endosulfan	mg/kg	0.05	< 0.05	<0.05	0	<0.05	<0.05	0
ਰੂ 🖟	cis-Chlordane	mg/kg	0.05	< 0.05	< 0.05	0	<0.05	<0.05	0
e e	Endrin aldehyde	mg/kg	0.05	< 0.05	< 0.05	0	<0.05	<0.05	0
- W	Endrin ketone	mg/kg		<0.05	<0.05	0	<0.05	<0.05	0
	beta-Endosulfan	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
-	Endosulfan sulphate	mg/kg	0.05	< 0.05	<0.05	0	<0.05	<0.05	0
. [Endrin	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
, ,	g-BHC (Lindane)	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
. [Heptachlor	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
. [Heptachlor epoxide	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
. [Methoxychlor	mg/kg	0.2	<0.2	<0.2	0	<0.2	<0.2	0
	Dichlorvos	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
, į	Demeton-S-methyl	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
, į	Monocrotophos	mg/kg	0.2	<0.2	<0.2	0	<0.2	<0.2	0
es	Dimethoate	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
ig i	Diazinon	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
est	Chlorpyrifos-methyl	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
ď	Parathion-methyl	mg/kg	0.2	<0.2	<0.2	0	<0.2	<0.2	0
Organophosphorous (OP) Pesticides	Malathion	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
ns	Fenthion	mg/kg	0.05	< 0.05	< 0.05	0	< 0.05	< 0.05	0
20	Chlorpyrifos	mg/kg	0.05	< 0.05	< 0.05	0	<0.05	< 0.05	0
효	Parathion	mg/kg	0.2	<0.2	<0.2	0	<0.2	<0.2	0
sou	Pirimphos-ethyl	mg/kg	0.05	< 0.05	<0.05	0	<0.05	< 0.05	0
g	Bromophos-ethyl	mg/kg	0.05	< 0.05	< 0.05	0	<0.05	< 0.05	0
gar	Fenamiphos	mg/kg	0.05	< 0.05	< 0.05	0	<0.05	<0.05	0
	Prothiofos	mg/kg	0.05	< 0.05	< 0.05	0	<0.05	<0.05	0
-	Ethion	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
. !	Carbophenothion	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
	Azinphos Methyl	mg/kg	0.05	<0.05	<0.05	0	<0.05	<0.05	0
Δ.	Total Polychlorinated biphenyls	mg/kg		<0.1	<0.1	0	<0.1	<0.1	0
-	Acenaphthene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Acenaphthylene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Anthracene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Benz(a)anthracene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
	Benzo(a) pyrene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Benzo(a)pyrene TEQ (zero)	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
	Benzo(a)pyrene TEQ (half LOR) Benzo(a)pyrene TEQ (LOR)	mg/kg		0.6	0.6	0	0.6	0.6 1.2	0
		mg/kg		1.2 <0.5	1.2 <0.5	0	1.2 <0.5	1.2 <0.5	0
	Benzo(k)fluoranthene Benzo(b)fluoranthene	mg/kg mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
جَ	Benzo(g,h,i)perylene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
¥	Chrysene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
	Dibenz(a,h)anthracene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Fluoranthene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Fluorene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Indeno(1,2,3-c,d)pyrene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Naphthalene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Phenanthrene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
	Sum of PAH	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
-	Pyrene	mg/kg		<0.5	<0.5	0	<0.5	<0.5	0
	C6-C10 Fraction	mg/kg		<10	<10	0	<10	<10	0
	C6-C10 Fraction minus BTEX (F1)			<10	<10	0	<10	<10	0
		mg/kg		<50	<50	0	<50	<50	0
9	>C10-C16 Fraction			<100	160	46	<100	<100	0
9	>C10-C16 Fraction >C16-C34 Fraction	mg/kg	100						0
ткн		mg/kg mg/kg		<100	100	67	<100	<100	U
ТКН	>C16-C34 Fraction		100	<100 <50	100 260	67 165	<100 <50	<100 <50	0
ТКН	>C16-C34 Fraction >C34-C40 Fraction	mg/kg	100 50						_
ТКН	>C16-C34 Fraction >C34-C40 Fraction >C10-C40 Fraction (sum)	mg/kg mg/kg	100 50 50	<50	260	165	<50	<50	0
ТКН	>C16-C34 Fraction >C34-C40 Fraction >C10-C40 Fraction (sum) >C10-C16 Fraction minus Naphthalene (F2)	mg/kg mg/kg mg/kg	100 50 50 10	<50 <50	260 <50	165	<50 <50	<50 <50	0
ТКН	>C16-C34 Fraction >C34-C40 Fraction >C10-C40 Fraction (sum) >C10-C16 Fraction minus Naphthalene (F2) C6 - C9	mg/kg mg/kg mg/kg mg/kg	100 50 50 10 50	<50 <50 <10	260 <50 <10	165 0	<50 <50 <10	<50 <50 <10	0 0
трн	>C16-C34 Fraction >C34-C40 Fraction >C10-C40 Fraction (sum) >C10-C16 Fraction minus Naphthalene (F2) C6-C9 C10-C14	mg/kg mg/kg mg/kg mg/kg mg/kg	100 50 50 10 50 100 100	<50 <50 <10 <50	260 <50 <10 <50	0 0 0	<50 <50 <10 <50	<50 <50 <10 <50	0 0 0

Note: Where RPD are above 30%, this is attributable to the heterogeneous nature of the materials sampled and not a reflection of the analytical methods used. Therefore, the results are considered to be an acceptable reflection of site conditions.



Table D3 - Soil Analytical Results (Salinity)

							Sali	nity			_
	<u> </u>			0		r of 8.6 (silty clay)					
				SElectrical Conductivity @ 25°C	mo/Sm	Applied soil conversion factor of 8.6 (silty clay)	Calculated ECe	pH Unit	% Moisture	mg/kg Sulfate as SO4	mg
OR Non Saline				1	1	NA	1 <2	0.1	1	10	10
Slightly saline Moderately saline							2 - 4 4 - 8				
Very saline Highly saline							8 - 16 >16				
Field_ID	Sampled_Date	SDG	Sample Depth								
S212 S262	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	23 16	0.023 0.016	8.6 8.6	0.2	-	-	-	
S287	6/03/2014	ES1405223	0-0.2	19	0.019	8.6	0.2				
S314 S338	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	64 22	0.064	8.6 8.6	0.6	-	-	-	-
S339 S340	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2	19 15	0.019 0.015	8.6 8.6	0.2				
3315	6/03/2014	ES1405223	0-0.2 0-0.2	19	0.015	8.6	0.1	-		-	<u> </u>
3364 3393	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	80 23	0.08 0.023	8.6 8.6	0.7				\vdash
392	6/03/2014	ES1405223	0-0.2	18	0.018	8.6	0.2				
3394 3369	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	45 15	0.045	8.6 8.6	0.4	-		-	-
3418	6/03/2014 6/03/2014	ES1405223	0-0.2	28	0.028	8.6	0.2				
6469 6444	6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	77 112	0.112	8.6 8.6	1.0				
3419 3367	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	35 17	0.035	8.6 8.6	0.3				-
342	6/03/2014	ES1405223	0-0.2	42	0.042	8.6	0.4	-	-	-	
293 292	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	22	0.022	8.6	0.2	-	-	-	-
133	4/03/2014	ES1405223	0-0.2	64	0.064	8.6	0.6	-	-	-	
6158 6179	4/03/2014 4/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	24 11	0.024	8.6 8.6	0.2	-	-	-	
S154 S131	4/03/2014 4/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	19 15	0.019	8.6 8.6	0.2				-
3155	4/03/2014	ES1405223	0-0.2	22	0.022	8.6	0.2				
3181 3206	4/03/2014 4/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	29 122	0.029 0.122	8.6 8.6	1.0				\vdash
S231 S281	4/03/2014 4/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	33 21	0.033	8.6 8.6	0.3				\vdash
3282	4/03/2014	ES1405223	0-0.2	17	0.017	8.6	0.1				
3307 3256	4/03/2014 4/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	23 17	0.023	8.6 8.6	0.2				-
3230 315/1	4/03/2014 4/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	27 80	0.027	8.6 8.6	0.2	6.9	12.7	60	2
315/2 - Field Duplicate	4/03/2014	ES1405223	0-0.2	126	0.126	8.6	1.1	6.3	36.7	210	5
91 140	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	76 34	0.076	8.6	0.7	-	-	-	
3164	6/03/2014	ES1405223	0-0.2	45	0.045	8.6	0.4	-	-	-	
3166 3142	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	21	0.021	8.6	0.2	-	-	-	
641 6167	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	31 58	0.031	8.6 8.6	0.3	-	-	-	F
92	6/03/2014	ES1405223	0-0.2	25	0.025	8.6	0.2			-	Ħ
3163 3118	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	8 44	0.008	8.6	0.1	-	-	-	+
5114	6/03/2014	ES1405223	0-0.2	15	0.015	8.6	0.1	-		-	
6117 665	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	33 16	0.033	8.6	0.3	-	-	-	\vdash
63 689	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	33 37	0.033	8.6 8.6	0.3	-	-	-	
143	6/03/2014	ES1405223	0-0.2	44	0.044	8.6	0.4			-	
165 38	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	214	0.214	8.6 8.6	1.8 0.1	-	-	-	
90	6/03/2014	ES1405223	0-0.2	36	0.036	8.6	0.3	-		-	
3113 3168	6/03/2014 6/03/2014	ES1405223 ES1405223	0-0.2 0-0.2	96 15	0.096 0.015	8.6 8.6	0.8	-		-	t
8284 85	14/03/2014 14/03/2014	ES1405892 ES1405892	0-0.2 0-0.2	33 21	0.033	8.6 8.6	0.3				+
86	14/03/2014	ES1405892	0-0.2	18	0.018	8.6	0.2	-		-	
261 260	14/03/2014 14/03/2014	ES1405892 ES1405892	0-0.2 0-0.2	107 20	0.107 0.02	8.6 8.6	0.9	-	-	-	
59 36	14/03/2014 14/03/2014	ES1405892 ES1405892	0-0.2 0-0.2	22 116	0.022 0.116	8.6 8.6	0.2 1.0	-		-	
:35	14/03/2014	ES1405892	0-0.2	30	0.03	8.6	0.3	-	Ė	-	
183 183/2 - Field Duplicate	14/03/2014 14/03/2014	ES1405892 ES1405892	0-0.2 0-0.2	6 7	0.006 0.007	8.6 8.6	0.1				\vdash
.08	14/03/2014	ES1405892	0-0.2	19	0.019	8.6	0.2	-	-	-	F
82 32	14/03/2014 14/03/2014	ES1405892 ES1405892	0-0.2 0-0.2	15	0.015	8.6	0.1	-		-	
30	14/03/2014	ES1405892	0-0.2	16	0.016	8.6	0.1	-	-	-	
Statistical Summary				72	72	NA	72	2	2	2	T :
				72	72	NA	72	2	2	2	
lumber of Results lumber of Detects											
Number of Results Number of Detects Minimum Concentration Minimum Detect				6	0.006 0.006	NA NA	0.0516 0.0516	6.3 6.3	12.7 12.7	60 60	2
Number of Results Number of Detects Minimum Concentration Minimum Detect Maximum Concentration				6 6 214	0.006 0.006 0.214	NA NA NA	0.0516 0.0516 1.8404	6.3 6.3 6.9	12.7 12.7 36.7	60 60 210	5
lumber of Results lumber of Detects linimum Concentration linimum Detect				6	0.006 0.006	NA NA	0.0516 0.0516	6.3 6.3	12.7 12.7	60 60	2

^{*} Average Soil Coversion Factor 'Silty Clay' - P. A. and Murphy, B. W, 2007 (Table 5.33)



SDG	ES1405223	ES1405223	RPD	ES1405892	ES1405892	RPD
Field ID	S15/1	S15/2	(%)	S283	S283/2	(%)
Date	6/03/2014	6/03/2014	(70)	14/03/2014	14/03/2014	(70)

Group	Analyte	Units	LOR						
	Electrical Conductivity @ 25℃	μS/cm	1	80	126	0	6	7	0
. <u>≩</u> .	рН	pH Unit	0.1	6.9	6.3	9	-		
를	Moisture	%	1	12.7	36.7	97	-		
Sa	Sulfate as SO4	mg/kg	10	60	210	111	-		
	Chloride	mg/kg	10	20	50	86	-	-	

Note: Where RPD are above 30%, this is attributable to the heterogeneous nature of the materials sampled and not a reflection of the analytical methods used Therefore, the results are considered to be an acceptable reflection of site conditions.

APPENDIX E – LABORATORY REPORTS

-	V = Vot Vot HC Preserved 1985 (C. V. = Nick Preserved Physic: ORC = Nick Preserved ORC; SH = Socium HydroddelCd Preserved; S = Socium HydroddelCd Preserved; AG = Anther Glass Uppreserved; AG = Anther Glass Uppreserved; AP - Artreight Unpreserved Plasik; F = Formardelityte Preserved; AF = NCI preserved Plasic; H = HCI preserved Plasic; H = HCI preserved Plasic; H = HCI preserved Speciation boille; SP = Suitinft Preserved Plasik; Preserved Plasic; H = HCI preserved Plasic; H = HCI preserved Plasic; H = HCI preserved Speciation boille; SP = Suitinft Preserved Plasic;	ved Plastic; AG = Amber Glass H = HCl preserved Plastic; HS	Xium Hydroxide Preser eserved Amber Glass; 4e: o - vopreservçu pa	d Preserved; S = 8; hal SG = Sullufo Pr	Preserved ORC, St1 = Socium HydroxidsiC Ob Preserved: AV = Airbeight Unpreserved V Mae: CY = Starta Datta, ASB = F17-44, 8-4	o Preservad Pisatio: ORO = Nitio sa Praservad VS = VOA Val Suli ad Bottle: E = EDTA Preservad Re	Proserved, VB = VOA Visi Sodium Bisulpha Proserved, VB = VOA Visi Sodium Bisulpha • Proverved Glass; Z = Zjinc/Acciate Prescri	V = VOA Va; HO
				TOTAL			Code: On the code of the code	Water Contains
THE PERSON NAMED IN COLUMN TO PERSON NAMED I	-							
***************************************			l				£	111
	31770/84 8555		•				151	T
Were recognized to the state of	Telephone: + 61 2 CT		1		_		4	7
			1		•		7 0 Y	, 0,
			1				36	
And the state of t			-				34	6
	F31405222		1				70	
	TO NOT OTHER		1				770	7
	Most		1		3		7.	4
	Sydney Sydney		1				600	w
	Environmental						692	Ŋ
			1		2 A C		4516	
Comments on likely contaminate it is contaminated to the levels, distributions, or samples requiring specific QC analysis etc.		<u>.</u> .	S-16		TYPE & PRESERVATIVE (refer to codes below)	DATE/TIME MATRIX	SAMPLE ID	LABIO
ile price) Where Additional information to required).	Merals are required, specify Total (unfiltered bottle required) or Dissolved (field filtered bottle required).	re required, specify Total (13,499		****		The state of the s	
1		REQUIRED including	ANALYSIS		CONTAINER-INFORMATION	DETAILS	SAMPLE DETAILS	ALS
THE PARTY OF THE P	manana manan				٠	AGE OR DISPOSAL:	COMMEN IS SPECIAL HANDLING/STORAGE OR DISPOSAL	COMMEN
	6:30pm	<u>.</u>	•			her addresses are listed)	Email Invoice to (will default to PM if no other addresses are listed):	Email invo
DATETIME	11/03/14 DATE/TIME:	DATE/TIME: 1		DATE/TIME:		ther addresses are listed	Email Reports to (will default to PM if no other addresses are listed):	Email Rep
RECEIVED BY:	RELINQUISHED BY:		: < (EDD FORMAT (or default):	COC emailed to ALS7 (YES / NO)	COC email
		RECEIVED BY	DBY: 17 K	RELINQUISHED BY:	1 CM2622	SAMPLER MOBILE:	つると	SAMPLER:
Nation() Salitple Temperature on Receipt	2 3 4 5 6 7 France College	9.			CONTACT PH:		MANAGER:	PROJECT
ent upon receipt ? Yes No No	(v#cis)	coc:	***************************************		-	10811	PURCHASE ORDER NUMBER: 1	PURCHAS
Free Ice / mozań ice bricks		COC SE			ALS QUOTE NO.:	COCC , N	5/ 108Ph.1	PROJECT
FOR LABORATORY USE ONLY (Circle)	19/2/16	Stendard TAT (List due date): Non Stendard or urgent TAT (List due date):	Stendard Non Stanc	<u>&</u>	(Standard TAT may be longer for some tests e.g. Ultra Trace Organics)	01, 80	101 (10)	OFFICE:
Fit 07 4796 0600 E Tunnishing and General 1910 1910 Will LONGORE 99 Korny Street Mylongory 165W 2550 E PRI 02 4225 3125 E confusional School on a Pri 02 4225 A confusional School on a Pri 02 4225 A confusional School on a Pri 02 4225 A con	PER CH 9209 7855 E sempres permonsteninhonn	eumsk@akgroost.com	MIDDGE 27 Springr fload Mudgeo NSM 2850 Pr. 02 6372 6775 E: mudgeo.mail@alagcoopt.com		Ph.07 4971 5800 & gradstyne gegegodoloon		CLIENT OWN Dease (IN-	CLIENT.
SYDIKEY 277 Woodpark fload Smithsfall NSW 21164 PIE 02 8784 6855 E. samples synthysfaldeswing.com	HWYUSSILE E Receipum Road Wardhook 155W 2554 Ph. 122 4968 9433 E samptes newcosile@alsenr.co.com 10WINA 4/13 (Samy Prace Worth News HSW 2541	Ph. 07 4344 0177 E. INEKRYÖBESJÖGELLIN MELBOWINE 2-4 Wastell Roed Springrafe WC 3171 Ph. 03 5540 (600) E. samplas melbourne Galsenvio com	en. 07 4344 0177 E makayesisgobar.cm MELBONRNE 2-4 Washil Road Syringvale NC PR. 03 8540 (600) E. samplas melbourne Gals		CHARLES OF THE CHARLES AND STATE OF THE CHARLES OF			
	HLW.		ACKAY 78 Hartour Brand		AUELAIDE 21 Burna Apad Pooraka SA 5000		CHAIN OF	

 $\gamma \sim 1$

S. .



CERTIFICATE OF ANALYSIS

Work Order Page ES1405222 : 1 of 15

Client : Environmental Division Sydney SMEC TESTING SERVICES PTY LTD Laboratory

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW. AUSTRALIA 2164

E-mail E-mail : enquiries@smectesting.com.au : sydney@alsglobal.com Telephone Telephone : +61-2-8784 8555 Facsimile Facsimile

Project QC Level : 19580 4030C : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Order number : 10818

C-O-C number **Date Samples Received** : 11-MAR-2014 Sampler Issue Date : J. KERR : 19-MAR-2014

Site

No. of samples received : 11 Quote number No. of samples analysed : EN/025/13 : 11

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Certificate of Analysis contains the following information:

: ----

- General Comments
- Analytical Results
- Surrogate Control Limits



NATA Accredited Laboratory 825

Accredited for compliance with ISO/IEC 17025.

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

: +61-2-8784 8500

Signatories	Position	Accreditation Category
Celine Conceicao	Senior Spectroscopist	Sydney Inorganics
Pabi Subba	Senior Organic Chemist	Sydney Organics
Shobhna Chandra	Metals Coordinator	Sydney Inorganics

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 PHONE +61-2-8784 8555 Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting


^ = This result is computed from individual analyte detections at or above the level of reporting

- ALS is not NATA accredited for the analysis of Bifenthrin in soils when performed under ALS Method EP068D
- EP068: Pozitive results on sample #S38 confirmed by re-extraction and re-analysis.

Page : 3 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580 4030C






Page : 4 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580 4030C






Page : 5 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C






Page : 6 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C






Page : 7 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C






Page : 8 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580 4030C






Page : 9 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C





Page : 10 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C






Page : 11 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C





Page : 12 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C





Page : 13 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C






Page : 14 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C





Page : 15 of 15 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C

Surrogate Control Limits

Sub-Matrix: SOIL		Recovery	Limits (%)
Compound	CAS Number	Low	High
EP066S: PCB Surrogate			
Decachlorobiphenyl	2051-24-3	39	149
EP068S: Organochlorine Pesticide Surrogate			
Dibromo-DDE	21655-73-2	49	147
EP068T: Organophosphorus Pesticide Surroga	nte		
DEF	78-48-8	35	143
EP075(SIM)S: Phenolic Compound Surrogates			
Phenol-d6	13127-88-3	63	123
2-Chlorophenol-D4	93951-73-6	66	122
2.4.6-Tribromophenol	118-79-6	40	138
EP075(SIM)T: PAH Surrogates			
2-Fluorobiphenyl	321-60-8	70	122
Anthracene-d10	1719-06-8	66	128
4-Terphenyl-d14	1718-51-0	65	129
EP080S: TPH(V)/BTEX Surrogates			
1.2-Dichloroethane-D4	17060-07-0	72.8	133.2
Toluene-D8	2037-26-5	73.9	132.1
4-Bromofluorobenzene	460-00-4	71.6	130.0





QUALITY CONTROL REPORT

Work Order : **ES1405222** Page : 1 of 14

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact ; ALL REPORTS (ENQUIRIES) Contact ; Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

 Telephone
 : +61-2-8784 8555

 Facsimile
 : +61-2-8784 8500

 Facsimile
 : +61-2-8784 8500

Project : 19580 4030C QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Site : ----

 C-O-C number
 : -- Date Samples Received
 : 11-MAR-2014

 Sampler
 : J. KERR
 Issue Date
 : 19-MAR-2014

Order number : 10.818

No. of samples received : 11

Quote number : EN/025/13

No. of samples analysed : 11

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits

NATA Accredited

Laboratory 825

Accredited for

compliance with

ISO/IEC 17025.



Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out ir compliance with procedures specified in 21 CFR Part 11.

Signatories Position Accreditation Category

Celine Conceicao Senior Spectroscopist Sydney Inorganics

Pabi SubbaSenior Organic ChemistSydney OrganicsShobhna ChandraMetals CoordinatorSydney Inorganics

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 |
Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

= Indicates failed QC

Page : 3 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C

Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR:-No Limit; Result between 10 and 20 times LOR:-0% - 50%; Result > 20 times LOR:-0% - 20%.

Sub-Matrix: SOIL						Laboratory I	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EA055: Moisture C	ontent (QC Lot: 333566	6)							
ES1405222-003	S444	EA055-103: Moisture Content (dried @ 103°C)		1.0	%	12.3	11.6	5.6	0% - 50%
ES1405224-003	Anonymous	EA055-103: Moisture Content (dried @ 103°C)		1.0	%	19.8	20.0	0.8	0% - 50%
EG005T: Total Meta	als by ICP-AES (QC Lot	: 3341731)							
ES1405194-004	Anonymous	EG005T: Cadmium	7440-43-9	1	mg/kg	<1	<1	0.0	No Limit
		EG005T: Chromium	7440-47-3	2	mg/kg	225	249	10.1	0% - 20%
		EG005T: Nickel	7440-02-0	2	mg/kg	49	56	14.2	0% - 20%
		EG005T: Arsenic	7440-38-2	5	mg/kg	<5	<5	0.0	No Limit
		EG005T: Copper	7440-50-8	5	mg/kg	42	38	9.4	No Limit
		EG005T: Lead	7439-92-1	5	mg/kg	56	51	9.1	0% - 50%
		EG005T: Zinc	7440-66-6	5	mg/kg	141	165	16.0	0% - 20%
ES1405199-001	Anonymous	EG005T: Cadmium	7440-43-9	1	mg/kg	<1	<1	0.0	No Limit
		EG005T: Chromium	7440-47-3	2	mg/kg	360	306	16.3	0% - 20%
		EG005T: Nickel	7440-02-0	2	mg/kg	81	71	13.0	0% - 20%
		EG005T: Arsenic	7440-38-2	5	mg/kg	6	<5	0.0	No Limit
		EG005T: Copper	7440-50-8	5	mg/kg	45	44	3.5	No Limit
		EG005T: Lead	7439-92-1	5	mg/kg	65	61	6.5	0% - 50%
		EG005T: Zinc	7440-66-6	5	mg/kg	282	302	6.8	0% - 20%
EG005T: Total Meta	als by ICP-AES (QC Lot	: 3341733)							
ES1405222-004	S212	EG005T: Cadmium	7440-43-9	1	mg/kg	<1	<1	0.0	No Limit
		EG005T: Chromium	7440-47-3	2	mg/kg	9	9	0.0	No Limit
		EG005T: Nickel	7440-02-0	2	mg/kg	6	9	36.4	No Limit
		EG005T: Arsenic	7440-38-2	5	mg/kg	<5	<5	0.0	No Limit
		EG005T: Copper	7440-50-8	5	mg/kg	18	18	0.0	No Limit
		EG005T: Lead	7439-92-1	5	mg/kg	49	49	0.0	No Limit
		EG005T: Zinc	7440-66-6	5	mg/kg	98	85	14.6	0% - 50%
ES1405224-003	Anonymous	EG005T: Cadmium	7440-43-9	1	mg/kg	<1	<1	0.0	No Limit
		EG005T: Chromium	7440-47-3	2	mg/kg	25	28	11.8	0% - 50%
		EG005T: Nickel	7440-02-0	2	mg/kg	<2	<2	0.0	No Limit
		EG005T: Arsenic	7440-38-2	5	mg/kg	<5	<5	0.0	No Limit
		EG005T: Copper	7440-50-8	5	mg/kg	<5	<5	0.0	No Limit
		EG005T: Lead	7439-92-1	5	mg/kg	<5	<5	0.0	No Limit
		EG005T: Zinc	7440-66-6	5	mg/kg	<5	<5	0.0	No Limit
G035T: Total Rec	overable Mercury by FI	MS (QC Lot: 3341732)							
ES1405194-004	Anonymous	EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	<0.1	0.0	No Limit
ES1405199-001	Anonymous	EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	<0.1	0.0	No Limit

Page : 4 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL						Laboratory	Duplicate (DUP) Report	!	
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EG035T: Total Reco	overable Mercury by FIMS								
ES1405222-004	S212	EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	<0.1	0.0	No Limit
ES1405224-003	Anonymous	EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	<0.1	0.0	No Limit
EP066: Polychlorina	ated Biphenyls (PCB) (QC	C Lot: 3335080)							
ES1405222-001	S154	EP066: Total Polychlorinated biphenyls		0.1	mg/kg	<0.1	<0.1	0.0	No Limit
ES1405222-011	S15/2	EP066: Total Polychlorinated biphenyls		0.1	mg/kg	<0.1	<0.1	0.0	No Limit
EP068A: Organochl	orine Pesticides (OC) (Q								
ES1405222-001	S154	EP068: alpha-BHC	319-84-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Hexachlorobenzene (HCB)	118-74-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: beta-BHC	319-85-7	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: gamma-BHC	58-89-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: delta-BHC	319-86-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Heptachlor	76-44-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Aldrin	309-00-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Heptachlor epoxide	1024-57-3	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: trans-Chlordane	5103-74-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: alpha-Endosulfan	959-98-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: cis-Chlordane	5103-71-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Dieldrin	60-57-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: 4.4`-DDE	72-55-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Endrin	72-20-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: beta-Endosulfan	33213-65-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: 4.4`-DDD	72-54-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Endrin aldehyde	7421-93-4	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Endosulfan sulfate	1031-07-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Endrin ketone	53494-70-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: 4.4`-DDT	50-29-3	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP068: Methoxychlor	72-43-5	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
ES1405222-011	S15/2	EP068: alpha-BHC	319-84-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Hexachlorobenzene (HCB)	118-74-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: beta-BHC	319-85-7	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: gamma-BHC	58-89-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: delta-BHC	319-86-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Heptachlor	76-44-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Aldrin	309-00-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Heptachlor epoxide	1024-57-3	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: trans-Chlordane	5103-74-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: alpha-Endosulfan	959-98-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: cis-Chlordane	5103-71-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Dieldrin	60-57-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: 4.4`-DDE	72-55-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit

Page : 5 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL				Laboratory Duplicate (DUP) Report						
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)	
EP068A: Organochi	orine Pesticides (OC)	(QC Lot: 3335079) - continued								
ES1405222-011	S15/2	EP068: Endrin	72-20-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: beta-Endosulfan	33213-65-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: 4.4`-DDD	72-54-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endrin aldehyde	7421-93-4	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endosulfan sulfate	1031-07-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endrin ketone	53494-70-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: 4.4`-DDT	50-29-3	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
		EP068: Methoxychlor	72-43-5	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
EP068B: Organopho	osphorus Pesticides (C	OP) (QC Lot: 3335079)								
ES1405222-001	S154	EP068: Dichlorvos	62-73-7	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Demeton-S-methyl	919-86-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Dimethoate	60-51-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Diazinon	333-41-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Chlorpyrifos-methyl	5598-13-0	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Malathion	121-75-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Fenthion	55-38-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Chlorpyrifos	2921-88-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Pirimphos-ethyl	23505-41-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Bromophos-ethyl	4824-78-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Fenamiphos	22224-92-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Prothiofos	34643-46-4	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Ethion	563-12-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Carbophenothion	786-19-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Azinphos Methyl	86-50-0	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Monocrotophos	6923-22-4	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
		EP068: Parathion-methyl	298-00-0	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
		EP068: Parathion	56-38-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
ES1405222-011	S15/2	EP068: Dichlorvos	62-73-7	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Demeton-S-methyl	919-86-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Dimethoate	60-51-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Diazinon	333-41-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Chlorpyrifos-methyl	5598-13-0	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Malathion	121-75-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Fenthion	55-38-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Chlorpyrifos	2921-88-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Pirimphos-ethyl	23505-41-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Bromophos-ethyl	4824-78-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Fenamiphos	22224-92-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Prothiofos	34643-46-4	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Ethion	563-12-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	

Page : 6 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL						Laboratory	Duplicate (DUP) Report	t	
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EP068B: Organopho	osphorus Pesticides (O	P) (QC Lot: 3335079) - continued							
ES1405222-011	S15/2	EP068: Carbophenothion	786-19-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Azinphos Methyl	86-50-0	0.05	mg/kg	<0.05	<0.05	0.0	No Limit
		EP068: Monocrotophos	6923-22-4	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP068: Parathion-methyl	298-00-0	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP068: Parathion	56-38-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
EP075(SIM)B: Polyn	uclear Aromatic Hydro	carbons (QC Lot: 3335631)							
ES1405194-003	Anonymous	EP075(SIM): Naphthalene	91-20-3	0.5	mg/kg	0.9	1.0	0.0	No Limit
		EP075(SIM): Acenaphthylene	208-96-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Acenaphthene	83-32-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Fluorene	86-73-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Phenanthrene	85-01-8	0.5	mg/kg	4.1	4.9	18.1	No Limit
		EP075(SIM): Anthracene	120-12-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Fluoranthene	206-44-0	0.5	mg/kg	2.2	3.0	30.0	No Limit
		EP075(SIM): Pyrene	129-00-0	0.5	mg/kg	1.5	2.1	31.7	No Limit
		EP075(SIM): Benz(a)anthracene	56-55-3	0.5	mg/kg	0.9	1.1	25.9	No Limit
		EP075(SIM): Chrysene	218-01-9	0.5	mg/kg	1.0	1.3	22.2	No Limit
		EP075(SIM): Benzo(b)fluoranthene	205-99-2	0.5	mg/kg	<0.5	0.6	0.0	No Limit
		EP075(SIM): Benzo(k)fluoranthene	207-08-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Benzo(a)pyrene	50-32-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Indeno(1.2.3.cd)pyrene	193-39-5	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Dibenz(a.h)anthracene	53-70-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Benzo(g.h.i)perylene	191-24-2	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Sum of polycyclic aromatic		0.5	mg/kg	10.6	14.0	# 27.6	0% - 20%
		hydrocarbons							
		EP075(SIM): Benzo(a)pyrene TEQ (zero)		0.5	mg/kg	<0.5	<0.5	0.0	No Limit
ES1405222-003	S444	EP075(SIM): Naphthalene	91-20-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Acenaphthylene	208-96-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Acenaphthene	83-32-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Fluorene	86-73-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Phenanthrene	85-01-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Anthracene	120-12-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Fluoranthene	206-44-0	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Pyrene	129-00-0	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Benz(a)anthracene	56-55-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Chrysene	218-01-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Benzo(b)fluoranthene	205-99-2	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Benzo(k)fluoranthene	207-08-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Benzo(a)pyrene	50-32-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Indeno(1.2.3.cd)pyrene	193-39-5	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Dibenz(a.h)anthracene	53-70-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit

Page : 7 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL						Laboratory	Duplicate (DUP) Report	•	
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EP075(SIM)B: Polyr	nuclear Aromatic Hydro	carbons (QC Lot: 3335631) - continued							
ES1405222-003	S444	EP075(SIM): Benzo(g.h.i)perylene	191-24-2	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP075(SIM): Sum of polycyclic aromatic		0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		hydrocarbons							
		EP075(SIM): Benzo(a)pyrene TEQ (zero)		0.5	mg/kg	<0.5	<0.5	0.0	No Limit
EP080/071: Total Pe	etroleum Hydrocarbons	(QC Lot: 3334827)							
ES1405222-001	S154	EP080: C6 - C9 Fraction		10	mg/kg	<10	<10	0.0	No Limit
ES1405222-010	S15/1	EP080: C6 - C9 Fraction		10	mg/kg	<10	<10	0.0	No Limit
EP080/071: Total Pe	etroleum Hydrocarbons	(QC Lot: 3335630)							
ES1405194-003	Anonymous	EP071: C15 - C28 Fraction		100	mg/kg	1040	1000	4.0	0% - 50%
		EP071: C29 - C36 Fraction		100	mg/kg	260	260	0.0	No Limit
		EP071: C10 - C14 Fraction		50	mg/kg	100	100	0.0	No Limit
ES1405222-003	S444	EP071: C15 - C28 Fraction		100	mg/kg	<100	<100	0.0	No Limit
		EP071: C29 - C36 Fraction		100	mg/kg	<100	<100	0.0	No Limit
		EP071: C10 - C14 Fraction		50	mg/kg	<50	<50	0.0	No Limit
EP080/071: Total Re	ecoverable Hydrocarbo	ns - NEPM 2013 (QC Lot: 3334827)							
ES1405222-001	S154	EP080: C6 - C10 Fraction	C6 C10	10	mg/kg	<10	<10	0.0	No Limit
ES1405222-010	S15/1	EP080: C6 - C10 Fraction	 C6 C10	10	mg/kg	<10	<10	0.0	No Limit
EP080/071: Total Re	ecoverable Hydrocarbo	ns - NEPM 2013 (QC Lot: 3335630)	_						
ES1405194-003	Anonymous	EP071: >C16 - C34 Fraction		100	mg/kg	1110	1040	6.4	0% - 50%
	, , , , , ,	EP071: >C34 - C40 Fraction		100	mg/kg	150	130	18.5	No Limit
		EP071: >C10 - C16 Fraction	>C10_C16	50	mg/kg	200	250	24.2	No Limit
ES1405222-003	S444	EP071: >C16 - C34 Fraction		100	mg/kg	<100	<100	0.0	No Limit
		EP071: >C34 - C40 Fraction		100	mg/kg	<100	<100	0.0	No Limit
		EP071: >C10 - C16 Fraction	>C10 C16	50	mg/kg	<50	<50	0.0	No Limit
EP080: BTEXN (QC	C Lot: 3334827)		_						
ES1405222-001	S154	EP080: Benzene	71-43-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP080: Toluene	108-88-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Ethylbenzene	100-41-4	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: meta- & para-Xylene	108-38-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		2. see med a para / yiene	106-42-3						
		EP080: ortho-Xylene	95-47-6	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Naphthalene	91-20-3	1	mg/kg	<1	<1	0.0	No Limit
ES1405222-010	S15/1	EP080: Benzene	71-43-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP080: Toluene	108-88-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Ethylbenzene	100-41-4	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: meta- & para-Xylene	108-38-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		, ,	106-42-3						
		EP080: ortho-Xylene	95-47-6	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Naphthalene	91-20-3	1	mg/kg	<1	<1	0.0	No Limit

Page : 8 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Sample (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: SOIL				Method Blank (MB)	Laboratory Control Spike (LCS) Report					
				Report	Spike	Spike Recovery (%)	Recovery	Limits (%)		
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High		
EG005T: Total Metals by ICP-AES (QCLot: 3341)	731)									
EG005T: Arsenic	7440-38-2	5	mg/kg	<5	21.7 mg/kg	108	87	129		
EG005T: Cadmium	7440-43-9	1	mg/kg	<1	4.64 mg/kg	102	80	122		
EG005T: Chromium	7440-47-3	2	mg/kg	<2	43.9 mg/kg	100	71	133		
EG005T: Copper	7440-50-8	5	mg/kg	<5	32.0 mg/kg	112	86	128		
EG005T: Lead	7439-92-1	5	mg/kg	<5	40.0 mg/kg	103	81	123		
EG005T: Nickel	7440-02-0	2	mg/kg	<2	55.0 mg/kg	108	84	130		
EG005T: Zinc	7440-66-6	5	mg/kg	<5	60.8 mg/kg	94.7	81	133		
EG005T: Total Metals by ICP-AES (QCLot: 3341)	733)									
EG005T: Arsenic	7440-38-2	5	mg/kg	<5	21.7 mg/kg	113	87	129		
EG005T: Cadmium	7440-43-9	1	mg/kg	<1	4.64 mg/kg	107	80	122		
EG005T: Chromium	7440-47-3	2	mg/kg	<2	43.9 mg/kg	102	71	133		
EG005T: Copper	7440-50-8	5	mg/kg	<5	32.0 mg/kg	111	86	128		
EG005T: Lead	7439-92-1	5	mg/kg	<5	40.0 mg/kg	108	81	123		
EG005T: Nickel	7440-02-0	2	mg/kg	<2	55.0 mg/kg	111	84	130		
EG005T: Zinc	7440-66-6	5	mg/kg	<5	60.8 mg/kg	104	81	133		
EG035T: Total Recoverable Mercury by FIMS (C	QCLot: 3341732)									
EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	2.57 mg/kg	77.9	66	112		
EG035T: Total Recoverable Mercury by FIMS (C	QCLot: 3341734)									
EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	2.57 mg/kg	76.7	66	112		
EP066: Polychlorinated Biphenyls (PCB) (QCLo	t: 3335080)									
EP066: Total Polychlorinated biphenyls		0.1	mg/kg	<0.1	1 mg/kg	87.0	57.4	117		
EP068A: Organochlorine Pesticides (OC) (QCLo	ot: 3335079)									
EP068: alpha-BHC	319-84-6	0.05	mg/kg	<0.05	0.5 mg/kg	80.6	71	113		
EP068: Hexachlorobenzene (HCB)	118-74-1	0.05	mg/kg	<0.05	0.5 mg/kg	93.8	66	122		
EP068: beta-BHC	319-85-7	0.05	mg/kg	<0.05	0.5 mg/kg	88.2	69	119		
EP068: gamma-BHC	58-89-9	0.05	mg/kg	<0.05	0.5 mg/kg	82.6	71	115		
EP068: delta-BHC	319-86-8	0.05	mg/kg	<0.05	0.5 mg/kg	86.6	65	113		
EP068: Heptachlor	76-44-8	0.05	mg/kg	<0.05	0.5 mg/kg	87.5	68	116		
EP068: Aldrin	309-00-2	0.05	mg/kg	<0.05	0.5 mg/kg	83.8	68	118		
EP068: Heptachlor epoxide	1024-57-3	0.05	mg/kg	<0.05	0.5 mg/kg	85.5	68	116		
EP068: trans-Chlordane	5103-74-2	0.05	mg/kg	<0.05	0.5 mg/kg	86.5	68	120		
EP068: alpha-Endosulfan	959-98-8	0.05	mg/kg	<0.05	0.5 mg/kg	76.4	69	119		
EP068: cis-Chlordane	5103-71-9	0.05	mg/kg	<0.05	0.5 mg/kg	78.9	67	121		
EP068: Dieldrin	60-57-1	0.05	mg/kg	<0.05	0.5 mg/kg	80.8	66	118		

Page : 9 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL				Method Blank (MB)		Laboratory Control Spike (LC	S) Report	
				Report	Spike	Spike Recovery (%)	Recovery L	imits (%)
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High
EP068A: Organochlorine Pesticides (OC) (QCLot: 3335079	- continued							
EP068: 4.4`-DDE	72-55-9	0.05	mg/kg	<0.05	0.5 mg/kg	82.6	69	117
EP068: Endrin	72-20-8	0.05	mg/kg	<0.05	0.5 mg/kg	77.4	67	123
EP068: beta-Endosulfan	33213-65-9	0.05	mg/kg	<0.05	0.5 mg/kg	84.4	76	120
EP068: 4.4`-DDD	72-54-8	0.05	mg/kg	<0.05	0.5 mg/kg	83.8	76	120
EP068: Endrin aldehyde	7421-93-4	0.05	mg/kg	<0.05	0.5 mg/kg	82.9	57.3	115
EP068: Endosulfan sulfate	1031-07-8	0.05	mg/kg	<0.05	0.5 mg/kg	85.2	60	124
EP068: 4.4`-DDT	50-29-3	0.2	mg/kg	<0.2	0.5 mg/kg	100	67	127
EP068: Endrin ketone	53494-70-5	0.05	mg/kg	<0.05	0.5 mg/kg	87.3	65	123
EP068: Methoxychlor	72-43-5	0.2	mg/kg	<0.2	0.5 mg/kg	106	65	129
EP068B: Organophosphorus Pesticides (OP) (QCLot: 3335	079)							
EP068: Dichlorvos	62-73-7	0.05	mg/kg	<0.05	0.5 mg/kg	75.0	56	126
EP068: Demeton-S-methyl	919-86-8	0.05	mg/kg	<0.05	0.5 mg/kg	86.8	64	128
EP068: Monocrotophos	6923-22-4	0.2	mg/kg	<0.2	0.5 mg/kg	103	54	122
EP068: Dimethoate	60-51-5	0.05	mg/kg	<0.05	0.5 mg/kg	90.4	64	124
EP068: Diazinon	333-41-5	0.05	mg/kg	<0.05	0.5 mg/kg	75.4	73	117
EP068: Chlorpyrifos-methyl	5598-13-0	0.05	mg/kg	<0.05	0.5 mg/kg	88.4	55	119
EP068: Parathion-methyl	298-00-0	0.2	mg/kg	<0.2	0.5 mg/kg	87.0	69	123
EP068: Malathion	121-75-5	0.05	mg/kg	<0.05	0.5 mg/kg	87.2	70	120
EP068: Fenthion	55-38-9	0.05	mg/kg	<0.05	0.5 mg/kg	81.8	71	115
EP068: Chlorpyrifos	2921-88-2	0.05	mg/kg	<0.05	0.5 mg/kg	87.1	68	114
EP068: Parathion	56-38-2	0.2	mg/kg	<0.2	0.5 mg/kg	87.7	68	122
EP068: Pirimphos-ethyl	23505-41-1	0.05	mg/kg	<0.05	0.5 mg/kg	82.1	69	115
EP068: Bromophos-ethyl	4824-78-6	0.05	mg/kg	<0.05	0.5 mg/kg	85.5	68	116
EP068: Fenamiphos	22224-92-6	0.05	mg/kg	<0.05	0.5 mg/kg	85.4	64	120
EP068: Prothiofos	34643-46-4	0.05	mg/kg	<0.05	0.5 mg/kg	82.7	68	116
EP068: Ethion	563-12-2	0.05	mg/kg	<0.05	0.5 mg/kg	84.0	70	118
EP068: Carbophenothion	786-19-6	0.05	mg/kg	<0.05	0.5 mg/kg	84.4	67	123
EP068: Azinphos Methyl	86-50-0	0.05	mg/kg	<0.05	0.5 mg/kg	94.0	42	126
EP075(SIM)B: Polynuclear Aromatic Hydrocarbons (QCLot	: 3335631)							
EP075(SIM): Naphthalene	91-20-3	0.5	mg/kg	<0.5	4 mg/kg	98.3	80	124
EP075(SIM): Acenaphthylene	208-96-8	0.5	mg/kg	<0.5	4 mg/kg	96.2	77	123
EP075(SIM): Acenaphthene	83-32-9	0.5	mg/kg	<0.5	4 mg/kg	92.8	79	123
EP075(SIM): Fluorene	86-73-7	0.5	mg/kg	<0.5	4 mg/kg	107	77	123
EP075(SIM): Phenanthrene	85-01-8	0.5	mg/kg	<0.5	4 mg/kg	97.7	79	123
EP075(SIM): Anthracene	120-12-7	0.5	mg/kg	<0.5	4 mg/kg	96.5	79	123
EP075(SIM): Fluoranthene	206-44-0	0.5	mg/kg	<0.5	4 mg/kg	97.7	79	123
EP075(SIM): Pyrene	129-00-0	0.5	mg/kg	<0.5	4 mg/kg	95.8	79	125
EP075(SIM): Benz(a)anthracene	56-55-3	0.5	mg/kg	<0.5	4 mg/kg	92.8	73	121
EP075(SIM): Chrysene	218-01-9	0.5	mg/kg	<0.5	4 mg/kg	94.6	81	123

Page : 10 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Sub-Matrix: SOIL				Method Blank (MB)	Laboratory Control Spike (LCS) Report					
				Report	Spike	Spike Recovery (%)	Recovery	Limits (%)		
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High		
EP075(SIM)B: Polynuclear Aromatic Hydrocart	oons (QCLot: 3335631) - cor	itinued								
EP075(SIM): Benzo(b)fluoranthene	205-99-2	0.5	mg/kg	<0.5	4 mg/kg	79.8	70	118		
EP075(SIM): Benzo(k)fluoranthene	207-08-9	0.5	mg/kg	<0.5	4 mg/kg	82.8	77	123		
EP075(SIM): Benzo(a)pyrene	50-32-8	0.5	mg/kg	<0.5	4 mg/kg	91.4	76	122		
EP075(SIM): Indeno(1.2.3.cd)pyrene	193-39-5	0.5	mg/kg	<0.5	4 mg/kg	80.1	71	113		
EP075(SIM): Dibenz(a.h)anthracene	53-70-3	0.5	mg/kg	<0.5	4 mg/kg	78.8	71.7	113		
EP075(SIM): Benzo(g.h.i)perylene	191-24-2	0.5	mg/kg	<0.5	4 mg/kg	77.7	72.4	114		
EP080/071: Total Petroleum Hydrocarbons (Qe	CLot: 3334827)									
EP080: C6 - C9 Fraction		10	mg/kg	<10	26 mg/kg	79.3	68.4	128		
EP080/071: Total Petroleum Hydrocarbons (Qu	CLot: 3335630)									
EP071: C10 - C14 Fraction		50	mg/kg	<50	200 mg/kg	90.7	71	131		
EP071: C15 - C28 Fraction		100	mg/kg	<100	300 mg/kg	127	74	138		
EP071: C29 - C36 Fraction		100	mg/kg	<100	200 mg/kg	101	64	128		
EP080/071: Total Recoverable Hydrocarbons -	NEPM 2013 (QCLot: 3334827	7)								
EP080: C6 - C10 Fraction	C6_C10	10	mg/kg	<10	31 mg/kg	73.2	68.4	128		
EP080/071: Total Recoverable Hydrocarbons -	NEPM 2013 (QCLot: 3335630	0)								
EP071: >C10 - C16 Fraction	>C10_C16	50	mg/kg	<50	250 mg/kg	87.5	70	130		
EP071: >C16 - C34 Fraction		100	mg/kg	<100	350 mg/kg	121	74	138		
EP071: >C34 - C40 Fraction		100	mg/kg	<100						
		50	mg/kg		150 mg/kg	72.2	63	131		
EP080: BTEXN (QCLot: 3334827)										
EP080: Benzene	71-43-2	0.2	mg/kg	<0.2	1 mg/kg	73.1	62	116		
EP080: Toluene	108-88-3	0.5	mg/kg	<0.5	1 mg/kg	75.6	62	128		
EP080: Ethylbenzene	100-41-4	0.5	mg/kg	<0.5	1 mg/kg	70.8	58	118		
EP080: meta- & para-Xylene	108-38-3	0.5	mg/kg	<0.5	2 mg/kg	66.6	60	120		
	106-42-3									
EP080: ortho-Xylene	95-47-6	0.5	mg/kg	<0.5	1 mg/kg	72.0	60	120		
EP080: Naphthalene	91-20-3	1	mg/kg	<1	1 mg/kg	82.0	62	138		

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: SOIL			Matrix Spike (MS) Report						
				Spike SpikeRecovery(%) Recovery Lin					
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High		
EG005T: Total Met	als by ICP-AES (QCLot: 3341731)								
ES1405194-004	Anonymous	EG005T: Arsenic	7440-38-2	50 mg/kg	107	70	130		
		EG005T: Cadmium	7440-43-9	50 mg/kg	97.3	70	130		

Page : 11 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



b-Matrix: SOIL					atrix Spike (MS) Report		
				Spike	SpikeRecovery(%)	Recovery L	· · ·
boratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High
3005T: Total Meta	als by ICP-AES (QCLot: 3341731) - co	ntinued					
S1405194-004	Anonymous	EG005T: Chromium	7440-47-3	50 mg/kg	# Not Determined	70	130
		EG005T: Copper	7440-50-8	125 mg/kg	121	70	130
		EG005T: Lead	7439-92-1	125 mg/kg	105	70	130
		EG005T: Nickel	7440-02-0	50 mg/kg	123	70	130
		EG005T: Zinc	7440-66-6	125 mg/kg	122	70	130
G005T: Total Meta	als by ICP-AES (QCLot: 3341733)						
S1405222-004	S212	EG005T: Arsenic	7440-38-2	50 mg/kg	113	70	130
		EG005T: Cadmium	7440-43-9	50 mg/kg	109	70	130
		EG005T: Chromium	7440-47-3	50 mg/kg	112	70	130
		EG005T: Copper	7440-50-8	125 mg/kg	113	70	130
		EG005T: Lead	7439-92-1	125 mg/kg	109	70	130
		EG005T: Nickel	7440-02-0	50 mg/kg	105	70	130
		EG005T: Zinc	7440-66-6	125 mg/kg	98.0	70	130
G035T: Total Rec	overable Mercury by FIMS (QCLot: 33	341732)					
ES1405194-004	Anonymous	EG035T: Mercury	7439-97-6	5 mg/kg	99.9	70	130
G035T: Total Rec	coverable Mercury by FIMS (QCLot: 33	341734)					
	S212	EG035T: Mercury	7439-97-6	5 mg/kg	93.5	70	130
P066: Polychlorin	ated Biphenyls (PCB) (QCLot: 333508						
	S154	EP066: Total Polychlorinated biphenyls		1 mg/kg	84.0	70	130
P068A: Organoch	lorine Pesticides (OC) (QCLot: 33350						
	S154	EP068: gamma-BHC	58-89-9	0.5 mg/kg	98.2	70	130
		EP068: Heptachlor	76-44-8	0.5 mg/kg	102	70	130
		EP068: Aldrin	309-00-2	0.5 mg/kg	99.9	70	130
		EP068: Dieldrin	60-57-1	0.5 mg/kg	104	70	130
		EP068: Endrin	72-20-8	2 mg/kg	85.4	70	130
		EP068: 4.4`-DDT	50-29-3	2 mg/kg	81.3	70	130
P068B: Organoph	osphorus Pesticides (OP) (QCLot: 33	35079)					
	S154	EP068: Diazinon	333-41-5	0.5 mg/kg	106	70	130
		EP068: Chlorpyrifos-methyl	5598-13-0	0.5 mg/kg	74.2	70	130
		EP068: Pirimphos-ethyl	23505-41-1	0.5 mg/kg	100	70	130
		EP068: Bromophos-ethyl	4824-78-6	0.5 mg/kg	102	70	130
		EP068: Prothiofos	34643-46-4	0.5 mg/kg	75.5	70	130
P075(SIM)B: Poly	nuclear Aromatic Hydrocarbons(QCL	ot: 3335631)					
	Anonymous	EP075(SIM): Acenaphthene	83-32-9	10 mg/kg	94.9	70	130
	· , · · · · ·	El 070(Olivi). Accriaphiliche	129-00-0	10 mg/kg	71.8	70	130

Page : 12 of 14
Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Sub-Matrix: SOIL				Ma	atrix Spike (MS) Report		
				Spike	SpikeRecovery(%)	Recovery Li	mits (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High
EP080/071: Total F	Petroleum Hydrocarbons (QCLot: 3334827) - continued						
ES1405222-001	S154	EP080: C6 - C9 Fraction		32.5 mg/kg	80.5	70	130
EP080/071: Total F	Petroleum Hydrocarbons (QCLot: 3335630)						
ES1405194-003	Anonymous	EP071: C10 - C14 Fraction		640 mg/kg	89.3	73	137
		EP071: C15 - C28 Fraction		3140 mg/kg	83.2	53	131
		EP071: C29 - C36 Fraction		2860 mg/kg	68.7	52	132
EP080/071: Total F	Recoverable Hydrocarbons - NEPM 2013 (QCLot: 33348)	27)					
ES1405222-001	S154	EP080: C6 - C10 Fraction	C6_C10	37.5 mg/kg	75.0	70	130
EP080/071: Total F	Recoverable Hydrocarbons - NEPM 2013 (QCLot: 33356	30)					
ES1405194-003	Anonymous	EP071: >C10 - C16 Fraction	>C10_C16	850 mg/kg	114	73	137
		EP071: >C16 - C34 Fraction		4800 mg/kg	74.8	53	131
		EP071: >C34 - C40 Fraction		2400 mg/kg	53.6	52	132
EP080: BTEXN (Q	CLot: 3334827)						
ES1405222-001	S154	EP080: Benzene	71-43-2	2.5 mg/kg	72.3	70	130
		EP080: Toluene	108-88-3	2.5 mg/kg	78.5	70	130
		EP080: Ethylbenzene	100-41-4	2.5 mg/kg	78.3	70	130
		EP080: meta- & para-Xylene	108-38-3	2.5 mg/kg	74.2	70	130
			106-42-3				
			95-47-6	2.5 mg/kg	79.9	70	130
		EP080: Naphthalene	91-20-3	2.5 mg/kg	77.8	70	130

Matrix Spike (MS) and Matrix Spike Duplicate (MSD) Report

The quality control term Matrix Spike (MS) and Matrix Spike Duplicate (MSD) refers to intralaboratory split samples spiked with a representative set of target analytes. The purpose of these QC parameters are to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: SOIL					Matrix Spike (N	IS) and Matrix Spi	ke Duplicate	(MSD) Repo	rt	
				Spike	Spike Red	covery (%)	Recovery	Limits (%)	RPD)s (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	MSD	Low	High	Value	Control Limit
EP080/071: Total P	etroleum Hydrocarbons (QCLot: 333482	r)								
ES1405222-001	S154	EP080: C6 - C9 Fraction		32.5 mg/kg	80.5		70	130		
EP080/071: Total R	ecoverable Hydrocarbons - NEPM 2013(QCLot: 3334827)								
ES1405222-001	S154	EP080: C6 - C10 Fraction	C6_C10	37.5 mg/kg	75.0		70	130		
EP080: BTEXN (Q	CLot: 3334827)									
ES1405222-001	S154	EP080: Benzene	71-43-2	2.5 mg/kg	72.3		70	130		
		EP080: Toluene	108-88-3	2.5 mg/kg	78.5		70	130		
		EP080: Ethylbenzene	100-41-4	2.5 mg/kg	78.3		70	130		
		EP080: meta- & para-Xylene	108-38-3	2.5 mg/kg	74.2		70	130		
			106-42-3							

Page : 13 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL			Matrix Spike (MS) and Matrix Spike Duplicate (MSD) Report							
				Spike	Spike Rec	overy (%)	Recovery	Limits (%)	RP	PDs (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	MSD	Low	High	Value	Control Lim
EP080: BTEXN (Q	CLot: 3334827) - continued									
ES1405222-001	S154	EP080: ortho-Xylene	95-47-6	2.5 mg/kg	79.9		70	130		
		EP080: Naphthalene	91-20-3	2.5 mg/kg	77.8		70	130		
EP068A: Organoch	nlorine Pesticides (OC) (QCL	ot: 3335079)								
ES1405222-001	S154	EP068: gamma-BHC	58-89-9	0.5 mg/kg	98.2		70	130		
		EP068: Heptachlor	76-44-8	0.5 mg/kg	102		70	130		
		EP068: Aldrin	309-00-2	0.5 mg/kg	99.9		70	130		
		EP068: Dieldrin	60-57-1	0.5 mg/kg	104		70	130		
		EP068: Endrin	72-20-8	2 mg/kg	85.4		70	130		
		EP068: 4.4`-DDT	50-29-3	2 mg/kg	81.3		70	130		
EP068B: Organoph	nosphorus Pesticides (OP)(QCLot: 3335079)								
ES1405222-001	S154	EP068: Diazinon	333-41-5	0.5 mg/kg	106		70	130		
		EP068: Chlorpyrifos-methyl	5598-13-0	0.5 mg/kg	74.2		70	130		
		EP068: Pirimphos-ethyl	23505-41-1	0.5 mg/kg	100		70	130		
		EP068: Bromophos-ethyl	4824-78-6	0.5 mg/kg	102		70	130		
		EP068: Prothiofos	34643-46-4	0.5 mg/kg	75.5		70	130		
EP066: Polychlorin	nated Biphenyls (PCB) (QCL	ot: 3335080)								
ES1405222-001	S154	EP066: Total Polychlorinated biphenyls		1 mg/kg	84.0		70	130		
ED080/071: Total D	etroleum Hydrocarbons (QC									
ES1405194-003	Anonymous	EP071: C10 - C14 Fraction		640 mg/kg	89.3		73	137		
201100101000	, wienymode	EP071: C15 - C28 Fraction		3140 mg/kg	83.2		53	131		
		EP071: C13 - C26 Fraction		2860 mg/kg	68.7		52	132		
ED000/074: Total D		NEPM 2013 (QCLot: 3335630)			55.			.02		
ES1405194-003	Anonymous		>C10 C16	850 mg/kg	114		73	137		
E3 1403 194-003	Anonymous	EP071: >C10 - C16 Fraction		4800 mg/kg	74.8		53	131		
		EP071: >C16 - C34 Fraction		2400 mg/kg	53.6		52	132		
		EP071: >C34 - C40 Fraction		2400 mg/kg	33.0		32	102		
	nuclear Aromatic Hydrocarb		22.22.2	10 "	0.1.0			400		
ES1405194-003	Anonymous	EP075(SIM): Acenaphthene	83-32-9	10 mg/kg	94.9		70	130		
		EP075(SIM): Pyrene	129-00-0	10 mg/kg	71.8		70	130		
	als by ICP-AES (QCLot: 334	1731)								
ES1405194-004	Anonymous	EG005T: Arsenic	7440-38-2	50 mg/kg	107		70	130		
		EG005T: Cadmium	7440-43-9	50 mg/kg	97.3		70	130		
		EG005T: Chromium	7440-47-3	50 mg/kg	# Not		70	130		
					Determined					
		EG005T: Copper	7440-50-8	125 mg/kg	121		70	130		
		EG005T: Lead	7439-92-1	125 mg/kg	105		70	130		
		EG005T: Nickel	7440-02-0	50 mg/kg	123		70	130		
		EG005T: Zinc	7440-66-6	125 mg/kg	122		70	130		

Page : 14 of 14 Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Sub-Matrix: SOIL					Matrix Spike (N	IS) and Matrix Spi	ike Duplicate	(MSD) Repor	t	
				Spike	Spike Red	overy (%)	Recovery	Limits (%)	RPL	Os (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	MSD	Low	High	Value	Control Limit
EG035T: Total Rec	EG035T: Total Recoverable Mercury by FIMS (QCLot: 3341732) - continued									
ES1405194-004	Anonymous	EG035T: Mercury	7439-97-6	5 mg/kg	99.9		70	130		
EG005T: Total Meta	als by ICP-AES (QCLot: 3341733)									
ES1405222-004	S212	EG005T: Arsenic	7440-38-2	50 mg/kg	113		70	130		
		EG005T: Cadmium	7440-43-9	50 mg/kg	109		70	130		
		EG005T: Chromium	7440-47-3	50 mg/kg	112		70	130		
		EG005T: Copper	7440-50-8	125 mg/kg	113		70	130		
		EG005T: Lead	7439-92-1	125 mg/kg	109		70	130		
		EG005T: Nickel	7440-02-0	50 mg/kg	105		70	130		
		EG005T: Zinc	7440-66-6	125 mg/kg	98.0		70	130		
EG035T: Total Rec	overable Mercury by FIMS (QCLot: 33417	734)								
ES1405222-004	S212	EG035T: Mercury	7439-97-6	5 mg/kg	93.5		70	130		



INTERPRETIVE QUALITY CONTROL REPORT

Work Order : **ES1405222** Page : 1 of 7

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

Telephone : ---- Telephone : +61-2-8784 8555
Facsimile : ---- Facsimile : +61-2-8784 8500

Site : ----

 C-O-C number
 : -- Date Samples Received
 : 11-MAR-2014

 Sampler
 : J. KERR
 Issue Date
 : 19-MAR-2014

Order number : 10818

No. of samples received : 11

Quote number : EN/025/13

No. of samples analysed : 11

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Interpretive Quality Control Report contains the following information:

- Analysis Holding Time Compliance
- Quality Control Parameter Frequency Compliance
- Brief Method Summaries
- Summary of Outliers

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 7

Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Analysis Holding Time Compliance

This report summarizes extraction / preparation and analysis times and compares each with recommended holding times (USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive <u>or</u> Vinyl Chloride and Styrene are not key analytes of interest/concern.

			Evaluation:	x = Holding time	breach ; ✓ = Withir	holding time.
Sample Date	Ex	traction / Preparation			Analysis	
	Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
06-MAR-2014				12-MAR-2014	20-MAR-2014	✓
06-MAR-2014	17-MAR-2014	02-SEP-2014	✓	17-MAR-2014	02-SEP-2014	✓
06-MAR-2014	17-MAR-2014	03-APR-2014	✓	18-MAR-2014	03-APR-2014	✓
06-MAR-2014	12-MAR-2014	20-MAR-2014	✓	14-MAR-2014	21-APR-2014	✓
	06-MAR-2014 06-MAR-2014	06-MAR-2014 06-MAR-2014 17-MAR-2014 06-MAR-2014 17-MAR-2014	Date extracted Due for extraction	Sample Date Extraction / Preparation Date extracted Due for extraction Evaluation	Sample Date Extraction / Preparation Date extraction Date extraction Date extraction Date analysed	Date extracted Due for extraction Evaluation Date analysed Due for analysis 06-MAR-2014 12-MAR-2014 20-MAR-2014 06-MAR-2014 17-MAR-2014 02-SEP-2014 ✓ 17-MAR-2014 02-SEP-2014 06-MAR-2014 17-MAR-2014 03-APR-2014 ✓ 18-MAR-2014 03-APR-2014

Page : 3 of 7
Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Matrix: SOIL					Evaluation	× = Holding time	breach; ✓ = Withir	holding tin
Method		Sample Date	Ex	traction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EP068A: Organochlorine Pesticides (C	OC)							
Soil Glass Jar - Unpreserved (EP068)								
S154,	S469,	06-MAR-2014	12-MAR-2014	20-MAR-2014	✓	14-MAR-2014	21-APR-2014	✓
S444,	S212,							
S38,	S91,							
S140,	S164,							
S41,	S15/1,							
S15/2								
EP068B: Organophosphorus Pesticide	es (OP)							
Soil Glass Jar - Unpreserved (EP068)								
S154,	S469,	06-MAR-2014	12-MAR-2014	20-MAR-2014	✓	14-MAR-2014	21-APR-2014	✓
S444,	S212,							
S38,	S91,							
S140,	S164,							
S41,	S15/1,							
S15/2								
EP080/071: Total Recoverable Hydroc	arbons - NEPM 2013							
Soil Glass Jar - Unpreserved (EP071)								
S154,	S469,	06-MAR-2014	13-MAR-2014	20-MAR-2014	✓	14-MAR-2014	22-APR-2014	✓
S444,	S212,							
S38,	S91,							
S140,	S164,							
S41,	S15/1,							
S15/2								
EP075(SIM)B: Polynuclear Aromatic H	ydrocarbons							
Soil Glass Jar - Unpreserved (EP075(S								
S154,	S469,	06-MAR-2014	13-MAR-2014	20-MAR-2014	✓	14-MAR-2014	22-APR-2014	✓
S444,	S212,							
S38,	S91,							
S140,	S164,							
S41,	S15/1,							
S15/2								
EP080: BTEXN								
Soil Glass Jar - Unpreserved (EP080)								
S154,	S469,	06-MAR-2014	12-MAR-2014	20-MAR-2014	✓	14-MAR-2014	20-MAR-2014	✓
S444,	S212,							
S38,	S91,							
S140,	S164,							
S41,	S15/1,							
S15/2								

Page : 4 of 7
Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Matrix: SOIL					Evaluation:	x = Holding time	breach ; ✓ = Within	n holding time.	
Method			Ex	traction / Preparation		Analysis			
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation	
EP080/071: Total Petroleum Hyd	rocarbons								
Soil Glass Jar - Unpreserved (EPC	080)								
S154,	S469,	06-MAR-2014	12-MAR-2014	20-MAR-2014	1	14-MAR-2014	20-MAR-2014	✓	
S444,	S212,								
S38,	S91,								
S140,	S164,								
S41,	S15/1,								
S15/2									

Page : 5 of 7
Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C



Quality Control Parameter Frequency Compliance

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(where) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: **SOIL**Evaluation: ★ = Quality Control frequency not within specification; ✓ = Quality Control frequency within specification.

watrix: SOIL				Evaluation	i Quality Co	itioi irequericy ri	iot within specification; 🔻 = Quality Control frequency within specific
Quality Control Sample Type		Co	ount		Rate (%)		Quality Control Specification
Analytical Methods	Method	QC	Regular	Actual	Expected	Evaluation	
aboratory Duplicates (DUP)							
Noisture Content	EA055-103	2	20	10.0	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
AH/Phenols (SIM)	EP075(SIM)	2	19	10.5	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
esticides by GCMS	EP068	2	11	18.2	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
olychlorinated Biphenyls (PCB)	EP066	2	17	11.8	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Mercury by FIMS	EG035T	4	35	11.4	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Metals by ICP-AES	EG005T	4	32	12.5	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH - Semivolatile Fraction	EP071	2	19	10.5	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH Volatiles/BTEX	EP080	2	19	10.5	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
aboratory Control Samples (LCS)							
PAH/Phenols (SIM)	EP075(SIM)	1	19	5.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
esticides by GCMS	EP068	1	11	9.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
olychlorinated Biphenyls (PCB)	EP066	1	17	5.9	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Mercury by FIMS	EG035T	2	35	5.7	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Metals by ICP-AES	EG005T	2	32	6.3	5.0	1	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH - Semivolatile Fraction	EP071	1	19	5.3	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH Volatiles/BTEX	EP080	1	19	5.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Method Blanks (MB)							
PAH/Phenols (SIM)	EP075(SIM)	1	19	5.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Pesticides by GCMS	EP068	1	11	9.1	5.0	1	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Polychlorinated Biphenyls (PCB)	EP066	1	17	5.9	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Mercury by FIMS	EG035T	2	35	5.7	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Metals by ICP-AES	EG005T	2	32	6.3	5.0	1	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH - Semivolatile Fraction	EP071	1	19	5.3	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH Volatiles/BTEX	EP080	1	19	5.3	5.0	<u>√</u>	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Matrix Spikes (MS)							
PAH/Phenols (SIM)	EP075(SIM)	1	19	5.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Pesticides by GCMS	EP068	1	11	9.1	5.0		NEPM 2013 Schedule B(3) and ALS QCS3 requirement
olychlorinated Biphenyls (PCB)	EP066	1	17	5.9	5.0		NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Mercury by FIMS	EG035T	2	35	5.7	5.0		NEPM 2013 Schedule B(3) and ALS QCS3 requirement
otal Metals by ICP-AES	EG005T	2	32	6.3	5.0		NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PH - Semivolatile Fraction	EP071	1	19	5.3	5.0	√	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH Volatiles/BTEX	EP080	1	19	5.3	5.0		NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Page : 6 of 7
Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C

Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
Moisture Content	EA055-103	SOIL	A gravimetric procedure based on weight loss over a 12 hour drying period at 103-105 degrees C. This method is compliant with NEPM (2013) Schedule B(3) Section 7.1 and Table 1 (14 day holding time).
Total Metals by ICP-AES	EG005T	SOIL	(APHA 21st ed., 3120; USEPA SW 846 - 6010) (ICPAES) Metals are determined following an appropriate acid digestion of the soil. The ICPAES technique ionises samples in a plasma, emitting a characteristic spectrum based on metals present. Intensities at selected wavelengths are compared against those of matrix matched standards. This method is compliant with NEPM (2013) Schedule B(3)
Total Mercury by FIMS	EG035T	SOIL	AS 3550, APHA 21st ed., 3112 Hg - B (Flow-injection (SnCl2)(Cold Vapour generation) AAS) FIM-AAS is an automated flameless atomic absorption technique. Mercury in solids are determined following an appropriate acid digestion. Ionic mercury is reduced online to atomic mercury vapour by SnCl2 which is then purged into a heated quartz cell. Quantification is by comparing absorbance against a calibration curve. This method is compliant with NEPM (2013) Schedule B(3)
Polychlorinated Biphenyls (PCB)	EP066	SOIL	(USEPA SW 846 - 8270B) Extracts are analysed by Capillary GC/MS and quantification is by comparison against an established 5 point calibration curve. This method is compliant with NEPM (2013) Schedule B(3) (Method 504)
Pesticides by GCMS	EP068	SOIL	(USEPA SW 846 - 8270B) Extracts are analysed by Capillary GC/MS and quantification is by comparison against an established 5 point calibration curve. This technique is compliant with NEPM (2013) Schedule B(3) (Method 504,505)
TPH - Semivolatile Fraction	EP071	SOIL	(USEPA SW 846 - 8015A) Sample extracts are analysed by Capillary GC/FID and quantified against alkane standards over the range C10 - C36. This method is compliant with NEPM (2013) Schedule B(3) (Method 506.1)
PAH/Phenols (SIM)	EP075(SIM)	SOIL	(USEPA SW 846 - 8270B) Extracts are analysed by Capillary GC/MS in Selective Ion Mode (SIM) and quantification is by comparison against an established 5 point calibration curve. This method is compliant with NEPM (2013) Schedule B(3) (Method 502 and 507)
TPH Volatiles/BTEX	EP080	SOIL	(USEPA SW 846 - 8260B) Extracts are analysed by Purge and Trap, Capillary GC/MS. Quantification is by comparison against an established 5 point calibration curve. This method is compliant with NEPM (2013) Schedule B(3) (Method 501)
Preparation Methods	Method	Matrix	Method Descriptions
Methanolic Extraction of Soils for Purge and Trap	* ORG16	SOIL	(USEPA SW 846 - 5030A) 5g of solid is shaken with surrogate and 10mL methanol prior to analysis by Purge and Trap - GC/MS.
Tumbler Extraction of Solids (Option A - Concentrating)	ORG17A	SOIL	In-house, Mechanical agitation (tumbler). 20g of sample, Na2SO4 and surrogate are extracted with 150mL 1:1 DCM/Acetone by end over end tumble. The solvent is decanted, dehydrated and concentrated (by KD) to the desired volume for analysis.
Tumbler Extraction of Solids (Option B - Non-concentrating)	ORG17B	SOIL	In-house, Mechanical agitation (tumbler). 10g of sample, Na2SO4 and surrogate are extracted with 20mL 1:1 DCM/Acetone by end over end tumble. The solvent is transferred directly to a GC vial for analysis.

Page : 7 of 7

Work Order : ES1405222

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 4030C

Summary of Outliers

Outliers : Quality Control Samples

The following report highlights outliers flagged in the Quality Control (QC) Report. Surrogate recovery limits are static and based on USEPA SW 846 or ALS-QWI/EN/38 (in the absence of specific USEPA limits). This report displays QC Outliers (breaches) only.

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

Matrix: SOIL

Compound Group Name	Laboratory Sample ID	Client Sample ID	Analyte	CAS Number	Data	Limits	Comment
Duplicate (DUP) RPDs							
EP075(SIM)B: Polynuclear Aromatic Hydrocarbons	ES1405194-003	Anonymous	Sum of polycyclic aromatic		27.6 %	0-20%	RPD exceeds LOR based limits
			hydrocarbons				
Matrix Spike (MS) Recoveries							
EG005T: Total Metals by ICP-AES	ES1405194-004	Anonymous	Chromium	7440-47-3	Not		MS recovery not determined,
					Determined		background level greater than or
							equal to 4x spike level.

- For all matrices, no Method Blank value outliers occur.
- For all matrices, no Laboratory Control outliers occur.

Regular Sample Surrogates

• For all regular sample matrices, no surrogate recovery outliers occur.

Outliers: Analysis Holding Time Compliance

This report displays Holding Time breaches only. Only the respective Extraction / Preparation and/or Analysis component is/are displayed.

No Analysis Holding Time Outliers exist.

Outliers: Frequency of Quality Control Samples

The following report highlights breaches in the Frequency of Quality Control Samples.

No Quality Control Sample Frequency Outliers exist.



Head Properties Propertie	ANALYSIS RECUIRED including SUITES (Ng. Suite Codes must be listed to attract suite price) Where Metals are required, specify Total (untitored bottle required) or Dissolved (field filtared bottle required). Comments on likely contaminant	Environmental Division Sydney Work Order	Telephone . + 61-2-6784 85555	Anther Glass Unpreserved; AP - Airtrophit Urpreserved Plastic; In Plastic; HS = HCI preserved Speciation bolite; SP = Sultitle Preserved Plastic;
AD RANDE 21 Burne Papel Pocada SA 1005. Billison Residence Selection of the Control of the Cont	CONTAINER INFORMATION Metals are required, s REPRESERVATIVE A HESSERVATIVE A HESSERVATIVE			Water Container Goules: P = Unpresonvec Plastic, N = Nutric Presenved Positic: ORC = Native Presenved, S = Souther Highton (10 Presenved, S = Souther Highton (10 Presenved, S = VOA) Vial Solding Presenved, V3 = VOA) Vial Solding Presenved, V3 = VOA) Vial Solding E = EDIA Presenved Ratio of ST = Presenved Anticopy of the Souther Ander Glass; Z = Zinc. Actio of Market Glass; Z = Zinc. Actio of M
CHAIN OF CUSTODY ALS Laboratory CLUENT: CLUE	ALS SAMPLE DETAILS USE MATRIX - SOLID (S), WATER (W) LAB ID SAMPLE ID DATE/ TIME	1 5 2055/ 2 5 207/ 3 5 3001		Water Container Codes: P = Unpresorved Plastic; N = Nitht Preserved Plastic; OR V = VOA Volat Hell Preserved: VB = VOA Volat Behavior of F = Forma Religious Preserved: VB = VOA Volat Behavior of F = Forma Religious Preserved: Social Mass, Z = Zinc Acetale Preserved: Social E = Forta Preserved: Social Preserved: Socia



CERTIFICATE OF ANALYSIS

Work Order : **ES1405891** Page : 1 of 7

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

 Telephone
 : --- Telephone
 : +61-2-8784 8555

 Facsimile
 : --- Facsimile
 : +61-2-8784 8500

Project : 19580 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement Order number : 10833

C-O-C number : ---- Date Samples Received : 19-MAR-2014

Sampler : JK Issue Date : 25-MAR-2014 Site : ----

No. of samples received : 3

Quote number : EN/025/13 No. of samples analysed : 3

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results
- Surrogate Control Limits



NATA Accredited Laboratory 825

Accredited for compliance with ISO/IEC 17025.

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories

Position

Accreditation Category

Sydney Inorganics

Celine Conceicao

Senior Spectroscopist
Sydney Inorganics

Sydney Inorganics

Sydney Inorganics

Sydney Organics

Sydney Organics

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 PHONE +61-2-8784 8555 Facsimile +61-2-8784 8500
Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 7 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting


^ = This result is computed from individual analyte detections at or above the level of reporting

ALS is not NATA accredited for the analysis of Bifenthrin in soils when performed under ALS Method EP068D

Page : 3 of 7 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580





Page : 4 of 7 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580





Page : 5 of 7 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580





Page : 6 of 7

Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580





Page : 7 of 7 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

Surrogate Control Limits

Sub-Matrix: SOIL		Recovery	Limits (%)
Compound	CAS Number	Low	High
EP066S: PCB Surrogate			
Decachlorobiphenyl	2051-24-3	39	149
EP068S: Organochlorine Pesticide Surrogate	•		
Dibromo-DDE	21655-73-2	49	147
EP068T: Organophosphorus Pesticide Surro	gate		
DEF	78-48-8	35	143
EP075(SIM)S: Phenolic Compound Surrogate	es		
Phenol-d6	13127-88-3	63	123
2-Chlorophenol-D4	93951-73-6	66	122
2.4.6-Tribromophenol	118-79-6	40	138
EP075(SIM)T: PAH Surrogates			
2-Fluorobiphenyl	321-60-8	70	122
Anthracene-d10	1719-06-8	66	128
4-Terphenyl-d14	1718-51-0	65	129
EP080S: TPH(V)/BTEX Surrogates			
1.2-Dichloroethane-D4	17060-07-0	72.8	133.2
Toluene-D8	2037-26-5	73.9	132.1
4-Bromofluorobenzene	460-00-4	71.6	130.0





QUALITY CONTROL REPORT

: ES1405891 **Work Order** Page : 1 of 12

Client SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact · Client Services

Address Address : 277-289 Woodpark Road Smithfield NSW Australia 2164 : P O BOX 6989

WETHERILL PARK NSW. AUSTRALIA 2164

E-mail : enquiries@smectesting.com.au E-mail : sydney@alsglobal.com

Telephone +61-2-8784 8555 Telephone · ____ Facsimile Facsimile +61-2-8784 8500

Project : 19580 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Site

C-O-C number **Date Samples Received** : 19-MAR-2014 : ----: 25-MAR-2014 Sampler : JK Issue Date

Order number : 10833

No. of samples received : 3 Quote number : EN/025/13 No. of samples analysed : 3

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Quality Control Report contains the following information:

Accredited for

compliance with

ISO/IEC 17025.

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits



NATA Accredited Laboratory 825

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories Position Accreditation Category

Sydney Inorganics Celine Conceicao Senior Spectroscopist Sydney Inorganics Pabi Subba Senior Organic Chemist Sydney Organics

> Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

= Indicates failed QC

Page : 3 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR:-No Limit; Result between 10 and 20 times LOR:-0% - 50%; Result > 20 times LOR:-0% - 20%.

Sub-Matrix: SOIL				Laboratory Duplicate (DUP) Report								
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%			
EA055: Moisture Co	ontent (QC Lot: 3350010	0)										
ES1405883-009	Anonymous	EA055-103: Moisture Content (dried @ 103°C)		1.0	%	11.2	10.2	9.3	0% - 50%			
ES1405938-008	Anonymous	EA055-103: Moisture Content (dried @ 103°C)		1.0	%	20.3	18.7	7.9	0% - 20%			
EG005T: Total Meta	ils by ICP-AES (QC Lot:	: 3351439)										
ES1405739-002	Anonymous	EG005T: Cadmium	7440-43-9	1	mg/kg	<1	<1	0.0	No Limit			
		EG005T: Chromium	7440-47-3	2	mg/kg	8	7	0.0	No Limit			
		EG005T: Nickel	7440-02-0	2	mg/kg	<2	<2	0.0	No Limit			
		EG005T: Arsenic	7440-38-2	5	mg/kg	<5	<5	0.0	No Limit			
		EG005T: Copper	7440-50-8	5	mg/kg	8	7	0.0	No Limit			
		EG005T: Lead	7439-92-1	5	mg/kg	6	5	21.4	No Limit			
		EG005T: Zinc	7440-66-6	5	mg/kg	15	6	83.7	No Limit			
ES1405891-001	S283	EG005T: Cadmium	7440-43-9	1	mg/kg	<1	<1	0.0	No Limit			
		EG005T: Chromium	7440-47-3	2	mg/kg	<2	4	70.5	No Limit			
		EG005T: Nickel	7440-02-0	2	mg/kg	<2	<2	0.0	No Limit			
		EG005T: Arsenic	7440-38-2	5	mg/kg	<5	<5	0.0	No Limit			
		EG005T: Copper	7440-50-8	5	mg/kg	<5	<5	0.0	No Limit			
		EG005T: Lead	7439-92-1	5	mg/kg	8	9	0.0	No Limit			
		EG005T: Zinc	7440-66-6	5	mg/kg	10	9	15.6	No Limit			
G035T: Total Rec	overable Mercury by FIM	MS (QC Lot: 3351440)										
ES1405739-002	Anonymous	EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	<0.1	0.0	No Limit			
ES1405891-001	S283	EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	<0.1	0.0	No Limit			
EP066: Polychlorin	ated Biphenyls (PCB) (QC Lot: 3349459)										
ES1405891-001	S283	EP066: Total Polychlorinated biphenyls		0.1	mg/kg	<0.1	<0.1	0.0	No Limit			
EP068A: Organoch	lorine Pesticides (OC) (QC Lot: 3349458)										
ES1405891-001	S283	EP068: alpha-BHC	319-84-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: Hexachlorobenzene (HCB)	118-74-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: beta-BHC	319-85-7	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: gamma-BHC	58-89-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: delta-BHC	319-86-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: Heptachlor	76-44-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: Aldrin	309-00-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: Heptachlor epoxide	1024-57-3	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: trans-Chlordane	5103-74-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: alpha-Endosulfan	959-98-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: cis-Chlordane	5103-71-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			
		EP068: Dieldrin	60-57-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit			

Page : 4 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL				Laboratory Duplicate (DUP) Report						
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)	
EP068A: Organochic	orine Pesticides (OC) (QC	C Lot: 3349458) - continued								
ES1405891-001	S283	EP068: 4.4`-DDE	72-55-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endrin	72-20-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: beta-Endosulfan	33213-65-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: 4.4`-DDD	72-54-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endrin aldehyde	7421-93-4	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endosulfan sulfate	1031-07-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Endrin ketone	53494-70-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: 4.4`-DDT	50-29-3	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
		EP068: Methoxychlor	72-43-5	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
EP068B: Organopho	sphorus Pesticides (OP)	(QC Lot: 3349458)								
ES1405891-001	S283	EP068: Dichlorvos	62-73-7	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Demeton-S-methyl	919-86-8	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Dimethoate	60-51-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Diazinon	333-41-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Chlorpyrifos-methyl	5598-13-0	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Malathion	121-75-5	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Fenthion	55-38-9	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Chlorpyrifos	2921-88-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Pirimphos-ethyl	23505-41-1	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Bromophos-ethyl	4824-78-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Fenamiphos	22224-92-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Prothiofos	34643-46-4	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Ethion	563-12-2	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Carbophenothion	786-19-6	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Azinphos Methyl	86-50-0	0.05	mg/kg	<0.05	<0.05	0.0	No Limit	
		EP068: Monocrotophos	6923-22-4	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
		EP068: Parathion-methyl	298-00-0	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
		EP068: Parathion	56-38-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit	
EP075(SIM)B: Polyni	uclear Aromatic Hydroca	rbons (QC Lot: 3347805)								
ES1405601-001	Anonymous	EP075(SIM): Naphthalene	91-20-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit	
		EP075(SIM): Acenaphthylene	208-96-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit	
		EP075(SIM): Acenaphthene	83-32-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit	
		EP075(SIM): Fluorene	86-73-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit	
		EP075(SIM): Phenanthrene	85-01-8	0.5	mg/kg	1.0	0.8	18.4	No Limit	
		EP075(SIM): Anthracene	120-12-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit	
		EP075(SIM): Fluoranthene	206-44-0	0.5	mg/kg	1.2	1.1	8.9	No Limit	
		EP075(SIM): Pyrene	129-00-0	0.5	mg/kg	1.0	0.8	20.6	No Limit	
		EP075(SIM): Benz(a)anthracene	56-55-3	0.5	mg/kg	0.6	<0.5	0.0	No Limit	
		EP075(SIM): Chrysene	218-01-9	0.5	mg/kg	0.7	0.5	20.7	No Limit	
		EP075(SIM): Benzo(b)fluoranthene	205-99-2	0.5	mg/kg	0.6	0.6	0.0	No Limit	
	1	(, (, , , , , , , , , , , , , , , , ,				1	1		-	

Page : 5 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL				Laboratory Duplicate (DUP) Report							
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)		
EP075(SIM)B: Polyn	uclear Aromatic Hydro	ocarbons (QC Lot: 3347805) - continued									
ES1405601-001	Anonymous	EP075(SIM): Benzo(k)fluoranthene	207-08-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benzo(a)pyrene	50-32-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Indeno(1.2.3.cd)pyrene	193-39-5	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Dibenz(a.h)anthracene	53-70-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benzo(g.h.i)perylene	191-24-2	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Sum of polycyclic aromatic		0.5	mg/kg	5.1	3.8	29.2	0% - 50%		
		hydrocarbons									
		EP075(SIM): Benzo(a)pyrene TEQ (zero)		0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
ES1405891-003	S130	EP075(SIM): Naphthalene	91-20-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Acenaphthylene	208-96-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Acenaphthene	83-32-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Fluorene	86-73-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Phenanthrene	85-01-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Anthracene	120-12-7	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Fluoranthene	206-44-0	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Pyrene	129-00-0	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benz(a)anthracene	56-55-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Chrysene	218-01-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benzo(b)fluoranthene	205-99-2	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benzo(k)fluoranthene	207-08-9	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benzo(a)pyrene	50-32-8	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Indeno(1.2.3.cd)pyrene	193-39-5	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Dibenz(a.h)anthracene	53-70-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Benzo(g.h.i)perylene	191-24-2	0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		EP075(SIM): Sum of polycyclic aromatic		0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
		hydrocarbons									
		EP075(SIM): Benzo(a)pyrene TEQ (zero)		0.5	mg/kg	<0.5	<0.5	0.0	No Limit		
EP080/071: Total Pe	troleum Hydrocarbons	s (QC Lot: 3347806)									
ES1405601-001	Anonymous	EP071: C15 - C28 Fraction		100	mg/kg	350	310	10.2	No Limit		
		EP071: C29 - C36 Fraction		100	mg/kg	220	210	0.0	No Limit		
		EP071: C10 - C14 Fraction		50	mg/kg	<50	<50	0.0	No Limit		
ES1405891-003	S130	EP071: C15 - C28 Fraction		100	mg/kg	<100	<100	0.0	No Limit		
		EP071: C29 - C36 Fraction		100	mg/kg	<100	<100	0.0	No Limit		
		EP071: C10 - C14 Fraction		50	mg/kg	<50	<50	0.0	No Limit		
EP080/071: Total Pe	troleum Hydrocarbons	s (QC Lot: 3347810)									
ES1405878-001	Anonymous	EP080: C6 - C9 Fraction		10	mg/kg	<10	<10	0.0	No Limit		
ES1405883-002	Anonymous	EP080: C6 - C9 Fraction		10	mg/kg	<10	<10	0.0	No Limit		
EP080/071: Total Re	coverable <u>Hydrocarbo</u>	ons - NEPM 2013 (QC Lot: 3347806)									
ES1405601-001	Anonymous	EP071: >C16 - C34 Fraction		100	mg/kg	480	440	8.5	No Limit		
	,	EP071: >C34 - C40 Fraction		100	mg/kg	150	150	0.0	No Limit		
l .	I				33	1 22			. =		

Page : 6 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL						Laboratory	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EP080/071: Total Re	coverable Hydrocarbo	ns - NEPM 2013 (QC Lot: 3347806) - continued							
ES1405601-001	Anonymous	EP071: >C10 - C16 Fraction	>C10_C16	50	mg/kg	50	<50	0.0	No Limit
ES1405891-003	S130	EP071: >C16 - C34 Fraction		100	mg/kg	<100	<100	0.0	No Limit
		EP071: >C34 - C40 Fraction		100	mg/kg	<100	<100	0.0	No Limit
		EP071: >C10 - C16 Fraction	>C10_C16	50	mg/kg	<50	<50	0.0	No Limit
EP080/071: Total Re	coverable Hydrocarbo	ns - NEPM 2013 (QC Lot: 3347810)							
ES1405878-001	Anonymous	EP080: C6 - C10 Fraction	C6_C10	10	mg/kg	<10	<10	0.0	No Limit
ES1405883-002	Anonymous	EP080: C6 - C10 Fraction	C6_C10	10	mg/kg	<10	<10	0.0	No Limit
EP080: BTEXN (QC	Lot: 3347810)								
ES1405878-001	Anonymous	EP080: Benzene	71-43-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP080: Toluene	108-88-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Ethylbenzene	100-41-4	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: meta- & para-Xylene	108-38-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
			106-42-3						
		EP080: ortho-Xylene	95-47-6	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Naphthalene	91-20-3	1	mg/kg	<1	<1	0.0	No Limit
ES1405883-002	Anonymous	EP080: Benzene	71-43-2	0.2	mg/kg	<0.2	<0.2	0.0	No Limit
		EP080: Toluene	108-88-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Ethylbenzene	100-41-4	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: meta- & para-Xylene	108-38-3	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
			106-42-3						
		EP080: ortho-Xylene	95-47-6	0.5	mg/kg	<0.5	<0.5	0.0	No Limit
		EP080: Naphthalene	91-20-3	1	mg/kg	<1	<1	0.0	No Limit

Page : 7 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Sample (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: SOIL				Method Blank (MB)		Laboratory Control Spike (LCS) Report		
				Report	Spike	Spike Recovery (%)	Recovery	Limits (%)
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High
EG005T: Total Metals by ICP-AES (QCLot: 335	1439)							
EG005T: Arsenic	7440-38-2	5	mg/kg	<5	21.7 mg/kg	112	87	129
EG005T: Cadmium	7440-43-9	1	mg/kg	<1	4.64 mg/kg	107	80	122
EG005T: Chromium	7440-47-3	2	mg/kg	<2	43.9 mg/kg	102	71	133
EG005T: Copper	7440-50-8	5	mg/kg	<5	32.0 mg/kg	113	86	128
EG005T: Lead	7439-92-1	5	mg/kg	<5	40.0 mg/kg	105	81	123
EG005T: Nickel	7440-02-0	2	mg/kg	<2	55.0 mg/kg	110	84	130
EG005T: Zinc	7440-66-6	5	mg/kg	<5	60.8 mg/kg	114	81	133
EG035T: Total Recoverable Mercury by FIMS	(QCLot: 3351440)							
EG035T: Mercury	7439-97-6	0.1	mg/kg	<0.1	2.57 mg/kg	90.5	66	112
EP066: Polychlorinated Biphenyls (PCB) (QCL	ot: 3349459)							
EP066: Total Polychlorinated biphenyls		0.1	mg/kg	<0.1	1 mg/kg	82.0	57.4	117
EP068A: Organochlorine Pesticides (OC) (QCI	Lot: 3349458)							
EP068: alpha-BHC	319-84-6	0.05	mg/kg	<0.05	0.5 mg/kg	80.4	71	113
EP068: Hexachlorobenzene (HCB)	118-74-1	0.05	mg/kg	<0.05	0.5 mg/kg	94.6	66	122
EP068: beta-BHC	319-85-7	0.05	mg/kg	<0.05	0.5 mg/kg	101	69	119
EP068: gamma-BHC	58-89-9	0.05	mg/kg	<0.05	0.5 mg/kg	98.7	71	115
EP068: delta-BHC	319-86-8	0.05	mg/kg	<0.05	0.5 mg/kg	89.2	65	113
EP068: Heptachlor	76-44-8	0.05	mg/kg	<0.05	0.5 mg/kg	88.8	68	116
EP068: Aldrin	309-00-2	0.05	mg/kg	<0.05	0.5 mg/kg	80.9	68	118
EP068: Heptachlor epoxide	1024-57-3	0.05	mg/kg	<0.05	0.5 mg/kg	92.4	68	116
EP068: trans-Chlordane	5103-74-2	0.05	mg/kg	<0.05	0.5 mg/kg	105	68	120
EP068: alpha-Endosulfan	959-98-8	0.05	mg/kg	<0.05	0.5 mg/kg	85.0	69	119
EP068: cis-Chlordane	5103-71-9	0.05	mg/kg	<0.05	0.5 mg/kg	88.4	67	121
EP068: Dieldrin	60-57-1	0.05	mg/kg	<0.05	0.5 mg/kg	89.9	66	118
EP068: 4.4`-DDE	72-55-9	0.05	mg/kg	<0.05	0.5 mg/kg	93.1	69	117
EP068: Endrin	72-20-8	0.05	mg/kg	<0.05	0.5 mg/kg	85.7	67	123
EP068: beta-Endosulfan	33213-65-9	0.05	mg/kg	<0.05	0.5 mg/kg	92.6	76	120
EP068: 4.4`-DDD	72-54-8	0.05	mg/kg	<0.05	0.5 mg/kg	100	76	120
EP068: Endrin aldehyde	7421-93-4	0.05	mg/kg	<0.05	0.5 mg/kg	89.5	57.3	115
EP068: Endosulfan sulfate	1031-07-8	0.05	mg/kg	<0.05	0.5 mg/kg	87.2	60	124
EP068: 4.4`-DDT	50-29-3	0.2	mg/kg	<0.2	0.5 mg/kg	96.1	67	127
EP068: Endrin ketone	53494-70-5	0.05	mg/kg	<0.05	0.5 mg/kg	88.1	65	123
EP068: Methoxychlor	72-43-5	0.2	mg/kg	<0.2	0.5 mg/kg	102	65	129

Page : 8 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL			Method Blank (MB)		Laboratory Control Spike (LC	S) Report	
			Report	Spike	Spike Recovery (%)	Recovery I	imits (%)
Method: Compound CAS Numb	er LOR	Unit	Result	Concentration	LCS	Low	High
EP068B: Organophosphorus Pesticides (OP) (QCLot: 3349458) - cont	nued						
EP068: Dichlorvos 62-73-	0.05	mg/kg	<0.05	0.5 mg/kg	74.0	56	126
EP068: Demeton-S-methyl 919-86-	0.05	mg/kg	<0.05	0.5 mg/kg	78.6	64	128
EP068: Monocrotophos 6923-22-	0.2	mg/kg	<0.2	0.5 mg/kg	78.3	54	122
EP068: Dimethoate 60-51-	0.05	mg/kg	<0.05	0.5 mg/kg	80.9	64	124
EP068: Diazinon 333-41-	0.05	mg/kg	<0.05	0.5 mg/kg	86.5	73	117
EP068: Chlorpyrifos-methyl 5598-13-	0.05	mg/kg	<0.05	0.5 mg/kg	91.6	55	119
EP068: Parathion-methyl 298-00-	0.2	mg/kg	<0.2	0.5 mg/kg	89.3	69	123
EP068: Malathion 121-75-	0.05	mg/kg	<0.05	0.5 mg/kg	98.7	70	120
EP068: Fenthion 55-38-	0.05	mg/kg	<0.05	0.5 mg/kg	90.4	71	115
EP068: Chlorpyrifos 2921-88-	0.05	mg/kg	<0.05	0.5 mg/kg	94.3	68	114
EP068: Parathion 56-38-		mg/kg	<0.2	0.5 mg/kg	105	68	122
EP068: Pirimphos-ethyl 23505-41-	0.05	mg/kg	<0.05	0.5 mg/kg	94.9	69	115
EP068: Bromophos-ethyl 4824-78-	0.05	mg/kg	<0.05	0.5 mg/kg	97.9	68	116
EP068: Fenamiphos 22224-92-		mg/kg	<0.05	0.5 mg/kg	89.7	64	120
EP068: Prothiofos 34643-46-		mg/kg	<0.05	0.5 mg/kg	94.5	68	116
EP068: Ethion 563-12-	0.05	mg/kg	<0.05	0.5 mg/kg	96.8	70	118
EP068: Carbophenothion 786-19-	0.05	mg/kg	<0.05	0.5 mg/kg	90.7	67	123
EP068: Azinphos Methyl 86-50-	0.05	mg/kg	<0.05	0.5 mg/kg	97.1	42	126
EP075(SIM)B: Polynuclear Aromatic Hydrocarbons (QCLot: 3347805)							
EP075(SIM): Naphthalene 91-20-	0.5	mg/kg	<0.5	4 mg/kg	101	80	124
EP075(SIM): Acenaphthylene 208-96-	0.5	mg/kg	<0.5	4 mg/kg	95.3	77	123
EP075(SIM): Acenaphthene 83-32-	0.5	mg/kg	<0.5	4 mg/kg	99.0	79	123
EP075(SIM): Fluorene 86-73-	0.5	mg/kg	<0.5	4 mg/kg	97.6	77	123
EP075(SIM): Phenanthrene 85-01-	0.5	mg/kg	<0.5	4 mg/kg	103	79	123
EP075(SIM): Anthracene 120-12-	0.5	mg/kg	<0.5	4 mg/kg	101	79	123
EP075(SIM): Fluoranthene 206-44-	0.5	mg/kg	<0.5	4 mg/kg	98.5	79	123
EP075(SIM): Pyrene 129-00-	0.5	mg/kg	<0.5	4 mg/kg	100	79	125
EP075(SIM): Benz(a)anthracene 56-55-	0.5	mg/kg	<0.5	4 mg/kg	92.0	73	121
EP075(SIM): Chrysene 218-01-	0.5	mg/kg	<0.5	4 mg/kg	98.4	81	123
EP075(SIM): Benzo(b)fluoranthene 205-99-	2 0.5	mg/kg	<0.5	4 mg/kg	88.8	70	118
EP075(SIM): Benzo(k)fluoranthene 207-08-	0.5	mg/kg	<0.5	4 mg/kg	101	77	123
EP075(SIM): Benzo(a)pyrene 50-32-	0.5	mg/kg	<0.5	4 mg/kg	90.1	76	122
EP075(SIM): Indeno(1.2.3.cd)pyrene 193-39-	0.5	mg/kg	<0.5	4 mg/kg	83.5	71	113
EP075(SIM): Dibenz(a.h)anthracene 53-70-	0.5	mg/kg	<0.5	4 mg/kg	83.5	71.7	113
EP075(SIM): Benzo(g.h.i)perylene 191-24-	0.5	mg/kg	<0.5	4 mg/kg	81.4	72.4	114
EP080/071: Total Petroleum Hydrocarbons (QCLot: 3347806)							
EP071: C10 - C14 Fraction	- 50	mg/kg	<50	200 mg/kg	109	71	131
EP071: C15 - C28 Fraction	- 100	mg/kg	<100	300 mg/kg	96.0	74	138
EP071: C29 - C36 Fraction	- 100	mg/kg	<100	200 mg/kg	93.6	64	128

Page : 9 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Sub-Matrix: SOIL				Method Blank (MB)		Laboratory Control Spike (LC	S) Report	
				Report	Spike	Spike Recovery (%)	Recovery	Limits (%)
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High
EP080/071: Total Petroleum Hydrocarbons (QCLo	ot: 3347810)							
EP080: C6 - C9 Fraction		10	mg/kg	<10	26 mg/kg	83.2	68.4	128
EP080/071: Total Recoverable Hydrocarbons - NE	PM 2013 (QCLot: 334780	6)						
EP071: >C10 - C16 Fraction	>C10_C16	50	mg/kg	<50	250 mg/kg	94.4	70	130
EP071: >C16 - C34 Fraction		100	mg/kg	<100	350 mg/kg	94.7	74	138
EP071: >C34 - C40 Fraction		100	mg/kg	<100				
		50	mg/kg		150 mg/kg	114	63	131
EP080/071: Total Recoverable Hydrocarbons - NE	PM 2013 (QCLot: 334781	0)						
EP080: C6 - C10 Fraction	C6_C10	10	mg/kg	<10	31 mg/kg	80.3	68.4	128
EP080: BTEXN (QCLot: 3347810)								
EP080: Benzene	71-43-2	0.2	mg/kg	<0.2	1 mg/kg	87.5	62	116
EP080: Toluene	108-88-3	0.5	mg/kg	<0.5	1 mg/kg	92.2	62	128
EP080: Ethylbenzene	100-41-4	0.5	mg/kg	<0.5	1 mg/kg	86.2	58	118
EP080: meta- & para-Xylene	108-38-3	0.5	mg/kg	<0.5	2 mg/kg	83.0	60	120
	106-42-3							
EP080: ortho-Xylene	95-47-6	0.5	mg/kg	<0.5	1 mg/kg	90.3	60	120
EP080: Naphthalene	91-20-3	1	mg/kg	<1	1 mg/kg	85.5	62	138

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: SOIL				M	atrix Spike (MS) Report		
				Spike	SpikeRecovery(%)	Recovery I	_imits (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High
EG005T: Total Met	als by ICP-AES (QCLot: 3351439)						
ES1405739-002	Anonymous	EG005T: Arsenic	7440-38-2	50 mg/kg	107	70	130
		EG005T: Cadmium	7440-43-9	50 mg/kg	105	70	130
		EG005T: Chromium	7440-47-3	50 mg/kg	105	70	130
		EG005T: Copper	7440-50-8	125 mg/kg	106	70	130
		EG005T: Lead	7439-92-1	125 mg/kg	104	70	130
		EG005T: Nickel	7440-02-0	50 mg/kg	97.6	70	130
		EG005T: Zinc	7440-66-6	125 mg/kg	101	70	130
EG035T: Total Re	coverable Mercury by FIMS (QCLot: 3351440)						
ES1405739-002	Anonymous	EG035T: Mercury	7439-97-6	5 mg/kg	94.4	70	130
EP066: Polychlorir	nated Biphenyls (PCB) (QCLot: 3349459)						
ES1405891-001	S283	EP066: Total Polychlorinated biphenyls		1 mg/kg	91.0	70	130
EP068A: Organoch	nlorine Pesticides (OC) (QCLot: 3349458)						
ES1405891-001	S283						

Page : 10 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL				M	atrix Spike (MS) Repor	t	
				Spike	SpikeRecovery(%)	Recovery L	imits (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High
EP068A: Organoch	nlorine Pesticides (OC) (QCLot: 3349458) - continued						
ES1405891-001	S283	EP068: gamma-BHC	58-89-9	0.5 mg/kg	96.3	70	130
		EP068: Heptachlor	76-44-8	0.5 mg/kg	95.6	70	130
		EP068: Aldrin	309-00-2	0.5 mg/kg	101	70	130
		EP068: Dieldrin	60-57-1	0.5 mg/kg	109	70	130
		EP068: Endrin	72-20-8	2 mg/kg	105	70	130
		EP068: 4.4`-DDT	50-29-3	2 mg/kg	75.7	70	130
EP068B: Organopl	nosphorus Pesticides (OP) (QCLot: 3349458)						
ES1405891-001	S283	EP068: Diazinon	333-41-5	0.5 mg/kg	103	70	130
		EP068: Chlorpyrifos-methyl	5598-13-0	0.5 mg/kg	76.7	70	130
		EP068: Pirimphos-ethyl	23505-41-1	0.5 mg/kg	103	70	130
		EP068: Bromophos-ethyl	4824-78-6	0.5 mg/kg	107	70	130
		EP068: Prothiofos	34643-46-4	0.5 mg/kg	91.4	70	130
EP075(SIM)B: Poly	rnuclear Aromatic Hydrocarbons (QCLot: 3347805)						
ES1405601-001	Anonymous	EP075(SIM): Acenaphthene	83-32-9	10 mg/kg	91.1	70	130
		EP075(SIM): Pyrene	129-00-0	10 mg/kg	84.1	70	130
EP080/071: Total P	etroleum Hydrocarbons (QCLot: 3347806)						
ES1405601-001	Anonymous	EP071: C10 - C14 Fraction		640 mg/kg	86.8	73	137
		EP071: C15 - C28 Fraction		3140 mg/kg	80.2	53	131
		EP071: C29 - C36 Fraction		2860 mg/kg	74.8	52	132
EP080/071: Total P	Petroleum Hydrocarbons (QCLot: 3347810)	El 071. 020 GGG Haddigh		3 3			
ES1405878-001	Anonymous	EP080: C6 - C9 Fraction		32.5 mg/kg	77.3	70	130
	, ,			OZ.O Mg/kg	77.0	70	100
	Recoverable Hydrocarbons - NEPM 2013 (QCLot: 3347)	806)					
ES1405601-001	Anonymous	EP071: >C10 - C16 Fraction	>C10_C16	850 mg/kg	96.0	73	137
		EP071: >C16 - C34 Fraction		4800 mg/kg	71.4	53	131
		EP071: >C34 - C40 Fraction		2400 mg/kg	57.4	52	132
EP080/071: Total R	Recoverable Hydrocarbons - NEPM 2013 (QCLot: 3347)	810)					
ES1405878-001	Anonymous	EP080: C6 - C10 Fraction	C6_C10	37.5 mg/kg	72.5	70	130
EP080: BTEXN (Q	CLot: 3347810)						
ES1405878-001	Anonymous	EP080: Benzene	71-43-2	2.5 mg/kg	73.4	70	130
		EP080: Toluene	108-88-3	2.5 mg/kg	75.8	70	130
		EP080: Ethylbenzene	100-41-4	2.5 mg/kg	74.0	70	130
		EP080: meta- & para-Xylene	108-38-3	2.5 mg/kg	72.3	70	130
			106-42-3				
		EP080: ortho-Xylene	95-47-6	2.5 mg/kg	74.8	70	130
		EP080: Naphthalene	91-20-3	2.5 mg/kg	76.6	70	130

Page : 11 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



The quality control term Matrix Spike (MS) and Matrix Spike Duplicate (MSD) refers to intralaboratory split samples spiked with a representative set of target analytes. The purpose of these QC parameters are to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: SOIL					Matrix Spike (I	MS) and Matrix S	pike Duplicate	(MSD) Repor	t	
				Spike	Spike Re	covery (%)	Recovery	Limits (%)	RP	Ds (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	MSD	Low	High	Value	Control Lin
P075(SIM)B: Poly	nuclear Aromatic Hydrocarb	ons (QCLot: 3347805)								
ES1405601-001	Anonymous	EP075(SIM): Acenaphthene	83-32-9	10 mg/kg	91.1		70	130		
		EP075(SIM): Pyrene	129-00-0	10 mg/kg	84.1		70	130		
P080/071: Total P	etroleum Hydrocarbons (QC	Lot: 3347806)								
ES1405601-001	Anonymous	EP071: C10 - C14 Fraction		640 mg/kg	86.8		73	137		
		EP071: C15 - C28 Fraction		3140 mg/kg	80.2		53	131		
		EP071: C29 - C36 Fraction		2860 mg/kg	74.8		52	132		
P080/071: Total R	Recoverable Hydrocarbons - N	NEPM 2013 (QCLot: 3347806)								
S1405601-001	Anonymous	EP071: >C10 - C16 Fraction	>C10 C16	850 mg/kg	96.0		73	137		
		EP071: >C16 - C34 Fraction		4800 mg/kg	71.4		53	131		
		EP071: >C34 - C40 Fraction		2400 mg/kg	57.4		52	132		
P080/071: Total P	etroleum Hydrocarbons (QC	Lot: 3347810)								
ES1405878-001	Anonymous	EP080: C6 - C9 Fraction		32.5 mg/kg	77.3		70	130		
P080/071: Total R	ecoverable Hydrocarbons -	NEPM 2013 (QCLot: 3347810)		5 5						
ES1405878-001	Anonymous	EP080: C6 - C10 Fraction	C6_C10	37.5 mg/kg	72.5		70	130		
	,	El 000. Co - C lo i l'action	55_5.6	or to mg/ng				.00		
P080: BTEXN (Q	Anonymous	ED000 D	71-43-2	2.5 mg/kg	73.4		70	130		
S1405878-001 Anony	Anonymous	EP080: Benzene	108-88-3	2.5 mg/kg 2.5 mg/kg	75.8		70	130		
		EP080: Toluene	100-00-3	2.5 mg/kg 2.5 mg/kg	74.0		70	130		
		EP080: Ethylbenzene			72.3		70	130		
		EP080: meta- & para-Xylene	108-38-3 106-42-3	2.5 mg/kg	12.3		70	130		
		EP080: ortho-Xylene	95-47-6	2.5 mg/kg	74.8		70	130		
		EP080: Naphthalene	91-20-3	2.5 mg/kg	76.6		70	130		
DOCOA : Ourses sh	olonino Bostinidos (OC) (OC)		31 23 3	gg				.00		
S1405891-001	nlorine Pesticides (OC) (QCL S283	EP068: gamma-BHC	58-89-9	0.5 mg/kg	96.3		70	130		
-01403091-001	0203	EP068: Heptachlor	76-44-8	0.5 mg/kg	95.6		70	130		
		EP068: Aldrin	309-00-2	0.5 mg/kg 0.5 mg/kg	101		70	130		
		EP068: Dieldrin	60-57-1	0.5 mg/kg	109		70	130		
		EP068: Endrin	72-20-8	2 mg/kg	105		70	130		
		EP068: 4.4`-DDT	50-29-3	2 mg/kg	75.7		70	130		
D069B: Organish	nosphorus Pesticides (OP) (00 20 0	gg				.00		
P068B: Organopr S1405891-001	S283	EP068: Diazinon	333-41-5	0.5 mg/kg	103		70	130		
-0.1-0.0091-001	0200		5598-13-0	0.5 mg/kg	76.7		70	130		
		EP068: Chlorpyrifos-methyl	23505-41-1	0.5 mg/kg 0.5 mg/kg	103		70	130		
		EP068: Promonhos othyl	4824-78-6	0.5 mg/kg 0.5 mg/kg	103		70	130		
		EP068: Bromophos-ethyl EP068: Prothiofos	34643-46-4	0.5 mg/kg 0.5 mg/kg	91.4		70	130		
		EP000. PIOIIII0I0S	34043-40-4	0.5 mg/kg	J1. 4		70	130		

Page : 12 of 12 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Sub-Matrix: SOIL					Matrix Spike (A	IS) and Matrix Sp	oike Duplicate	(MSD) Repor	t	
				Spike	Spike Red	covery (%)	Recovery	Limits (%)	RPL	Ds (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	MSD	Low	High	Value	Control Limit
EP066: Polychlorin	ated Biphenyls (PCB) (QCLot: 3349459)	- continued								
ES1405891-001	S283	EP066: Total Polychlorinated biphenyls		1 mg/kg	91.0		70	130		
EG005T: Total Meta	ils by ICP-AES (QCLot: 3351439)									
ES1405739-002	Anonymous	EG005T: Arsenic	7440-38-2	50 mg/kg	107		70	130		
		EG005T: Cadmium	7440-43-9	50 mg/kg	105		70	130		
		EG005T: Chromium	7440-47-3	50 mg/kg	105		70	130		
		EG005T: Copper	7440-50-8	125 mg/kg	106		70	130		
		EG005T: Lead	7439-92-1	125 mg/kg	104		70	130		
		EG005T: Nickel	7440-02-0	50 mg/kg	97.6		70	130		
		EG005T: Zinc	7440-66-6	125 mg/kg	101		70	130		
EG035T: Total Rec	overable Mercury by FIMS (QCLot: 33514	40)								
ES1405739-002	Anonymous	EG035T: Mercury	7439-97-6	5 mg/kg	94.4		70	130		



INTERPRETIVE QUALITY CONTROL REPORT

Work Order : **ES1405891** Page : 1 of 6

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

 Telephone
 : --- Telephone
 : +61-2-8784 8555

 Facsimile
 : --- Facsimile
 : +61-2-8784 8500

Project : 19580 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Site : ----

 C-O-C number
 : -- Date Samples Received
 : 19-MAR-2014

 Sampler
 : JK
 Issue Date
 : 25-MAR-2014

Order number : 10833

No. of samples received : 3

Quote number : EN/025/13 No. of samples analysed : 3

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Interpretive Quality Control Report contains the following information:

Analysis Holding Time Compliance

- Quality Control Parameter Frequency Compliance
- Brief Method Summaries
- Summary of Outliers

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 6 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Analysis Holding Time Compliance

This report summarizes extraction / preparation and analysis times and compares each with recommended holding times (USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive <u>or</u> Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: SOIL					Evaluation:	× = Holding time	breach ; ✓ = Withir	n holding time.
Method		Sample Date	Ex	traction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EA055: Moisture Content								
Soil Glass Jar - Unpreserved (EA055-103) S283, S130	S283/2,	14-MAR-2014				20-MAR-2014	28-MAR-2014	✓
EG005T: Total Metals by ICP-AES								
Soil Glass Jar - Unpreserved (EG005T) S283, S130	S283/2,	14-MAR-2014	21-MAR-2014	10-SEP-2014	✓	24-MAR-2014	10-SEP-2014	✓
EG035T: Total Recoverable Mercury by FIMS								
Soil Glass Jar - Unpreserved (EG035T) S283, S130	S283/2,	14-MAR-2014	21-MAR-2014	11-APR-2014	✓	24-MAR-2014	11-APR-2014	✓
EP066: Polychlorinated Biphenyls (PCB)								
Soil Glass Jar - Unpreserved (EP066) S283, S130	S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	21-MAR-2014	29-APR-2014	✓
EP068A: Organochlorine Pesticides (OC)								
Soil Glass Jar - Unpreserved (EP068) S283, S130	S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	21-MAR-2014	29-APR-2014	✓
EP068B: Organophosphorus Pesticides (OP)								
Soil Glass Jar - Unpreserved (EP068) S283, S130	S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	21-MAR-2014	29-APR-2014	✓
EP080/071: Total Recoverable Hydrocarbons -	NEPM 2013							
Soil Glass Jar - Unpreserved (EP071) S283, S130	S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	21-MAR-2014	29-APR-2014	✓
EP075(SIM)B: Polynuclear Aromatic Hydrocart	oons							
Soil Glass Jar - Unpreserved (EP075(SIM)) S283, S130	S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	21-MAR-2014	29-APR-2014	✓

Page : 3 of 6
Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD



Matrix: SOIL					Evaluation:	x = Holding time	breach ; ✓ = Withir	holding time.
Method		Sample Date	Ex	traction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EP080: BTEXN								
Soil Glass Jar - Unpreserved (I S283, S130	(EP080) S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	23-MAR-2014	28-MAR-2014	✓
EP080/071: Total Recoverable	e Hydrocarbons - NEPM 2013							
Soil Glass Jar - Unpreserved (I S283, S130	(EP080) S283/2,	14-MAR-2014	20-MAR-2014	28-MAR-2014	✓	23-MAR-2014	28-MAR-2014	✓

Page : 4 of 6 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Quality Control Parameter Frequency Compliance

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(where) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: SOIL

Evaluation: * = Quality Control frequency not within specification: * = Quality Control frequency within specification.

Matrix: SOIL				Evaluation	n: 🗴 = Quality Co	ntrol frequency n	not within specification; ✓ = Quality Control frequency within specification
Quality Control Sample Type		Co	ount		Rate (%)		Quality Control Specification
Analytical Methods	Method	QC	Regular	Actual	Expected	Evaluation	
Laboratory Duplicates (DUP)							
Moisture Content	EA055-103	2	18	11.1	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
PAH/Phenols (SIM)	EP075(SIM)	2	14	14.3	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Pesticides by GCMS	EP068	1	7	14.3	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Polychlorinated Biphenyls (PCB)	EP066	1	7	14.3	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Mercury by FIMS	EG035T	2	14	14.3	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Metals by ICP-AES	EG005T	2	17	11.8	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH - Semivolatile Fraction	EP071	2	18	11.1	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH Volatiles/BTEX	EP080	2	18	11.1	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Laboratory Control Samples (LCS)							
PAH/Phenols (SIM)	EP075(SIM)	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Pesticides by GCMS	EP068	1	7	14.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Polychlorinated Biphenyls (PCB)	EP066	1	7	14.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Mercury by FIMS	EG035T	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Metals by ICP-AES	EG005T	1	17	5.9	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH - Semivolatile Fraction	EP071	1	18	5.6	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH Volatiles/BTEX	EP080	1	18	5.6	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Method Blanks (MB)							
PAH/Phenols (SIM)	EP075(SIM)	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Pesticides by GCMS	EP068	1	7	14.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Polychlorinated Biphenyls (PCB)	EP066	1	7	14.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Mercury by FIMS	EG035T	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Metals by ICP-AES	EG005T	1	17	5.9	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH - Semivolatile Fraction	EP071	1	18	5.6	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH Volatiles/BTEX	EP080	1	18	5.6	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Matrix Spikes (MS)							
PAH/Phenols (SIM)	EP075(SIM)	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Pesticides by GCMS	EP068	1	7	14.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Polychlorinated Biphenyls (PCB)	EP066	1	7	14.3	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Mercury by FIMS	EG035T	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Total Metals by ICP-AES	EG005T	1	17	5.9	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH - Semivolatile Fraction	EP071	1	18	5.6	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
TPH Volatiles/BTEX	EP080	1	18	5.6	5.0	<u>√</u>	NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Page : 5 of 6
Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
Moisture Content	EA055-103	SOIL	A gravimetric procedure based on weight loss over a 12 hour drying period at 103-105 degrees C. This method is compliant with NEPM (2013) Schedule B(3) Section 7.1 and Table 1 (14 day holding time).
Total Metals by ICP-AES	EG005T	SOIL	(APHA 21st ed., 3120; USEPA SW 846 - 6010) (ICPAES) Metals are determined following an appropriate acid digestion of the soil. The ICPAES technique ionises samples in a plasma, emitting a characteristic spectrum based on metals present. Intensities at selected wavelengths are compared against those of matrix matched
			standards. This method is compliant with NEPM (2013) Schedule B(3)
Total Mercury by FIMS	EG035T	SOIL	AS 3550, APHA 21st ed., 3112 Hg - B (Flow-injection (SnCl2)(Cold Vapour generation) AAS) FIM-AAS is an automated flameless atomic absorption technique. Mercury in solids are determined following an appropriate acid digestion. Ionic mercury is reduced online to atomic mercury vapour by SnCl2 which is then purged into a heated quartz cell. Quantification is by comparing absorbance against a calibration curve. This method is compliant with NEPM (2013) Schedule B(3)
Polychlorinated Biphenyls (PCB)	EP066	SOIL	(USEPA SW 846 - 8270B) Extracts are analysed by Capillary GC/MS and quantification is by comparison against an established 5 point calibration curve. This method is compliant with NEPM (2013) Schedule B(3) (Method 504)
Pesticides by GCMS	EP068	SOIL	(USEPA SW 846 - 8270B) Extracts are analysed by Capillary GC/MS and quantification is by comparison against an established 5 point calibration curve. This technique is compliant with NEPM (2013) Schedule B(3) (Method 504,505)
TPH - Semivolatile Fraction	EP071	SOIL	(USEPA SW 846 - 8015A) Sample extracts are analysed by Capillary GC/FID and quantified against alkane standards over the range C10 - C36. This method is compliant with NEPM (2013) Schedule B(3) (Method 506.1)
PAH/Phenols (SIM)	EP075(SIM)	SOIL	(USEPA SW 846 - 8270B) Extracts are analysed by Capillary GC/MS in Selective Ion Mode (SIM) and quantification is by comparison against an established 5 point calibration curve. This method is compliant with NEPM (2013) Schedule B(3) (Method 502 and 507)
TPH Volatiles/BTEX	EP080	SOIL	(USEPA SW 846 - 8260B) Extracts are analysed by Purge and Trap, Capillary GC/MS. Quantification is by comparison against an established 5 point calibration curve. This method is compliant with NEPM (2013) Schedule B(3) (Method 501)
Preparation Methods	Method	Matrix	Method Descriptions
Methanolic Extraction of Soils for Purge and Trap	* ORG16	SOIL	(USEPA SW 846 - 5030A) 5g of solid is shaken with surrogate and 10mL methanol prior to analysis by Purge and Trap - GC/MS.
Tumbler Extraction of Solids (Option A - Concentrating)	ORG17A	SOIL	In-house, Mechanical agitation (tumbler). 20g of sample, Na2SO4 and surrogate are extracted with 150mL 1:1 DCM/Acetone by end over end tumble. The solvent is decanted, dehydrated and concentrated (by KD) to the desired volume for analysis.
Tumbler Extraction of Solids (Option B - Non-concentrating)	ORG17B	SOIL	In-house, Mechanical agitation (tumbler). 10g of sample, Na2SO4 and surrogate are extracted with 20mL 1:1 DCM/Acetone by end over end tumble. The solvent is transferred directly to a GC vial for analysis.

Page : 6 of 6 Work Order : ES1405891

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Summary of Outliers

Outliers: Quality Control Samples

The following report highlights outliers flagged in the Quality Control (QC) Report. Surrogate recovery limits are static and based on USEPA SW 846 or ALS-QWI/EN/38 (in the absence of specific USEPA limits). This report displays QC Outliers (breaches) only.

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

- For all matrices, no Method Blank value outliers occur.
- For all matrices, no Duplicate outliers occur.
- For all matrices, no Laboratory Control outliers occur.
- For all matrices, no Matrix Spike outliers occur.

Regular Sample Surrogates

• For all regular sample matrices, no surrogate recovery outliers occur.

Outliers: Analysis Holding Time Compliance

This report displays Holding Time breaches only. Only the respective Extraction / Preparation and/or Analysis component is/are displayed.

No Analysis Holding Time Outliers exist.

Outliers: Frequency of Quality Control Samples

The following report highlights breaches in the Frequency of Quality Control Samples.

No Quality Control Sample Frequency Outliers exist.

K <	3	<u>, </u>	1	{			T-	1	1	<u> </u>	<u>.</u>	<u> </u>	<u> </u>		e pije in	R	T.	Ē	2	S.	3	ğ	밁	916	2	en	
V × VDA, Vial HCI Preserved, VB = VOA Vial Sodzum Bisupkiale Preserved; VS = VOA Vial Sulturio Preserved; AV = Airfeight Unpreserved Vial SG = Z = Zpc Accetate Preserved Bothe; E = EDTA Preserved Sodiles; ST = Sterile Bothe, ASS = Plastia Bog for Acid Sulphate Sodie; B = Unpreserved Bog.	ier Conte	7	=	5	٠.	Ð	1	6	S	4	6	Ю	-	CAS ID	SE S	COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL:	Email Involce to (will default to PM if no other addresses are listed): accounts@emactesting.com.au	Email Reports to (will default to PM if no other addresses are listed); enquiries@smeciesting.com.au	COC emailed to ALS? NO	SAMPLER	PROJECT MANAGER: N/A	ORDER NUMBER	PROJECT	OFFICE:	- 1		
HCI Pres	alder Cod	995c	2265	7363	L SC	5	\$340	52,39	53	5	J. J. J.	ک کی	ر ارگر	7		'S/SPEC	ice to (w	orts to (ed to Al	11	MANAG			14/1 COMPASTURE PLACE	SWEC T	Since of the same	>
erved: Vi	ag; P≟	6	(2)	£	শ্ব	て	O.	2	4	्राष्ट्र भारत	Ĭ	200	ىع			IAL HA	ili defau	wii defa	S? NO	J./e	ER: N/A		28 61	WPAST	CIMITAG		
Her HE HE	vasaudu		***************************************											SAMPLE ID	-	VDLING	# to PM	il to PM		2		-	Ö	URE PL	CEBUS	14 A	
Vial Sodi. O'(A Pres	red Plasti		-											2	A I	/STORA	if no oth	if no oth					न्न	2 5		္န င္တ	升
en Bisuty	N P N													***************************************	8 to	GE OR	er addra	er addr		,		ব	S		- volt propriet	CUSTODY	CHAIN OF
hale Presilikes; ST =	ric Prase			ļ									o)		- \$2 - \$4	DISPOS	eye sess	75 Seb 50				97.			, , , , , , , , , , , , ,	iş X	¥
erved: VS	vec Plas		···· · · · · · · · · · · · · · · · · ·	-									133	DATE	T T	₽.	listed):	e listed):				Q					
= VOA V	ir ORC												8	DATE / TIME			account	enquírie	50 GO3	SAMPL	CONTA					PH 07	S 4d
S = Plast	n Mitric P			1									/		_		s@smæc	жижДв	EDD FORMAT (or default):	SAMPLER MOBILE: 02-9758	CONTACT PH: 02 9756 2166		> 5	<u> </u>	-	인원제3회사이트 32 Zhanc Strach 정보하나 ሲኒር) 40년3 Phr 07 3243 7722 등 vermieks kirbianm관리님grobol com Phr 07 3243 7722 등 vermieks kirbianm관리님grobol com DCG, AUSTONEE (KC Galestone과 Australa During AR20) Phr 07 727 56730 등 gardstone과 Australa	내시안도, 4인용 21 Burma Road Frombin SA 5095 Ph
ic Presen	reserved	#	ļ										7	MATRIX			clesting.	ctesting.	or defa	31LE: 02	02 9756		ALS QUOTE NO.	I ORNAROUND REQUIREMENTS: (Standard TAT cray be longer for some tests e.g., that Tags Organize)		Eliphic Stro Eliphic Stro Cosligator	duma Roa
Acid Sul	ORC: SI												e	TYPE & PRESERVATIVE codes but	4		nerwoo.	merwoo	uh):	9750.2	2166		TE NO	AT may I		et Stafford S Misballing Suph Drive Obstation	d Frootoka Cassylota
Altfreigh	X ≈ Sa¢io												3	PRESE	2					Ž				NE CONSER		ČLO 40E3 Žalsgjoba Cialom OL	SA 5095
I Unpress	ил Нуфго									_		-	1	RVATIVE codes below)						choho				for some		D 4660	
treserve	ide/Qu P							,					Q	(w))	A INFO				`	7367	.		1	S:			
SG = S	reserved													(re	iniver (Neormation			DATE	{	7			1	_		PROPERTY OF STREET	PK 37 46
Muric Pre	S			1										(refer to	2			TIME		ka cansinovim a k				Standard Von Stan		465 ZC 1812 4635 67 75 95 95	9.2410 94 949-93 A
served An	ium Hydrox													TOTAL CONTAINERS	19		,	DATECTIME: 4/5/1	<u></u>	γaα3				Standard TAT (Llat due da		Westell Ross	ar Atal Kar
/OA Visi Sulturio Preserved: AV = Alfreight Unpreserved Vial SG = Sulfurio Preserved Archer Glass; H = HCl preserved Plastic; HS = HCl preserved Speciation bottle; SP = Sulfurio Preserved Plastic; F = Formelitetryde Preserved Glass; H = HCl preserved Plastic; Beg for Acid Sulphate Scie; B = Unpreserved Bag.	de Preserva	1	1	J	1	İ	ı	1	1	•	ţ	ł	1	£c	ANALI Where N			74	5	7/1		1		Non Standard or urgent TAT (LI-	Service strategy	CINECEDURAS DA WESSIEROS SANDYAR VICOTOS POR 33 SAND PRODES SENDRES RESPONDENCIÓNES CON CINCOCED 27 SENDRE ROLD EN USANDO LOS POR 12 COUTO CESTO EN LINGUES POR SANDO LOS POR 12 COUTO CESTO EN LINGUES POR LA PORTO DE PORTO DE LA PORTO DE LA PORTO DE LA PORTO DEL PORTO DE LA PORTO DEL PORTO DE LA PORTO DE LA PORTO DE LA PORTO DE LA PORTO DEL PORTO DE LA PORTO DEL PORTO DE LA PORTO DEL PORTO DE LA PORTO DE LA	CIMACKAY 16 -Babeur Blad Maskey CLD 474o Pix 37 4944 0177 Cr mirkey/gabigtekei Joon
4=HClp	Plastic		ŕ												(SIS REC			Ö						te): [ˈ{List due date]:	"	caltr meainm	
pevese)	* * * * * * * * * * * * * * * * * * *														Cequired,			DATE/TIME: 11,		RECEIVED BY:	Ţ	COCC		-			
Pastic; h	ar Goss														specify T		_	m H		DBY:	ימ	22	COC SAQUENCE NUMBER	Ó	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Chicona Chicon	FM 02.4%
₹	Unprese														SETTES (6130p~	<u> </u>	るるなって	;	(u)	4	NCE NO	W		TO THE COLUMN	\$11.5 m
preserved	AP				-	_									required)	_	*	<u>-</u>	`.5`	•	44 NU	4		B	5.2:0/CHS	Poze II	AR CHIEF R
Speciati	Aktroigh								131	<u> </u>					ANALYSIS REQUIRED Including SUITES (N.B. Suite Codes must be listed to etract suite price) Where Metals are required, specify Total (unfiltened bottle required) or Ditsolved (field filtered bottle (cogulired).				· ·-	_(3)	(Crole)		Buckey State	CHONERA 413 Geery Have To Haves NSW 25 Fir 024-123 CC63 & rewrathersprose out	THE SAME SAME TO STATE OF THE SAME SAME SAME SAME SAME SAME SAME SAM
on bodder	Lingiese		Telephone: +61-2-8784 8555			ľ	Π.	_	Environmental Division						ust be l'a			DATE/I'ME:		RELINQUISHED BY:	7			0 Z	Linnson	Nova NS/V2541 98: cum	Oct NSW
SP = Su	ryed Pila	+	e: +(-	「「ハイベンスつつつ	s Sys	nme e						led to elli salved (f			ME		USHEE		enter de campia la repai ativa del Revalei	Section (asset from an unital and ear	FORTUABORATORY, USE ONLY ACTICLE)	The Court	Ş	2324
Julia Pra	Ř		31-2-8			S	ב ק	Sydney	ntal C						ræct suite feld filfen					BY:			e, G	8	Service Servic		
served Pi			784 85			,	ئ ب	ŧ) Jivisi						price) ed bolt:g							Ú.		KY USE	5 5 5	CHOOKSYLLE HAY DIAPU COUR SAME LE SELVICE CHOOKSYLLE HAY DIAPU COUR SAME LE SELVICE CHOOKSYLLE TO KOME SAME COUR SAME LE SELVICE CHOOKSYLLE SO KOME SELVICE WESONGOUT SAME LESS CHOOKSYLLE SO KOME SELVICE WESONGOUT SAME LESS	LYCYONEY 2:7-259 Woodson Road Smelled NSW 2:54
autic; F:		+	8 =			U	J		ä					Cors anny										Q F	0 3 10 m	SOURCE SOURCE	2:7:259
= Formel	.,			1]			ŀ					Comprents on likely contaminant levels, dutaions, or samples requiring specific of analysis etc.	Ad			DATE		RECE				Y CH	Parketto.	to Diamen townesupe) Konny St	Моофранк
lehyde P														ı ikely co	Additional Information			DATE/TIME		RECEIVED BY:				i.	and and one	Court Sofil Englishment Hugherman	Raad Smi
reserved	.	_												भावातांतुः - अर्थातांतुः	Intorm					¥.		e.	71.		Date of the	Sylfusfer Sychology Sychology	Sald NS
Glass;														Completes on thely contaminant levels. Clubions, or samples requiring specific Oc analysis etc.	ation					THE PERSON NAMED IN	,		•	L		WASSER Special SP	W 2754
<u></u>																				estentan Telephone			\$		O CONTRACTOR	·····	

18. **8**3.

22	V	2	<u>}</u>	- 29	-\$			_	<u>_</u>	छ	LAS ID	52	COM	Email	Espai	8	SAME	PRO	ORO1	PRO.	OFFICE:	e e
5 C	50	1	20 19/19	2		7 5	χ.	رب د	 	1		7 F G	VIENTS/S	invoice t	Reports	emailed !	SAMPLER:	ECT MA	ORDER NUMBER:	PROJECT:	1	-M3
262	7225	\$367	410	5446	5969	2618	2368	5399	392	$\frac{1}{2}$			PECIAL H	to (will def	to (will de	COC emailed to ALS7 NO	ر	PROJECT MANAGER: N/A	9	_	COWPA	ALS Environmental
								2			SAMPLEID		ANDLING	aut to PM	fault to PM	0	~ 	A		42/07	1411 COWPASTURE PLACE	A SE
											9	ANNES.	STORAG	if no other	If no other		Ļ		_	٦ ج	ACE	
	<u>.</u>				,							O I I I I	COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL:	addresses	addresse				どり	$\sum_{i} C_i$	3	CHAIN OF CUSTODY ALE Laboratory: phoase lick >
	-		-						•	5 D	DAT	ATERIW	OSAL:	ana listed)	are listed				Ć			
									-	93/3	DATE /TIME			accounts): enquirles	EDD FO	SAMPLE	CONTAC				0.0057 0.0057 0.0075 0.
										c-,	MAYRIX			Email invoice to (will default to PM if no other addresses are listed); accounts@smectesting.com.au	Emeil Reports to (will default to PM if no other addresses are listed): enquiries@smectosting.com.au	EDD FORMAT (or default):	SAMPLER MOBILE: 02 9756 2166	CONTACT PH: 02 9755 2166		ALS	(Stand	UkbitLAUSE 21 Bornia Road Postalia SiA 5/58 Ph. 08 853 JEBUS — steenin-kgargacticson QBA198ANE 27 Signrd Stock Ellahrid QLD 4053 Ph. 03 2043 7272 — steepies sektaan Quidajobey mm UGCA/957CYSE 46 Clabinatrickik Dirke Cturan CLD 4000 Phr. 07 7271 5500 = glatakern@alegisked torn
											TYPE 8	nt - 202		ing.com.aı	\u00e4ng.com.a	efault):	: 02 9756	755 2166		ALS QUOTE NO.:	TURNAROUND R (Standard TAT may b Ultra Trace Organics)	Road Pooral Steat Actains the state the control of the the control of the the control of the control of the the control of the
										8	TYPE & PRESERVATIVE	2			<u> </u>	7700	2186			0.:	TURNAROUND REQUIREMENTS; (Standard TAT may be longer for some tests e.g., Ultra Trace Organics)	a SA 5086 atolican ad GLD 4083 regalegiotes re Cartes GLD Arbet som
											VATIVE odes below	MAINER									or some tes	+ 462G
										Ó	·	TAWER WEOHMATION			Q,		20					DAN Ph. O. Pr. o. Ph. o. Ph. o.
											(refer to	ğ Y			DATE/TIME:		RELINQUISHED BY:			,		二分本のCYAY 7年 Haitonar Read Aasday QLD 47-62 門, 27 4月4 で打了 E: mades/jybalyghdai awm 以外側を見ない得近では、hortpes makko-ameの指示jybalya-com Pr. 02 45年9 585分 E: yampes makko-ameの指示jybalya-com には、1952 できらかが、Propete makkgalego-akona
					-						TOTAL CONTAINERS						ED BY:			***************************************	Standard TAT (List due date): Non Standard or utgant TAT (Li	car Read Ado medicyffels Wester Road writes not writes not moges mai
	1	1	1	1	•	1	1	ŧ	1	ħ	tc	ANAL Waste N								*********	due date): entTAT (Li	iny OLD 4760 grivin tem Epsispasie V to aneglosaj gre NSW 205 Galsglosal te
				•								rsis REQUI			D _A		R	OF:	600		St due dat	0 000:000
										1		RED includi quirod, spac			DATE/TIME		RECEIVED BY:	۰,			<u>*</u>	20 00 00 00 00 00 00 00 00 00 00 00 00 0
							_		-			AMALYSIS REQUIRED including SUITES (NB. Suite Codes must be listed to streat suite price) Where Metals are required, specify Total (unfiltered bottle required) or Dissolved (field filtered bottle required).		୍ . କୁ	110014	2. E.		~ (\mathcal{O}	COC SEQUENCE NUMBER	本	CHENYCASTLES Rope Goet Roped Wildeltrock Light 2004 TH: 12 4605 Heid E. Bumphie Awacestrographic Modern THE 12 4405 Heid E. Bumphie Awacestrographic Modern THE 124473 1058 S. The Awacestrophic drop THE 124473 1058 S. The Awacestrophic drop THE 144 THE MODERN INTERCRETARY SOLD THE 145 THE SAMPHIN INTERCRETARY DECEMBER THE 125 7505 TEST E. SAMPHIN INTERCRETARY DE
			2000	,, um rr , .		,, .						(NB. Suite i (Ritured both required).	-	30 pm	<u>+</u>	24		.	<u>5.</u>		F	coso Gian Po inampissi ily ety Pruor Nor incertigati yay Maragati semples pe
		ì										(payindal e			DA:	•••••	₹	<u>ي</u>	ø 7	(Circle)	18/67	rea Gian Rhad Waratrook (8) Barnjasa Awacastrojaalykka y Pistor Ricch Navira Hely Es Kwa Zijou yattol can Kwa Zijou yattol can yannjas janngaasja bakom
		:								1		be listed to or Dissolved	:		DATE/TIME:		RELINQUISHED BY:			8		COM CONTRACTOR
			.									atraci suile d (Reid filled)					ED BY:		Sample Ten	de (licas), co proce presenta	BORATO	(
												price) at boilte							ample Tempetarum od Receipt	desic sych	AN LISE O	PH 02 4756 O DE 4786 O DE 476
											Commonts of chitchens, or sensitysis etc.				9		R.		(Applied	Ĭ	BORILABORATORY USE CHLY (CICIO)	17-239 Woods 655 Er nampe "E 14-18 Dess 659 E. Norman ONG 28 Kanna 125 E. Porves
				-							on likely co r samples n c.	Additional			DATECTIME		RECEIVED BY:				•	orkitoad Sim Ausydrawgber Na Court Sch Hallerviranne P Steek Weller Riboghalsging
Limited											Commonis on likely contaminant levels, Cikutions, or samples requiring specific QC znatysis etc.	Additional Information	—				Υ:		Ď	- - - - -	7	Lightonety 27: 2000 Woodcook Road Smothisk 188W 2184 Pit, 02 8784 8650 Et aangles sydnoxigar zglobal con DC-07/805Vil. Et 14: 12 desma douri fielde Gid 1889 Pit 07 4786 0000 Et Inmanida endramentingsgrotte on CHVOLL DIVIDONIC 50 Kaning Stadingship x507 2500 Pit 12 4055 3185 E porventingsglotigen om Pit 12 4055 3185 E porventingsglotigen om
		-								***************************************	vets, site QC	'n					100 A					SS 12

	36	×2,	3 2	\$3	- 32	3	30	C	122	750	٢	<u>*</u>	LA8 ID	E 2	COMM	Emalit	Email	000	SAMPLER	PROJE	ORDE	PROJECT	OFFICE:	CLIENT	9	
	5307	Tar.	132F)	र्ट वर्डे	Mrs	(8)	ع احجر	5131	25.18	ر داع ع	712g	131	D SAMPLE (D	TWO CONTRACTOR	COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL	Email invoice to (will default to PM if no other addresses are listed); accounts@smedesting.com.au	Email Reports to (will default to PM if no other addresses are listed); engulnes@smecteeling.com.eu	COC emailed to ALS? NO	.ER: 37/4 / D.	PROJECT MANAGER: NIA	ORDER NUMBER:	143 G C	14/1 COMPASIURE PL	T: SMECTESTING SERVICES	Environnement	
							•				***************************************	%		SAMPLE DETALS	ORAGE OR DISPOSAL:	other addresses are listed);	o other addresses are listed):		1		07/01	1687.	*/ / ~		CHAIN OF CUSTODY ALS Laboratory pheaso cick >	
												4	DATE /TIME			accounts@sme	engulries@sm	EDD FORMAT (or detault):	SAMPLER MOBILE: 02 9756 2166	CONTACT PH: 02 9756 2168					OFFICE OFFICE OFFI OFFI OFFI OFFI OFFI OFFI OFFI OFF	CALCULATES 2
			<u> </u>	-								٢	MATRIX			desting	actosting	(or det	S11183	02 975		ALS QU	Siandard Signatura	TURNA	GE GARGE	a music
					A		THE I I I PROPERTY PROPERTY AND AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERT	, , , , , , , , , , , , , , , , , , ,		: : : :		σω /.	Type & Preservative codes below!	The ChianteringO		J.CO:fi.du	P.E. WOOL	ault):	12 9758 2166	6 2108		ALS QUOTE NO.:	(Siendard TAT may be singer for sorny fests e.g., Litra Trace Oxpenies)	TURNAROUND REQUIREMENTS :	নৈ যে বৈশি এইটাই ই ক্ষমানত কিন্তুন্ত কোনো কৰে। প্ৰস্থাইনিন্দাৰ বি হ'নকৈ হৈ বিধান কৈ নাকিব এটে গতেই প্ৰথম কৈ ইন্ডৰ "হৈবই হ'-ককেইচাই কিন্তুন্ত কিন্তুন্ত কোনো ইন্যান্দ্ৰ কিন্তুন্ত কিন্তুন্ত কৰি কিন্তুন্ত কিন্তুন্ত কিন্তুন্ত কৰে। কিন্তুন্ত কিন্তুন্ত কৰি কৰিব কিন্তুন্ত কৰা কোনা	to Francis Ch Shut
igna.		-										œ((refer to	NOTAMION			DATETIME		RELINQUISHED BY:					C Standard	PH. (** 4544 OVY* E. Medylynyboby cam CHES ECHRHE 24 Weshill broad Springrale Viz- FW CLI Shot, 1600 S. Surple, medsourie (fluight) CHES ECHRHE 25 Strong Broad House (SNY OSO) CHES ECHRHE 25 Strong Broad House (SNY OSO) CHES ECHRHE 25 Strong Broad House (SNY OSO) CHES ECHRHE 25 Strong Broad House (SNY OSO)	CIMACKAY AN ISSUE
									•				TOTAL CONTAINERS						ED 8Y:				dend of un	TAT (List	Mediaggy Westal Ros Samples in Samples in Meg Rosel ku	and Constitution
	1	1	1	1	1	1	1	1	1	1	1	ı	EC	Analysis Wrote Hotels									Non Standard or urgent TAT (List due date):	Standard TAT (List due date):	Pal (To abid Olyt E MacKong Englishe com Pal (To abid Olyt E MacKong Englishe com Pal (South House) maybe melovor (Spinguste NC 3174 Par (South House) maybe melovor (Spinguste NC 2007) Chall (South House) maybe melovor (Spinguste NC 2007) Par (Colot II (19) E reacybe melighinguste (con	
				_	-								•	AVAL YS IS REQUIRED instrating Stiffes (NB. Suin: Codes caus: he listed to attect sale price) have Medals are required, specify total (unfalsased battle required) or Dissolved (their diseased battle required).			DATE/IME:		RECEIVED BY:	0F:	CUC:	coc s	ogate): Ch	And place in the control of the cont		
												-		oting SulT ecky Total		Ξ	ب ک	Ē.	84:	~(<u></u>	STATE OF	70		PACKET REPORTED TO A CONTROL OF THE	
							-							ES (NB. Sub pridiesed by required)		35.50	<u>کے</u> چ	Ź		4 5	` *	E NUMBER	<u>ر</u>		THE CONTROL BRANCH PROOF THE BOOK HAND THE CONTROL AND THE BOOK HAND THE CONTROL AND THE BOOK	***************************************
	•								***************************************					e Codes m		~ *			<	٣	Ä	(Cireta)			Aradaleg Aradaleg Rafh Nova Raficolicon Raficolicon	
							**************************************					- N		ius: he listed to rd) or Dissolve			DATE/TIME:		RELINQUISHED BY:	7	7			200	THE CASTLE Race She Page the Hotock KEW State No. 12 ANS CALL IS Bropped workers (Question to you CHOOMER, whi Goard Muc I talk below 115 m San Mr. (Sed 25 196) If the working logical com (PRICE) 12 No Hotock Way Named WASOD THE CASTLE SHOW WAY Named WASOD THE CASTLE SHOW WAY Named WASOD	
									-			· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	attract subo , d (Nord filtere)					ED8Y:						DC 800 25	
		-		-]										prices) d borde											CONTROL ZO TO DE STORA BE TOTAL SOULL TOTAL SOULL TOTAL SOUT TOTAL	
							•		property and the second				Comutants on thely contaminent levels, dictions, or samples requiring specific QC analysis the	Additional Internation		••	DATE/TIME:		RECEIVED BY:					FOR LUBERATURY LIST DISCYTORING	(CVUNET 777-389 (1) sed 500 tel Bruil den selvja 1954 Ph. (18 3764 888) E. salvipela symenytti sejte zi Livir Varral Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court Bohn (2), o den 3774 Milly Vell B. (18 15 Deutra Court	
										-		***************************************	nt levels.	ation					- Barrana and A		ě				SW 2500	

sales distriction	malgra was in remains and						1	4/	ş: c:::::::::::::::::::::::::::::::::::	****	·	مانت ساء	****	····			·				····
		-	The second secon		40	35	35	かっ	L 810	AUS.	COMMENT	Email Invo	Enrail Repo	COC email	SAMPLER:	PROJECT	ORDER NUMBER:	PROJECT:	ŧ	CLENT:	most.
					Sish	7(3)	Jaco	5256	SAMPLE ID	SANEURICE!	COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL:	Email Involce to (will defaul to PM if no other addresses are listed): accounts@amectessing.com.su	Estail Reports to (will default to PM if no either addresses are fisted); corquiries@smectesting.com, au	COC emailed to ALS? NO	J~ / D, L,	PROJECT MANAGER: N/A	MBER: (04.20	14290 / 4030		SMED TESTING SERVICES	CUSTODY ALS ALS Laboratory phosos sick +
	***************************************							A CONTRACTOR OF THE CONTRACTOR	date / time	ATES WITE	OSAL:	are listed): accounts@s	are fisted): enquiries@s	EDD FORMAT (or default):	Sampler 1	CONTACT PH: 02 9756 2166		റ് റ			55 274 20 40 CASCATOR SWE 20 44 BRESSERIO ALCOMANDO ALCO
	-							4	MATRIX			mectesin	meclegăr	AT (or da	NOSILE:	ԴH: 02 97		ALSO	(Standar	TURN	SHOCE ON 32 Shand S 7324 Er ske 7326 Captur 5500 Er gunt
			and the second s				*	OT / M	TYPE & PRESERVATIVE COGS OBOW)	Gir Banyıng: — f		(g.com.gu	ng com, au	fault):	SAMPLER MOBILE: 02 9758 2168	₹6 21 69		ALS QUOTE NO.:	(Standard TAT may be tanger for some lecta e.g. (Itra Track Omanics)	TURNAROUND REQUEREMENTS:	PHY OF BATA CHANGE CONTRIVING PHY OF BATA CHANGE CH
ĕ ≱	a a consequence of the consequen								(refer to	RMATION			Эхтеліме:		RELINQUISHED BY:				3	. postorens	DARLECHBAR LA CHOANNE RANK PRAKTONIA DARLECHBAR LA WANNE RANK PRAKTONIAJANG WOODING DARLECHBAR LANKA BENAKAN NAKONIAJANG WANDE DARLECHBAR STATE E MANDE MARKAN SANDEN PAR SY COMBETTE E MANDE MARKAN SANDEN
	, , , , , , , , , , , , , , , , , , , ,								TOTAL CONTAINERS						:Xa G;				Non Stendard of Higant	YAT' (1 lst /	Control Road Washel Road Washel Road Washel Road Washel Road
					1	1	İ	t	Ec	ANAL Where h									METAT (LI	line d'alloh	Jasapasam Spilografie V Schrödigs Spilografie Spilogra
					1	J			CH	รรร REQU			ğ	•••••	짇	OF:	Çoc	-	TAT (List due dale):		O State
					ţ	1			Soq	RED Inclu			BATE/TIME:		RECEIVED BY:		.Ω Ω		۾ ج <u>ن</u>		본대 보 단 및
					(j			C(ding SUITES (chy Total (an)		دسر	<u></u>	かび	,	1.2 U	,	COC SEQUENC NU	12/4		Ph. 02 4590 5433 8: numphot newforthey) stephool out. SLEWING AND Steph Pater York Nowa NSW 1541 Ph. 12442 2058 6: news 05 regions out. STEPH 10 Feet View Making a Wyl Cliff Ph. 1845 20 1556 6: stepholo per fights policion.
									*	(NS. Suito C litered bold required)		C-3 17	3	į.	,	۱۶. (ق	Ö	NUMBER (Circle)	0		ist sidues is edippy in the German top, and de
										requiros)					V R R	٣	>	(cle)			Cherké jarágudei e. Komo NSV 1541 Mi cen Elefo Elefo
			٠,							be lisled to attre or Dispoked (fo			DATE/FIME		RELINQUISHED BY:		i i	Ġ.			eon A 1244 A 1244
										ANALYSIS REQUIRED Including SUITES (M.S. Suite Cocce must be Islad to ratinest suite price) Where Metale are required, specify Total juristicated bould (equires), or Discovered (field fatures boatts)					BY:			Tipo de sides in		2000	7000 7000 7000 7000 7000 7000
					o proposal de la casa				Comments on likely centermicant levels, distincts, or samples requiring specific QC analyzes out.	Additional information			BATEMME		RECEIVED BY:						Pt. 02 EP94 #556 fl. wittstekkeydreit@beigneit.com 11 TOWNSONEE15 Opping Court Series Court (e19 15 TOWNSONEE15 Opping Court Series Court (e19 15 TOWNSONEE
									hant levels, ig specific QC	rmation											MESA COD

		Water Container Codes: P = Ungreserved Plastic: N = Natio Preserved Plastic: OHIC = Mish December CDC - City		TOTAL	Water Container Codes: P= Ungreserved Plastic: N= 1990 Preserved October 1990 - 1990 Preserved Plastic: N= 1990 Preserved Plastic	Preservant Practice Oldon Resident	vice: Deliberariania dinsin di 197.	ter Container Co
				Industrial Industrial		<u>;</u>	***************************************	
								-
>		***************************************						-
***************************************			1				8	7
		MANUAL MA						200
							10	
					A THE RESERVE THE PROPERTY OF	***************************************	3 H	3 7
		And the second second second second second second second second second second second second second second second					3	<u> </u>
			1		The same of the sa			
					***************************************		7	4
A Secure of the second			1		***************************************		TK@	53
	And the second s				1 15/1 23/		260	72
ota.				-{	- AT	(A) (B)	र्रह्म	٤
Comments on likely contaminant levels, cilutions, of semples requiring specific QC analysis			Ec.	TOTAL CONTAINER	TYPE & PRESERVATIVE (refer to codes below)	DATE/TIME	SAMPLE ID	LAB IID
Additional information	t bottle required).	Metals are required, specify Total (unfillered bottle required) or Dissolved (field filtered bottle required).	Metals are required, specify Total (until	s		- N		
		HTES (AB Schools)	ANALYSIS REQUIRED including SII		CONTAINER INFORMATION	DETAILS	SAMPLE DETAILS MATRIX - SOLID (S) WATER (W)	ALS
				W		GE OR DISPOSAL:	comments/ special handling/storage or disposal:	OMMENTS/
DAI E/FIME:	<u> </u>		,			or addresses are listed):	Email Invoice to (will default to PM if no other addresses are listed):	mail Invoice
(18/19 DATE FINE	DATE/TIME:	TIME:	рате/тіме:	er addresses are listed):	Email Reports to (will default to PM If no other addresses are listed):	mail Report
RECEIVED BY:	22	PELINOTISHED BY:	XECHVED BY:			EDD FORMAT (or default):	COC emailed to ALS? (YES / NO)	OC emailed
Other commet):	Other comment	2 3 4 5 6 7	OF:	X 100	CONTACT PH: 7 6 64 6	SAMPLER MOBILE;	/DC;	SAMPLER:
pt) Yes No No Xey emperatura on Retend	Prasent upon roge Random Sample Ti	ම් * *	coc;	1		740	PROJECT MANAGER: (1/4	PROJECT MANAGER
e bricks No No SN	Free los / frozen los biloss	B (Circle)	OOC SEQUE	المعدودة والمتارك وال	ALS QUOTE NO.:	STV JOSC	3 14200/ ex	PROJECT:
FOR LABORATORY USE ONLY (Circle)	FORILABORATO	es/s/la	Standerd TAT (List due date): Non Standard or urgent TAT (List due date):	a de	(Standard TAT may be longer for some tests e.g. Ultra Trace Organics)	P State	1 Charles	OFFICE: V
This and the forest was consulted that the forest of the f	000	Hours 413 deep Pass Agris Newastelogisterina com Priza 442 deep Pass Agris Newastelogisterina com Priza 442 deep Pass Agris Newastelogisterina com Petiti 10 Hed Way Makagi wa 6030 Petiti 9208 7000 E-semples partikalaterinina com	KEE BOURHE 2-4 Rochal Royad Spirignals VC 317; Pir. CU 3049 9800 E. samplos melburne@alsenvio.com HUBOSEE 27 Sydany Road Mudgae KSVV 2850 Pir. CO 8572 6735 E. masgramasi@obsgobaccom	Market 2	Pit 07 224 7 727 E scripts the state of story scory scripts the disconsisting con scripts the state of story scory scripts the state of story scory scripts the scory sc		_j^	CLIENT ALS)
Management of the state of the	_	HEWCASTLES Roseguen Fload Whiteleggs ASSW 2304	MACKAY 78 lighbour Road Waskay CLD 4740 71: 07 4944 0177 E. meksyo abglobal.com		Phi 03 8355 0690 F. Francis Contra an Sussi	70	CUSTODY	

Emulianization ALS Laboratory		PR 07 3243 7222 E samples luisbarie Balschivin com st. 40 33100 et galemandan Onive Chabri duo 4620 et galemandan Onive Chabri duo 4620 et galescone Butter d'an com	Interventing 2-4 Westell Road Styring-de-VFC 3171 Interventing 2-4 Westell Road Styring-de-VFC 3171 Interventing 2-4 Westell Road Styring-Road Styring Committee Styring Plant Austriage (NSV 2005) Interventing 2-4 Westell Road Styring 2005 Interventing 2-4 Westell Road Styring-de-VFC 3171 Interventing 2-4 Westell Road Styring 3-4 Westel	C3171 N9/HBA 4/13 (bear) Fines from home commence with commence of the commen	tech kowa NAW 2541 Godsgebatenn 1984 6090	THE US OF COSTS E SEMINES SYSTEM WAS SERVICED IN THE LOCAL STATE OF TH
OFFICE: CAN CONTROL OF THE CONTROL O	Se Collaboration	TURNAROUND REQUIREMENTS: (Standard TAT may be longer for	Standard TAT (List due date): Non Standard or utroot TAT (1 <u>6</u>		Print CES 3105 E. porteen begins and some 2003. BORATORY IIS E ONITY 1611 E.
PROJECT: 19580/1 408	Cr Wir, sor	some tests e.g. Ultra Trace Organics) ALS QUOTE NO	twoii otalidard	or urgent IAT (List due date): 67/3	[P Custod	Custody Seal in last? Yes (Citcle)
PURCHASE ORDER NUMBER:	2420	***************************************		E NUMBER	(Circle)	P. 20 No. 2008 - Cideba Jacking Bardines de la constanta de la
PROJECT MANAGER: 6/4,		CONTACT PH: 9736216 6	05.	ن ن	` ``	Rendom Sample Temperature on Receipt
SAMPLER: The 10,C	SAMPLER MOBILE:	RELINO	JISHED BY:	1 2 3 A	5 (0) 7	
COC emailed to ALS? (YES / NO)	EDD FORMAT (or default):				RELINQUISHED BY:	RECEIVED BY:
Email Reports to (will default to PM if no other addresses are listed):	o other addresses are listed):	DATE/TIME		DATE/TIME: WAS	DATEMINE	
Email invoice to (will default to PM if no other addresses are listed):	other addresses are listed):	***************************************		130 V		OA E/ HWE:
COMMENTS/ SPECIAL HANDLING/STORAGE OR DISPOSAL:	ORAGE OR DISPOSAL:		***************************************	6		
ALS SAMOIE DETAILS		From the second				
	MATRIX - SOLID (5), WATER (W)	CONTAINER IN FORMATION	ANALYSIS RE	ALYSIS REQUIRED Including SUITES (NB. Suite Codes must be listed to attract suite price) Where Metals are required, specify Total (unfiltered bottle required) or Dissolved (field filtered bottle required).	s must be listed to attract suite politie of the source of the suite o	co) Where Additional Information cuired).
LAB ID SAMPLE ID	DATE! TIME	TYPE & PRESERVATIVE (refer to codes below)	TOTAL ONTAINERS	-		Comments on likely contaminant levels, dilutions, of samples requiring specific QC analysis
इ० जार	S) 163	√m/ Ja,	1			eic.
2016						
52 3117		***************************************				The state of the s
7						
24 067						# ************************************
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		The second secon				
でいる。			444444			
	,	man, james and service and service and service and service and service and service and service and service and	1			***************************************
رع		The second of the second secon				
		THE RESERVE THE PROPERTY OF TH				
277 200		The state of the s	1			
0 1 2 2 2 1 0					Ville	The same of the sa
Water Contains Contain B = Locumentain Black Bin		TOTAL			Constant of the Constant of th	
V = VOA Visi (1C) Preserved (19 = VOA Visi Sodian Baukhale Preserved VS = VOA Visi (10 Preserved VS = VOA VIsi (10 Preserved VS = VOA VISI (10 Preserved VS = VOA VISI (10 Preserved VS = VOA VISI (10 Preserved VS = VOA VISI (10 Preserved VS = VOA VISI (10 Preserved VS = VOA VISI (10	THE PROPERTY OF THE RESIDENCE OF THE PROPERTY	Tobarved CRC; SM = Sodium Hydroxide/Co Preserve	rd: 5 = Sodium Hydroxide Preserved Plastic; AG	Sodium Hydraxide Presenced Plastic; AG = Amber Glass Unpresenced; AP - Addingst Unpresenced Plastic;	reserved Plasis:	

Commetts on thely contaminant levels. distributs, or samples requiring specific QC analysis etc. CIVIDLE CNEICHS 89 Kenny Street Wodengerg, NSW 2000 Ph. U2 4225 3125 ff. porteen Madascobalkom Water Container Codes: P. L. Universerved Plastic, O. A. Natic Preserved DRC: SH = Ecotim Hydroxide/C2 Preserved, S = Sodium Hydroxide Plastic, AS = Amber Glass, Universerved, AP - Artheight Universerved, AP - Artheight Universerved, VS = VOA Viel Sulfure Preserved, lastic, IS = HOTA Preserved Specialism business ST = Static Preserved Plastic, F = Formside Soig, B = Unpreserved Bag.

Z = Zing Acetate Preserved Bottle: E = EDIA Preserved Bottles, ST = Static Preserved Plastic, F = Formside Soig, B = Unpreserved Bag. LESYKNEY 277-289 Woodern Road Smithfield May 218-Ph. 02 8784 8155 E. dengter bythorgjangedal con Additional Information DIOWNSMLE 14-15 Deems Court Bode OLD 46/15 RECEIVED BY: DATE/TIME Telephone: +61-2-8784 8555 Environmental Division ES1405223 ANALYSIS REQUIRED including BUITES (NB. Buile Codes must be listed to attract surie price) Where Metals are required, specify Total (uniflered bottle required) or Dissolved (field filtered bottle required). Work Order RELINGUISHED BY: DATE/NIME: DMFWDASTLE S Rose Gum Fond Warracost nasy 2304 Pri 12 1938 9403 Ei eamples seweside@galigusbaloom Choura and Geer Proc Bath Rome NSW 2541 Pr Coast 103 E. Roma gosposal con ОРЕЯТН 10 мостуму мяюда гул сово Рт. 38 5000 7655 🗗 вапиня респорянаювают COC STOUENCE NUMBER (CIMM) DATESTIME 11/50/14 63308 (5/3) RECEIVED BY: (Standard TAT may be longer for some lessis e.g., Loch Standard or urgent TAT fList due date): Utre Trace Organics) CAMELEOURNE 24 Wester Road Belingwak VIO 3171 FIT 03 85-N 900 E. Strapks mesteure (Geograpical con OMULGER II Sydnay Road Mugari New 1985 Ph. 82 6372 6736 El mulgea mylgalsyddal own ДКІ ХОКАХ 78 НИЗКИГ КОЛО МАККИУ ОЕВ АТАВ РК ОТ 4844 СТРТ В. НИКИЗУДУМЯВОВНІ КОМ Standard TAT (List due date);) I į 1 COSOS ARELINGUISHED BY CONTAINERS JATOT DATE/TIME: TOTAL (refer to ONTAINER INECRMATION g TYPE & PRESERVATIVE codes below) TURNAROUND REQUIREMENTS UGLADSTONE Ağ Cəfəmordab Dirəs Okton ULD ANSO On Cli 1471 5500 El gradstaneğ zügüblel onn LIBRISBANE 32 Shard Sycel Station Outh 4058 Fit: 07 3043 7222 E. Samples Liebans glasgictar, com SAMPLER MOBILE: 62.9758.2405 ALS QUOTE NO.: Email Reports to (will default to PM if no other addresses are lined); enquiries@amedesting.com.au Email involce to (will default to PM) if no other addresses are listed): accounte@smedesting.com.au CONTACT PH: 92 9758 2166 EDD FORMAT (pr default): XINTAM 7) DATE / TIME 0 E E COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL: CHAIN OF CUSTODY ALS Laboratory: please lick OFFICE: 14/1 COWPASTURE PLACE CLIENT: SMEC TESTING SERVICES SAMPLEID 0861 Erredf Carrange Careful PROJECT MANAGER: N/A COC emailed to ALS? NO 5315 £340 2368 57.39 はなっ 7525 536 2396 ORDER NUMBER SAMPLER: PROJECT: 5 LABED GY 1 P ダ

Commonts on likely conteminant levels, dilutions, or semples nequiting specific QC analysis etc. LYXXX EONGCMS 99 Kenny Steet Weisnasing NSW 2000 Phi UX 4225 5125 Ei parkemble@dfgfetal.com ZEVLYLEY ZZY-ZZBY Wkoczpak Posta Śmitałski MSW 2 164 Prz CZ 6784 H655 E. Rampiensykowykanyczakon DTOWNSVILE 14-15 Overn Court Sohn OLD (618 Ph. 07 4796 0000 Et bensenskumformerbiggsegabelom **Well Consider Codes: P = Unpreserved Plastic; N= Minc Preserved Plastic; ORC = Natio Preserved ORC; SH = Society Hydroxide/Cd Preserved; SH = Society Hydroxide/Cd Preserved; SH = Minc Preserved; AP = Minc Preserved Plastic; Preserved Plastic; Preserved Plastic; F = Floritation Preserved Aufteright Unpreserved Auteright Unpreserved Plastic; Preserved Plastic; F = Stelle Bottle ASS = Phatoc Blastic; F = Floritation Preserved Plastic; Preserved Ballier; ST = Stelle Bottle ASS = Phatoc Blastic; F = Floritation Preserved Plastic; Preserved Ballier; ST = Stelle Bottle ASS = Phatoc Blastic; F = Unpreserved Ballier; ST = Stelle Bottle ASS = Phatoc Ballion Brastic; F = Unpreserved Plastic; Preserved Ballion Blastic; F = Stelle Bottle ASS = Phatoc Ballion Brastic; F = Floritation Brasilia; F = Floritation Brastic; F = Additional Information RECEIVED BY: DATE/TIME: ANALYSIS REQUIRED including SUITES (NB. Sulin Codes must be fished to attract suite price). Where Metals are required, specify Total (unfiltered bottle required) or Diasolved (field filtered bottle required). RELINQUISHED BY: DATECTIME Darbwijas ile i kose Gun Road Wiererok naw 2004 Pri 02 4055 5435 Ei sampen neurunlegalsgjobs ma Davinra 4413 Geory Place North Noves High CE41 Pri 024423 IGES Eliphyrolythiaethalloith DPERTH 10 thod Way halaga WA 6090 Ph. 69 9099 1665 E. pamplas pertigologional COC SEQUENCE NUMBER (Circle) 1100114 RECEIVED BY: DATE/TIME: 1 :000 <u>9</u>. (Standard TAT may be tonger for some tests a.g., [F. Non Standard or urgent TAT (List due date): CINELECURISE and Wester Read Springware VIC 3 ft* Per 02 8549 5060 in samples melbourie@ainglobal.com Chilodee 21 sylvey Raid Mudove NSW 2500 Pt 02 6372 6736 E' macoso maligalayora rom Calacitan 78 Portour Road Markay Old 4743 Ph. 07 4844 0077 El matkay@algiolot vess C Standard TAT (List due date): ١ RELINQUISHED 8Y: TOTAL CONTAINERS DATE/TIME: (refer to codes before) TURNAROUND REQUIREMENTS TYPE & PRESERVATIVE ධරා පටුරුවන් අවරක්ෂණයක් පැහැ Chalon OLD පැහැ Prv 07 7471 0000 මී ඉන්ණකෙළින් නැහැ Chalon OLD පැහැ DASSLANDE 21 Surma Roozt Poornina S.A. gsaab Per C.D. Strissurgen E. Abenduckjangsbrasionn LEG 1920-V.B. 22 Septem Struck Stristor CLD AGG Pr. CJ. 2042 TZP E. tempers Proportegishignedicum SAMPLER MOBILE: 02 9756 2166 ALS QUOTE NO.: Email Reports to (will default to PM if no other addresses are issed); enquiries@smeclesting.com.au Email Involce to (wit default to PM if no other addresses are listed): accounts@smecfasting.com.au CONTACT PH: 02 9756 2166 EDD FORMAT (or default): XISTAM Э DATE / TIME SAMPLE DETAILS MATEIX SOLID (S) WATER (M) COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL: CUSTODY ALS Laboratory: please tick → CHAIN OF Som B acs 9 = CLIENT: SMEC TESTING SERVICES OFFICE: 14/1 COWPASTURE PLACE SAMPLE ID SEFT SHEET THE SEFT SEEDS PROJECT MANAGER: N/A COC emailed to ALS? NO 27.00 5965 5444 5.367 12 pc 7419 いかつつ 2361 5293 329 ORDER NUMBER: SAMPLER: PROJECT: 0.897 × ુ 3 <u>~</u> <u>o</u> 7

CONOLLANGONG 99 Faziny Shaal Violengong MSW 2500-Pry 02-1223 3123 E. portemiala@algonericom CTOWARMILE 14-15 Diama Ceut Brink QLD 4818 Ph. D7 4700 0000 3, semicana envienne salgatogradian RECEIVED BY: DATE/TIME: RELINQUISHED BY DATE/TIME: DNOMRA 4713 Geery Place Heats Borne NSW 2545 Ph. 026429 2063 B. Jowns@physickalcon DE ERTH 10 Had Way Malaga IVA Glob Ph. 68 9009 1000 E. Bropbes princ@alagobal cam COC SEQUENCE NUMBER (CITCH) M 05 C まるに RECEIVED BY: Ø DATECTME 0000 Whon Stendard or urgent TAT (List due date): Ë ORECEDURAE 24 Weeds Read Sparovey VID 317. Ph. 03 8049 9600 E. samples methodrae phragitations.com UNIVOSEE 27 Sydnay Road Mudgoo NSW 2833 Pry 02 6372 P136 Et madgee mail@aksyobst.com Standard TAT (List due date): RELINQUISHED BY: DATECTME (Shaddard TAT may be longer for some lesis e.g., Una Trace Organics) TURNAROUND REQUIREMENTS 11G. ADSTONÉ 18 Chizmando Dinc Cintor CLD 1889 ett 07 1971 3500 E. partikonsky dipolokal osm CBRYSSANE 31 Strand Street Stallon GLD 40t3 げた 07 1350 T222 E esemples britistne数akstratic SAMPLER MOBILE: 02 9756 2166 ALS QUOTE NO .: Email Reports to (will default to PM if no other addresses are listed); enquiries@smeclesting.com.au Email involce to (will default to PM if no other addresses are listed): accounte@smectesting.com.au CONTACT PH: 02 9755 2166 EDD FORMAT (or default): COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL: Ş ALS Laboratory: please tok → CUSTOBY OFFICE: 14/1 COMPASTURE PLACE CLIENT: SMEC TESTING SERVICES entrate the second second PROJECT MANAGER: N/A COC emailed to ALS? NO ORDER NUMBER: SAMPLER

ZEVENIEV 277-289 Woodpak Pond Sondalek: NSW 2-64 Ptt 02-878- 8556 E- remplessycher@asgeba.com

INEW-CASTLE B Ropa Grim Read (Hara) reck 1830/2304 Phr. CA 4923 ACCS III Amerika demonstratishing balanda solo

DMACKAY 70 Mark dia Road Malkoy OLD A749 Ph. Of 1944 OTH B. markayidaksgrond woo

DACELADE 21 Bures Road Poortus SA 2092 Pre OS 8089 VRPO (Laures de grasspira II.A.D.)

CHAIN OF

ALS L	SAMPLE DESAIS MATTOTSOLICISIMATERY	ALS VATERIUM: 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO 10 TO		Z. Z. CATAINERIN CORMATO	FORMATION	ij.	ANALYSIS H Where Metals i	IEQUIRED Inchi are required, spo	iding SURTES (N xsify Total (unilly rec	(NB. Suta Codos n filzered bottle requir required).	ANALYSIS REQUIRED including SUMTES (NB. Suho Codos must be listed to attest suite prite) There Metals are required, specify Total (unitiesed bollle (equired) or Diaschved (field likered bott required).	ANALYSIS REQUIRED trejuding SUNTES (NB. Suto Codes must be isled to atlead suite price). Where Metals are required, specify Total (unfliered bottle required) or Dissolved (field likered bottle required).	Additional Infortination	
LABID	SAMPLEID	DATE / TIME	XISTLAM	TYPE & PRESERVATIVE codes below)	(refor to	TOTAL COUNTRINGS	つ ∄			,			Comments on itsely contentnant lavels. disultons or samples requiring specific QC enables s.c.	
15 5/3/		4131114	5	Jer /	B		1						***************************************	
20 J.S	4				· · ·		<u> </u>						de de la companya de la companya de la companya de la companya de la companya de la companya de la companya de	,
4年15日		<u>.</u>					ŀ							
35 1S V	. 3	,					1		-					·
1815 2				A. 4			1							
30' 15 LSU							1							·
31 5181							1						**************************************	
22 SJOK						i	1							
53 SA31	,						1							
5 4 A S26	F.)						1			***********				1
es Jan		-			-		1							······
36 530	7		_				1			ì				,
					TOTAL									,

Water Contains Codes: P = Unperserved Plastic: ONG = New Proberved CRC: SH = Sodian HotcodeCd Preserved S = Sodian HotcodeCd Preserved Session Ander Glass Inpreserved AP = Aktragat Unpreserved Plastic: AS = WOA Vial Solitaric Preserved Specialion Preserved Specialion Preserved Specialion Preserved Specialion Preserved Specialion Preserved Specialion Preserved Specialion Preserved Specialion Preserved Specialion SP = Solitaric Preserved Plastic: ASS = Plastic Fa = Farmerichia Preserved Specialion Preserved Specialion Preserved Solition SP = Solitaric Preserved Plastic: ASS = Plastic Fa = Farmerichia Preserved Plastic Fa = EDIA Preserved Pl

Comments on likely conteminant levels, dilutions, of samples requiring specific QC snelysis etc. CTCHRISHILE 14-15 ESTA CON BONE (LL) (FIN 21, 07-1720 0520 E. 190-00018 emission entrational and an 190-1625 1757 E. PORTWHINE (BONE) (190-1700) 1750 - 550 21 02-1625 1757 E. PORTWHINE (BONE) Wider Contains Codes: 7 = Universaried Plastic, ORC = Minic Preserved ORC = Minic Preserved ORC = SH = Sodium Hydroxide Preserved; Plastic, AS = Amber Glass Unpreserved; AP - Arteignt Uncreasived Plastic

2 = Zinc Activity Preserved; VB = VOA Val Bodium Bridge, F = Famel Preserved Plastic; F = Famel Plastic; LESYXAEY ITT-289 Woospak Road Smakkelo NSW 1164 Ph. 02 after 8556 E. Gerraka aydrenggadanoon Additional information RECEIVED BY: DATE/TIME: ANALYSIS REGUIRED including SUTTES (NG. Sake Codes must be isled to streat suite price). Where Matais are required, specify Total (unfiltered bottle required) or Dissolved (field filtered solite RELINQUISHED BY: DAEWICASTLE II Rose Cum Read Wathrock NSW 2314 Phi 02 4988 9403 El samplar, new mellegyasglobal con DATE(TIME) DNOWRA 4413 Greey Mace Nutti Nowa 1588 2543 Ostonin vali i sa vysy Massay i wa kono 21 i de 9009 1608 fi i sampies pathigasigishai aum විදු කිණිවය 2000 සී. posta මුරු සුත්ලේක් පො G. 3 spr required). RECEIVED BY: 1 DATE/IME: CDC: -Standard TAT (List due date):

Non Standard or urgent TAT (List due date); ő Ì CIMELBOURNE ALA MARINI RAZO Epinguaia VIO 3 1711 Ph. 02 RM9 SRM E. samples neftaurnefijakgiotal am CMITCHOEE 27 Sydney Rand Mudges NSW 2010 Pr. O2 (CVC GTOS El modges matigatoporalitus) Listocyan Ta Merboar Read Mapay (NLD 4740) Pit Gridda 0127 III medaygetsglevel eyen 1 RELINQUISHED BY: CONTAINERS TATOT DATE/TIME: (refer to CONTAINER INFORMATIONS (Standard TAT may be longer for some lests e.g.. TYPE & PRESERVATIVE codes below) TURNAROUND REQUIREMENTS OGLAGSTINE 66 falemender örne Cinten OLD Jono Fin 07 7471 5656 ärgentleregalsgiven nom UER:984VE 32 8nand Sheet Staffon GuD 4053 Po∵රි 3043 1722 දි. නොතුමs පරාසිකමෙනින් අවර්ත com CADELAUSE 11 Suem Road Poetike SA 5095 Ph. (\$ 8359 DBN) Et adelaide ((p. 8300-1, co.) SAMPLER MOBILE: 02 9756 2166 ALS QUOTE NO .: Email Reports to (will default to PM if no other addresses are listed); enquiries@smoclesting.com.au Email Invoice to (will default to PM if no other addresses are listed); accounts@smeciesting.com.zu CONTACT PH: 02 9755 2166 EDD FORMAT (or default): XISTAM DATE / TIME COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL: ALS Laboratory. please tick → CUSTODY CHAIN OF OFFICE: 14/1 COWPASTURE PLACE CLIENT; SMEC TESTING SERVICES SAMPLE ID Correspondent and Contractions PROJECT MANAGER: N/A COC emailed to ALS? NO 34 S230 ORDER NUMBER: PROJECT: SAMPLER 14810

SYGNEY 277 Wordput had Sharifed ISSY 2164 Ph. D. Edish Sidd. Examples syring-Guernin con TOWNSHIEL 44-15 Dean Chin School Old 18 Ph. D. 4252 1125 E. parker the Walcopy HSV 2000 Ph. D. 4252 1125 E. parker the Walcopy HSV 2000 Ph. D. 4252 1125 E. parker the Walcopy HSV 2000 Soath Infection of the State of the St	RECEIVED BY: DATE/TIME: Additional Information Percentage.	Comments on likely conteminant lavels, disultons, or samplos requiring specific QC analysis etc.		
HEWICHSTIE 5 Resepun haart Waraboock New 2304 Pri 102 4635 9432 E some serves reference on the 102 4432 3033 E some serves serves reference on the 102 4432 3033 E normal serves serves (102 21) Pri 102 403 7635 E serves serves on the 102 103 103 103 103 103 103 103 103 103 103	RECEIVED BY: 12/3/11 RELINQUISHED BY: RE DATE/TIME: 6:30 P ANALYSIS REQUIRED including SUITES (NB. Suite Codes must be listed to attract suite prios) where Mobals are required, specify Total (unliftened bottle required) or Dissolved (field filtered bottle reculred).			49 Sq. 44 Si 63
D WEBSING OF WEBSING O	SHED BY:	TOTAL CONTRINERS		49 Sq. 1 Contains Codes: P. Unpresenced Plastic: ORC = Natice Proceed Offices Bl = Sodian Method-for Proceed Plastic: ORC = Natice Procedure Proce
ADELANE 27 Burns free frozen St. 6555 Pr. D8 8559 (690 E autherboaksennon.com SHESTANE 22 Shand Street Station of 4653 Fr. 07 5273 17272 C Street Station of 6253 Fr. 07 5273 17272 C Street Station of 6254 Fr. 07 6527 1500 E 45 Selementon 6254 c from Code 6653 TURNARCOUND REQUIREMENTS: (Standard TAT may be longer for some tasts e.g. Ultra Trace Organics) ALS QUOTE NO.: CONTACT PH: 4 664 [6]	container	TYPE & PRESERVATIVE (refer to codes below)		TOTAL
STOD OF STOD O	I NO) OPM if no other LING/STORAG	SAMPLE ID DATE/TIME	0 0 4	P = Unpresenced Plastic: N = Nitric Presenced Plastic; C
ETTUTE OFFICE OFFICE: UN COLOR OFFICE: UN COLOR OFFICE OFF	COC emailed to ALS? (YES Email Reports to (will default to Email Invoice to (will default to COMMENTS/ SPECIAL HAND ALS SUSE MATRIX	11 SG 47 47 554	37375	49 5916

STENKY 277 word got fear Smalthair NSW 2184 STENKY 277 word got fear Smalthair NSW 2184 DIWINSTALE 1-15 been Bown Bord web at Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land Day On the Land On the Land Day On the Land On the Land Day On	RECEIVED BY: DATE/TIME:	e price) Where Additional Information (2)	Comments on likely contaminant tevels, dilutions, or samples requiring specific QC analysis etc.			-						
THE S Respons Raad Warsbrook ISSN 23304 68 9433 E. Semples so weeds being the sent of the	POW IN RELINQUISHED BY:	ANALYSIS REQUIRED Including SUITES (NB. Suite Codes must be listed to attract strite price) Where Metals are required, specify Total (unliftered bottle required) or Dissolved (fillered bottle required).										Water Conteiner Codes: P = Unpreserved Plastic: N = Nhiric Preserved Plastic: OR D = Nhiric Preserved ORC; SH = Sodium Hydroxide/Cd Preserved; S = Sodium Hy
MAKKAT 78 Islange Read Mackay OLD 4740 MicLi 4944 Old The Entranger Committee Comm	RELINQUISHED BY: DATE/TIME: DATE/TIME:		TOTAL CONTRINERS]]		\	1	7 1			Water Conteiner Codess: P = Unpreserved Plastic: N = Minic Preserved Plastic: OBC = Ninic Preserved OBCs; SH = Sodium Hydroxide/Cd Preserved; S = Sodium Hydroxide/Cd Preserved; Plastic: A = White Plastic
ADELGIP 21 Burns free Roade St. 5095 Ph. 06 8095 0690 E edesia-Galzenfra.com Ph. 07 3249 T.Z.E. Sample Stree Stand at 0.9 439 Ph. 07 469 T.Z.E. Sample Stree Street Self-Galzen Full May 645 T.S.C. Sample Street Self-Galzen TURNAROUND REQUIREMENT (Slandard TAT may be longer for some tasts e.g. Ultra Trace Organ ALS QUOTE NO.: CONTACT PH. Cy 26	autt);	CONTAINERINFORMATION	TYPE & PRESERVATIVE (refer to codes below)	5 (Tar / Ja,								ORC = White Presumed ORC; SH = Sociom Hydroxide/Cd Preserved;
20 SO	EDD FORMAT (or default): ther addresses are listed): her addresses are listed): AGE OR DISPOSAL;	J. WATER (W)	DATE/TIME	M/M9		***************************************						ric Preserved Plastic, ORO
CHAIN OF CUSTODY (ALS) (ALS) (ALS) (CUSTODY (CUSTODY) (CUSTODY) (CUSTODY (CUSTODY) (CUSTODY (CUSTOD	COC emailed to ALS? (YES / NO) EDD FORMAT (or defe Email Reports to (will default to PM if no other addresses are listed): Email Invoice to (will default to PM if no other addresses are listed): COMMENTS/ SPECIAL HANDLING/STORAGE OR DISPOSAL;	SAMPLE DETAILS MATRIX - SOLID (S), WATER (W)	SAMPLE ID	(18 A A A A A A A A A A A A A A A A A A A	2117	S	2	2	Ar.	0	8915 A	ides: P = Unpreserved Plastic; N = R/u iserved; VB = VCA Vral Sod/un Bieulsh
CLIENTY MI CLIENTY MI OFFICE: CP/ PROJECT: T PURCHASE OR PROJECT MAN	COC emailed Email Report	ALS	LABID	1 (2)	2	52 25	\$ 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	5000	26 23 26 82	60 5	19	Water Conteiner Co

Fig. 1977 97.2 and sweep our lesses a confider http: 1978 1978 1978 1978 1978 1978 1978 1978	LABORATORY, USE SONLY (IDITIVE) BETTER THE					3Y: RECEIVED BY:	*******	0.00780			d seile dident	d filered boile Addisonal information	Comments on I kely pontaminant foreks	Churans, or samplins requiring pageter closes analysis etc.			**************************************	147- 47- 47- 47- 47- 47- 47- 47- 47- 47-	(al Division	(e)	Though the second secon	770					The state of the s
DESPICACION IN EL Rosse Com Troute and Voluments (Refly 2004 Part of these Commons and Voluments (Refly 2004 Part of the 2004		(a): (人) (A): (a): (a): (a): (a): (a): (a): (a): (a	COC SEQUENCE NUMBER (CINA) TRANSMITTER			RELINGUE		Datesime 11/5/14	6.30		NOT includion 2017 S. 2.180 Selfs Pades served has listed to release	Photos Pacial menores inspects from the commentaries personal respect to the control some productions are required, specify Total (undistant build required) or Dissolved (field filered boills required).					-		Environmental Division	Sydney	BUCACA CA	1			Telephone 181.0 and account	The assessment of the state of	
DIAM, CAN PROPERTY FOR INDIANG (ILL) TO S Pr. O' 6644 ILY I anneany begins were Chief edular & Annean Faul Fringenk vic Usy- Pr. O'S 1998 BACO F. Marker present effects only DIAM DESTA USE I centre an INSPANSATION I'M DESTA USE I centre and Shapanahaman.	Slandard TAT (List due date):	D. L. Non Standard or Ingent TAT (List due date):		000		PRELINGUISHED BY	? _	INATEMME: QUE CONTROL INS			ANALYSIS DECA	ORMATICANO TENTO Where Metals are n	(Merco CATACETS	EC conty	1	7		4					THE PARTY OF THE P	1	emer'emer ve	A CONTRACTOR OF THE CONTRACTOR	
Charte, Jane F. Seylea Rose Inc. 440 de 1852 Fr. 187 Inc. 1850 per la Central Company and Inc. Pr. 187 Per 187 De 2 en ende strone Soulian Geo e 400 Fr. 187 Per 187 De 2 En ende strone Soulian Geo e 400 Fr. 187 Per 187 De 2 En en en en en en en en en en en en en en	TURNAROUND REQUIREMENTS:	(Supdant TAT may be longer for some tests e.g., Utile Trace Organics)	ALS QUOTE NO.:		CONTACT PH: 03 9768 2166	SAMPLER MOBILE: B29755 2406 COPCOS	EDD FORMAT (or default):	sraechston com au	sneckesting.com.au			CONTRINECTION	K TYPE & PRESERVATIVE	Codies before)	5 Jer 12a					- 1		,	THE PROPERTY AND THE PR				
CHAIN OF PROBLEM CUSTODY REPROPERTIES MAS EXECUTED TO THE PROBLEM OF THE PROBLEM	ļ			0760	CONTACT	SAMPLER	EDD FORM	Email Reports to (will default to PM if no other addresses are listed); enquirities (Pagnechashen gon au	Email Invoice to (xill default to PM is no other addresses are listed); accounts@snectesting.com.au	SAGE DE DISCOSAL	Made on the room.	S UD STATERWAY	H WY		0/2/16								**************************************				
Emilianismical	CLIENT: SMEC TESTING SERVICES	1471 CO	PROJECT: 1420/4	ORDER NUMBER:	PROJECT MANAGER: NIA	SAMPLER: J./C /D./	COC emailed to ALS? NO	Email Reports to (will default to PM if no	Email Invoice to (will default to PM it no	COMMENTS/Special HANDI NOSTOBAGE OB DISCOSAL		JOSE MATER	- CAMPIETS		1 22(2	2 J262	3 487	4 BIG	£25 S	6 5339	7 5340	5313	9 5362	10 C 363	े । ऽत्रथ्र	12 3396	

Commons on likely conteminant levels, diulions, or semples requiring specific CIC analysis etc. DMOLLONDONG 92 Keny Shaei Welingong MSN 2503 PN 02 4225 3125 E. perkembagasplobal.com Water Container Codes: P. = Unpreserved Plastic, in = unite Preserved CRC = Ninc Preserved CRC, SH = Sodium Hydroxide Preserved, S = Sodium Hydroxide Preserved Plastic, AG = Amber Glass. Unpreserved, AP - Airfield Unpreserved Plastic, AS = Work Visit Sodium Preserved Plastic, AS = Work Visit Sodium Studie; SP = Sulfuto Preserved Plastic, AB = AC preserved Plastic, AS = Plastic, Preserved Plastic, F = Formation Solids, ASS = Plastic, ASS -Xetoney 277-288 Phyodork Rosa Sminhad RSW (184 Ph. DR 8784 283) El Geoples sydionégasymastran OTONMSVILE 14-15 factory Ocea Sonie OLD 4610 Ph. 07 4702 1800 E. comessio em-formental@vispebi.com Additional Information RECEIVED BY: ANALYDIS RECUMRED Including SUITES (NB. Suite Codes must be fished to attact suite price). Where Metals are required, specify Total furfillered boths required; or Dissolvad (field filtered boths required). RELINCUISHED BY: DATE/TIME: Colemnatic E Kose Ger And Warmood (457) 2204 Po. O? 4410 5435 El caraféa rescasios política da GMOWRA 4/13 (kesty Place Node Noves NSW 254) Pri 024423 2003 E. Howago igolod com DPERTY 10 HALTER MARKE WAS 0090 PA 0090 PA 03 0109 7055 E. REMARKS SERIES COC SEQUENCE NUMBER (Circle) RECEIVED BY: DATEMINE The Non Standard or urgent TAT (List due date); ö 8 DNELBOURNE 24 Westus Road Springwass VIO 3177 Ph. 02 8549 5000 E. samstas melicume (§atsglobal, ope CONTOCKE IT Sympty Read Narigue ARV 2000 Pr. 02 8372 9733 R. madew maligatspland com DDARCKAY 10 Harbour Road Wassay DLO 47kg Phy Of 40kd 9477 El moetalygaagiskut som C Stendard TAT (List due data): 1 ı ١ Į ١ RELINQUISHED BY: CONTAINERS SATOT DATEMME (refer to TOTAL (Standard TAT may be longer for some tests e.g.. Uttor Trace Organics) TYPE & PRESERVATIVE COCIOS BOIOW) TURNAROUND REQUIREMENTS: USINASSTOKE 40 ÇARBANASA Dike Cikatos QLD 4699 Ph G7 7471 5000 हैं अस्परितामार्थे स्वतृत्यत उत्ता DBRINGANI IZ Shand Sheet Blaffon CLD 4069 Phi OT 3243 7242 Eigemples ortsbaneglielogickytos h DACELAGE 11 Gema Rood Boseton SA Englisher George SAMPLER MOBILE: 02 9755 2166 ALS QUOTE NO.: Email Reports to (will default to PM If no other addresses are listed); enquiries@smectasting.com.au Email trivoice to (will default to PM if no other addresses are listed): accounts@smeclosking.com.au CONTACT PH: 02 9756 2166 EDD FORMAT (or, default): MATRIX 7 DATE / TIME COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL. ALS Laboratory: please fick → CUSTODY PROJECT: (47 COWPASTURE PLACE
PROJECT: (4010) CHAIN OF Som & as 9. 二米 CLIENT: SMEC TESTING SERVICES SAMPLE ID EFFACTOR CONTRACTOR PROJECT MANAGER: N/A COC emailed to ALS? NO 2300 2469 5446 4.367 200 **539** 5293 3292 ORDER NUMBER: SAMPLER LAB 10 M u 3 Ø.

ONVORIGINATE HATS Desira Desir Beshe UND 1816s for or a real control on the control on the control on the control on the control on the control of the contr RECEIVED BY DATECTIVE RELINGUISHED BY: DATE/THE: CINOMRA 473 Gest Place Hath Yorks NSW 25M PP C2A423 DC83 E. norms@akgloberinan DPCPTH 10 Hos Wer, Malage Wakdofo PH 08 9009 WAG E. semples periti@akglobel.com COC SEQUENCE NUMBER (CIPCIE) 3000 10/60 RECEIVED BY: DATE/TIME: Ö Whon Standard or urgen! TAT (List due date): ä CIMELBOURNE 24 Versial Real Boungrain VIC 3 115 Ptr C3 8549 1900 E. samples desbourne(3skylntal.com Dalugsber 17 splasy from Modern 11504 1120 Pt. 02 6372 0785 El marken emissen males ☐ Standard TAT (List due dete): RELINQUISHED BY: DATE/TIME: (Slandard TAT may be longer for some tasts e.g.. Ukra Ttace (1986)(53) TURNAROUND REQUIREMENTS: OGLAOSTONE GEOGRAPHICA GARANGO ASSO PRIOT 7471 SOME gradionagia sgribal can CDRNSBANE IZ Shand Smire Suited OLD 4053 Ph. VI 3243 1722 E. Bamples Vishar-Egishgobal, com SAMPLER MOBILE: 02 9755 2166 ALS QUOTE NO.: Email Reports to (will default to PM if no other addresses are listed): enquince@smectesting.com.au Email Invoice to (will default to PM if no other addresses are listed): accounts@smeckepting.com.au CONTACT PH: 02:9755 2166 EDD FORMAT (ondefault): COMMENTS/SPECIAL HANDLING/STORAGE DR DISPOSAL: ALS Laboratory. please tick → CUSTODY OFFICE: 14/1 COMPASTURE PLACE CLIENT: SMEC TESTING SERVICES motor manual PROJECT MANAGER: N/A COC emailed to ALS? NO ORDER NUMBER: SAMPLER: PROJECT:

J. SEYCHEY 277-289 Woodpar Rond Smahler 1892-2754 Pr. 02 8794-8155 F. Azmolensyd-entgranjanskom

DNEWCASTI, E.B. Sope Gum Road Vizaringok NSIN 2304 Pr. 02 4038 9433 K. damilée navoralegasgoba com

DMACAAY 16 Nerbour Rood Mackay CB 13-5740 Ph. 07-4044 0111 Et marksy@degelobet com:

CADELAGE 2: Surpa Roas Podsika St. 509? Pr. CS 8350 MBY E. adnolaethausgebistom

CHAIN OF

Comments on their conteminant levels, dilutions, or samples requiring specific QC analysis etc. Additional information ANALYSIS RECUMEND Including Stuffes (NB. State Codes must be issed to stiract suite price) Where Metals are majured, specify Total (anithmed bolice required) or Elesalved (flexi filtered bolice). 3 Ì ı J TOTAL CONTAINERS (refer to CONTAINER WEORWATION Ŕ TYPE & PRESERVATIVE codes befow? ્કુ XISTAM Ī J DATE / TIME SAMPLEID 25.52 212 518 Slog 4 0 1 1 1 1 1 20,

Water Coostan Coosta. ? = Untresswed Plastic. Name Preserved ORC. * Name Preserved ORC. * SH = Section Pycroxistic As = Section Preserved Plastic As = Amber Glass Urpareserved Ab Action Preserved As = Authority that Preserved As = Authority that Preserved Ander Glass. H = HCI preserved Plastic. H = HCI preserved Plastic. H = Carried Brain Preserved As = Authority Brain Preserved Ander Glass. H = HCI preserved Plastic. H = EEPTA Preserved Bottles, ST = Static Brain Preserved Plastic. F = Formation Preserved Glass.

TOTAL

5307

Oximinents on Ikely contentinant levels, dilutions, or samples requiring specific QC analysis etc. LINGSHANGELE SASSMENT CHAIR BOSH (BLD CA) At 107 ATES 8800 E. IRONAL TO ENGINEERING CHAIR AND CONTRACTOR DE SOND SON TOWNER THE WAS ATES TO CONTRACTOR TO THE CONTRACTOR OF THE SON TH [7] Sythey 27-289 Woodpan Hoes Shariffie NSB 7187 Pot 22 8784 8785 E. Gottfanydonyjdonycom ** Sodium Hydroxide Preserved Plastic; ORC = Ninc Preserved Plastic; ORC = Ninc Preserved Plastic; ORC = Ninc Preserved Plastic; ORC = Ninc Preserved Plastic; ORC = Ninc Preserved Plastic; ORC = Ninc Preserved Plastic; Pre Additional information RECEIVED BY: DATE/TIME: ANALYSIS REGUNRED Including SUITES (ND. Suite Codes must be isled to ellect suite price). When Melais are required, specify Total (unittored bolite required) or Dissolved (field filtered bette RELINQUISHED BY: DNEWDAET EI Rose Cam Rosa Warkfosk NIN 3304 4th 32 4650 bald Ei Karybo nawoolagoskoodda oon DATERIME CHAPTER AND DOMY PASS BUILD NOWS NOST 2591 ОРЕВТИ 10 НОУ МИУ МАТОЛА WA СОЗО РИ ОВ 9000 7050 ЕГ МИТОМУ БАТИФОМДОМДОМИ Phy 024 d22 2068 Et new augusphobal com RECEIVED BY: 1 DATE/TIME: COC: 1 Slenderg TAT (List due date):

Non Slandard or urgent TAT (List due date): . H ſ 1 OMELECUTARE 24 Weami Rosh Springs or VID 3171 Ph 03 9549 960 E samples metalme@eligicial.com DARROGEE ZY Sydney Popy Blackon NSW 1780 Phy 32 (1977 (173) El muogos makgalagiosalsom GRACKAY PERSENSI BOSEMAKKIY GLD A740 Paligy eft efter Strakkyyj elegebal syst 1 RELINQUISHED BY: TOTAL CONTAINERS DATE/TIME: TOTAL (refer to CONTAINERINFORMATION (Standard TAT may be longer for some tests e.g., codes below) TURNAROUND REQUIREMENTS: TYPE & PRESERVATIVE Gill ADSTONE AS Calumentals Dirk Carps: 01.0 #380 Phr 07 7471 G100 Biglassland@eligicisal.com GBRISBANE 32 Shand Sheet Bushed But 653 Phr of 3043 7322 Enterholds beispansgalsglobaldan 多う SAMPLER MOBILE: 02 9755 2166 ALS QUOTE NO.: Email Reports to (will default to PM If no other addresses are listed); enquiries@smeclesting.com.au Email invoice to (will default to PM if no other addresses are listed); accounts@smedesting.com.au CONTACT PH: 02 9756 2166 EDD FORMAT (or default): XISTLAM DATE / TIME COMMENTS/SPECIAL HANDLING/STORAGE OR DISPOSAL: ALS Laboratory. ploase fick → CUSTODY CHAIN OF OFFICE: 147 COWPASTURE PLACE
PROJECT: 430 CLIENT: SMEC TESTING SERVICES SAMPLEID Estable correspondent Cons PROJECT MANAGER: N/A COC emailed to ALS? NO ORDER NUMBER: SAMPLER: 3 7 Š LABID

7.00	% <u> </u>	, v	<u>.</u>	. 1.3,	·····						*	· · · · · · · · · · · · · · · · · · ·		·		y 4.1				-0	511 S	· · ·	1.19.1	 	
STRINEY 277 Mondank Assi Smithcul NSW 7164 Price Bry 874 Res Stranger Sydnay Geles minosom TOWNSHILE IL-15 Desira Sydnay Geles minosom TOWNSHILE IL-15 Desira Sydnay Geles minosom TOWNSHILE IL-15 Desira Sydnay Geles minosom TOWNSHILE IL-15 Desira Sydnay Workmann Res Sydnay Steff Color	oglibelican (Circle) (***)	Free To Higgenics bricks present upon receipt if was	Y.,		RECEIVED BY:	CATETION				Additional Information		Comments on likely contaminant levels, ditutions, or samples requiring specific QC analysis	310				-		-				-		· · · · · · · · · · · · · · · · · · ·
NEWFASTILE 5 Rassoum Rad Vlanderak NSW 2334 Fit 02 4908 9423 E-samples newtastikoosicundin.com; NBYRN 4/13 Casy, Flore fasti kati Newa NSW 2641 Fit 02 4423 2553 E-rawrastals close com PRTH III IND MEM-Rassoum M 6009 Tit 08 8229 2355 E-samples netticase com		***************************************	2 3 4 6 6 7	2 3 4 5 6 7		(19)				ANALYSIS REQUIRED including SUITES (N3. Suite Codes must be listed to attract suite price) Where Metals me monitoring recording to the control of the contro	is turnificated bottle fequirekt) or Dissolved (field filtered &		COMPANY COLOR MANAGEMENT AND ADMINISTRATION OF THE PROPERTY OF						***************************************						Water Containst Codes; P = Unpreserved Pression in a White Proserved Preserved Preserved Plantic ORG = White Proserved CRC; SH = Bodium Hydroxide Procerved; S = Sodium Hydroxide Procerved Plantic AG = Anther Glass Unpreserved AP - Adringful Unpreserved Plantic. F = Formethylyde Preserved Glass, Z = ZDG, Argible Preserved Glass (E) = EGTA Procerved Bankser, ST = Source Preserved Glass, AP = Argible Preserved Glass, AP = Argible Preserved Glass (E) = EGTA Procerved Bankser, ST = Source Preserved Glass, AP = Argible Preserved Glass (E) = EGTA Procerved Bankser, ST = Source Preserved Glass, AP = Argible Argible Preserved Glass, AP = Argible Preserved Glass, AP = Argible Preserved Glass, AP = Argible Preserved Glass, AP = Argible Argible Preserved Glass, AP = Argible Preserved Glass, AP = Argible A
MANAN STATEGOS READ ANGENESS ILD 9746 Ph. U7 4944 6077 E restoy Park Status Cont. NESSUME 2-4 Westel Read Sindenes VIC 3171 Ph. 107 8549 9900 E Semples, nei brockostemvico com NUBBEL 27 Syktem Float Margae NSV 26-09 Ph. 102 6372 6035 E medignes minimosio plata com	Standard TAT (List due date): On Standard or urgent TAT (900	COC:	-		IME: DATE/TIME:		THE THE THE THE THE THE THE THE THE THE				тоты оитейиея .ЭЭ												 	Water Containst Codes; P = Urgresserned Pleate; N = Ninip Preserved Plante; ORO = Ninip Preserved ORC; SH = Bodium Hydroxider Cheestrod; S = Sodium Hydroxide Preserved Plaste; AG = Anther Glass Unplesserved; AP = Anther British Unpreserved Plaste; AG = Anther Glass Unplesserved Plaste; AG = ETTA Preserved Bankae; BT * Section Plaste; AG = Section Plaste; AG = Section Plaste; AG = Anther Glass Unplesserved Plaste; AG = ETTA Preserved Plaste; AG = Part Plaster AG =
THE DESIGNATION OF A MATERIAL BASENATORY BUSSANCES STAND SEARCH STAND SEARCH STAND SEARCH STAND SEARCH STAND SEARCH SEARC	TURNAROUND REQUIREMENTS: (Glandard TAT may be longer for some tests e.g. Ultra Trace Organics)	ALS QUOTE NO.;	CONTACT PH: Q XEA IN		(dt);	(sted): DATE/TIME:	sted):			CONTAINER:INFORMATION		TYPE & PRESERVATIVE (refer to codes below)							**************************************	**************************************	***************************************			TOTAL	= Nitro Prosenced ORC; SI+= Soddum Hyckoxide(Cd Presentel) SULvinia Prosenced RV = Alife@ht Unprosenced viel SG = area Bankeas ST * Sound - Partin, Acco = Partin Bankeas ST * Factorial Partin, Acco
CUSTODY ALS Laboratory: please fick —	The carter of the control of the carter of t	1000/ 4050c		() (SAMPLER MOBILE:	(YES / NO) EDD FORMAT (or default):	Email Reports to (will default to PM if no other addresses are listed):	Email Involce to (will cefeult to PM if no other addresses ere listed);	COMMENTS/ SPECIAL HANDLING/STORAGE OR DISPOSAL;	Additional and a second	SAMPLE DETALLS MATRIX - SOLID (S), WATER (W)	, market 1971	SAMPLE ID DATE/TIME	2)/(0	The second secon					THE THE PARTY OF T		***************************************				prezervtd Perix: N = Nihô Prosonyod Phreis: ORO = VOA Vial Sodam Disulphale Prosonyod; VS = VOA V SS. Z = ZDS. Argillo Presonyol Bollie: E = Entra Proso
Environmental	OFFICE: CA	PURCHASE ORDER NUMBER:	PROJECT MANAGER:	SAMPLER: JAK	COC emailed to ALS? (YES	Email Reports to (will a	Email Involce to (will ci	COMMENTS/ SPECIAL	A L G	ALS USE M		LABID SAI	150	27 5160	43 5160	3975	145 24	ار گر ا	りで	115 8h	49 3163				Water Container Codes; P≈Un V≈VOA Vial HCt Preserved; VB: F≈Formetidityde Preserved Glas

STOREY ZZZ MONTEK flood Sministed KSW 2169 TUNKSKILLE 14: 15 Details Date State flood Sministed KSW 2169 TUNKSKILLE 14: 15 Details Date State flood	CEIVED BY:	quired), quired), Comments on likely conteminant levels, diutions, or semples requiring specific QC analysis						
THE S FOSSBURN Fract Waterbrook NEW 2204 147 Day P Fice It for Wars RSW 2641 147 Day P Fice It for Wars RSW 2641 151 Day Markey New To The Control of The	PORTING BY: OR DATE TIME:	AWALY 31S KEAUIKED including SUITES (NB. Suite Codes must be listed to altract suite price) Where Metals are required, specify Total (unfiltered bottle required) or Dissokved (field filtered bottle required).						l kooren en sist at 17 states to 11 states t
Statuter East Marker OLD 4740 40177 E. makes Sersification 11. 24 Prosition Sersificate Com 10.9500 E. serspace medical Read Sersification Revealed 10.9500 E. serspace medical Read Sersification Revealed 10.9500 E. serspace medical Research 10.9500 E. serspace medical Revealed 10.9500 E. serspace medical R	ISHED BY:	TOTAL		1		17,		ALG Co. 1961 S = Sodiam Hydroxida Pleserved Plastic: A.G.: Amher Clase I becomment A.D. Addition
ADELMIEZI Sarma Read Popales SA 5565 Pr. 08 839 0630. E. abreleographo.com BRIGARIO 224/1722 E. striptischerior dig acts Pr. 07 224/1722 E. striptischerior dig acts Pr. 07 224/1722 E. striptischerior digescriptischerior director dig acts TURNAROUND REQUIREMENTY (Slandard TAT may be longor for some tosts a.g. ultra Trace Organ ALS QUOTE NO.: CONTACT PH: \$\frac{Q}{2}\frac{7376}{2}\frac{C}{2}\frac{1}{2}\fr	Buff):	्राज्ञ XIATAM अर्थ	5 Ter /Ja,					Water Container Coutes; P = Unpresented Flastic; N = Nato Presented Plastic; ORC = Nate Presented ORC; 8H = Soutum HydroxiderCd Presented; S = V = VOA Vial HCI Presented; VB = VOA Vial Rodinin Residented Presented; S = VOA Vial Rodinin HydroxiderCd Presented; S = VOA Vial Rodinin Hydroxider
	to PM if no other addresses are listed); to PM if no other addresses are listed); buing/storage or disposal: Sample Detalls	MATER (W)	31/2/9					- Mirc Proserved Plastic; ORG
CHAIN OF CUSTODY (ALS)	COC emailed to ALS7 (YES / NO) EDD FORMAT (or definant) Email Reports to (will default to PM if no other addresses are listed). COMMENTS/ SPECIAL HANDLING/STORAGE OR DISPOSAL: ALS SAMPLE DETAILS MATRIX SOLID ON WITH STORY	SAMPLE ID	Sirk Sirk	535	263 189	\$15C	1900 1(1)	Water Consainer Coutes: P = Unpreserved Plastic: N = Nitic Preserved Plastic; ORC = Nitic Preserved ORC; V = VOA Vial HOI Preserved; VB = VOA Vial Revision Residented Desire; ORC = Nitic Preserved ORC;
CLENTY) OFFICE [PROJECT: PURCHASE PROJECT M SAMPLER:	COC emaile Email Repor Email Invoic COMMENTS	LAB D	87	22.5	25 25	282	09	Water Container



CERTIFICATE OF ANALYSIS

Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : SMEC TESTING ALL RESULTS Contact : Client Services

Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

Project : 19580 40300 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Order number : 10920

 C-O-C number
 : --- Date Samples Received
 : 11-MAR-2014

 Sampler
 : JK/DL
 Issue Date
 : 19-MAR-2014

No. of samples received : 58

Quote number : EN/025/13 No. of samples analysed : 58

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Certificate of Analysis contains the following information:

٠ ____

- General Comments
- Analytical Results



Site

NATA Accredited Laboratory 825

Accredited for compliance with ISO/IEC 17025.

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

: 1 of 14

Signatories

Position

Accreditation Category

Sydney Inorganics

Ankit Joshi

Inorganic Chemist
Sydney Inorganics

Sydney Inorganics

Sydney Inorganics

Sydney Inorganics

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 |
Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300

ALS

General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

^ = This result is computed from individual analyte detections at or above the level of reporting

Page : 3 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300





Page : 4 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300





Page : 5 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300






Page : 6 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300






Page : 7 of 14
Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300






Page : 8 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300






Page : 9 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300






Page : 10 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300






Page : 11 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300





Page : 12 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300





Page : 13 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300





Page : 14 of 14 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300







QUALITY CONTROL REPORT

Work Order : **ES1405223** Page : 1 of 4

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : SMEC TESTING ALL RESULTS Contact : Client Services

Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

E-mail : enquiries@smectesting.com.au : sydney@alsglobal.com

 Telephone
 : +61-2-8784 8555

 Facsimile
 : +61-2-8784 8500

 Facsimile
 : +61-2-8784 8500

Project : 19580 40300 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Site : ----

 C-O-C number
 : -- Date Samples Received
 : 11-MAR-2014

 Sampler
 : JK/DL
 Issue Date
 : 19-MAR-2014

Order number : 10920

Quote number : EN/025/13 No. of samples analysed : 58

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Quality Control Report contains the following information:

NATA Accredited

Laboratory 825

Accredited for

compliance with

ISO/IEC 17025.

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits



Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out ir compliance with procedures specified in 21 CFR Part 11.

No. of samples received

: 58

Signatories Position Accreditation Category

Ankit Joshi Inorganic Chemist
Shobhna Chandra Metals Coordinator

Sydney Inorganics Sydney Inorganics Sydney Inorganics

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 4 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

= Indicates failed QC

Page : 3 of 4
Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300

Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR:-No Limit; Result between 10 and 20 times LOR:-0% - 50%; Result > 20 times LOR:-0% - 20%.

Sub-Matrix: SOIL						Laboratory L	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EA002 : pH (Soils) (QC Lot: 3334853)								
ES1405172-004	Anonymous	EA002: pH Value		0.1	pH Unit	4.3	4.2	0.0	0% - 20%
ES1405240-001	Anonymous	EA002: pH Value		0.1	pH Unit	6.3	6.3	0.0	0% - 20%
EA010: Conductivity	(QC Lot: 3334845)								
ES1405223-001	S212	EA010: Electrical Conductivity @ 25°C		1	μS/cm	23	19	18.3	0% - 20%
ES1405223-011	S392	EA010: Electrical Conductivity @ 25°C		1	μS/cm	18	18	0.0	0% - 50%
EA010: Conductivity	(QC Lot: 3334846)								
ES1405223-024	S292	EA010: Electrical Conductivity @ 25°C		1	μS/cm	23	23	0.0	0% - 20%
ES1405223-034	S281	EA010: Electrical Conductivity @ 25°C		1	μS/cm	21	21	0.0	0% - 20%
EA010: Conductivity	(QC Lot: 3334847)								
ES1405223-046	S41	EA010: Electrical Conductivity @ 25°C		1	μS/cm	31	30	0.0	0% - 20%
ES1405223-056	S143	EA010: Electrical Conductivity @ 25°C		1	μS/cm	44	44	0.0	0% - 20%
EA010: Conductivity	(QC Lot: 3334849)								
ES1405032-001	Anonymous	EA010: Electrical Conductivity @ 25°C		1	μS/cm	504	533	5.6	0% - 20%
ES1405172-004	Anonymous	EA010: Electrical Conductivity @ 25°C		1	μS/cm	34	36	7.1	0% - 20%
EA055: Moisture Cor	ntent (QC Lot: 3336930)								
ES1405067-034	Anonymous	EA055-103: Moisture Content (dried @ 103°C)		1.0	%	19.6	20.1	2.4	0% - 20%
ES1405194-006	Anonymous	EA055-103: Moisture Content (dried @ 103°C)		1.0	%	9.0	8.2	9.3	No Limit
ED040S: Soluble Ma	or Anions (QC Lot: 3334852	2)							
ES1405172-004	Anonymous	ED040S: Sulfate as SO4 2-	14808-79-8	10	mg/kg	50	40	0.0	0% - 20%
ED045G: Chloride by	Discrete Analyser (QC Lot	: 3334851)							
ES1405072-001	Anonymous	ED045G: Chloride	16887-00-6	10	mg/kg	25200	25300	0.5	0% - 20%



Page : 4 of 4 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Sample (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: SOIL				Method Blank (MB)		Laboratory Control Spike (LC	S) Report	
				Report	Spike	Spike Recovery (%)	Recovery	Limits (%)
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High
EA010: Conductivity (QCLot: 3334845)								
EA010: Electrical Conductivity @ 25°C		1	μS/cm	<1	1412 μS/cm	99.6	70	130
EA010: Conductivity (QCLot: 3334846)								
EA010: Electrical Conductivity @ 25°C		1	μS/cm	<1	1412 μS/cm	97.9	70	130
EA010: Conductivity (QCLot: 3334847)								
EA010: Electrical Conductivity @ 25°C		1	μS/cm	<1	1412 μS/cm	96.6	70	130
EA010: Conductivity (QCLot: 3334849)								
EA010: Electrical Conductivity @ 25°C		1	μS/cm	<1	1412 μS/cm	99.6	70	130
ED040S: Soluble Major Anions (QCLot: 3334852)								
ED040S: Sulfate as SO4 2-	14808-79-8	10	mg/kg	<10	750 mg/kg	103	84	112
ED045G: Chloride by Discrete Analyser (QCLot: 3334851)								
ED045G: Chloride	16887-00-6	10	mg/kg	<10	5000 mg/kg	99.0	79	125

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: SOIL				Matrix Spike (MS) Report				
				Spike	SpikeRecovery(%)	Recovery Limits (%)		
Laboratory sample ID	Client sample ID	Method: Compound CAS N	Number	Concentration	MS	Low	High	
ED045G: Chloride	by Discrete Analyser (QCLot: 3334851)							
ES1405072-001	Anonymous	ED045G: Chloride 16887	37-00-6	1250 mg/kg	# Not	70	130	
					Determined			

Matrix Spike (MS) and Matrix Spike Duplicate (MSD) Report

The quality control term Matrix Spike (MS) and Matrix Spike Duplicate (MSD) refers to intralaboratory split samples spiked with a representative set of target analytes. The purpose of these QC parameters are to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: SOIL			Matrix Spike (MS) and Matrix Spike Duplicate (MSD) Report							
			Spike	Spike Recovery (%)		Recovery Limits (%)		RPDs (%)		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	MSD	Low	High	Value	Control Limit
ED045G: Chloride b	by Discrete Analyser (QCLot: 3334851)									
ES1405072-001	Anonymous	ED045G: Chloride	16887-00-6	1250 mg/kg	# Not		70	130		
					Determined					



INTERPRETIVE QUALITY CONTROL REPORT

Page

: 1 of 7

Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : SMEC TESTING ALL RESULTS Contact : Client Services

Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

E-mail : enquiries@smectesting.com.au : sydney@alsglobal.com

 Telephone
 : -- Telephone
 : +61-2-8784 8555

 Facsimile
 : -- Facsimile
 : +61-2-8784 8500

Project : 19580 40300 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

C-O-C number : ---- Date Samples Received : 11-MAR-2014
Sampler : JK/DL Issue Date : 19-MAR-2014

Order number : 10920

No. of samples received : 58

Quote number : EN/025/13 No. of samples analysed : 58

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Interpretive Quality Control Report contains the following information:

- Analysis Holding Time Compliance
- Quality Control Parameter Frequency Compliance

: ----

- Brief Method Summaries
- Summary of Outliers

Site



Page : 2 of 7

Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project · 19580 40300



Analysis Holding Time Compliance

This report summarizes extraction / preparation and analysis times and compares each with recommended holding times (USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive or Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: SOIL					Evaluation	× = Holding time	breach; ✓ = Withir	n holding tim	
Method		Sample Date	Extraction / Preparation			Analysis			
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation	
EA002 : pH (Soils)									
Soil Glass Jar - Unpreserved (EA002) S15/1,	S15/2	04-MAR-2014	12-MAR-2014	11-MAR-2014	±c.	12-MAR-2014	12-MAR-2014	✓	
EA010: Conductivity									
Soil Glass Jar - Unpreserved (EA010)									
S15/1,	S15/2	04-MAR-2014	12-MAR-2014	11-MAR-2014	<u>*</u>	12-MAR-2014	09-APR-2014	✓	
Soil Glass Jar - Unpreserved (EA010)									
S133,	S158,	04-MAR-2014	12-MAR-2014	11-MAR-2014	<u>*</u>	13-MAR-2014	09-APR-2014	✓	
S179,	S154,								
S131,	S155,								
S181,	S206,								
S231,	S281,								
S282,	S307,								
S256,	S230								
Soil Glass Jar - Unpreserved (EA010)									

Page : 3 of 7

Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300



Matrix: SOIL Evaluation: **x** = Holding time breach ; ✓ = Within holding time. Method Sample Date Extraction / Preparation Analysis Container / Client Sample ID(s) Date extracted Due for extraction Evaluation Date analysed Due for analysis Evaluation **EA010: Conductivity - Continued** 06-MAR-2014 13-MAR-2014 09-APR-2014 S212, S262, 12-MAR-2014 13-MAR-2014 S287, S314, S338. S339, S340, S315, S364, S393. S392. S394, S369, S418, S469. S444, S419, S367, S342, S293. S292, S91, S140, S164, S166. S142, S41, S167, S92, S163, S118, S114, S117, S65, S63, S89, S143, S165, S38, S90, S113, S168 EA055: Moisture Content Soil Glass Jar - Unpreserved (EA055-103) 04-MAR-2014 13-MAR-2014 18-MAR-2014 S15/1. S15/2 ED040S: Soluble Sulfate by ICPAES Soil Glass Jar - Unpreserved (ED040S) 04-MAR-2014 01-APR-2014 09-APR-2014 S15/1, S15/2 12-MAR-2014 12-MAR-2014 ED045G: Chloride Discrete analyser Soil Glass Jar - Unpreserved (ED045G) 01-APR-2014 09-APR-2014 04-MAR-2014 12-MAR-2014 1 12-MAR-2014 S15/1, S15/2

Page : 4 of 7 Work Order ES1405223

Client SMEC TESTING SERVICES PTY LTD

19580 40300 Project



Quality Control Parameter Frequency Compliance

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(where) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: SOIL				Evaluation	: × = Quality Cor	ntrol frequency r	not within specification ; \checkmark = Quality Control frequency within specification.
Quality Control Sample Type		Co	unt		Rate (%)		Quality Control Specification
Analytical Methods	Method	OC	Reaular	Actual	Expected	Evaluation	
Laboratory Duplicates (DUP)							
Chloride Soluble By Discrete Analyser	ED045G	1	6	16.7	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Electrical Conductivity (1:5)	EA010	8	69	11.6	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Major Anions - Soluble	ED040S	1	10	10.0	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Moisture Content	EA055-103	2	20	10.0	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
pH (1:5)	EA002	2	12	16.7	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Laboratory Control Samples (LCS)							
Chloride Soluble By Discrete Analyser	ED045G	2	6	33.3	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Electrical Conductivity (1:5)	EA010	4	69	5.8	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Major Anions - Soluble	ED040S	1	10	10.0	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Method Blanks (MB)							
Chloride Soluble By Discrete Analyser	ED045G	1	6	16.7	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Electrical Conductivity (1:5)	EA010	4	69	5.8	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Major Anions - Soluble	ED040S	1	10	10.0	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Matrix Spikes (MS)							
Chloride Soluble By Discrete Analyser	ED045G	1	6	16.7	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Page : 5 of 7 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300

Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
pH (1:5)	EA002	SOIL	(APHA 21st ed., 4500H+) pH is determined on soil samples after a 1:5 soil/water leach. This method is
			compliant with NEPM (2013) Schedule B(3) (Method 103)
Electrical Conductivity (1:5)	EA010	SOIL	(APHA 21st ed., 2510) Conductivity is determined on soil samples using a 1:5 soil/water leach. This method is
			compliant with NEPM (2013) Schedule B(3) (Method 104)
Moisture Content	EA055-103	SOIL	A gravimetric procedure based on weight loss over a 12 hour drying period at 103-105 degrees C. This method
			is compliant with NEPM (2013) Schedule B(3) Section 7.1 and Table 1 (14 day holding time).
Major Anions - Soluble	ED040S	SOIL	In-house. Soluble Anions are determined off a 1:5 soil / water extract by ICPAES.
Chloride Soluble By Discrete Analyser	ED045G	SOIL	APHA 21st edition 4500-CI- E. The thiocyanate ion is liberated from mercuric thiocyanate through sequestration
			of mercury by the chloride ion to form non-ionised mercuric chloride.in the presence of ferric ions the librated
			thiocynate forms highly-coloured ferric thiocynate which is measured at 480 nm. Analysis is performed on a 1:5
			soil / water leachate.
Preparation Methods	Method	Matrix	Method Descriptions
1:5 solid / water leach for soluble	EN34	SOIL	10 g of soil is mixed with 50 mL of distilled water and tumbled end over end for 1 hour. Water soluble salts are
analytes			leached from the soil by the continuous suspension. Samples are settled and the water filtered off for analysis.

Page : 6 of 7

Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300

Summary of Outliers

Outliers : Quality Control Samples

The following report highlights outliers flagged in the Quality Control (QC) Report. Surrogate recovery limits are static and based on USEPA SW 846 or ALS-QWI/EN/38 (in the absence of specific USEPA limits). This report displays QC Outliers (breaches) only.

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

Matrix: SOIL

Compound Group Name	Laboratory Sample ID	Client Sample ID	Analyte	CAS Number	Data	Limits	Comment
Matrix Spike (MS) Recoveries							
ED045G: Chloride by Discrete Analyser	ES1405072-001	Anonymous	Chloride	16887-00-6	Not		MS recovery not determined,
					Determined		background level greater than or
							equal to 4x spike level.

- For all matrices, no Method Blank value outliers occur.
- For all matrices, no Duplicate outliers occur.
- For all matrices, no Laboratory Control outliers occur.

Regular Sample Surrogates

• For all regular sample matrices, no surrogate recovery outliers occur.

Outliers: Analysis Holding Time Compliance

This report displays Holding Time breaches only. Only the respective Extraction / Preparation and/or Analysis component is/are displayed.

Matrix: SOIL

Method		E	traction / Preparation			Analysis	
Container / Client Sample ID(s)		Date extracted	Due for extraction		Date analysed	Due for analysis	D
Container / Client Sample ID(s)		Date extracted	Due for extraction	Days	Date allalysed	Due for arranysis	Days
				overdue	<u> </u>		overdue
EA002 : pH (Soils)							
Soil Glass Jar - Unpreserved							
S15/1,	S15/2	12-MAR-2014	11-MAR-2014	1			
EA010: Conductivity							
Soil Glass Jar - Unpreserved							
S15/1,	S15/2	12-MAR-2014	11-MAR-2014	1			
Soil Glass Jar - Unpreserved							
S133,	S158,	12-MAR-2014	11-MAR-2014	1			
S179,	S154,						
S131,	S155,						
S181,	S206,						
S231,	S281,						
S282,	S307,						
S256,	S230						



Page : 7 of 7 Work Order : ES1405223

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580 40300

Outliers : Frequency of Quality Control Samples

The following report highlights breaches in the Frequency of Quality Control Samples.

No Quality Control Sample Frequency Outliers exist.



SYDNEY 277 Wordpark Read Shitushan ISW 2104 Rt. 20 Birk 8556 E. sandyes, sydlay Rashmon com IBWISNILE 14-15 Desra Court Boho D.D. 481 Rt. Df. 4756 0670 E. zhanshille il mandhandag Alsy Patol F. Ph. Df. 4754 3135 E. marketska shankon ogga May Patol F. F. marketska shankon og ga May Patol F. May Pat	FOR LABORATORY USE ONLY (Globa) Custony Seal Integit	Fige ice i frozbi ice pribis Oraceli, upprirecept i 11 - 145	Kandomisampe (emperating on Recent)		RECEIVED BY:	DATE/TIME:		6	Mices Where Additional Information	Comments on likely contaminant levels, dilutions, or samples requiring specific QC analysis	, A17.		***************************************							**************************************		-	
PAYDASTLE 5 Reseguin Road Vienthrosy (AVY 2304 Pr. 02 4593 9433 Examples in everations (AVY 2304 Pr. 02 4422 0515 Everadesidesidesin Roya 2541 Pr. 02 4422 0515 Everadesidesidesin Control 10 10 10 10 10 10 10 10 10 10 10 10 10	20/2/16, Promise	MBER (Circle)		SOUTH THE INC.)sey. 1	DATE/TIME:	0830		ANALYSIS REQUIRED including SUITES (NB. Suite Codes mast be listed to attract suite price) Where Metals are required, specify Total (unfiltered bothe required) or Discolused (Paper Fernance).	Proportion of the state of the		Environmental Division	Sydney	Work Order	ES1405892				Telephone: +61-2-8784 8555				Sodium Hydroxide Presoned Plastic, KG = Amber Gass Ligrasenved; AP - Airtiedifi Unpresoned Plastic, Presenced Amber Glass, N ≠ HCI presenved Plastic, HS = HCI presenved Spanialkan bodilg, SP ≈ Sodium Presenved Plastic,
HINDON 10 HEINWINGOO MEADEN OO 1440 NELECCRONICA - MEETING TOO HE MEETING TO 1440 NELECCRONICA - MEETING TOO HE MEETING TO 1711 FILE 03 GA49 5600 E SERVICE AND TOO TO 1711 MUDERE 27 Sydney Pood Nove, mellouing to 1715 NECCESTS 6735 E muser mailwate, gas on 1715	C) Standard TAT (List duo date); A Non Standard or urgent TAT (List due date);	000 8				DATETTIME				CONTRINERS 33	***************************************							MALAMA AMARA MARA MARA MARA MARA MARA MA					.S.= Scotum Hydroxide Preserved Plastic, AG = Amber Glass Urgraserved; APAirteight Unpreserved Plastic; Ilurc Preserved Ambor Glass; H = HCI preserved Plastic; HS = HCI preserved Specialish Italile; SP = Scilutio
E •	TURNAROUND REQUIREMENTS: (Standard TAT may be longer for some tests e.g. Ultra Trace Organics)	ALS QUOTE NO.:	CONTACT PHE 87562166	CHOCOLO RELINQUISHED BY:	ni(1):	DATEDIME		The state of the s	CONTAINER INFORMATION	TYPE & PRESERVATIVE (refer to codos below)	(m) / fw			**************************************								TOTAE	Weler Container Coulos: P = Urgreserros Plasico: N = Nitro Preserved Pressiro; ORC = Nitro Preserved ORC; SH = Bodism Hydroxide(CP Preserved; S = V = VOA Vial HO; Preserved; AV = Asireight Unpreserved Vial SG = Sullanc; F = Fermaldehyde Preserved; AV = Asireight Unpreserved Vial SG = Sullanc; F = Fermaldehyde Pressured Glass: Z = Zinc Adalth Preserved Bodis: E = FINTA Proserved Bodis: ST = Stanta Anno - Reserved Glass: Z = Zinc Adalth Preserved Bodis: E = FINTA Proserved Bodis: ST = Stanta Anno - Reserved Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Bodis: E = FINTA Proserved Glass: Z = Stanta Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Bodis: E = FINTA Proserved Glass: Z = Stanta Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Bodis: E = FINTA Proserved Glass: Z = Stanta Glass: Z = Anno - Reserved Glass: Z = Anno - Reserved Bodis: E = FINTA Proserved Glass: Z = Stanta Glass: Z = Anno - Reserved Glass
	DT (St.	108E1		SAMPLER MOBILE: (EDD FORMAT (or defauil):	Other addresses are listed): Ther addresses are listed):	RAGE OR DISPOSAL:		BI WATER (W)	DATE/TIME KX	1813/4-15												thin Preserved Plastin; ORC - Nitric thate Preserved; VS = VOA Vei Suff. ared Boillo: E = EDYA Preserved R.
O A SI	HELL BAC.	PURCHASE ORDER NUMBER:	inager: √ ,	J.K.	COC emailed to ALS? (YES / NO)	Email Invoice to (Will default to PM if no other addresses are listed):	COMMENTS/ SPECIAL HANDLING/STORAGE OR DISPOSAL:	THE PERSON NAMED IN COLUMN NAM	MATRIX - SOLID (S), WATER (W)	SAMPLE ID	3996	78°C	1.86		200	04	35	7,65	*	2/2	***		odas: P = Unosesanos Plastos: N = N eserved; VB = VOA Vial Sodium Dieus; Pestured Glass; Z = Z(no Acatata Pigs;
Environmental	13,	PURCHASE O	PROJECT MANAGER:	SAMPLER:	COC emailed	Email Invoice	COMMENTS/	a a	USE	LAB ID	3	٦ م	7	J.	y 5	- 0	1	_}	3 3	-	11 308	۰۵	Water Container Co Vm VOA Vial HCI Pie Fin Formaldeliyde Pr

FOR LABORATORY USE Carpets from Selection 1509 7104 Online State 150 Sears Does for the Market Control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 6000 E starsoch control of the UT 7786 E starsoch contr	CEIVED BY;		919	
HWCASTLES Roseium Road Washnook KSW 2384 No. 02 495 9433 E. Sernoles new resistant Royn 2384 No. 045 9433 E. Sernoles new resistant Royn 2341 P. C. 426 975 S. En Amelango Spain Com P. C. 426 975 S. En Amelango Spain Com P. C. 436 975 S. En Amelango Spain Com P. C. 436 975 S. E. C. C. C. L. 536 975 S. E. C. C. C. L. 536 975 S. E. C. C. C. C. S. F. C. C. C. S. S. E. C. C. C. C. S. S. E. C. C. C. S. S. E. C. C. C. S. S. E. C. C. C. C. C. C. S. S. E. C.	BY: Dall Relinguished BY: Daley IME:	ANALYSIS REQUIRED including SUITES (NB. Suite Codes must be listed to atract suite price) Where Metals are required, specify Total (unlitered bottle required) or Dissolved (field filtered bottle required).		Water Container Codos: P = Unprocessored Plastic. ORC = Nitho Prejected ORC; SN = Souten hydroxiado Preserved, SN = Souten hydroxiado Preserved, SN = NOA Vial HOI Preserved Plastic. ORC = Nitho Prejected ORC; SN = Souten hydroxiado Preserved, SN = NOA Vial Bullante Preserved, NS = NOA Vial HOI Preserved, NS = Sulfario Preserved, SN = Sulfario Preserved Organization
MACKN 73 Harbay Rack Macks 010 4740 MRI 60 4549 1677 E-mack-stack occur. MRI 60 6249 6600 E-strainblassephasicon. MRI 62 5272 6735 E-mucker florisephasicon. C Standard TAT (Liet due c. C. Standard or urgent. MRI 60 6572 6735 E-mucker milosissephasico. C Standard TAT (Liet due c. C. C. C. C. C. C. C. C. C. C. C. C. C.	Gradu DY:	TOTAL SONTAINERS		Presive: S = Sodum Hydroxia Preserved Plastic, AG = Amber (of 36 = Sultimb Preserved Plastic, H = HC) preserved Plastic
ADBLANDE 21 Barrie Prod Poseita 64 1905 Ph. 08 2339 0808 E arbeica 28 servicoum Ph. 08 2339 0809 E arbeica 28 servicoum Ph. 09 2339 0809 E arbeica 28 servicoum Ph. 00 1904 172 E carpies Distance 28 servicoum Ph. 00 1904 1730 E grassione 28 servicoum Ph. 00 1904 1730 E grassione 28 servicoum TURNAROUND REQUIREMENTS: (Standard TAT may be tonger for service 28 servicoum ALS QUOTE NO.: CONTACT PH.: Q. 20 21 C	100 miles (100 miles (TIME TO CONTAINERINFORMATION TIME TO TYPE & PRESERVATIVE (refer to codes below)	1 0 0 1 0 1 0 1 0 0 1 0 0 0 0 0 0 0 0 0	Stir: ORC = Nithe Projector ORC; SN = Sodium Hydroxize/Cot NS = VOA Net Sulfarin: Preserved: AV = Aufreight Unpreserved Vas EDIA Preserved Boiling: SY = Remits Bestim Ann = Forces = a-p.
CHAIN OF CUSTODY ALS Laborator ALS Laborator ALS Laborator LACTODY ALS Laborator LACTODY ALS Laborator LACTODY ALS Laborator LACTODY ALS L	COC emailed to ALS? (YES / NO) EDD FORMAT (or defa Email Reports to (will default to PM if no other addresses are listed): COMMENTS/ SPECIAL HANDLING/STORAGE OR DISPOSAL: ALS SAMPLE DETAILS	MATRI	184 134 130	uiner Codos: P = Umprosaved Plastic. N = Nitire Preserved Pla N-MC: Presarved: VB = VCA Vrai Sadkm Disulphate Preserved; v chydo Prosoved Glass; Z = Zho Areliala Preserved Bottle: E = E
ETTLIFE CLIENT OFFICE: PROJECT PROJECT SAMPLER:	Email R Email In COMME	USE LAB ID	527	Water Conti V = VOA Vis F = Formski



CERTIFICATE OF ANALYSIS

Work Order : **ES1405892** Page : 1 of 5

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

Telephone : +61-2-8784 8555
Facsimile : +61-2-8784 8500

Project : 19580 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Order number : 10841

 Order number
 : 10841

 C-O-C number
 : ---

 Date Samples Received
 : 19-MAR-2014

Sampler : JK Issue Date : 24-MAR-2014

No. of samples received : 14

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for

This Certificate of Analysis contains the following information:

: ----

: EN/025/13

- General Comments
- Analytical Results



Site

Quote number

release.

NATA Accredited Laboratory 825

Accredited for compliance with ISO/IEC 17025.

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

: 14

Signatories Position Accreditation Category

Ankit Joshi Inorganic Chemist Sydney Inorganics

No. of samples analysed

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 PHONE +61-2-8784 8555 Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

^ = This result is computed from individual analyte detections at or above the level of reporting

Page : 3 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

Analytical Results





Page : 4 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

Analytical Results





Page : 5 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

Analytical Results







QUALITY CONTROL REPORT

Work Order : **ES1405892** Page : 1 of 4

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

Telephone : +61-2-8784 8555
Facsimile : +61-2-8784 8500

Project : 19580 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Site : ----

 C-O-C number
 : -- Date Samples Received
 : 19-MAR-2014

 Sampler
 : JK
 Issue Date
 : 24-MAR-2014

Order number : 10841

Quote number : EN/025/13 No. of samples analysed : 14

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Quality Control Report contains the following information:

NATA Accredited

Laboratory 825

Accredited for

compliance with

ISO/IEC 17025.

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits



Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out ir compliance with procedures specified in 21 CFR Part 11.

No. of samples received

: 14

Signatories Position Accreditation Category

Ankit Joshi Inorganic Chemist Sydney Inorganics

Address 277-289 Woodpark Road Smithfield NSW Australia 2164 | PHONE +61-2-8784 8555 | Facsimile +61-2-8784 8500 Environmental Division Sydney ABN 84 009 936 029 Part of the ALS Group An ALS Limited Company



Page : 2 of 4 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

ALS

General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

= Indicates failed QC

Page : 3 of 4
Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580

Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR:-No Limit; Result between 10 and 20 times LOR:-0% - 50%; Result > 20 times LOR:-0% - 20%.

Sub-Matrix: SOIL						Laboratory E	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EA010: Conductivity	(QC Lot: 3351327)								
ES1405892-001	S284	EA010: Electrical Conductivity @ 25°C		1	μS/cm	33	33	0.0	0% - 20%
ES1405892-012	208	EA010: Electrical Conductivity @ 25°C		1	μS/cm	19	20	5.4	0% - 20%



Page : 4 of 4 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Sample (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: SOIL				Method Blank (MB)	Laboratory Control Spike (LCS) Report					
				Report	Spike	Spike Recovery (%)	Recovery Limits (%)			
Method: Compound CAS N	ımber	LOR	Unit	Result	Concentration	LCS	Low	High		
EA010: Conductivity (QCLot: 3351327)										
EA010: Electrical Conductivity @ 25°C		1	μS/cm	<1	1412 μS/cm	101	70	130		

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

• No Matrix Spike (MS) Results are required to be reported.

Matrix Spike (MS) and Matrix Spike Duplicate (MSD) Report

The quality control term Matrix Spike (MS) and Matrix Spike Duplicate (MSD) refers to intralaboratory split samples spiked with a representative set of target analytes. The purpose of these QC parameters are to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

No Matrix Spike (MS) or Matrix Spike Duplicate (MSD) Results are required to be reported.



INTERPRETIVE QUALITY CONTROL REPORT

Work Order : **ES1405892** Page : 1 of 5

Client : SMEC TESTING SERVICES PTY LTD Laboratory : Environmental Division Sydney

Contact : ALL REPORTS (ENQUIRIES) Contact : Client Services

Address : P O BOX 6989 Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

WETHERILL PARK NSW, AUSTRALIA 2164

 Telephone
 : -- Telephone
 : +61-2-8784 8555

 Facsimile
 : -- Facsimile
 : +61-2-8784 8500

Project : 19580 QC Level : NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Site : ----

 C-O-C number
 : -- Date Samples Received
 : 19-MAR-2014

 Sampler
 : JK
 Issue Date
 : 24-MAR-2014

Order number : 10841

No. of samples received : 14

Quote number : EN/025/13 No. of samples analysed : 14

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. All pages of this report have been checked and approved for release.

This Interpretive Quality Control Report contains the following information:

- Analysis Holding Time Compliance
- Quality Control Parameter Frequency Compliance
- Brief Method Summaries
- Summary of Outliers





Page : 2 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Analysis Holding Time Compliance

This report summarizes extraction / preparation and analysis times and compares each with recommended holding times (USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive <u>or</u> Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: **SOIL**Evaluation: × = Holding time breach ; ✓ = Within holding time

Matrix: SOIL					Evaluation.	× = Holding time	breach; ▼ = vvitnir	i nolaing time.
Method		Sample Date	Ex	traction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EA010: Conductivity								
Soil Glass Jar - Unpreserved (EA010)								
S284,	285,	14-MAR-2014	21-MAR-2014	21-MAR-2014	✓	21-MAR-2014	18-APR-2014	✓
286,	261,							
260,	259,							
236,	235,							
283,	283/2,							
208,	182,							
132,	130							

Page : 3 of 5 Work Order ES1405892

Client SMEC TESTING SERVICES PTY LTD

Project



Quality Control Parameter Frequency Compliance

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(where) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: SOIL				Evaluation	: × = Quality Co	ntrol frequency no	of within specification; \checkmark = Quality Control frequency within specification.
Quality Control Sample Type		С	ount		Rate (%)		Quality Control Specification
Analytical Methods	Method	OC	Reaular	Actual	Expected	Evaluation	
Laboratory Duplicates (DUP)							
Electrical Conductivity (1:5)	EA010	2	14	14.3	10.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Laboratory Control Samples (LCS)							
Electrical Conductivity (1:5)	EA010	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Method Blanks (MB)							
Electrical Conductivity (1:5)	EA010	1	14	7.1	5.0	✓	NEPM 2013 Schedule B(3) and ALS QCS3 requirement

Page : 4 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 19580



Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
Electrical Conductivity (1:5)	EA010	SOIL	(APHA 21st ed., 2510) Conductivity is determined on soil samples using a 1:5 soil/water leach. This method is compliant with NEPM (2013) Schedule B(3) (Method 104)
			compliant with the for confedence b(c) (method 10-1)
Preparation Methods	Method	Matrix	Method Descriptions
1:5 solid / water leach for soluble	EN34	SOIL	10 g of soil is mixed with 50 mL of distilled water and tumbled end over end for 1 hour. Water soluble salts are
analytes			leached from the soil by the continuous suspension. Samples are settled and the water filtered off for analysis.

Page : 5 of 5 Work Order : ES1405892

Client : SMEC TESTING SERVICES PTY LTD

Project : 1958



Summary of Outliers

Outliers: Quality Control Samples

The following report highlights outliers flagged in the Quality Control (QC) Report. Surrogate recovery limits are static and based on USEPA SW 846 or ALS-QWI/EN/38 (in the absence of specific USEPA limits). This report displays QC Outliers (breaches) only.

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

- For all matrices, no Method Blank value outliers occur.
- For all matrices, no Duplicate outliers occur.
- For all matrices, no Laboratory Control outliers occur.
- For all matrices, no Matrix Spike outliers occur.

Regular Sample Surrogates

• For all regular sample matrices, no surrogate recovery outliers occur.

Outliers: Analysis Holding Time Compliance

This report displays Holding Time breaches only. Only the respective Extraction / Preparation and/or Analysis component is/are displayed.

No Analysis Holding Time Outliers exist.

Outliers: Frequency of Quality Control Samples

The following report highlights breaches in the Frequency of Quality Control Samples.

No Quality Control Sample Frequency Outliers exist.

APPENDIX F - GEOTECHNICAL REPORT




Ingleside Precinct

Slope Risk Assessment Report

Prepared for: Department of Planning and

Environment

Date: 1 September, 2015



DOCUMENT CONTROL

Title	Ingleside Precinct S	Ingleside Precinct Slope Risk Assessment Report									
Prepared for	Department of Plan	Department of Planning and Environment									
Project Ref	30012289	30012289									
	Name Position Date										
Originator	Ben Morris	Senior Geotechnical Engineer									
Review	Simon Baldock	Senior Engineering Geologist	15/08/2014								
Approval	Project Manager										

Details of Revisions

Rev	Date	Description	WVR Number
DRAFT	15/08/2014	Draft Report	
FINAL	01/09/2015	Final Report	001

CONTACT DETAILS

SMEC Australia Pty Ltd | www.smec.com

Level 5, 20 Berry Street, North Sydney, NSW 2060

Tel: 02 9925 5555 Fax: 02 9925 5566

Representative: Name: Ben Morris

P: 02 4925 9649

E: ben.morris@smec.com

DISCLAIMER

The information within this document is and shall remain the property of SMEC Australia Pty Ltd. This report has been prepared for Department of Planning and Environment in accordance with the terms and conditions of appointment for Department of Planning and Environment. SMEC Australia Pty Ltd and its servants, employees and officers otherwise expressly disclaim responsibility to any person other than Department of Planning and Environment arising from or in connection with this Report.

To the maximum extent permitted by law, all implied warranties and conditions in relation to the services provided by SMEC and the Report are excluded unless they are expressly stated to apply in this Report.

EXECUTIVE SUMMARY

Ingleside Release Area (Ingleside Precinct) is located within the Pittwater Local Government Area and is approximately 700 hectares in size.

The Minister for Planning and Pittwater Council have agreed to undertake a Precinct Planning Process for the Ingleside Precinct to confirm development potential and to establish planning controls to enable development consistent with that potential.

As part of this process the Department of Planning and Environment wish to identify areas where slopes pose a risk to future development within the Ingleside Precinct.

SMEC has undertaken an inspection of the site where current and potential failure mechanisms were identified. A slope risk analysis of the failure mechanisms has been carried out in line with Australian Geomechanics Society method "A National Landslide Risk Management Guideline for Australia (2007)".

Previous work undertaken had delineated set zones within the Ingleside Precinct that contain slopes that may potentially pose a risk to future development; these can be grouped into ten sites.

Three main slope instability mechanisms were identified. A risk analysis was undertaken for each of the slope instability mechanisms based on three future land uses. The risk analysis framework can be found in Appendix C.

For the risk to property, the analysis was primarily based on a qualitative approach involving the estimation of the likelihood of a slope failure versus the consequence of the failure. SMEC also undertook an estimation of the risk to life in accordance with the AGS (2007). This approach is primarily based on a quantitative approach.

Based on the findings of the risk analysis it has been established that the tolerable risk to future development for the identified slope failure mechanisms has not been met, as the risk for the ten sites inspected within the precinct is classed as moderate.

The assessed risk for loss of life considering the assumed temporal probabilities are within an acceptable risk level for all three conceptualised mechanisms.

The risk levels determined should be considered where the instability mechanisms are present where development occurs within the subject area and implementation of treatment options should be considered as part of any application.

Recommendations to reduce the risk to tolerable levels may include; scaling the slope, installation of rock bolts and consideration of development location.

These risk analyses were based on high level observations. The analysis is conservative because comprehensive and detailed geological mapping of the site was not possible. As such it should be noted that there may be other active or potential slope mechanisms that were not identified. On this basis it is recommended that for any site development a specific slope stability assessment should be undertaken to assess the slope risk based on a detailed site inspection or investigation. For any development that is undertaken on slopes it is recommended that the advice presented in Appendix B "Examples of good and poor hillside construction" is followed.

TABLE OF CONTENTS

EXE	CUTIN	/E SUMMARY	3
1.	1.1	ODUCTIONProject Background	1
	1.2	Scope of Works	
2.		DESCRIPTION AND GEOLOGY	
	2.1	Site Description	
	2.2	Regional Geology and Material Description	3
3.	INSP	ECTION AND RISK ASSESSMENT METHODOLOGY	4
	3.1	General	4
	3.2	Site Inspection	4
	3.3	Hazard Identification	5
	3.4	Risk Estimation	6
	3.4.1	Risk to Property	6
	3.4.2	Risk to Life	6
4.	RISK	ASSESSMENT	8
	4.1	General	8
	4.2	Risk Acceptance Criteria	8
	4.3	Risk Assessments	9
	4.3.1	Hazard Mechanisms	
	4.3.2	Understanding Failure Modes and Triggering Factors	
	4.3.3 4.3.4	Assets at Risk Temporal Probability	
	4.3.5	Assessed Risk	
5.	DISC	USSION AND RECOMMENDATIONS	
6	CON	CLUSIONS	15
			15
APF	PENDI	CES	
APF	PENDI	X A: PHOTOS AND NOTES	
APF	PENDI	X B: EXAMPLES OF HILLSIDE PRACTICE	

APPENDIX C: RISK TO PROPERTY TERMINOLOGY

INTRODUCTION

1.1 **Project Background**

Ingleside Release Area (Ingleside Precinct) is located within the Pittwater Local Government Area and is approximately 700 hectares in size.

The majority of the Ingleside precinct is zoned RU2 Rural Landscape under the Pittwater LEP 2014. A mix of public and private land ownership exists in the Precinct. Approximately one third of the area is in State Government ownership.

The Minister for Planning and Pittwater Council have agreed to undertake a Precinct Planning Process for the Ingleside Precinct to confirm development potential and to establish planning controls to enable development consistent with that potential.

As part of this planning process a land capability, salinity and contamination assessment is required. As part of the land capability assessment slope stability assessments across the site are required; identifying areas which are, or are likely to be, prone to stability problems.

This report details the findings of SMEC's slope stability assessments undertaken for the Ingleside Precinct.

1.2 Scope of Works

Based on the original scope of works it was planned to undertake intrusive ground investigations across the area to determine the ground conditions and allow detailed slope stability assessments to be undertaken. Subsequent issues with gaining access to private property has meant that an intrusive ground investigation was not possible, therefore, SMEC have undertaken a visual slope risk analysis.

Previous work undertaken had delineated set zones within the Ingleside Precinct that contain slopes that may potentially pose a risk to property. These can be grouped into ten sites as shown on Figure 1.

The scope of work was to undertake an inspection of the ten sites to identify current and potential failure mechanisms; to inform a slope risk assessment of the categorised slope mechanisms in accordance with the Landslide Risk Management guidelines dated March 2007 by Australian Geomechanics Society (AGS, 2007).

Specifically, this role included:

- Site inspection of the slope characteristics as visible from the road side or clearly identifiable public land;
- Risk estimation (comparative analysis of likelihood of a slope failure versus consequence of the failure).
- Evaluation of the estimated (assessed) risk by comparing against acceptance criteria.

SITE DESCRIPTION AND GEOLOGY

2.1 **Site Description**

The Ingleside Precinct area is bounded by Gilwinga Drive to the north, Minkara Road and Ingleside Road to the east, Wilga Street to the south and Wirreanda Road to the west. The area is intersected in an east-west direction by Mona Vale Road.

The topography of the area consists of undulating hillsides with some steepened precipices and valleys that make up the upper reaches of the Pittwater Plateau. Based on site observations undertaken during a site visit on 6th August 2014 and GIS extracted information (Figure 3) much of the area comprises of slopes with a slope angle of less than 20°. There are some isolated areas where slopes have an angle of up to 30° and a very minor component with slope angles between 30° and 40°. A few vertical precipices were observed, up to 5m in height, some containing overhangs.

Land use across the site comprised urban sized residential blocks; large rural residential blocks; rural acreages with farming; light industrial blocks; quarries and Crown Land.

Table 1 below provides a summary of the topography, land use, and identified slope characteristics within each of the ten previously identified sites.

Appendix A presents a plan with comments and collation of photographs for each of the ten sites.

Table 1 - Summary of Site Characteristics

Site	Land Use	Topography and Slope Characteristics
1	Undeveloped land	Undulating terrain with precipices along the eastern and southern extents (Walter Road and Cicada Glen Road). Sandstone precipices up to 5m high with minor overhangs.
2	Undeveloped land and large rural residential blocks	Gently dipping valley (up to 30°) north of Cicada Glen Road between resuidential blocks. Some sandstone precipices up to 2m high.
3	Large rural residential blocks	Private property frontage restricted visibility of slope characteristics, however, it is considered to be similar to Site 2 above.
4	Large rural residential blocks, open farming areas	Gently graded slopes (up to 20°) and some minor sandstone precipices up to 2m in height adjacent to Addison Road.
5 and 6	Undeveloped land, large rural residential blocks, commercial blocks, quarry	Slopes up to 30° with sandstone precipices up to 3m in height between Mona Vale Road and Wirreanda Road, loose sandstone blocks up to 1.5m in size on upper slope adjacent to Mona Vale Road (remnants of cutting Mona Vale Road).
7	Undeveloped land	Gently graded slope from Mona Vale Road to Wirreanda Road in the order of 15°, sandstone precipices up to 2m high.

8	Undeveloped land and urban size residential blocks	Generally undulating slopes 15° to 35°, sandstone precipices up to 4m in height adjacent to Mona Vale Road, with overhangs .
9	Light industrial blocks	Unable to access or view portions of land likley to contain slopes. Considered to be similar to Site 7 above.
10	Large rural residential blocks, open farming areas	Gently graded land sloping at an angle of up to 10° towards creek crossing Powder Works Road.

2.2 **Regional Geology and Material Description**

The 1:250,000 Geological Series map S1 56-5 for Sydney indicates that the Pittwater Plateau is underlain by near-horizontally bedded sequence of sedimentary rocks of Triassic Age. The ridges, which make up the majority of the Ingleside Precinct are formed by Hawkesbury Sandstone, medium to coarse grained quartzose sandstone, very minor shale and laminite lenses, reasonably distinct bedding and well developed, typically widely spaced near-vertical joints. The slopes surrounding the plateau are underlain by an interbedded sequence of laminite, siltstone, shale and sandstone of the Narrabeen Formation. On the slopes these rocks are overlain by talus which has fallen from the sandstone uphill and by clayey colluvium derived by the weathering process of the sandstone and siltstone rock units. (MacGregor et al, 2007)

An extract of the geological map for the area is presented as Figure 2.

3. INSPECTION AND RISK ASSESSMENT METHODOLOGY

3.1 General

The Australian Geomechanics Society sub-committee first developed and published, 'Landslide Risk Assessment Procedures' in Australian Geomechanics, Volume 35, Number 1 dated March 2000. The intention of this system of slope risk classification was to establish terminology, define the general framework, provide guidance on risk analysis methods and provide sufficient information on tolerable and acceptable risks for loss of life.

Since then, several published papers have progressed the understanding of the landslide risk framework for these assessments and the procedures have subsequently been adjusted. The updated benchmark guidelines on Landslide Risk Management (LRM) are presented in the Australian Geomechanics publication, Volume 42, Number 1, dated March 2007. This issue presents a series of LRM guidelines and further understanding on the application of the risk assessments for the recommended use by all practitioners nationwide.

This investigation was undertaken in accordance with the LRM guidelines dated March 2007.

The methodology of assessing the risks at the site comprised the following steps:

- Site inspection involving a geological and geomorphologic appraisal;
- Hazard identification; and
- Risk Estimation.

3.2 Site Inspection

The site inspection involved a walkover of the ten respective sites within the Ingleside Precinct that have been previously identified as containing slopes which may potentially pose a risk to future development. The site visit was undertaken on 6th August 2014 by a senior geotechnical engineer and included a walkover survey of the areas by accessing clearly identifiable public land and road reserves. Many of the sites were entirely bounded by private property and therefore identifiable slope features was restricted to that visible from the road.

The site inspections comprised site observations and recording of surface features including geomorphological characteristics, evident failure mechanisms, erosion and indications of slope instability.

Slope characterisation was undertaken for each precipice in order to:

- identify if the slope has current or potential slope instability issues;
- classify the types of slope instability, if applicable;
- assess the physical extent of the areas affected by instability being considered, including the location, areal extent and volume involved;
- assess the likely initiating event(s), the physical characteristics of the materials involved, and the failure mechanics;
- estimate the resulting anticipated travel distance and velocity of movement; and

identify if risk from a possible slope hazards to existing or future property are acceptable.

3.3 Hazard Identification

A landslide is defined as "the movement of a mass of rock, debris or earth down a slope". Apart from ground subsidence and collapse, this definition is open to the movement of material types including rock, earth and debris downslope. The causes of landslides can be complex. However, two common factors include the occurrence of a failure of part of the soil or rock material on a slope and the resulting movement is driven by gravity. The actual motion of a landslide is subdivided into the five kinematically distinctive types of material movement including fall, topple, slide, spread, and flow. Table 2 shows the major types of landslides (AGS, 2007).

Table 2 - Major Types of Landslides

	Type of Material		
Type of Movement	Bedrock	Engineering Soils	
		Predominantly Coarse	Predominantly Fine
Falls	Rock fall	Debris fall	Earth fall
Topples	Rock topple	Debris topple	Earth topple
Rotational slide	Rock slide	Debris slide	Earth slide
Translational slide			Earth spread
Lateral spread	Rock spread	Debris spread	Earth flow
Flows	Rock flow (deep creep)	Debris flow (soil creep)	Earth flow (soil creep)
Complex	Combination of two or more principle types of movement		

The more common landslides occurring along plateaus and the surrounding slopes include falling or toppling rocks and rotational earth or debris slides.

Rock falls generally result from the under-cutting of the precipice by erosional processes, including scour from surface flows and direct rainfall. Rock topple mechanisms occur in a similar fashion to rock falls, however, the inherent jointing structure within the bedrock and root jacking may be additional factors for the instability of a precipice.

Rotational landslides typically develop in moderate to steep slopes where earth or debris becomes inundated by water and downward movement occurs. They are semi-circular in shape and exhibit a back tilted upper section and a disrupted toe section. Translational slides are similar to rotational slides but may feature downward movement of weak material along a more competent planar surface.

The frequency of landslides is generally complex and typically dependent on the interrelationship between the factors influencing the stability of the slope. Some of the common factors affecting the stability of slopes within plateau landscapes include land development, vegetation removal and changes in drainage. Some of the potential failure triggers that may affect the stability of slopes include:

- undercutting of erosion;
- prolonged rainfall with water percolating into rock mass defects causing washout of fines and reduction of rock mass strength;
- earthquakes.

One or a combination of these conditions could result in a landslide failure event

Risk Estimation 3.4

A risk assessment was undertaken for each of the categorised slope hazards. The risk assessment and management process adopted for this study in general complies with AGS (2007a). Definition of the terms used in this report with respect to the slope risk assessment and management is as per AGS (2007b).

3.4.1 Risk to Property

For risk to property, the assessment was primarily based on a qualitative approach. The assessment process for each hazard involved the following:

- Risk estimation (comparative analysis of likelihood of a slope failure versus consequence of the failure).
- Evaluation of the estimated (assessed) risk by comparing against acceptance criteria.

Risk management and control strategies are recommended where the estimated risk is beyond the acceptable/tolerable limit.

The qualitative terminology for use in assessing risk to property is presented in Appendix C.

3.4.2 Risk to Life

In accordance with the AGS 2007c Landslide Risk Management Guidelines for loss of life, the risk assessment was primarily based on a quantitative approach. The individual risk for loss of life can be calculated from:

$$R(LoL) = P(H) \times P(S:H) \times P(T:S) \times V(D:T)$$

Where:

- R (LoL) is the risk (annual probability of loss of life (death) of an individual).
- P (H) is the annual probability of the landslide.
- P (S:H) is the probability of spatial impact of the landslide impacting a building (location) taking into account the travel distance and travel direction of a given event.

- P (T:S) is the temporal spatial probability (e.g. of the building or location being occupied by the individual) given the spatial impact and allowing for the possibility of evacuation given there is warning of the landslide occurrence.
- V (D:T) is the vulnerability of the individual (probability of loss of life of the individual given the impact).

Risk management and control strategies are recommended where the estimated risk is beyond the acceptable/tolerable limit.

RISK ASSESSMENT

4.1 General

The benchmark guidelines on Landslide Risk Management (LRM) are presented in the Australian Geomechanics publication, Volume 42, Number 1, dated March 2007. As noted in Section 3.1, this document presents a series of LRM guidelines and further understanding on the application of the risk assessments recommended for use by all practitioners nationwide. This investigation was undertaken in accordance with the LRM guidelines dated March 2007.

4.2 **Risk Acceptance Criteria**

The risk acceptance criteria consider the occurrence of the potential hazards identified and evaluate the risks against a Tolerable Risk Criteria.

The AGS 2007 guidelines indicate that the regulator, with assistance from the practitioner where required, is the appropriate authority to set the standards for tolerable risks relating to perceived safety in relation to other risks and government policy. The importance of the implementation of levels of the tolerable risk should not be understated due to the wide ranging implications, both in terms of the relative risks or safety to the community and the potential economic impact on the community.

For property loss, the tolerable risk criterion may be determined by the importance level of infrastructure. The importance level is directly related to societal requirements during or immediately after extreme events. The AGS provided recommendation for tolerable risk level to property is the "low" risk level. Where treatment has been required to reduce the risk to this level, ongoing maintenance is required. Otherwise the "very low" risk level is acceptable.

For tolerable risk related to loss of life, the following risk levels are as recommended by AGS. For the purpose of this risk assessment the site may be broadly defined as a new development. The AGS risk threshold provided in Table 3 for new developments suggests the 'Tolerable Loss of Life for the person most at risk' is 1x10⁻⁵ per annum.

Table 3 - AGS Suggested Tolerable Risk (AGS, 2007).

Situation	Suggested tolerable loss of life risk for the person most at risk
Existing Slope (1) / Existing Development (2)	1x10 ⁻⁴ /annum or 0.01%
New Constructed Slope (3) / New Development (4) / Existing Landslide (5)	1x10 ⁻⁵ /annum or 0.001%

Notes:

- 1. "Existing Slopes" in this context are slopes that are not part of a recognisable landslide and have demonstrated non-failure performance over at least several seasons or events of extended adverse weather, usually being a period of at least 10 to 20 years.
- 2. "Existing Development" includes existing structures, and slopes that have been modified by cut and fill, that are not located on or part of a recognisable landslide and have demonstrated non-failure

performance over at least several seasons or events of extended adverse weather, usually being a period of at least 10 to 20 years.

- 3. "New Constructed Slope" includes any change to existing slopes by cut or fill or changes to existing slopes by new stabilisation works (including replacement of existing retaining walls or replacement of existing stabilisation measures, such as rock bolts or catch fences).
- 4. "New Development" includes any new structure or change to an existing slope or structure. Where changes to an existing structure or slope result in any cut or fill of less than 1.0m vertical height from the toe to the crest and this change does not increase the risk, then the Existing Slope / Existing Structure criterion may be adopted. Where changes to an existing structure do not increase the building footprint or do not result in an overall change in footing loads, then the Existing Development criterion may be adopted.
- 5. "Existing Landslides" have been considered likely to require remedial works and hence would become a New Constructed Slope and acquire the lower risk. Even where remedial works are not required per se, it would be a reasonable expectation of the public for a known landslide to be assessed against the lower risk category as a matter of "public safety".

4.3 Risk Assessments

As noted in Section 3.2, these risk assessments were based on high level observations made during a limited site visit by a senior geotechnical engineer. The assessments are conservative because comprehensive and detailed geological mapping of the site was not possible under the prescribed scope of work and the limitations of being able to access all areas of the sites. Any future detailed evaluations of particular sites may change the quantification of the hazard risk.

The data collected for this report has enabled the definition and characterisation of slope instability hazards.

4.3.1 Hazard Mechanisms

Photographs showing various site locations where representative slope mechanisms were identified are provided in Appendix A.

During the site inspection the following slope failure mechanisms were identified and conceptualised. For each of these failure mechanisms a risk assessment was carried out.

4.3.1.1 Mechanism 1 (M1): Block Falls up to 1m from Precipices up to 2m in Height

Mobilisation of block falls to 1m are considered to arise from the precipices with jointed sandstone units up to 2m in height and influenced by exposure conditions to wind and rain.

4.3.1.2 Mechanism 2 (M2): Block Falls up to 1m from Precipices up to 5m in Height

Mobilisation of block falls to 1m are considered to arise from the precipices with jointed sandstone units up to 5m in height and influenced by exposure conditions to wind and rain.

4.3.1.3 Mechanism 3 (M3): Block Falls up to 2m from Overhangs

Mobilisation of block falls from overhangs are considered to arise from the precipices with major overhangs and influenced by exposure to wind and rain.

4.3.2 **Understanding Failure Modes and Triggering Factors**

In view of the site observations, measurements and experience, a conceptual understanding of the failure mechanisms and contributing factors was developed to comprehend its vulnerability and associated risks. The main points describing this phenomenon and triggering factors are summarised below:

- The slopes are directly exposed to weathering processes, wind, rain and atmospheric exposure. This causes the rock mass and joints in the rock to be weakened and blocks are loosened.
- The largely absent sub-vertical joint sets lead to the mechanisms being more stable than would be in a highly fractures and frequently jointed rock mass.

4.3.3 Assets at Risk

As this risk assessment is a high level assessment for future development it is considered that the assets at risk would be newly constructed dwellings or other buildings, roads or areas of congregation of persons such as parks and other recreation areas.

4.3.4 Temporal Probability

The following assumptions have been made with respect to temporal probability. Alteration of these assumptions will inevitably alter the magnitude of risk.

Table 4 - Adopted Temporal Probability

Aspect of Assessment	Assumed Temporal Probability P(T:S)
Residential Areas	It is assumed that people would be present below the slope within residential areas on an average of 30mins/day. This would include being in an area of vulnerability to the mechanism and may include being inside the dwelling.
Roads	For the suburban roads it is assumed that the temporary probability would be 0.001*.
Recreational Areas	It is assumed that people would be present below the slope within recreational areas on an average of 30mins/day.

Notes: *Allocation of temporal probability is based on the Temporal Probability Rating Definitions adopted by RMS for Slope Risk Analysis, Table 11 RMS Guide to Slope Risk Analysis Version 4 (RMS 2011).

With regards to the above temporal probabilities, common usage has been assumed. Allowance for more frequent presence for specific situations, such as persons seeking refuge in adverse weather conditions, has not been considered and therefore re-assessment of the specific land use at the slope is to be undertaken prior to application of these probabilities.

4.3.5 Assessed Risk

Table 5 and 6 below show the assessed risk to property and the risk of loss of life associated with conceptualised failure mechanisms.

Table 5 – Summary of Risk Assessment – Risk to Property

		M1: Block Falls (1.0m) from Precipices up to 2m in Height	M2: Block Falls (1.0m) from Precipices up to 5m in Height	M3: Block Falls (up to 2m) from Overhangs	
Dechability	Descriptor	Likely	Possible	Possible	
Probability P(H)	Level	В	С	С	
	Rate	0.01	0.001	0.001	
Consequence	Level	Minor	Minor	Medium	
to Building	Descriptor	4	4	3	
Risk To Property		Moderate	Moderate	Moderate	

Table 6 – Summary of Risk Assessment - Level of Risk for Loss of Life

		M1: Block Falls (1.0m) from Precipices up to 2m in Height	M2: Block Falls (1.0m) from Precipices up to 5m in Height	M3: Block Falls (up to 2m) from Overhangs		
Probability P(H)	0.01	0.001			
Probability of Spatial Impact (P _{S:H})		0.02 (1.0m block on 50m long section of slope)	0.04 (2.0m length failure over 25m section of slope)			
Vulnerability of an Individual (P _{D:T})		1.0 (person killed) 0.1 (person injured)				
Drobobility	Residential Areas	0.021				
Probability of Temporal	Roads	0.001				
Impact (P _{T:S})	Recreational Areas	0.021				
	Residential Areas	Death 4.2x10 ⁻⁶ Injury 4.2x10 ⁻⁷	Death 4.2x10 ⁻⁷ Injury 4.2x10 ⁻⁸	Death 8.4x10 ⁻⁷ Injury 8.4x10 ⁻⁸		
Risk (loss of life)	Roads	Death 2.0x10 ⁻⁷ Injury 2.0x10 ⁻⁸	Death 2.0x10 ⁻⁸ Injury 2.0x10 ⁻⁹	Death 4.0x10 ⁻⁸ Injury 4.0x10 ⁻⁹		
	Recreational Areas	Death 4.2x10 ⁻⁶ Injury 4.2x10 ⁻⁷	Death 4.2x10 ⁻⁷ Injury 4.2x10 ⁻⁸	Death 8.4x10 ⁻⁷ Injury 8.4x10 ⁻⁸		

According to the AGS suggested tolerable levels for loss of property for the above conceptualised mechanisms do not yield acceptable levels. Noted implications in the AGS guideline is that for risk to loss of property of "moderate" levels "may be tolerated in certain circumstances (subject to regulator's approval) but requires investigation, planning and implementation of treatment options to reduce the risk to Low. Treatment options to reduce to Low risk should be implemented as soon as practicable."

Based on the AGS suggested tolerable levels for loss of life outlined in Table 3 and considering the assumed temporal probability an acceptable risk level is obtained for all conceptualised mechanisms.

5. DISCUSSION AND RECOMMENDATIONS

As previously stated the original scope of works allowed for intrusive ground investigations to be undertaken across the Ingleside Precinct to determine ground conditions for slope stability assessments.

As access to private property was not possible, SMEC, have undertaken a visual slope risk analysis in line with AGS (2007) guidelines. These slope risk analysis involved the inspection of the slope characteristics at ten sites from accessible areas, generally either from the roadside or clearly identifiable public land.

The data collected during the site visit by a senior geotechnical engineer has enabled the definition and characterisation of slope instability mechanisms at the ten sites. Three main mechanisms were identified. These are listed below:

- Mechanism 1: Block Falls up to 1m from precipices up to 2m in Height
- Mechanism 2: Block Falls up to 1m from precipices up to 5m in Height
- Mechanism 3: Block Falls up to 2m from overhangs

SMEC considered three future uses for any land development and made assumptions with regards to the temporal probability for these uses (detailed in Section 4.3.4). The three land uses considered are:

- Residential Areas
- Roads
- Recreational Areas

A risk assessment was undertaken for each of the slope instability mechanisms. For risk to property, the assessment was primarily based on a qualitative approach involving the estimation of the likelihood of a slope failure versus the consequence of the failure.

In addition to the risk to property SMEC also undertook an estimation of the risk to life in accordance with the AGS (2007). This approach is primarily based on a quantitative approach.

Based on the findings of the risk assessment, as presented in Section 4.3.5, it has been established that the tolerable risk to future development for the identified failure mechanisms has not been met as the risk is classed as moderate.

It is noted that in the AGS guidelines that for risk to loss of property of "moderate" levels "may be tolerated in certain circumstances (subject to regulator's approval) but requires investigation, planning and implementation of treatment options to reduce the risk to Low. Treatment options to reduce to Low risk should be implemented as soon as practicable."

The assessed risk for loss of life considering the assumed temporal probabilities are within an acceptable risk level for all three conceptualised mechanisms.

The risk levels determined should be considered where the instability mechanisms are present within the subject area and implementation of treatment options should be considered as part of any application.

A summary of stabilisation recommendations for reducing the risk levels is presented in Table 7 below.

Table 7 – Summary of Stabilisation Recommendations

Recommendation	Description
Scaling	Removal of rock blocks/mass can be coupled with site earthworks process
Rock Bolts	Rock bolts are frequently used for stabilisation applications of potentially unstable rock blocks due to their relative low cost and fast installation process
Appropriateness of Building	Location of proposed buildings, and suitability of building to withstand a dislodged block may be considered to accept a high level of risk or to derive a tolerable risk level

As noted in Section 3.2, these risk assessments were based on high level observations made during a limited site visit by a senior geotechnical engineer. The assessments are conservative because comprehensive and detailed geological mapping of the site was not possible under the prescribed scope of work and the limitations of being able to access all areas of the sites.

It should be noted that due to the high level nature of the site inspection there may be other active or potential slope mechanisms that were not identified and conceptualised. Any future detailed evaluations of particular sites may change the quantification of the hazard risk.

On this basis it is recommended that for any site development a specific slope stability assessment should be undertaken to assess the slope risk based on a detailed site inspection or investigation. For any development that is undertaken on slopes it is recommended that the advice presented in Appendix B "Examples of good and poor hillside construction" is followed.

6. CONCLUSIONS

SMEC have undertaken a site visit and a subsequent slope risk analysis in line with AGS (2007) guidelines for ten sites within the Ingleside Precinct.

Three main slope instability mechanisms were identified. A risk analysis was undertaken for each of the slope instability mechanisms based on three future land uses.

For the risk to property, the analysis was primarily based on a qualitative approach involving the estimation of the likelihood of a slope failure versus the consequence of the failure. SMEC also undertook an estimation of the risk to life in accordance with the AGS (2007). This approach is primarily based on a quantitative approach.

Based on the findings of the risk analysis it has been established that the tolerable risk to property for the identified failure mechanisms has not been met, as the risk is classed as moderate.

The assessed risk for loss of life considering the assumed temporal probabilities are within an acceptable risk level for all three conceptualised mechanisms.

AGS guidelines state that for risk to loss of property "moderate" levels "may be tolerated in certain circumstances (subject to regulator's approval) but requires investigation, planning and implementation of treatment options to reduce the risk to Low. Treatment options to reduce to Low risk should be implemented as soon as practicable."

The risk levels determined should be considered where the instability mechanisms are present where development occurs within the subject area and implementation of treatment options should be considered as part of any future application. Recommendations to reduce the risk to tolerable levels may include; scaling the slope, installation of rock bolts and consideration of development location.


These risk analyses were based on high level observations. The analysis is conservative because comprehensive and detailed geological mapping of the site was not possible. As such it should be noted that there may be other active or potential slope mechanisms that were not identified. In addition no details on proposed future development were available. The location and proximity of any future development to an identified slope failure mechanism will potentially alter the calculated risk level.


On this basis it is recommended that for any site development a specific slope stability assessment should be undertaken to assess the slope risk based on a detailed site inspection or investigation. For any development that is undertaken on slopes it is recommended that the advice presented in Appendix B "Examples of good and poor hillside construction" is followed.


REFERENCES

- AGS (2007a). "Guideline for landslide susceptibility, hazard and risk zoning for land use planning", Australian Geomechanics, Vol 42, No. 1, March 2007.
- AGS (2007b). "Commentary on guideline for landslide susceptibility, hazard and risk zoning for land use planning", Australian Geomechanics, Vol 42, No. 1, March 2007.
- AGS (2007c). "Practice note guidelines for landslide risk management", Australian Geomechanics, Vol 42, No. 1, March 2007.
- AGS (2007d). "Commentary on practice note guidelines for landslide risk management", Australian Geomechanics, Vol 42, No. 1, March 2007.
- AGS (2007e). "Australian GeoGuides for slope management and maintenance", Australian Geomechanics, Vol 42, No. 1, March 2007.
- DM (1966). "1:250,000 Geological Series Sheets S1 56-5", Department of Mines, Third Edition, 1966.
- MacGregor et al (2007). "Assessment of Landslide Likelihood in the Pttwater Local Government Area", Australian Geomechanics, Vol 42, No. 1, March 2007.
- RMS (2011). "RMS Guide to Slope Risk Analysis", 2011.

FIGURES







APPENDIX A: PHOTOGRAPHS AND NOTES



Figure 1: Site 1



Figure 2: Site 1



Figure 3: Site 1



Figure 4: Site 1



Figure 5: Site 2



Figure 6: Site 2



Figure 7: Site 2



Figure 8: Site 2



Figure 9: Site 2



Figure 10: Site 3



Figure 11: Site 3



Figure 12: Site 4



Figure 13: Site 4



Figure 14: Site 4



Figure 15: Site 6



Figure 16: Site 6



Figure 17: Site 6



Figure 18: Site 6



Figure 19: Site 6



Figure 20: Site 6




Figure 21: Site 6




Figure 22: Site 7



Figure 23: Site 7



Figure 24: Site 8



Figure 25: Site 8



Figure 26: Site 8



Figure 27: Site 8



Figure 28: Site 8



Figure 29: Site 10







Figure 30: Site 10



APPENDIX B: EXAMPLES OF HILLSIDE PRACTICE



EXAMPLES OF POOR HILLSIDE PRACTICE



APPENDIX C: RISK TO PROPERTY TERMINOLOGY

PRACTICE NOTE GUIDELINES FOR LANDSLIDE RISK MANAGEMENT 2007

APPENDIX C: LANDSLIDE RISK ASSESSMENT

QUALITATIVE TERMINOLOGY FOR USE IN ASSESSING RISK TO PROPERTY

QUALITATIVE MEASURES OF LIKELIHOOD

Approximate A Indicative Value	nnual Probability Notional Boundary	Implied Indicative Landslide Recurrence Interval		Description	Descriptor	Level
10-1	5x10 ⁻²	10 years		The event is expected to occur over the design life.	ALMOST CERTAIN	A
10 ⁻²	5x10 ⁻³	100 years	20 years 200 years	The event will probably occur under adverse conditions over the design life.	LIKELY	В
10 ⁻³		1000 years	200 years 2000 years	The event could occur under adverse conditions over the design life.	POSSIBLE	C
10 ⁻⁴	5x10 ⁻⁴	10,000 years	20,000 years	The event might occur under very adverse circumstances over the design life.	UNLIKELY	D
10 ⁻⁵	$5x10^{-5}$ $5x10^{-6}$	100,000 years		The event is conceivable but only under exceptional circumstances over the design life.	RARE	Е
10 ⁻⁶	3810	1,000,000 years 200,000 years		The event is inconceivable or fanciful over the design life.	BARELY CREDIBLE	F

Note: (1) The table should be used from left to right; use Approximate Annual Probability or Description to assign Descriptor, not *vice versa*.

QUALITATIVE MEASURES OF CONSEQUENCES TO PROPERTY

Approximate Cost of Damage		Description	Descriptor	T
Indicative Value	Notional Boundary	Description	Descriptor	Level
200%	1000/	Structure(s) completely destroyed and/or large scale damage requiring major engineering works for stabilisation. Could cause at least one adjacent property major consequence damage.	CATASTROPHIC	1
60%	100%	Extensive damage to most of structure, and/or extending beyond site boundaries requiring significant stabilisation works. Could cause at least one adjacent property medium consequence damage.	MAJOR	2
20%	40% 10%	Moderate damage to some of structure, and/or significant part of site requiring large stabilisation works. Could cause at least one adjacent property minor consequence damage.	MEDIUM	3
5%	1%	Limited damage to part of structure, and/or part of site requiring some reinstatement stabilisation works.	MINOR	4
0.5%	170	Little damage. (Note for high probability event (Almost Certain), this category may be subdivided at a notional boundary of 0.1%. See Risk Matrix.)	INSIGNIFICANT	5

Notes:

- (2) The Approximate Cost of Damage is expressed as a percentage of market value, being the cost of the improved value of the unaffected property which includes the land plus the unaffected structures.
- (3) The Approximate Cost is to be an estimate of the direct cost of the damage, such as the cost of reinstatement of the damaged portion of the property (land plus structures), stabilisation works required to render the site to tolerable risk level for the landslide which has occurred and professional design fees, and consequential costs such as legal fees, temporary accommodation. It does not include additional stabilisation works to address other landslides which may affect the property.
- (4) The table should be used from left to right; use Approximate Cost of Damage or Description to assign Descriptor, not vice versa

PRACTICE NOTE GUIDELINES FOR LANDSLIDE RISK MANAGEMENT 2007

APPENDIX C: - QUALITATIVE TERMINOLOGY FOR USE IN ASSESSING RISK TO PROPERTY (CONTINUED)

QUALITATIVE RISK ANALYSIS MATRIX – LEVEL OF RISK TO PROPERTY

LIKELIHOOD		CONSEQUENCES TO PROPERTY (With Indicative Approximate Cost of Damage)				
	Indicative Value of Approximate Annual Probability	1: CATASTROPHIC 200%	2: MAJOR 60%	3: MEDIUM 20%	4: MINOR 5%	5: INSIGNIFICANT 0.5%
A – ALMOST CERTAIN	10 ⁻¹	VH	VH	VH	Н	M or L (5)
B - LIKELY	10 ⁻²	VH	VH	Н	M	L
C - POSSIBLE	10 ⁻³	VH	Н	M	M	VL
D - UNLIKELY	10 ⁻⁴	Н	M	L	L	VL
E - RARE	10 ⁻⁵	M	L	L	VL	VL
F - BARELY CREDIBLE	10 ⁻⁶	L	VL	VL	VL	VL

Notes: (5

- For Cell A5, may be subdivided such that a consequence of less than 0.1% is Low Risk.
- (6) When considering a risk assessment it must be clearly stated whether it is for existing conditions or with risk control measures which may not be implemented at the current time.

RISK LEVEL IMPLICATIONS

	Risk Level	Example Implications (7)		
VH	VERY HIGH RISK	Unacceptable without treatment. Extensive detailed investigation and research, planning and implementation of treatment options essential to reduce risk to Low; may be too expensive and not practical. Work likely to cost more than value of the property.		
Н	HIGH RISK	Unacceptable without treatment. Detailed investigation, planning and implementation of treatment options required to reduce risk to Low. Work would cost a substantial sum in relation to the value of the property.		
M	MODERATE RISK	May be tolerated in certain circumstances (subject to regulator's approval) but requires investigation, planning and implementation of treatment options to reduce the risk to Low. Treatment options to reduce to Low risk should be implemented as soon as practicable.		
L	LOW RISK	Usually acceptable to regulators. Where treatment has been required to reduce the risk to this level, ongoing maintenance is required.		
VL	VERY LOW RISK	Acceptable. Manage by normal slope maintenance procedures.		

Note: (7) The implications for a particular situation are to be determined by all parties to the risk assessment and may depend on the nature of the property at risk; these are only given as a general guide.