FLOS

■ 09.8310.DV Glossy Sage

Oblique Qi NEW

Designed by Vincent Van Duysen, 2020

LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Base with Qi compatible wireless recharging system for mobile devices and wireless recharging cases for compatible devices. Driver input: 12 V

Are you a professional and your project needs consulting and support?	BOOK AN APPOINTMENT

ø120
350
ø155

Main specifications

Mounting	Table
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	8
System power (W)	28
Source flux (lm)	754
System flux (lm)	479

Physical

Colour	Glossy Sage
Orientation	Fixed
Net weight (kg)	0.75
IP internal	20
IP external	20

Download

Mounting instructions	↓ PDF

Photometric Files

LDT / IES	↓ ZIP

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP
🔒Bim	↓ ZIP

CE   UKCA   GWT 850°   IP 20

Schematic light drawing

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	229	2.18
2	57	4.36
3	25	6.54
4	14	8.72
5	9	10.90

Luminous flux luminaire
479 lm

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46

Electrical

Insulation class	III
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable
Emergency	No
Induction recharge QI	Yes
Charging socket/connector	USB-C