

New RallySafe Information

During competitors' final preparations for this year, you need to be aware of a change with the RallySafe units we will use all year. In previous years, you have connected three antennas to the RallySafe unit;

- Yellow Roof Antenna (Satellite)
- Green Roof Antenna (GPS)
- Blue - Internal Magnet Antenna (WiFi)

This year, RallySafe units need to connect the second blue antenna connection from the external roof antenna.



Do

- Connect RallySafe to permanent fused power (un-switched) so the unit continues transmitting, bypassing the safety isolation switch. (Power consumption is less than .003 Amp in sleep)
- Ensure the antenna is mounted with line-of-sight to the sky.
- Ensure you have the three roof antenna AND the internal blue WiFi antenna connected
- Mount the RallySafe unit so it is clearly visible to both driver and co-driver. Aim that both occupants can reach the unit and report an emergency if needed.
- Consider purchasing and installing the new RallySafe Remote LED Display and buttons available now.
- <https://shop.statusas.com/shop/category/remote-led-display/>

Do Not

- Cover the antenna in paint or vehicle wrap.
- Power the unit via the accessories power circuit.

SAS Manuals

https://statustech.sharepoint.com/:f:/s/SASManuals/ErAYiphTAFJGrKc-69_IL4sBa1K6v3uhulGq7aDYjHgorA?e=W0i7Di

SAS Installation Video

<https://www.youtube.com/watch?v=30uqktNtMRE>

If you need to purchase a new antenna (or power cable), please contact the RallySafe team in Tasmania.

<https://shop.statusas.com/>