MONDOLUX[™]





Introduction

Introducing Cosmos, a highbay with switchable power and CCT, making it a versatile fitting to suit various applications such as; warehouses, logistics centres, production workshops, storage facilities, commercial spaces, and retail stores. Cosmos offers a practical and great value lighting solution with flexible options.



Key Features:


- Lumen Efficiency: 150lm/W
- System Power: 80W/100W/120W/150W
- Beam Angles: 60°/90°/120°
- Aluminium Housing
- PC Optical Lens
- IP65 & IK08
- L70 >65,000 hours
- Accessories: PC/Al. Reflectors, Adj. Mounting Brackets & Plug-in Motion & Microwave Sensors
- CCT: 3000K/4000K/5000K
- CRI: >80



Features



CCT Switch






Power Switch





Dimensions





Accessories - Standard



Optic Lens
High transmittance
PC materials, UV test approved.



Aluminium Reflector Various beam angles, anti glare effect, black/ silver colour options.



PC Reflector
90°PC reflector with lid.



Plug-in Motion Sensor 12V DC input, IP65 rating, max detect height is 15m.

Accessories - Optional



Safety Chain 304 stainless steel, available in 0.25m, 1m, 1.5m and 5m long.



Adjustable Bracket ±30°/±45°/±60°, SPCC materials with outdoor powder coating.



PIR Sensor 12V DC input, IP65 rating, max detect height is 15m.



Remote ControlFor motion sensor and PIR sensor.

Code Information

Family Code +	Product +	Installation Type +	Colour +	Beam Angle +	CCT +		Dimming Type +
MH = Mondolux Highbay	60 = Cosmos	SU = Suspension	2 = Black	W = 60°	830 = 3000K	80W	O = Non-Dimmable
				F = 90°	840 = 4000K	100W	
				L = 120°	850 = 5000K	120W	
						150W	

Example: MH60SU2W-840-080W0

Mondolux Highbay Cosmos Suspension Black 60° 4000K 80W Non-Dimmable

MONDOLUX

- 1300 601 931
- **(E)** contact@mondolux.com
- w mondolux.com

Distributed by



w aglosystems.com.au