


## Contoured execution



- Trim Ø150mm, cut-out Ø135mm
- Wide range of beamspreads: 15°, 24°, 36°, 60°
- High light output ratio of >85%.
- Available in 11W, 17W, 25W, 32W

## Product info

System Lumen Range	850lm — 2400lm
System Power	13W, 19W, 28W, 36W
Forward Current	350mA, 500mA, 700mA, 900mA
System Efficacy Range	65lm/W to 67lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable
Accessories	Without Accessory
Warranty	5 years (T&C apply)
Custom Dimming Type	Available on request



## Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid
Beam Angle	15°, 24°, 38°, 55°
Light Output Ratio (LOR)	>85%
Custom Colour Temperature (CCT)	Available on request

## Compliance



## Packaging

Box Weight	1.2kg
Box Dimensions L x W x H mm	180 mm x 140 mm x 140 mm
Boxes per Carton	18
Carton Dimensions L x W x H mm	470 mm x 310 mm x 470 mm