# Albi Mini Deep Baffle Pro Fixed


DOWNLIGHT | MD30FR\_DB





# Installation Manual

Albi Mini Deep Baffle Pro Fixed 8W / 12W



\*allowed tolerance in mm

Albi Mini Deep Baffle Pro Fixed 20W



\*allowed tolerance in mm

### Albi Mini Deep Baffle Pro Fixed Downlight MD30FR\_DB Installation Manual

#### Warnings

- The safety and compliance of this fitting are not assured unless the following instructions are adhered to. Please retain these instructions for future reference.
- Always turn the mains OFF prior to installation.
- The luminaire is EN 60598-1:2015/A1:2018 compliant and Installation must be carried out by a licensed electrician.
- **Risk of Electric Shock:** Prior to installation or maintenance, disconnect the fitting from power supply and other control wiring. Faulty cables and wiring need to be replaced by manufacturer only.
- **Risk of Burns:** When in use, the fitting's surface may reach high temperatures and can cause skin burns. It is recommended to install the fitting out of reach to avoid any physical contact.
- It is recommended to always wear safety glasses and gloves during installation.
- For safety reasons please keep children away from installation site.
- Please follow below instructions for disposal in accordance with the local E-Waste or WEEE (Waste Electrical and Electronic Equipment):
- Fittings cannot be disposed alongside other household waste.
- Remove the lamp/ battery for decommissioning (if applicable)
- Send them to nearest E-Waste or WEEE collection center.

For further inquiries, please contact Mondolux at https://www.mondolux.com.au

# Albi Mini Deep Baffle Pro Fixed

DOWNLIGHT | MD30FR\_DB



### **Important Notes**

- This fitting requires 220-240V AC/50Hz power input to the driver.
- Do not interchange any parts of this fitting.
- A minimum distance of 75mm is required around the fitting to allow for air ventlation.
- Allow a minimum distance between fitting and illuminated subject of 800mm.
- Do not touch fitting when in use.
- Do not cover with any form of heat proof material.
- Do not install any inductive loads such as exhaust fans etc. within the same lighting circuit of the current fitting. Issues caused by such connections will not be covered under our warranty policy.

If you have any questions about the installation of this product, please contact Mondolux.

### **Installation Steps**

- 1. Ensure the mains power is turned off. 2. Cut required holes in ceiling. Ensure minimum space requirements between fitting and driver. See picture 1.
- 3. Pass the driver power supply wires through the cutout and plug into mains socket 4. Connect the driver to the light fitting using the quick connector. See picture 2. 5. Mount fixture into ceiling and secure using the spring loaded clamps. See picture 3 and 4.
- 6. Installation is complete. See picture 5.

