

Esen Eco

More for less

- Luminous flux of 900lm with 90lm/W efficacy
- Smooth dimming down to 5%
- Amazing low-glare attributes with UGR<19
- Compatible with a wide range of phase-cut dimmers
- Trim finish:




Introducing Esen Eco, our modularly designed downlight that offers impressive glare control. It's deep design provides a perfect balance of light output and reduced glare, delivering a comfortable visual experience. The improved aluminium heatsink ensures ideal thermal management for maximum performance. Esen Eco offers great value for most common directional lighting applications.



Available Options:

- System Power: 10W
- Beam Angle: 36°, 60°
- Dimming Type: Phase-Cut, DALI available on request
- Body/Trim Finish: White, Black
- Colour Temperature (CCT): 3000K, 4000K
- Colour Rendering Index (CRI): CRI80



Product Codes

MD02FR2M-830-023A2

MD02FR2M-840-023A2

MD02FR2W-830-023A2

MD02FR2W-840-023A2

MD02FR1M-830-023A2

MD02FR1M-840-023A2

MD02FR1W-830-023A2

MD02FR1W-840-023A2

Code Information

Family Code +	Product +	Installation Type +	Colour +	Beam Angle +	CCT +	Dimming Type +
MD = Mondolux Downlight	02 = Esen Eco	FR = Fixed Recessed	1 = White	M = 36°	830 = 3000K	A0 = Non-Dimmable*
			2 = Black	W = 60°	840 = 4000K	A2 = Phase-Cut Dimmable
						A3 = DALI Dimmable*

Example: MD02FR2M-830-023A2

Mondolux Downlight, Esen Eco, Fixed Recessed, Black, 36°, 3000K, Phase-Cut Dimmable

Example: MD02FR1W-840-023A2

Mondolux Downlight, Esen Eco, Fixed Recessed, White, 60° 4000K, Phase-Cut Dimmable

*Not standard with this fitting and available on special request only

T 1300 601 931

E sales@mondolux.com.au