



Sheet

Product Specification

Centerfire Pistol & Revolver

LOAD NUMBER: BC9NT3

CALIBER: 9 mm Luger

CASE: Brass (Copper Alloy No 260)

BULLET: 100 Gr. Frangible Copper-Tin

PRIMER: Federal No. 205 TMF (staked)

Primer Mix is Toxic Metal Free

Operating Range (-40 degrees to +125 degrees F)

PRIMER SEALANT: Loctite Primer Sealant

CASE MOUTH SEALANT: Water resistant.

CASE KNURL: No

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate non-toxic cartridge designation.

ACCURACY: Maximum average extreme spread of 3.5" at 50 yards, using a Mann Rest Test System.

BALLISTIC MATCH: The mean center of the group is 2" or less from the mean center of the group of service ammo at 25 yards.

INSTRUMENTAL VELOCITY: 1225 +/- 25 FPS using a 4.00" SAAMI standard test barrel.

MUZZLE ENERGY: 333 Ft-Lbs

CHAMBER PRESSURE: Piezotronic maximum average per 10 rounds – 35,000 PSI

BULLET PULL: Minimum individual 80 Lbs

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured.

PACKAGE: 50 rounds/carton
20 cartons /case

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
(800)322-2342, ext. 3822 or 2370