



Product Specification Sheet

LOAD NUMBER: LE308TT2

CALIBER: 308 Win.

CASE: Nickel plated brass, Copper Alloy No. 260

PROJECTILE: 168 gr. Tactical Bonded Tip

PRIMER: Federal GM210M

OPERATING RANGE: -40 °F to 125 °F

PRIMER SEALANT: Blue lacquer

CASE MOUTH SEALANT: None

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and year of manufacture

ACCURACY: Three, 5-round groups with maximum average extreme spread of 2.1 in. and a total 15-round group size of 2.5 in. at 200 yards using a Mann Rest Test System

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303

INSTRUMENTAL VELOCITY: Muzzle velocity = 2650 ± 50 fps

MUZZLE ENERGY: 2620 ft.-lbs.

CHAMBER PRESSURE: Piezotronic maximum average per 10 rounds = 60,000 psi maximum

BULLET PULL/PUSH: Minimum individual 60 lbs.

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

PACKAGE: 20 rounds per carton, 10 cartons per case