



Product Specification Sheet

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303

LOAD NUMBER: T308T

CALIBER: .308 Win.

CASE: Brass (Copper Alloy No. 260)

BULLET: 168 gr. Tactical Tip

PRIMER: Nickel Plated Federal GM210M
Operating Range (-40° F to 125° F)

PRIMER SEALANT: Water resistant
lacquer

CASE MOUTH SEALANT: None

CASE KNURL: None

HEADSTAMP: Each loaded cartridge
shall be headstamped with the
manufacturer's symbol and appropriate
cartridge designation

ACCURACY: Two 10-round groups with
maximum average extreme spread of 1.50"
at 200 yards

INSTRUMENTAL VELOCITY: 2650 ±
50 fps using a 24" SAAMI standard test
barrel

MUZZLE ENERGY: 2620 Ft-lbs

CHAMBER PRESSURE: Piezotronic
maximum average per 10 rounds – 60,000
psi

BULLET PULL: Minimum individual 40
Lbs.

PROPELLANT DETECTION: 100%
mechanical and/or electrical detection of
propellant levels within the cartridge

VISUAL INSPECTION: 100% visual
inspection of finished cartridges prior to
packaging

LOT IDENTIFICATION: Each lot of
ammunition is assigned a unique
identification number to include the day,
month and year of manufacture and
assembly line on which manufactured