



Product Specification Sheet
Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303

LOAD NUMBER: T65CRDTTMK1

CALIBER: 6.5mm Creedmoor

CASE: Brass (Copper Alloy No. 260)

BULLET: 140 Gr. Sierra Tactical Tipped Match

PRIMER: Federal No. GM205M Primer Mix contains Basic Lead Styphnate.

OPERATING RANGE: (-40° F to 125° F).

PRIMER SEALANT: Water Resistant Anaerobic Sealant

CASE MOUTH SEALANT: None

CASE KNURL: None

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation

ACCURACY: Two 10-round groups with maximum average extreme spread of 1.7" at 200 yards, using a Mann Rest Test System

INSTRUMENTAL VELOCITY: 2675 ± 50 fps using a 24.00" SAAMI standard test barrel

MUZZLE ENERGY: 2,225 Ft-lbs.

CHAMBER PRESSURE: Piezotronic maximum average per 10 rounds – 62,000 psi

BULLET PULL: Minimum individual 40 lbs.

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured.