



Product Specification Sheet Shotshell

LOAD NUMBER: LE132-00

CALIBER: 12 ga. 2 3/4"

SHOT BUFFER: Approximately 36 grains

SHOT VOLUME: 9 Pellets

SHOT DESCRIPTION: Copper Plated, 3% Antimony

WAD: One-piece FLITECONTROL

PRIMER: Federal No. 202 sealed with lacquer

DRAM EQUIVALENT: 2 3/4

TUBE: Red Plastic

CHAMFERED TUBE: Yes

BASEWAD: Integral Basewad

CRIMP: 6 Segment Standard

CRIMP SEAL: Yes

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation.

PATTERN (ACCURACY): 5 Round maximum average extreme spread of 1145 at 25 yards (IC choke)

INSTRUMENTAL VELOCITY: 1145 +/- 50 FPS at 3 feet from the muzzle of a standard SAAMI test barrel

CHAMBER PRESSURE: 11500 PSI maximum average

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
(800)322-2342, ext. 3822 or 2370