



Product Specification Sheet
Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303

LOAD NUMBER: LEB127 LRS

CALIBER: 12 ga. 2 3/4"

SLUG WEIGHT: 1 oz. slug

SLUG DESCRIPTION: Foster Rifled Slug

PRIMER: Federal No. 202 sealed with lacquer

DRAM EQUIVALENT: 3 1/4

TUBE: Blue Plastic

HEAD: Brass

CHAMFERED TUBE: No

WADDING: Recoil wad & plastic sphere

BASEWAD: 9/16" paper basewad

CRIMP: Roll crimp standard

CRIMP SEAL: No

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation

ACCURACY (TYPICAL): 4" extreme spread at 50 yards in test barrel

INSTRUMENTAL VELOCITY: 1300 ± 50 fps at 3 feet from the muzzle of a standard SAAMI test barrel

CHAMBER PRESSURE: 11500 psi maximum average

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture or assembly line on which manufactured