

GL05

5 x 1/1GN multifunction blast chiller/freezer

functions

Blast chilling cycles +3°C HARD/SOFT

Blast freezing cycles -18°C HARD/SOFT

Thawing

Retarder proofer

Low temperature cooking

Max. chilling capacity (+3°C) / kg **30**

Max. freezing capacity (-18°C) / kg **24**

Temperature range **+90 / -40°C**

Climatic class **5**

technical data

Width (mm) **790**

Depth (mm) **970**

Height (mm) **850**

Distance between runners (mm) **65**

N° trays 1/1GN (535x325) or 600x400 **5**

Electric connection (V/~ / Hz) **230/1/50**

Cooling power (W) **2002**

Electric power (W) **2100**

Max. absorbed current cooling (A) **9.15**

Noise level [dB(A)] **< 70**

Refrigerant type (gas) **R290**



main features

- 7" colourscreen (LCD - TFT - IPS) that is high definition and capacitive with "Touch Screen" functions.
- All processes are displayed with specific icons for every type of food, meat, fish, confectionery etc.
- Start of the work process with one Touch on the icon.
- Blast Chilling +90°C/ +3°C: it rapidly brings the product core temperature to +3°C, reduces natural product evaporation maintaining its humidity and preventing bacterial proliferation after cooking.
- Shock Freezing +90°C / -18°C: It rapidly brings the product core temperature to -18°C, keeping product structure and consistency in tact.
- Thawing: To control and determine product thawing means keeping the organoleptic properties in tact and optimizing stock, avoiding useless waste.
- Leavening Retarder: "Just in time" production flexibility is the best way to optimize resources, manage time and meet demand variability.
- Low temperature Cooking: allows temperature control and to keep it within set values for preparations that safeguard not only the flavour and taste, but moistness and softness for extremely satisfying results.

