

ELECTRIC COOKER 4 INDUCTION ZONES TOP VERSION

Project
Rev.:
Zone:
Location:



CODICE
CR1358339

MODELLO
Q70PC/IND801

SERIE
QUEEN 7

GENERAL CHARACTERISTICS

For those who do not want to give up the quality and solidity of a Queen stove, the Series 7 offers a 700 mm depth and more compact dimensions to fit any room, burners available in various configurations and wattages, enhanced by the refined Scotch Brite finish.

Thanks to its extreme compositional freedom, every composition is possible: you can combine Model i tops with accessorizable oven and neutral bases and hygienic finishes; create customized solutions by matching and attaching equipment back to back, sideways "flush" perfectly sealed, or "bridge" structures, offering high-level solutions that always perfectly meet the chef's needs.

As a total guarantee, all equipment that make up a Queen7 kitchen are certified in compliance with international standards, including CE, GAR, AGA and others.



TECHNICAL SPECIFICATIONS

Stainless steel outer shells and feet.

Height of the work surface adjustable from 840 to 900 mm.

Tops with a thickness of 2 mm.

Contoured dashboards with controls angled toward the operator.

Unbreakable glass-ceramic top.

Each cooking zone is marked with a circular silkscreen printing.

Heating achieved with a
inductance equipped with a device that detects the presence of the
cooking vessel on the cooking zone and automatically turns heating
on/off, and a device against overheating.
Power 5 kW cada zone.

ELECTRIC COOKER 4 INDUCTION ZONES TOP VERSION

Project
Rev.:
Zone:
Location:



CODICE
CR1358339

MODELLO
Q70PC/IND801

SERIE
QUEEN 7

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1358339
DEFINITION	Q70PC/IND801 INDUZIONE M80 TOP
COMMERCIAL LINE	QUEEN
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	250 mm
NET WEIGHT	54 Kg
VOLUME (net)	0.14
PACKAGE LENGTH	450 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,450 m3
GROSS PACKING WEIGHT	64.2 Kg
STANDARD POWER SUPPLY	380-415V 3
FREQUENCY	50/60 Hz
ELECTRICAL POWER	20 kW
IP GRADE	IPX4
CERTIFIED MODEL	Q70PC/IND801

ELECTRIC COOKER 4 INDUCTION ZONES TOP VERSION

Project
Rev.:
Zone:
Location:




CODICE
CR1358339

MODELLO
Q70PC/IND801

SERIE
QUEEN 7

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - INSTALLATIONSRIJNINGAR

MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm
MESURES EN mm - MEDIDAS EN mm - MATEN IN mm



Legenda - Legende - Key - Légende - Leyenda - Legenda

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief
Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel

H2O* Attacco arrivo acqua - Wasseranschluss - Water inlet
Arrivée eau - Union de agua - Wateraansluiting
EN ISO 228-1 G 3/4

ELECTRIC COOKER 4 INDUCTION ZONES TOP VERSION

Project
Rev.:
Zone:
Location:



CODICE
CR1358339

MODELLO
Q70PC/IND801

SERIE
QUEEN 7

PRODUCT'S RANGE PLUS



Professional components tested to
withstand intensive use over time



Power adjustable to 12 levels



Cooking zones with 5KW power



Mechanically controlled induction
ready for IOT connection to Cloud



Ensures the correct positioning and
suitability of the pot



Serigraphs identifying cooking
zones.