ICBCL4850S/S

FEATURES

Product availability pending in country approval

Sub-Zero offers an industry-leading full two-year warranty on appliances, along with a full five-year sealed system warranty

ClearSight™ LED lighting system fully illuminates the interior and reduces shadows

Split Climate™ intelligent cooling system revolutionizes Sub-Zero's already-superior preservation capabilities, keeping food even fresher for longer

Night Mode optimizes the interior lighting based on the detected ambient light, reducing the brightness by 90% in dim environments

Touch control panel is conveniently located for easy access at the tap of a finger

Sleek stainless accents trim the interior, matching the sophistication of the exterior

Stainless-steel exterior and tubular or pro handles to match other Sub-Zero and Wolf products

Lift the base of the flip-up dairy compartments to store taller items on the shelf below

Fresh-tasting, odorless, filtered ice ready on-demand and activate Max Ice Mode to temporarily increase ice production

Position adjustable door bins at various heights to accommodate assorted items

ACCESSORIES

Air Purification Cartridge

Egg Container

Stainless steel kickplate

Grilles for 2108 mm or 2235 mm finished height (2134 mm is standard)

Side panel mounting kit

Grilles for 2108 mm or 2235 mm finished height (2134 mm is standard)

90° door stop

Replacement water filter

Stainless steel kickplate

Replacement air purification cartridge

Dozen egg container

Accessories are available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.

HANDLE OPTIONS

PRO

TUBULAR

PRODUCT DETAILS

REFRIGERATOR

• 5 glass refrigerator shelves (4 adjustable; 1 stationary)

• 4 crisper drawers with removable dividers

• 5 refrigerator door bins (3 adjustable; 2 stationary)

• Air purification system

• LED refrigerator and freezer lights

FREEZER

• Ice drawer with automatic ice maker

• 5 adjustable door bins

• 2 storage drawers

• Water filtration system

PRODUCT SPECIFICATIONS

Model	ICBCL4850S/S
Dimensions	1219mmW x 2134mmH x 610mmD
Electrical Supply	220-240 VAC; 50/60 Hz
Electrical Service	≤ 4 A
Receptacle	3-prong grounding-type

ELECTRICAL

7" (178)

E

6" (152)

75 1/2" (1918) FROM FLOOR

RIGHT SIDE OF OPENING

PLUMBING

RIGHT SIDE OF OPENING

18" (457)

6" (152)

3" (76)

AREA EXTENDS 1/2" (13) FORWARD ON FLOOR

NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

INTERIOR VIEW

This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

DIMENSIONS

48" (1219)

26 3/16" (665)

84" (2134)

73 3/4" (1873)

HEIGHT DIMENSIONS ± 1/2" (13)

4" (102)

23 7/8" (606)

23 7/8" (606)

8 3/8" (213)

11 5/8" (295)

30" (762)

2 3/8" (60)

STANDARD INSTALLATION

24" (610) OPENING DEPTH

TOP VIEW

3/4" (19) TYPICAL

3 1/2" (89) FINISHED RETURN

47 1/2" (1206)

FRAMELESS CABINETRY

83 3/4" (2127) OPENING HEIGHT

47 1/2" (1206) OPENING WIDTH

3/4" (19) TYPICAL

3 1/2" (89) FINISHED RETURN

FILLER

47 1/2" (1206)

FRAMED CABINETRY

SIDE VIEW

FRONT VIEW

NOTE: 3 1/2" (89) finished returns will be visible and should be finished to match cabinetry
Shaded line represents profile of unit.